

COMP1521

Week 1 - Memory & C revision

Introductions

Name (optionally pronouns)

Degree

Highlight from the break

Preference for chocolate: TODO

Overview

Admin

Programming tools

Memory (Q2, Q3, Q4)

Compilation (Q8)

C revision (Q5, Q6, Q7)

MIPS intro

Admin

Assessment:

- Weekly labs (15%)
- Weekly tests (10%) (beginning in Week 3)
- Assignments (2 * 15%)
- Final (45%)

Challenge lab exercises:

- Complete 2 weeks worth to get full marks for the lab component
(Assuming you get full marks for everything)

Lab marking:

- Style is not marked for labs

Admin

Submission of work

- All work is submitted on the command line using give
- All required commands are provided in lab/assignment specs
- No work is submitted via Edstem (I think 1511 might use it, but not in 1521)

Admin

Course website tour: <https://cgi.cse.unsw.edu.au/~cs1521/24T2/>

Tools

Man pages (manual pages)

\$ man 3 [name]

(3 = C library functions, see “man man” for more detail)

Contains:

- Arguments
- Return values
- What it does
- Sometimes example of usage

DESCRIPTION

Never use this function.

```
SED(1)                                User Commands                                SED(1)

NAME
  sed - stream editor for filtering and
        transforming text

SYNOPSIS
  sed [OPTION]... {script-only-if-no-other-
script} [input-file]...

DESCRIPTION
  Sed is a stream editor. A stream editor is
  used to perform basic text transformations
  on an input stream (a file or input from a
  pipeline). While in some ways similar to an
  editor which permits scripted edits (such as
  ed), sed works by making only one pass over
  the input(s), and is consequently more
  efficient. But it is sed's ability to
  filter text in a pipeline which particularly
  distinguishes it from other types of
  editors.

  -n, --quiet, --silent

        suppress automatic printing of pattern
        space

  --debug

        annotate program execution

  -e script, --expression=script

        add the script to the commands to be
        executed

: █

ESC  CTRL  ALT  -  ↓  ↑
```


Makefiles

Instructions stored in Makefile

Convenient way to compile C programs.

Compile a single program:

`“make program_name”`

Compile all programs:

`“make”`

Pretty much just runs gcc for you

Not assessable, but useful for the exercises (we provide Makefiles for labs).




Memory in C



What is RAM?

Just a big 1D array that your computer can read and write to.



What is a process?

A smaller array, stored inside your computer's RAM.


This array has some different segments:

Stack (local vars)

Heap (malloc or other dynamic allocated)

Data (global variables)

Text (code)




Stack segment

A stack frame describes a small part of the process array which is used to store information about a function call, like local variables.

A stack frame is always located inside the stack segment.

Every time you call a function, the computer creates a new stack frame to keep track of its variables.


Whenever you return from a function, its stack frame is DESTROYED :(



Heap segment

The heap is a segment used to contain memory which is allocated by the programmer.

If you call malloc, the computer will set aside some heap memory and give you a pointer to it.




Data segment

The data segment stores global variables.

Kinda like the heap, but the data segment is static instead of dynamic

(so the data segment won't let you add more stuff at runtime, just whatever globals you defined originally)




Text segment

Stores a binary representation of your process's code.

This binary representation is produced by a compiler.

There is an “entry” address inside the text segment where the CPU will start reading the binary code from your program, and running it using the CPU hardware.



What is a pointer, exactly?

A pointer is simply an index into the process array!

NULL is the index 0.

This is valid C code:

```
#include <stdio.h>

int main(void) {
    int pointer = 1337;
    // Tell C that it's actually a pointer (to the address 1337) using type casting
    int *trust_me = (int*) pointer;
    // Dereference it and pray
    printf("%d\n", *trust_me);
    // Segmentation fault :(
}
```

Tute Questions

2. The following snippet of C code declares two variables, of the variables `s1` and `s2` with some subtle differences between them.

```
#include <stdio.h>

char *s1 = "abc";

int main(void) {
    char *s2 = "def";
    // ...
}
```

- What does the memory layout of a typical program look like?
- What is a *global variable*?
- How do they differ from local variables? Where are they each located in memory?
- What is a string literal? Where are they located in memory?

Tute Questions

3. What is wrong with the following code?

```
#include <stdio.h>

int *get_num_ptr(void);

int main(void) {
    int *num = get_num_ptr();
    printf("%d\n", *num);
}

int *get_num_ptr(void) {
    int x = 42;
    return &x;
}
```

Assuming we still want `get_num_ptr` to return a pointer, how can we fix this code?

How does fixing this code affect each variable's location in memory?

Tute Questions

4. Consider the following C program:

```
#include <stdio.h>

int main(void) {
    char str[10];
    str[0] = 'H';
    str[1] = 'i';
    printf("%s", str);
    return 0;
}
```

What will happen when the above program is compiled and executed?

In particular, what does this look like **in memory**?

How could we fix this program?

Compiling


Steps of a compiler

Preprocessing

Compiling (no way)

Assembling

Linking (dark arts)



Preprocessing


Take care of `#defines` and macros.

Take of `#includes` (literally just copy paste the entire included file into this file)

Remove comments (goodbye style)

Other directives which start with `#`

(you don't need to know weird C preprocessor directives for this course)



Compiling

Turns C code into assembly code which matches your CPU

(for example, produce x86 assembly code for a windows PC, ARM assembly code for a macbook, or MIPS assembly code if you are doing COMP1521)

(“Assembly” is just a weird programming language that maps nicely to the hardware inside a CPU.)

C code:

```
f = (g + h) - (i + j);
```

Compiled MIPS code:

```
add t0, g, h    # temp t0 = g + h
add t1, i, j    # temp t1 = i + j
sub f, t0, t1   # f = t0 - t1
```


Assembling

Turns the compiled assembly code into the binary code we mentioned earlier.

It doesn't work yet though, because we don't have a function definition for library functions like “printf”.

We need to include the definition of library functions like “printf” in our binary file somehow.

```
1010000111101100101010101010101010100101001111
1010111101010000101011110101010010101101010100
0101010101010000111110010100101101101010010110
0101110010100101011010101000101010101010101010
1101101010101010101010101010101111000101011101
1110000111100101010100111100101010100011111001
11010010101010101010100111010110010101001010101
01010101010101011101010111001001010101010101000
1010101010101001010101010010101010100101010010
110101010010101010100101010101010101010101001010
101010101010010101010101010101001010101001000110
101010101010100101010101010100100010011111010010
1010101011010101010100101010011100101001010101
0101010101010001011010101011001100110101010101
0010101010111001010100101010101010111001010101
0001011010101111100001010100010110110000111110
0101011011110101010101010101010110101010101011
110101110101110101010101011110110101010110100
0101010101101011010101110101010101010101001011
0101011111001010111101010111101010111101010000
000110100101010111111100011100011000110101101
1100011110001110100101010101010101010111111010
1110101011010101010110101010010111100011101010
0001110111101111100010101010101010111100011110
011011101011101010101011110001110101010111110
```

Linking

Link definitions of library functions to their calls in the binary code.

This is super complicated so we won't spend time going through exactly how it works.

To generalise, we either link the functions to definitions which exist elsewhere in RAM, or we copy-paste in the definitions themselves into this executable.



Tute Questions

8. For each of the following commands, describe what kind of output would be produced:

- a. `clang -E x.c`
- b. `clang -S x.c`
- c. `clang -c x.c`
- d. `clang x.c`

In particular, how do these commands relate to what we will be studying in COMP1521?

You can use the following simple C code as an example:

```
#include <stdio.h>
#define N 10

int main(void) {
    char str[N] = { 'H', 'i', '\0' };
    printf("%s\n", str);
    return 0;
}
```

C revision/new stuff

For loops

```
/* initialize stuff */  
while (/* loop condition */) {  
    /* stuff */  
    /* run this at the end of each loop */  
}
```

versus

```
for (/* initialize stuff */ ; /* loop condition */ ; /* run this at the end of each loop */) {  
    /* stuff */  
}
```

Tute Questions

5. Consider the following while loop:

```
#include <stdio.h>

int main(void) {
    int i = 0;
    while (i < 10) {
        printf("%d\n", i);
        i++;
    }
    return 0;
}
```

How could we rewrite the above program using a for loop? What subtle difference would there be between the two programs?

Argc and Argv

Argc = number of command line arguments

Argv = array containing command line arguments (array of strings)

Note that both include the name of the program as the first argument!!!!!!!!!!

```
#include <stdio.h>
```

```
int main(int argc, char *argv[]) {  
    return 0;  
}
```

Tute Questions

6. In the following program, what are argc and argv? The following program prints number of command-line arguments and each command-line argument on a separate line.

```
#include <stdio.h>

int main(int argc, char *argv[]) {
    printf("argc=%d\n", argc);
    for (int i = 0; i < argc; i++) {
        printf("argv[%d]=%s\n", i, argv[i]);
    }
    return 0;
}
```

What will be the output of the following commands?

```
$ gcc -o print_arguments print_arguments.c
$ ./print_arguments I love MIPS
```


Tute Questions

7. The following program sums up command-line arguments.

Why do we need the function `atoi` in the following program?

The program assumes that command-line arguments are integers. What if they are not integer values?

```
#include <stdio.h>
#include <stdlib.h>

int main(int argc, char *argv[]) {
    int sum = 0;
    for (int i = 0; i < argc; i++) {
        sum += atoi(argv[i]);
    }
    printf("sum of command-line arguments = %d\n", sum);
    return 0;
}
```

Sizeof

Given a variable or a type, sizeof will tell you how many bytes large it is.

Avoid using sizeof on arrays, as it can create confusing behaviour - sizeof will sometimes treat arrays as pointers and incorrectly return the size of the pointer type instead of the size of the entire array.

```
#include <stdio.h>

int main(void)
{
    char *s = "hello";

    printf("sizeof(char) = %u\n", sizeof(char));
    printf("sizeof(char*) = %u\n", sizeof(char*));
    printf("sizeof('a') = %u\n", sizeof('a'));
    printf("sizeof(*s+0) = %u\n", sizeof(*s+0));
    printf("sizeof(*s) = %u\n", sizeof(*s));
    printf("sizeof(s) = %u\n", sizeof(s));

    return 0;
}
```

Recursion

Recursion allows programmers to write more simple or concise code to solve certain types of problems.

Sometimes this code can be really confusing to read, compared to an iterative approach (like using a loop). Regardless, in a lot of cases recursion can massively simplify the logic for a program.



Recursion

How to write a recursive solution.

1: Find a “base case”, or a few. This is where your program will stop “recursing” and typically return a very simple answer.

2: Find a way to solve the other cases. It can be pretty easy, if you can recursively call a “smaller” case and use that information to trivially get a solution.


For example, solving “5!”, I can trivially call “4!” and multiply the result by 5.

The “base case” is “0!” - here we stop recursing and we return “1” to whoever called us (likely someone who wanted to calculate “1!”).

Recursion

Intuition:

We “walk” down to the smallest case, and figure out the solution on the way up.



MIPS intro



What is MIPS

Recall that second step of a compiler: transform C code into assembly code for a certain processor.

MIPS is an assembly language which was used in old CPUs, and is now mostly used to teach people about assembly (and program old CPUs).

For the first half of this course we will learn to become a compiler, and convert C code into MIPS assembly code by hand.

Why MIPS, why not something that is used more?

MIPS has great educational resources

Stuff like x86 and ARM can be much more complicated

By learning MIPS first you will have a much easier time learning x86 or ARM if that's something you are interested in.

