

INDEX

- accelerometer measurement, 300
- active antenna modules, for energy-efficient off-body communication systems, 261–313
- active antennas, full-wave/circuit co-design paradigm for energy-efficient, 270–273
- active wearable antennas, 262, 269–273
- adaptive antenna system, with frequency reconfigurability, 105–110
- adaptive capsule system, 106–107
- adaptive systems, frequency reconfigurable, 107
- adaptive tuning network, 109–110
- additive manufacturing technique, 351
- AMC-backed antennas, 74. *See also* artificial magnetic conductor (AMC)
- AMC-backed flexible near-endfire wearable antennas, 61–84
- AMC-backed near-endfire antennas, for on-body communications, 64–68
- AMC metasurfaces, 74
- AMC reflector surfaces, 69
- AMC surface, 65–68, 84
- ammonia (NH_3) sensing, 357–358
- amplifier-mixer-filter (AMF) cell, 424, 428, 434–435, 440–443
- analog to digital converter (ADC), 440
- analog identifier, 344
- analytical models, 280
- anatomical tissue models, 96
- animal testing, for wireless capsule endoscopy, 183–187
- antenna configurations, fabricating on flexible latex substrate, 68–69
- antenna deformations, 9–11, 76–79
- antenna designs, 129–130, 174–183.
See also capsule antenna design; circularly polarized; tag antenna design
- conformal capsule, 129–130
- external, 175, 189–192, 198–199
- at 4 GHz band, 192–199
- at 434 MHz band, 187–189
- for head implants, 161–162
- implant, 174
- for medical diagnostics/sensing, 87–130

Electromagnetics of Body-Area Networks: Antennas, Propagation, and RF Systems, First Edition.

Edited by Douglas H. Werner and Zhi Hao Jiang.

© 2016 The Institute of Electrical and Electronics Engineers, Inc. Published 2016 by John Wiley & Sons, Inc.

- antenna designs (*Continued*)
 - of metasurface-enabled compact wearable antennas, 29–31, 34–37
 - on-body, 97
 - RFID capsule, 113
 - suitability of, 47–55
 - for wireless medical implantable devices, 91–95
 - WMTS, 94, 97–103
 - antenna design strategies, 127
 - antenna efficiency, specific absorption rate and, 74
 - antenna efficiency evaluation, 11–15, 140–143
 - antenna fabrication procedure, 2–5
 - antenna freezing, 19
 - antenna gains, 6
 - antenna impedance, 112–114
 - antenna modeling, 280
 - antenna models, human body and
 - performance of, 225
 - antenna modules, active, 261–313
 - antenna performance, 52–55
 - frequency range in, 135–156
 - human body and, 225–227, 230
 - three-layered model and, 195–196
 - antenna performance assessment, 21, 47–55, 63
 - under bending deformation, 76–79
 - in free space, 69–72
 - on voxel model, 72–76, 78
 - antenna prototypes, 79–81, 82–83
 - antenna radiation vector, 285
 - antenna requirements, for off-body communications, 225
 - antennas, *see* adaptive antenna system; coil antennas; CP filtering antennas; epidermal antennas; head antennas; implanted antennas; PIFA antenna; textile antennas; Yagi antennas
 - AMC-backed, 74
 - AMC-backed near-endfire, 64–68
 - aperture-coupled patch head, 192–198
 - body-centric, 1–2
 - bow-tie head, 192, 195, 198–199
 - circularly polarized, 175–176, 178, 181–185
 - conformal meandered offset dipole, 100–101
 - conformal wearable, 29
 - crumpled, 16
 - dipole, 162, 164, 167–168, 324–325
 - dual-mode, 152–156
 - electrically large, 322–323
 - end-fire, 244–246
 - endfire radiation wearable planar, 84
 - epidermal, 319–348
 - filtering, 29
 - high permittivity periodic structure
 - loaded dipole, 191
 - implantable/ingestible, 90–97, 129–130
 - integrated, 30, 32, 45
 - interaction with lossy human body, 328
 - isotropic, 282
 - loop, 162, 164–165, 167–168, 324–325, 363–364
 - low-profile near-endfire, 63
 - as microfluidic-tunable elements, 362–363
 - microstrip patch, 28
 - off-body, 230
 - for off-body communications, 222–230
 - on-body, 233–235
 - for on-body propagation, 231–248
 - patch, 47–49, 222–230, 288, 305, 355
 - planar inverted-F, 28
 - planar monopole, 28, 30
 - radiation patterns of, 50–51, 53–55, 71–72, 74–76, 155–156, 194, 196–197, 226–227, 246, 284–285, 288, 308–309
 - surface wave, 28
 - textile, 1–21, 227–230
 - transmitting and receiving, 281
 - wearable, 2–3, 27–55, 61–84, 135–156, 233
 - for wireless capsule endoscopy, 162–187
 - in wireless implantable neuroprobe microsystem, 187–201
 - woodpile EBG-based, 234–235
- antenna safety limit, 18
 - antenna selection, in signal processing, 267
 - antenna simulation, 5–6
 - antenna size, efficiency and gain *vs.*, 324–326
 - antenna size reduction, 354
 - antenna surfaces, planar Yagi, 69
 - antenna under test (AUT), 6, 16–17

- aperture-coupled patch head antenna, 192–198
- aperture-coupled shorted patch antenna, 305
- applications
 - of RFID epidermal tags, 341–346
 - of sensors and smart skins, 351–371
 - for wearable antennas, 295–311
- artificial magnetic conductor (AMC), 63.
 - See also* AMC
- attenuation, simulated, 167–173
- attenuation measurements, 166–173
- BAN communication systems, frequency
 - bands for, 27–28. *See also* body area networks
- bandpass filter (BPF), 28–29, 37, 41–42.
 - See also* BPF circuits; Chebyshev BPF
- bandwidth extended design, of
 - metasurface-enabled compact wearable antennas, 34–37
- bandwidth tuning, 430–433
- bandwidth variation, 432
- baseband simulation, of data transmission, 286–287
- basic restrictions (BRs), 219, 221
- batch fabrication processes, 115–117
- battery operated devices, 473–474
- bending deformation, antenna performance
 - under, 76–79
- bending models/studies, 9–10
- bending radius, 77
- BER characteristics, 278–279, 293–295.
 - See also* bit error rate
- bidirectional Yagi antennas, 65
- binary frequency shift keying (BFSK), 440
- binary phase-shift keying (BPSK), 287–288, 290–293
- biofuel powered devices, energy harvesting
 - from, 481
- biosensors, *see* nano-biosensors
- bio-signals, 152
- bio-tags
 - planar fat-type folded dipole, 119–121
 - RFID, 118–119, 124–125, 130
- bio-telemetry, 161
 - antenna design and, 87
- bio-telemetry connecting, 129–130
- bio-telemetry systems, antenna design and, 89–90
- bit error rate (BER), 262, 268–269, 280, 287–289. *See also* BER
 - characteristics; MIMO BER characteristics
 - calculating, 275–276
- body-absorbed radiation, 72, 74
- body area networks (BANs), 27, 405–406, 485, 487–488. *See also* BAN;
 - on-body
 - progress in, 248
 - textile antennas for, 1–21
- body-centric antennas, 1–2
- body-centric communications, 261
- body-centric MIMO channels, 273–295.
 - See also* multiple-input multiple-output (MIMO) communication
- body-centric systems, 233
- body-centric wireless communications,
 - applications for, 135–136
- body-centric wireless communication
 - systems, 126, 312
- body channel communication (BCC), 376–377, 381, 384–388
- body dual polarized antennas, 287–289
- body fluids monitoring, 360
- body-matched tags, 117
- body movement, influences of, 143–149
- body sensor networks (BSNs), 61
 - wearable wireless, 299, 303–304
- body-worn networks, N-node, 298–300
- body-worn textiles, 61–62
- bow-tie head antenna, 192, 195, 198–199
- BPF circuits, 43. *See also* bandpass filter; stripline BPF circuit
- brain–machine interface system, 127–128
- BreathTaking application, 456–457
- bulk acoustic wave (BAW) resonators, 411–413
- Butterworth–Van Dyke model, 412
- CAD (computer aided design) tools, 282
- calculated electric field distributions, 150–151
- calculation models, 136–139
- calibrated dual-loop epidermal sensor, 341–342

- calibration, of personal distributed
 - exposimeter, 308–309
- canonical tissue models, 96
- capacitors (C_{itc}), 435–437. *See also* LC DCO; LC VCO; MIM (metal-insulator-metal) capacitors
- capsule antenna design
 - conformal, 129–130
 - RFID, 113
 - for through-body RF transmission, 179–181
- capsule antenna orientations, 178, 183
- capsule antennas, 183
- capsule endoscope system, 160, 162–187
- capsule endoscopy, antennas for wireless, 162–187
- capsule insertion, for wireless capsule endoscopy, 184–187
- capsule package, 175
- capsule systems, 97–110, 128–129
 - adaptive, 106–107
- carbon nanomaterial-based sensors, 358–360
- carbon nanotubes (CNTs), 352. *See also* CNT-based DMMP sensor
- carbon–silicate phantoms, 211
- cardiac recordings, 449–450
- cascode biasing, 399
- catalyst inks, inkjet printing of, 352–353
- CDF correlation properties, 292. *See also* cumulative distribution function
- channel characterization, for wireless capsule endoscopy, 168–173
- channel matrix, 274
- channel measurements
 - on-body, 241–244
 - for through-body RF transmission, 178
- channel models, correlated, 312
- channel responses, 282–284, 286
 - with Matlab model, 283–284
- Chebyshev BPF, 43–44. *See also* bandpass filter
- circuit fabrication, with inkjet-printed masking, 365–366
- circuit/full-wave co-design paradigm, for energy-efficient active antennas, 271–273
- circuit models, 40, 43–44
 - for planar fat-type folded dipole bio-tag, 119–121
- circuits, *see* BPF circuits; full-wave/circuit co-design paradigm; microwave-circuit-integrated wearable filtering antennas; printed circuit board (PCB) layout; stripline BPF circuit
- harvesting, 364–365
- receiver, 365
- RF-DC conversion, 366, 368
- for wireless body area networks, 375–402
- circularly polarized (CP) antenna, 175–176. *See also* CP
 - with through-body RF transmission, 178, 181–185
- circularly polarized wearable filtennas, 29
 - synthesis of narrowband, 37–41
 - synthesis of wideband, 41–46
- clock synthesis, 426–428
- CNT-based DMMP sensor, 359–360. *See also* carbon nanotubes
- coaxial probes, open-ended, 212
- coil antennas, 174
 - internal, 171–173
- coils, transmitter and receiver, 106–109
- commercial textiles, for textile antennas, 4–5
- communication channels, frequency dependence of, 136–142
- communication systems
 - body-centric wireless, 312
 - power-efficient, 312–313
- communication theory, 105
- compact planar dipole external antenna, 189–191
- compact sensor node designs, 389–400
- complex signal demodulation (CSD), 462–463
- composition/fabrication method, for solid skin-equivalent phantoms, 217–218
- concurrent dual-band operation, in MBAN hub design, 381–383
- conducting materials, inkjet printing of, 352
- conductive polymer-based sensors, 357–358
- conductive textiles/foils, 2–3, 18, 20–21
- conductivity, equivalent, 3
- conformal capsule antenna design, 129–130

- conformal meandered offset dipole antenna (CMODA), 100–101
 - inverted conical helical antenna vs., 101–105
- conformal RFID tag, 118. *See also* radio frequency identification
- conformal wearable antennas, 29
- contact-less sensing, 448
- continuous-wave (CW) methods, 457–463
- conventional radios, WBAN systems and, 407–408
- co-planar waveguide (CPW) line, 19
- co-polarization, 171–172
- copper foil tape, 3
- correlated channel model, 312
- co-simulations, on-body, 6–9
- coupling gap change, 114–115
- coupling matrix technique, 43
- coupling parameter, 39–40
- CP filtering antennas, 37–38, 40, 46.
 - See also* circularly polarized; narrowband CP filtering antenna; wideband CP filtering antenna
- performance of, 41
- CP radiation patterns, 50–51, 53–55
- cross-correlation values, 277–278
- cross-polarization, 171–173
- crumpled antennas, 16
- crumpling models, 11–12
- crystal-less sensor nodes, 379–381
- crystal oscillator (XO), 377, 408
- CST MWS voxel model, 84
- cumulative distribution function (CDF), 267–268, 303–304. *See also* CDF correlation properties
- cylindrical skin models, 239–240
- database calculation, 282
- data communication, 481–484
- data forwarding, 263
- data inversion curves, 345
- data telemetry applications, 129
- data transmission, baseband simulation of, 286–287
- Debye model, 214
 - extrapolation from, 212–213
- deformations, 9–11
- deformation studies, 63
- design paradigms, for energy-efficient active antennas, 270–273
- design strategies, for textile antennas, 5–20
- deterministic, 280
- deterministic models, 273, 280–289
- device flexibility, 62
- diagnostic capsule systems, 128–129
- dielectric materials, inkjet printing of, 352–354
- dielectric properties
 - of human phantoms and tissues, 211–213
 - measured, 216–218
- diffracted fields, 33–34
- diffraction, 283
- digital baseband, 416–418
- digitally controlled oscillator (DCO), 377–381, 393. *See also* FBAR DCO
- digital signal processing techniques, 467
- dimethyl methylphosphonate (DMMP), 359
- dipole antennas, 162, 164, 167–168, 189–192, 324–325
- distributed exposimeter, 263–264, 304–311
- distributed sensor networks, wearable, 295–304
- diversity/MIMO systems, signal processing techniques in, 266–269
- diversity/MIMO techniques, for off-body wireless channels, 264–269. *See also* multiple-input multiple-output (MIMO) communication
- diversity technique, 149
- Doppler radars, 467–468
- Doppler radar systems, 457–459
- Doppler shift, 264–265
- double-layered AMC, 67–68. *See also* artificial magnetic conductor
- drug delivery, 346
- drug release, 338
- drying/washing cycles, 20
- dual-band hub, 381–383
- dual-band hub transceiver, 383–389
- dual-loop epidermal sensors, calibrated, 341–342
- dual loop tag, 328–329
 - performance of epidermal, 328–335
- dual-mode antenna, 152–156
- dual-polarized patch antennas (DPPAs), 288

- duty cycling, 407–408
- dynamic human body model, 136, 143–149
- ECG (electrocardiogram) sensor, 401, 461–462
- effective isotropic radiated power (EIRP), 160, 296, 322, 381
- efficiency, antenna size vs., 324–326.
See also radiation efficiency; RF-DC conversion efficiency
- efficiency evaluation, for antennas, 11–15, 140–143
- E*-field distributions, 144. *See also* electric field; *E*-plane
- E*-field intensities, 140
- electrically large antennas, 322–323
- electric field, 150, 151. *See also* *E*-field
 - spectral-domain, 240–241
- electric field distributions, 139–140, 143, 150–151
 - calculated, 142, 144
- electromagnetic band gap (EBG), 222.
See also woodpile EBG-based antennas
- electromagnetic coupling, 223
- electromagnetic (EM) applications (electromagnetics), 110–114.
See also 3D EM solvers
 - antenna design and, 87–89
- electromagnetic energy harvesters, 480
- electromagnetic fields, 474–477
- electromagnetic propagation, 172–173.
See also on-body propagation
 - performance of, 245–246
- electromagnetic ray tracer, 282–283
- electromagnetic sensing systems, 449–451
 - non-invasive, 451
- electronic stirring, 13
- electrospinning, 336–337
- embedded software, 296
- “EME Spy 140,” 307–310
- empirical models, 280
- end-fire antennas, 244
 - wearable, 245–246
- endfire gain, 70–71, 83–84
- endfire radiation, 65. *See also* near-endfire
- endfire radiation wearable planar antennas, 84
- endoscope systems, capsule, 160, 162–187
- endoscopy diagnostics, 97–103
- energy-efficient active antennas, full-wave/circuit co-design paradigm for, 270–273
- energy-efficient MBAN hub design, 381–389. *See also* medical body area network (MBAN)
- energy-efficient off-body communication systems, wearable active antenna modules for, 261–313
- energy harvesting, 472
 - for wearable antennas, 364
- energy harvesting devices, 488
 - regenerative, 478–481
- energy harvesting technologies, 485
- envelope correlation, 292–293
- environment, influences of, 142–143
- environmental conditions, aging and varying, 18–20
- environmental drawing, 282
- epidermal antennas, 347
 - examples of, 320
 - radiation performance of, 322–328
 - as sensors, 327
 - for tracking and sensing, 319–348
- epidermal devices, 319, 335
 - radiation performance vs. trace conductivity in, 326–327
- epidermal membranes, functionalized, 335–341
- epidermal radiators, 347
- epidermal RFID dual-loop tag, performance of, 328–335
- epidermal RF thermometer, 341–342
- epidermal sensors, calibrated dual-loop, 341–342
- epidermal tags, 347
 - layout of, 329–330
 - prototypes and on-skin performance of, 330–332
 - sensing applications of, 341–346
- E*-plane, 30–31, 34–36. *See also* *E*-field
- equivalent conductivity, 3
- evaluation, for textile antennas, 5–20

- evaluations
 - antenna efficiency, 11–15
 - experimental, 6–9
- experimental evaluations, 6–9
- experimental phantoms, 213–218
- exposimeters
 - distributed, 263–264, 304–311
 - personal, 305
 - personal distributed, 305, 307–311
- exposimeter system design, 305–306
- exposure limits/guidelines, 218–222
- external antenna design, 175, 189–192, 198–199
- external antennas, 189–192, 198–199
 - wideband sleeve monopole, 191–193
- extravehicular activity (EVA) suit, 206–207
- fabricated filtering antenna, 51
- fabricated textile antennas, 228–230
- fabrication procedure, for textile antennas, 4–5
- fabrication process types, 18–19
- fabrication technology, inkjet printing in, 354
- fabric water-proofing, 20
- fading, 264–265. *See also* fast fading
 - separation from shadowing, 274
- fading characteristics, in simulated
 - attenuation, 168–169
- far-field RFID tags, 117–118. *See also* radio frequency identification
- fast fading, 148
- fat-dipole bio-tag, 119–121
- fat-type planar folded dipole, 119–121
- FBAR-based pseudo-lattice network, 428–430. *See also* thin-film bulk acoustic resonators
- FBAR-based radios, 413
- FBAR-based RF front end, 428–437
- FBAR-based RX, 443
- FBAR-based TX, 420–424
- FBAR-based TX architecture, 413–414
- FBAR DCO, 413–419, 421, 425–427, 440. *See also* digitally controlled oscillator
- FB ratio, 47–48
- Federal Communications Commission (FCC) requirements, 62
- feeding loop length, 114–115
- FET sensor concept, 129
- filtering antennas (filtennas), 29, 37–46. *See also* LP (linearly polarized) filtering antennas
 - circularly polarized, 29
 - fabricated, 51
 - integrated, 45
 - microwave-circuit-integrated wearable, 37–46
 - performance of, 41
- finite-difference time-domain (FDTD)
 - method/technique, 5, 96, 136, 138, 235–236
- finite element method (FEM), 5, 96
- finite integration technique (FIT), 5
- FIR (finite impulse response) filtering, 439–440
- flat skin models, 237–239
- Flectron electrotexile, 18–20
- fleece, polyester, 4
- flexible latex substrate, antenna
 - configuration fabrication on, 68–69
- flexible microfluidics, 361
- flexible near-endfire wearable antennas, AMC-backed, 61–84
- flip-chip CW radar sensor, 462
- fluid loss monitoring, 343–345
- fluid permittivity, 361
- foils, conductive, 2–3
- folded dipole bio-tag, planar fat-type, 119–121
- 4 GHz band, antenna designs at, 192–199
- 434 MHz band, antenna designs at, 187–189
- free space, antenna performances in, 69–72
- free-space experiments
 - with metasurface-enabled compact wearable antennas, 34
 - with microwave-circuit-integrated wearable filtering antennas, 46
- frequency bands, 159–160
 - for BAN communication systems, 27–28
 - in data communication, 483–484
- frequency calibration techniques, 379–381
- frequency dependences, 142, 147–148
 - of communication channels, 136–142
- frequency detuning, 72–74
- frequency domain plot, 455
- frequency modulated continuous wave (FMCW) method, 460

- frequency ranges
 - in antenna performance, 135–156
 - parameters for, 139
- frequency reconfigurability, with adaptive antenna system, 105–110
- frequency reconfigurable adaptive system, 107
- frequency retuning, 334
- frequency selective surface (FSS)
 - coverings, 29
- frequency-shift keying (FSK), 296, 381, 397, 398
- frequency stirring, 13
- frequency synthesis, receiver architecture and, 425–428
- frequency tuning, 433–434
- full-wave/circuit co-design paradigm, for energy-efficient active antennas, 270–273
- full-wave models, of on-body propagation, 236–241
- full-wave solvers, 96
- fully integrated on-body PDE, 313. *See also* personal distributed exposimeter
- functionalized epidermal membranes, 335–341
- gain, 70–71. *See also* endfire gain
 - antenna size vs., 324–326
 - realized, 344
 - trace width vs., 326
- gain antennas, 6
- gain measurements, 83–84
- gap coupling, 114–115
- Gaussian frequency-shift keying (GFSK), 296
- Gaussian minimum shift keying (GMSK), 296
- gel phantoms, 208
- geometrical optic (GO) fields (GOFs), 33–34, 237–239
- geometrical theory of diffraction (GTD), 29, 33–34
- global connectivity, 87
- glycerin phantom, 210
- graphene oxide (GO), 359
- Green's functions, 236
- half-power beamwidth (HPBW), 30, 34
- harvesting circuits, 364–365
- harvesting receivers, wearable, 367–368
- head antennas
 - primate demonstration for, 199–201
 - for wireless implantable neuroprobe microsystem, 187–190, 192–198, 199–201
- head implants, antenna design for, 161–162
- health monitoring applications, 7
- heating kinetics technique, 212
- high frequency, in data communication, 483–484
- high frequency power transfer, 475–476
- high permittivity periodic structure (HPPS), 189–190, 192
- high-resolution human body model, 154–155
- home base station, 89–90
- homogeneous phantoms, 207
- H*-plane, 30–31, 33–36
- hub transceiver, dual-band, 383–389
- HUGO human body model, 51–52, 55
- human–antenna interaction, 88, 328
- human body
 - antenna interactions with, 88, 328
 - patch antenna array for, 225–227
 - tag characterizations on, 121–124
 - wearable antennas mounted on, 136–142
- human body communication (HBC) band, 376
- human body models, 49–52, 55, 101, 137–138, 150, 207–222
 - dynamic, 136, 143–149
 - high-resolution, 154–155
 - walking, 146
- human body phantoms, 155, 207–211, 248–249
 - dielectric properties and measurement techniques for, 211–213
 - numerical and experimental, 213–218
 - propagation along, 241–242
 - propagation around, 242–244
 - skin-equivalent, 225–226, 229–230
- human tissues
 - dielectric properties and measurement techniques for, 211–213
 - permittivity of, 138
- human vital data acquisition system, 152–156
- hydrogel membranes, 338–341
- hydrogels, 345–346

- ideal power transmission efficiency, 140–143, 146
- IETR, University of Rennes, 222
- IF (intermediate frequency) amplifier, 390–392
- IIR (infinite impulse response) filtering, 439
- impedance, 112–114
 - mutual, 141
- impedance control, 114–115
- impedance matching, 141, 181, 200
 - in coil antennas, 174
 - optimal, 271–272
- impedance measurement, 120, 122–124
- implantable devices, *see* head implants
 - antenna design for wireless medical, 91–95
 - miniature, 127–128
 - wireless communication for, 161
- implantable/ingestible devices, 89–97, 129–130
- implantable neuroprobe microsystems, motor prosthesis for wireless, 187–201
- implantable sensor node transceiver, 389–394
- implant antenna design, 174
- implanted antennas, in through-body communications, 159–201
- implanted devices, 485
- implanted medical devices, 201
- implant node, 401
- implants, telemetry techniques for, 471–488
- in-body sensors, antenna design and, 89
- indoor environment, modeling, 282–283
- indoor off-body radio propagation channel, 264–265
- inductive coupling, 474–475
- inductively coupled near-field links, 108
- ingestible antenna designs, 97. *See also* implantable/ingestible devices
 - at ISM band, 110–117
 - link budget *vs.* SAR for, 101–105
 - at WMTS band, 97–103
- injection-locking DCO (IL-DCO), 379, 389, 391, 394–396. *See also* digitally controlled oscillator
- injection-locking oscillator (ILO), 379
- inkjet-printed masking, circuit fabrication with, 365–366
- inkjet-printed microfluidics, 360–364
- inkjet-printed sensors, 356–357
- inkjet-printed smart skins, applications of, 351–371
- inkjet printing, multilayer, 352–356
- inkjet-printing technologies, 365–366
- input power estimation, 366–368
- integer- N approach, 425–428
- integrated antennas, 30, 32, 45
- interdigital capacitance, 35
- interface systems, brain–machine, 127–128
- intermediate frequency (IF), 413–414
- internal coil antenna, 171
 - misalignment of, 172–173
- Internet of Things (IoT), 375
- interrogating devices, 341
- inverted conical helical antenna (ICHA), conformal meandered offset dipole antenna *vs.*, 101–105
- inverted-F antennas, 28
- ISM (industry-science-medical) band, 376
 - ingestible antenna design at, 110–117
 - wireless medical implantable devices and, 92–94
- isotropic antenna, 282
- Lab-on-a-chip (LOC), 360–361
- latex substrate, antenna configuration
 - fabrication on flexible, 68–69
- lattices, *see* pseudo-lattice network
 - bandwidth tuning in, 430–433
 - capacitors (C_{lc}) in, 435–437
 - frequency tuning in, 433–434
- layered phantoms, 207
- LC DCO (inductor-capacitor digitally controlled oscillator), 393. *See also* digitally controlled oscillator
- LC VCO (inductor-capacitor VCO), 387–388. *See also* VCO
- LHCP (left-hand circularly polarized) radiation patterns, 50–51, 53–54
- light-powered sources, 478
- linear-frequency modulated continuous wave (LFMCW) method, 460
- line-of-sight (LoS) conditions, 290
- link budget
 - SAR *vs.*, 101–105
 - for wireless capsule endoscopy, 183, 185
- link budget calculation, 104–105
- link loss, 184
- liquid phantoms, 207–209

- listen-before-talk (LBT) protocol, 381
- local oscillator (LO), 413–414
- location services, antenna design and, 89
- loop antennas, 162, 164–165, 167–168, 324–325, 363–364
- loop feeding scheme, 113–114
- low frequency (LF), in data communication, 482–483
- low frequency band, wireless medical implantable devices and, 91
- low-noise amplifier (LNA), 271–272, 384, 389, 395–396, 400, 424, 441–442.
See also Q-enhancement LNA (low noise amplifier)
- low-profile near-endfire antenna, 63
- LP (linearly polarized) filtering antennas, 43–44

- machine–brain interface system, 127–128
- magnetic current, 33
- masking, inkjet-printed, 365–366
- Matlab simulation model, 283–289
- maximal ratio combining (MRC) technique, 286–287
- maximum achievable data rate (MADR), 416, 418
- maximum frequency, defined, 138
- maximum power transmission, 141
- maximum radio combining (MRC) technique, 266
- MBAN hub design, energy-efficient, 381–389. *See also* medical body area network
- MBAN system concept, 377–381
- MBAN system implementation, 400–402
- meandered dipole antenna, 100–101
for head, 187–190
- measured dielectric properties, 216–218
- measured power density, 310–311
- measurement methodologies/techniques,
see transmitter measurement results
 - for accelerometers, 300
 - attenuation measurements, 166–173
 - channel measurement, 178
 - for four on-body nodes, 300
 - for human phantoms and tissues, 211–213
 - path loss measurement, 178–180
 - for PDE and PEM nodes, 310–311
 - reference measurements, 163–164
 - in RF transmission characterization, 162–168
 - for sensors, 300–301
 - temperature, 341, 343
 - through-body transmission measurement, 165, 175–183
- measurement results, for Yagi antennas, 79–84
- measurement setup
 - for NLoS conditions, 292–293
 - for spatial modulation, 291–292
 - for through-body RF transmission, 176–183
- mechanical energy harvesters, 479
- mechanical stirring, 12
- medical BAN (MBAN) band, 27–28, 30
- medical body area network (MBAN), 375–377. *See also* MBAN
- medical compliance sensing systems, 110–117
- medical diagnostics/sensing, antenna design and methodologies for, 87–130
- medical implantable devices, antenna design for wireless, 91–95
- medical implant communication services (MICS) band, 27–28, 376, 381, 383–390
wireless medical implantable devices and, 91–92
- medical implant communication services technologies, 159–160
- medical monitoring/sensing system, 130
- medical non-compliance, 111
- medicine monitoring schemes, 111
- membrane permittivity, 339–340
- membranes, 335–341
hydrogel, 338–341
scaffold, 336–337
- MEMS (microelectromechanical system)-based radios, ultra low-power, 405–443
- MEMS (MEM) resonators, 411–413, 443
- metallic materials, inkjet printing of, 352–353
- metasurface-enabled compact wearable antennas, 29–37
assessing performance of, 47–49
design of, 28–31, 34–37

- free-space experiments with, 34
- radiation mechanism of, 31–34
- metasurfaces, 29–30, 34–35, 62–63.
 - See also* AMC metasurfaces
- method of moments (MoM), 5, 236
- methodologies, *see* measurement methodologies/techniques
- for medical diagnostics/sensing, 87–130
- for numerical
 - simulations/characterizations, 95–97
- for RF transmission measurement, 162–168
- for wireless capsule endoscopy, 97–103
- microelectromechanical systems (MEMS), *see* MEMS
- microfabrication technology, 471
- microfluidics, 352
 - flexible, 361
 - inkjet-printed, 360–364
- microfluidic-tunable elements, antennas as, 362–363
- microstrip patch antenna array, 228–230
- microstrip patch antennas, 28, 222, 355
- Micro-Total-Analysis (μ TAS), 360–361
- microwave-circuit-integrated wearable filtering antennas, 37–46
 - free-space experiments with, 46
- microwave receiver design, 364–365
- microwave resonators, 361
- microwaves
 - human body models and, 207–211
 - off-body communications at, 222
- millimeter-waves, 212–218
 - off-body communications at, 222–223, 225, 230
 - studies at, 207
 - transceivers for wearable devices at, 247–248
- MIM (metal-insulator-metal) capacitors, inkjet printing of, 353
- MIMO BER characteristics, 278–279, 294–295. *See also* bit error rate; multiple-input multiple-output (MIMO) communication
- MIMO capacity, 278–279
- MIMO systems, 312
- MIMO techniques, 264–268
- MIMO transmission, 274
- miniature implantable devices, 127–128
- minimum shift keying (MSK), 296
- misalignment, of internal coil antenna, 172–173
- misalignment loss, 173
- mixer, 416–418
 - quadrature sub-sampling, 437–440
- mobile health, antenna design and, 89
- modeling framework, for off-body
 - deterministic modeling, 281–282
- monitoring, of body fluids, 360
- monitoring/sensing systems, 130
- monolithic microwave integrated circuits (MMICs), 466
- monopole antennas, 28, 30
 - wideband sleeve external, 191–193
- motion, impact on radio propagation characteristics, 452
- motor prosthesis, for wireless implantable neuroprobe microsystem, 187–201
- multilayer inkjet printing, 352–356
- multilayer printing process, 355–356
- multiple-input multiple-output (MIMO)
 - communication, 262–263, 267–268. *See also* body-centric MIMO channels; diversity/MIMO techniques; MIMO
- multiple-input single-output (MISO) links, 293–294
- multipostural realistic human torso phantom, 209
- mutual impedance, 141
- nano-biosensors, 128–129
- nanowire arrays, 129
- narrowband CP filtering antenna, 46
 - assessing performance of, 49–52
- narrowband CP filtering antenna synthesis, 37–41
- near-endfire antennas
 - AMC-backed, 64–68
 - low-profile, 63
- near-endfire wearable antennas, AMC-backed flexible, 61–84
- near-endfire Yagi antennas, 65–68
- near-field links, inductively coupled, 108
- network nodes, 300, 313
 - PDE and PEM, 306–308, 310–311
- neural implants, 127–128
- neural signal acquisition, 199, 201

- neuromotor prosthetic devices, 161
- neuroprobe microsystems, motor prosthesis for wireless implantable, 187–201
- N-node body-worn network, 298–300
- nodes, *see* network nodes; on-body nodes; sensor nodes; wireless sensor nodes
- node-to-node communication, on-body, 303
- node-to-node links, reliability of on-body, 300–302
- non-communicable diseases (NCDs), 405
- non-compliance, medical, 111
- non-conductive textiles, 3–4, 19–20
- non-invasive devices, 471–472
- non-invasive EM sensing systems, 451
- non-invasive monitoring system, 457
- non-invasive physiological detection, 449–466
- non-invasive sensing, 447–448
- non-invasive technologies, 466–468
- non-line-of-sight (NLoS) conditions, 290–293
- non-regenerative power sources, 472–478
- normalized radiation polar plots, 74, 76–79, 81–82
- normalized received open voltages, 145
- Norton wave, 237–240
- numerical phantoms, 213–218
- numerical simulations/characterizations, methodologies for, 95–97
- numerical skin-equivalent phantom, 213–215
- off-body antennas, 230
- off-body communications, 312–313
 - antenna requirements for, 225
 - antennas for, 222–230
 - wearable antennas for, 27–55
 - wireless, 312
- off-body communication system modeling, 280–281
- off-body communication systems, energy-efficient, 261–313
- off-body deterministic modeling, 280–289
- off-body mode, of dual-mode antenna, 152–153, 155
- off-body propagation, on-body to, 244–246
- off-body radio propagation channels, indoor, 264–265
- off-body stochastic modeling, 273–279
- off-body wireless channels, diversity/MIMO techniques for, 264–269
- off-body wireless communication, 261–262
- offset dipole antenna, 100–101
- on-body antenna designs, 97
 - at UHF bands, 117–125
- on-body antennas, 233–235
- on-body channel measurements, 241–244
- on-body communications
 - AMC-backed near-endfire antennas for, 64–68
 - wearable antennas for, 61–84
 - Yagi-Uda antennas for, 233–234
- on-body co-simulations, 6–9
- on-body measurement configurations, 8–9
- on-body mode, of dual-mode antenna, 152–154
- on-body nodes, measurements for four, 300
- on-body node-to-node communication, 303
- on-body node-to-node links, reliability of, 300–302
- on-body to off-body propagation scenario, 244–246
- on-body PDE, fully integrated, 313.
 - See also* personal distributed exposimeter
- on-body performance, of PDE and PEM nodes, 306–308
- on-body propagation, *see* electromagnetic propagation
 - analytical for, 236–237
 - antennas for, 231–248
 - simplified analyses of, 236
 - with and without textiles, 241–244
 - theoretical analysis of, 235–241
- on-body radio channels, 447–468
- on-body sensor network, 263, 297–300
- on-body sensors/devices, 126–127, 231
 - antenna design and, 89
- on-body simulations, 54
- on-body wearable antennas, 77
- on-body wireless communication, 261
- on-body wireless links, 249
- on-site battery operated devices, 473–474
- on-skin performance, of epidermal tags, 330–332
- on-skin retuning, 332–335
- on-voxel analysis, 84

- open-ended coaxial probe, 212
- open voltages, normalized, 145
- operating frequencies, for RFID systems, 321
- operation tests, 369–370
- optimal impedance matching, 271–272
- optimal simulation strategy, 5–6
- output voltage, measuring, 369
- paralysis, care for, 160–161
- patch antenna array, 230
 - for human body, 225–227
 - microstrip, 228–230
 - proximity-coupled, 354–355
- patch antennas, 47–49, 223–230
 - aperture-coupled shorted, 305
 - dual-polarized, 288
 - microstrip, 222, 355
 - textile, 224
- patch head antenna, 199
 - aperture-coupled, 192–198
- patch radiators, 39, 43
- path gain, 243–246
- path loss, 173, 264
 - in simulated attenuation, 169–171
 - with through-body RF transmission, 176
- path loss measurement, for through-body RF transmission, 178–180
- pattern diversity, 288
- PDE calibration, 308–309. *See also* personal distributed exposimeter
- PEM modules, 307. *See also* personal exposimeters
- perfect electrical conductor (PEC), 142–143
- performance, *see* radiation performance
 - assessing antenna, 21, 47–55, 63
 - of CP filtennas, 41
 - of epidermal RFID dual-loop tag, 328–335
 - of PDE and PEM nodes, 306–308
 - propagation, 245–246
 - spectral, 455
 - of a three-person network, 302–304
 - of wearable applications, 47–55, 135–156
- permanent magnet–based power transfer, 476–477
- permittivity, *see* high permittivity periodic structure
- fluid, 361
- of human tissue, 138
- of membranes, 339–340
- personal distributed exposimeter (PDE), 305, 307–311, 313
 - node performance of, 306–308
 - wearable, 311
- personal exposimeters (PEMs), 305, 313
 - node performance of, 306–308
- person-to-person links, 303
- phantom composition, 215–216
- phantom electrical properties, 210
- phantoms, *see* human body phantoms
- phase switching divider (PSD), 414, 416–417
- photovoltaic cells, 479–480
- physiological body signals, from on-body radio channels, 447–468
- physiological detection, non-invasive, 449–466
- physiological information parameters, 449
- piezoelectric transducers (PZTs), 477
- PIFA antenna, wireless medical implantable devices and, 92–94. *See also* planar inverted-F antenna (PIFA) topology
- planar antennas, endfire radiation wearable, 84
- planar dipole external antenna, compact, 189–191
- planar fat-type folded dipole bio-tag, circuit model for, 119–121
- planar inverted-F antenna (PIFA) topology, 3. *See also* PIFA antenna
- planar inverted-F antennas, 28
- planar monopole antennas, 28, 30
- planar thin-type folded dipole, 120–121
- planar Yagi antenna surfaces, 69
- plane-wave approximation, 282–283
- plaster prototype, 345–346
- plaster sensor, 343
- PLL-based SOTA TX, 422–423
- PLL-based TX, 422–423
- PLLs (phase-locked loops), 396–399, 408–410, 424
- polarization, of transmitting and receiving antennas, 281
- polarization diversity, 288
- polarization mismatch, in simulated attenuation, 171–172

- polarization stirring, 12–13
- poly(ϵ -caprolactone) (PCL), 336–337
- polyaniline (PANI), 357–358
- polydimethylsiloxane (PDMS), 217
- polyester fleece, 4
- poly(methylmethacrylate) (PMMA), 361
- polyvinyl acetate (PVA), *see* PVA/XG membranes
- position stirring, 13–14
- power amplifier (PA), 247
- power amplifier stage, 416–418
- power density, measured, 310–311
- power-efficient communication systems, 312–313
- powering, of implants and wearable systems, 472–481
- power reflection coefficient, 217–218
- power sources, non-regenerative, 472–478
- power spectrum/spectral density (PSD), 454, 456, 464
- power transfer technology, wireless, 105–110, 471–488
- power transmission
 - defined, 141
 - maximum, 141
- power transmission coefficient, 322
- power transmission efficiency, 140–143, 146
- prediction models, 312–313
- primate demonstrations, for head antennas, 199–201
- printed circuit board (PCB) layout, 296
- propagation channel response, 282
- propagation distance, 173
- proper polarizations, of dual-mode antenna, 153
- prosthetic devices, 472
 - neuromotor, 161
- prototype operation tests, 369–370
- proximity-coupled patch antenna array, 354–355
- pseudo-lattice network, FBAR-based, 428–430
- pulse amplitude modulation (PAM), 464
- pulse-based radio technologies, 464–465
- pulse position modulation (PPM), 464
- pure copper polyester taffeta fabric (PCPTF), 3–4
- PVA/XG membranes, 338
- Q (filter quality), 429–433
- Q-enhancement LNA (low noise amplifier), 389, 391, 394
- quadrature amplitude modulation (QAM), 247
- quadrature phase-shift keying (QPSK), 268, 275, 291, 293
- quadrature sub-sampling mixer, 437–440
- radiating PIFA antenna, wireless medical implantable devices and, 92–94. *See also* planar inverted-F antenna (PIFA) topology
- radiation, body-absorbed, 72, 74
- radiation characteristics, of implant antennas, 174
- radiation efficiency (η_{rad}), 14–15, 325, 327–328, 347
- radiation mechanism, of
 - metasurface-enabled compact wearable antennas, 31–34
- radiation pattern measurements, 81–83, 124
- radiation patterns, 50–51, 53–55, 71–72, 74–76, 155–156, 194, 196–197, 226–227, 246, 284–285, 288, 308–309
- radiation performance
 - of epidermal antennas, 322–328
 - skin spacing *vs.*, 327–328
 - trace conductivity *vs.*, 326–327
- radiation polar plots, 70–72
 - normalized, 74, 76–79, 81–82
- radio channels
 - on-body, 447–468
 - waist-to-chest, 452
- radio frequency identification (RFID), 89, 92–93, 110–114, 320. *See also* RFID
- radiofrequency (RF) transmissions, in
 - through-body communications, 159–201
- radio frequency transceivers, 488
- radio propagation channels, indoor
 - off-body, 264–265
- radio propagation characteristics, impact of motion on, 452
- radios, WBAN systems and, 407–408. *See also* conventional radios; ULP radios

- ray tracer, electromagnetic, 282–283
- ray tracing, 263, 280, 282–283
- read range measurements, 124–125
- realized gain, 344
- real-world measurements, of PDE and PEM nodes, 310–311
- receive diversity signal processing techniques, 266
- received open voltages, 140–143, 147
 - normalized, 145
- received signals, 286–287
- received signal strength (RSS), 452, 454.
 - See also* RSS measurements
- received signal strength–based methods, 451–457
- received voltage, 151
- receiver architecture, 424–442. *See also* RX antenna radiation pattern
- receiver circuits, 365
- receiver coil, 106–109
- receiver design, 364–365
- receiver measurement results, 440–442
- receivers, filtering in, 441–442. *See also*
 - FBAR-based RX; RX antenna radiation pattern
- receive/transmit diversity, 262
- receiving antennas, 281
- receiving coils, 129
- receiving power level, measured, 166–168
- reference levels (RLs), 220–221
- reference measurements, 13–14
 - in RF transmission characterization, 163–164
- reflection, 283
- reflection coefficients, 15, 18–19
- reflector surfaces, 69
- regenerative energy harvesting devices, 478–481
- remote monitoring, 448
 - antenna design and, 89–90
- residual sum of squares (RSS), 243
- resonators, microwave, 361. *See also* bulk acoustic wave (BAW) resonators; MEMS (MEM) resonators; solidly mounted resonators; split ring resonator; stripline open-loop resonators; thin-film bulk acoustic resonators; T-resonator method
- retinal prosthesis, 485–487
- retuning
 - frequency, 334
 - on-skin, 332–335
- return loss, 70, 73
- return loss graph, 77–78, 80–81
- return loss measurements, 80–81
- reverberation chamber (RC), 11–12, 15
 - measurement parameters for, 13
- RF-based techniques, 450. *See also* radio frequency
 - RF-DC conversion circuits, 366, 368
 - RF-DC conversion efficiency, 368–370
 - RF front end, FBAR-based, 428–437
 - RFID bio-capsule tag, 114. *See also* radio frequency identification
 - RFID bio-tags, 118–119, 124–125, 130
 - RFID capsule antenna design, 113
 - RFID dual-loop tag, performance of epidermal, 328–335
 - RFID epidermal tags, sensing applications of, 341–346
 - RFID pill tags, 111–112
 - RFID plaster, 345–346
 - RFID sensors, in epidermal RF thermometer, 341–342
 - RFID smart-plasters, 348
 - RFID systems, operating frequencies for, 321
 - RFID tag antennas, 97, 474
 - conformal, 118
 - far-field, 117–118
 - for patient monitoring, 117–125
 - RFID tag design, wireless medical implantable devices and, 92–93
 - RFID technology, 321–322
 - RF sources, for wireless energy harvesting, 364
 - RF technologies, non-invasive, 448–449
 - RF transmission characterization, 162–168.
 - See also* through-body RF transmission
 - RHCP (right-hand circularly polarized) radiation patterns, 50–51, 53–54
 - ring resonance, 339–340
 - robotic platforms, 201
 - RSS measurements, 454, 457. *See also* received signal strength
 - RX antenna radiation pattern, 285–286, 294. *See also* receiver

- SAR computation, 102–103. *See also*
 - specific absorption rate
- SAR level, 84
- SAR measurements, 16
- SAR measurement setup, 227
- SAR simulations, 15–16
- SAR values, 17, 48–49, 55, 62, 74–77, 103, 304
- scaffold membranes, 336–337
- scalar channel, 285
- scalar channel response, 282–284, 286
- selection combining (SC) technique, 266
- self-impedance, 141
- semi-solid phantoms, 208–210
- semi-solid skin-equivalent phantom, 215–217
- sensing applications, of RFID epidermal tags, 341–346
- sensing and tracking, epidermal antennas for, 319–348
- sensing/monitoring systems, 130
- sensor calibration, 341–342
- sensor devices, 61
- sensor measurements, 300–301
- sensor networks
 - on-body, 297–300
 - wearable distributed, 295–304
- sensor node designs, compact, 389–400
- sensor nodes
 - crystal-less, 379–381
 - wireless, 453
- sensor node transceivers
 - implantable, 389–394
 - wearable, 395–400
- sensor positions, 231
- sensors, *see* flip-chip CW radar sensor
 - applications of, 351–371
 - carbon nanomaterial-based, 358–360
 - conductive polymer-based, 357–358
 - epidermal antennas as, 327
 - inkjet-printed, 356–357
 - on-body, 126–127, 231, 447–468
 - plaster, 343
 - wearable, 447
 - wireless, 457, 487–488
- series inductors, 109
- shadowing, 264–265, 273
 - separation from fading, 274
- shadowing parameter extraction, 276–278
- shift keying modulation, 296
- Sigma-Delta modulator (SDM), 408
- signal generator, 163
- signal processing techniques, 286–287
 - in diversity/MIMO systems, 266–269
- signal-to-noise ratio (SNR), 262, 266, 268–269, 280, 293–295
- signal variation phenomena, 264–265
- simulated attenuation, 167–173
- simulation models, 155
 - Matlab, 283–289
- simulation results, 287–289
- simulation strategies, optimal, 5–6. *See also*
 - co-simulations
- simulation tools, 280
- simulator categorization, 5–6
- single-input single-output (SISO) channels, 267, 276–278
- single-layered AMC, 65–67. *See also*
 - artificial magnetic conductor
- skin dielectric properties, 213
- skin electronics, 319
 - research on, 347
- Skin-equivalent phantoms, 225–226, 229–230
 - numerical, 213–215
 - semi-solid, 215–217
 - solid, 217–218
- skin models
 - cylindrical, 239–240
 - flat, 237–239
 - textile materials in, 240–244
- skin spacing, radiation performance vs., 327–328
- sleeve monopole antennas, wideband
 - external, 191–193
- slope diffraction, 33–34
- SMA connector, 4
- small-scale fading, 264–265
- smart devices, 447
- smart diagnostic capsule system, 128
- smart electronic systems, 272
- smart fabrics and interactive textiles (SFIT), 270
- smart-plasters
 - RFID, 348
 - for wound healing, 342–346
- smart shirt, 206
- smart skins, applications of, 351–371

- smart textiles, 261
- software, embedded, 296
- solidly mounted resonators (SMR), 411–412
- solid phantoms, 210–211
- solid skin-equivalent phantom, 217–218
- SOTA TX, 422–423
- space-time code (STC), 290–293, 295, 313
- space-time coding (STC) technique, 267
- spatial considerations, in exposure limits/guidelines, 221–222
- spatial modulation (SM), 273, 289–295, 313
- spatial multiplexing (SMX), 290–295, 313
- specific absorption rate (SAR), 28, 51–52, 196–198. *See also* SAR
 - antenna efficiency and, 74
 - link budget *vs.*, 101–105
- specific absorption rate evaluation, 15–18
- specific anthropomorphic mannequin (SAM), 16
- specific anthropomorphic mannequin phantom, 209. *See also* human body phantoms
- spectral-domain electric field, 240–241
- spectral performance, 455
- spectrum analyzer, 163–164
- split ring resonator (SRR), 361
- standard deviation, 276
 - of received open voltage, 147–149
- stirring sequences, 12–13
- stochastic models, 280
 - off-body, 273–279
- stripline BPF circuit, 45. *See also* bandpass filter
- stripline open-loop resonators (SOLRs), 37, 39–40, 42–43
- sub-sampling clock synthesis, 426–428
- surface wave antennas, 28
- surrounding environment, influences of, 142–143
- system implementation, of MBAN system, 400–401
- system integration, for wireless capsule endoscopy, 183–187
- systems, *see* adaptive antenna system; adaptive capsule system; adaptive systems; BAN communication systems; bio-telemetry systems; communication systems; diversity/MIMO systems; Doppler radar systems; electromagnetic (EM) sensing systems; exposimeter system design; frequency reconfigurable adaptive system; human vital data acquisition system; interface systems; MBAN system concept; medical compliance sensing systems; medical monitoring/sensing system; MEMS; non-invasive monitoring system; off-body communication system modeling; off-body communication systems; RFID systems; textile systems; ultra low powered (ULP) systems; wall-mounted ID tag system; WBAN systems; wearable systems; wireless communication systems; wireless implantable neuroprobe microsystems
 - body-centric, 233
 - capsule, 97–110, 128–129
 - capsule endoscope, 160, 162–187
 - MIMO, 312
 - smart electronic, 272
 - for wireless body area networks, 375–402
- tag antenna design, 112–114
- tag characterizations, on human body, 121–124
- tag layout, 329–330
- tag reading, 124
- tags, with RFID technology, 321–322
- tag tuning, 334
- technological advancements, antenna design and, 87
- technologies, future outlook of, 126–129
- telemedicine, antenna design and, 89
- telemetry applications, 129
- telemetry techniques, for implants or wearable systems, 471–488
- temperature considerations, in exposure limits/guidelines, 221
- temperature measurements, 341, 343
- temperature sensing mechanism, 341–342

- textile antennas, 227–230
 - for body area networks, 1–21
 - design strategies and evaluation for, 5–20
 - fabricated, 228–230
 - fabrication procedure for, 4–5
- textile materials, 2–5
 - in skin models, 240–244
- textile patch antennas, 224
- textiles, 3, 4, 222–223, 228
 - body-worn, 61–62
 - conductive, 2–3, 18
 - non-conductive, 3–4, 19–20
- textile substrates, 5
- textile systems, wearable, 261–262, 269
- theoretical phantoms, 207
- thermoelectric substrate, energy harvesting
 - from, 480–481
- thermometers, epidermal RF, 341–342
- thick dielectric materials, inkjet printing of, 353–354
- thin-film bulk acoustic resonators (FBAR), 411–413. *See also* FBAR
- thin-type planar folded dipole, 120–121
- 3D EM solvers, 280
- three-layered model, in antenna
 - performance, 195–196
- three-person networks, performance
 - analysis for, 302–304
- through-body communications, implanted
 - antennas and RF transmissions in, 159–201
- through-body RF transmission, 175–183
- through-body transmission measurement, 165
- time considerations, in exposure
 - limits/guidelines, 221
- tissue/body models, 96
- tissue-equivalent model, 207
- tissue model, 47–48
- tooth-attached RFID tags, 117
- total efficiency (η_{tot}), 15
- trace conductivity, radiation performance
 - vs., 326–327
- trace width, gain vs., 326
- tracking and sensing, epidermal antennas
 - for, 319–348
- transceivers
 - dual-band hub, 383–389
 - implantable sensor node, 389–394
 - for wearable devices, 247–248
 - wearable sensor node, 395–400
- transmission, 283. *See also* TX
- transmission efficiency, 140–143, 146
- transmission line matrix (TLM) method, 5
- transmission measurement, through-body, 165, 175–183
- transmission packets, 298, 300
- transmission schemes, 464
- transmit diversity signal processing
 - techniques, 267
- transmitter coil, 106–109. *See also* TX
- transmitter measurement results, 418–424
- transmitting antennas, 281
- T-resonator method, 69
- tuning networks, adaptive, 109–110
- tuning parameters, 114–115
- turn-on power, 344
- two-third muscle-equivalent phantom, 210
- TX antenna radiation pattern, 284–285, 291. *See also* transmission; transmitter
- TX architecture, FBAR-based, 413–414, 420–424
- TX operation, 420–424
- UHF (ultra-high frequency) bands, 135, 321–322
 - on-body antennas at, 117–125
- UHF RFID tag antennas, 97. *See also* Radio frequency identification
- UHF RFID tag design
 - for patient monitoring, 117–125
 - wireless medical implantable devices and, 92–93
- UHF RFID tags, performance of, 328–329
- ULP radios, 408–410
- ULP WBAN systems, 443. *See also* ultra low powered (ULP) systems; wireless body area networks
- ultra-high frequency, *see* UHF
- ultra low powered (ULP) systems, 408. *See also* ULP
- ultra low-power MEMS-based radios, for wireless body area networks, 405–443
- ultrasound-powered sources, 477–478

- ultra-wideband (UWB), 376
 - wireless medical implantable devices and, 94–95
- ultra-wide band (UWB) pulse-based radio technologies, 464–465
- uniform linear array (ULA), 291
- upper limb kinesthetic garment (ULKG), 231
- useful energy threshold (UET), 409
- VCO (voltage-controlled oscillator), 396.
 - See also* LC VCO
- vectorial channel responses, 282–285
- vector network analyzer (VNA), 6, 163
- vertical polarization, of dual-mode antenna, 153
- vital signs detection, 462
- voltage fluctuations, 147–149
- voxel model, 15, 17
 - antenna performances on, 72–76, 78
 - CST MWS, 84
- voxel phantoms, 207
- waist-to-chest radio channels, 452
- walking human body model, 146
- wall-mounted ID tag system, 149–152
- washing/drying cycles, 20
- water-proofing, 20
- WBAN requirements, 406–407. *See also*
 - wireless body area networks
- WBAN systems, 406. *See also* ULP WBAN systems
 - conventional radios and, 407–408
- wearable active antenna modules, for
 - energy-efficient off-body communication systems, 261–313
- wearable antennas, 2–3
 - active, 262, 269–273
 - AMC-backed flexible near-endfire, 61–84
 - applications for, 295–311
 - configurations for, 28
 - conformal, 29
 - metasurface-enabled compact, 29–37
 - mounted on the human body, 136–142
 - for off-body communications, 27–55
 - on-body, 77
 - performance characteristics of, 135–156
 - requirements for, 233
 - wireless energy harvesting for, 364
- wearable antenna technologies, 249
- wearable applications, performance of, 47–55, 135–156
- wearable devices, 205–207
 - transceivers for, 247–248
- wearable distributed sensor networks, 295–304
- wearable electronics, 472
- wearable end-fire antenna, 245–246
- wearable filtering antennas,
 - microwave-circuit-integrated, 37–46
- wearable harvesting receiver, 367–368
- wearable node design, 296
- wearable PDE, 311. *See also* personal distributed exposimeter
- wearable planar antennas, endfire radiation, 84
- wearable sensor node transceiver, 395–400
- wearable sensors, 447
 - wireless, 231
- wearable systems, telemetry techniques for, 471–488
- wearable textile systems, 261–262, 269
- wearable wireless body sensor network, 299, 303–304
- wearable wireless devices, 159
- whole-body resonance, 220–221
- wideband CP filtering antenna, 46
- wideband CP filtering antenna, assessing performance of, 52–55
- wideband CP filtering antenna synthesis, 41–46
- wide band pulsed radar method, 464–466
- wideband sleeve monopole external antenna, 191–193
- Wi-Fi band, wireless medical implantable devices and, 92–94
- windowing, 454–455
- wireless body area networks (WBANs).
 - See also* WBAN
 - circuits and systems for, 375–402
- wireless body area network technology, 61–62
 - ultra low-power MEMS-based radios in, 405–443
- wireless body sensor networks, wearable, 299, 303–304

- wireless brain-machine interface system, 127–128
- wireless capsule, for wireless capsule endoscopy, 186
- wireless capsule endoscopy, antennas for, 162–187
- wireless capsule endoscopy diagnostics, 97–103
- wireless channels, in off-body stochastic modeling, 273–274
- wireless communication
 - for implantable devices, 161
 - off-body, 261–262
 - on-body, 261
- wireless communication systems,
 - body-centric, 126, 135–136, 312
- wireless data telemetry applications, 129
- wireless devices, 451–452
 - wearable, 159
- wireless diagnostic capsules, 128
- wireless energy harvesting, for wearable antennas, 364
- wireless implantable neuroprobe
 - microsystems, motor prosthesis for, 187–201
- wireless links, on-body, 249
- wirelessly-powered devices, 474–477
- wirelessly-powered sensors, applications of, 351–371
- wireless medical implantable devices,
 - antenna design for, 91–95
- wireless medical telemetry services (WMTS) band
 - wireless capsule endoscopy and, 97–103
 - wireless medical implantable devices and, 94
- wireless network topology, 456
- wireless off-body communications, 312
- wireless power, 485–487
- wireless power transfer (WPT), 472
- wireless power transfer systems, 474–478
- wireless power transfer technology,
 - 105–110, 471–488
- wireless sensor nodes, 296–297, 453
- wireless sensors, 457, 487–488
- wireless technology, antenna design and, 89
- wireless wearable sensors, 231
- woodpile EBG-based antennas, 234–235.
 - See also* electromagnetic band gap
- wound healing, smart-plaster for, 342–346
- wound treatment, 338
- xyloglucan (XG), *see* PVA/XG membranes
- Yagi antennas, 63, 84
 - AMC-backed, 64–65
 - bidirectional, 65
 - endfire gain of, 70–71
 - measurements of, 79–84
 - near-endfire, 65–68
 - performance under bending
 - deformation, 76–79
 - performances on voxel model, 72–74, 78
 - radiation patterns of, 71–72, 74–76
 - return loss of, 70
- Yagi antenna surfaces, planar, 69
- Yagi radiator, 66, 68, 79
- Yagi-Uda antennas, for on-body communications, 233–234