Index

A

Accelerometer, 226–230
AGC, 176
Amplifier, 40–44, 54–56, 154–169, 239
  Bi-MOS, 188
  bootstrap, 159
  direct, DC 51
  discrete, 160–162, 166
  feedback, 44, 55, 164, 205
  FET input, 166
  headroom, 219
  high-Z, 41, 54, 154–162, 204, 244
  high-Z, guarded, 155
  input resistance, 155
  inverting, 204
  low-Z, 40, 55, 63, 162–164
  MOS, 189
  noise, 167–169
  operational, 169
  rise time, 159
  saturation, 76
  slew rate, 160
  stray capacitance, 156
  T configuration, 164
  transient response, 157
Amplitude sensitivity, 108
Analog Devices, 226
Applications
  accelerometer, 226, 281
  clinometer, 145–146, 265–270
  communications, 5
  computer graphic input, 5
  electret microphone, 221
  keypad, 135–138
  liquid level sense, 140–144
  measurement, 4, 243–249
  micrometer, 45, 61–65
  motion detect, 45
  motion detect, *x-y*, 45
  motion sense, 83–104, 124–129
  motor commutator, 129–131
  pressure sensor, 122–124, 279–281
  proximity detector, 37, 45, 66–82, 236–242
  six-axis transducer, 144–145
  spacing measurement, 139
  StudSensor, 231
  switches, 4
  touch switch, 134
  touchpad, 138–139
  water/oil mixture probe, 131–134
Area variation, 39

B

Bandpass filter, 50, 60
BiCMOS, 180, 228
Bridge, 52, 63
Brushless motors, 129

C

Capacitance, 13
  analytical solutions, 20
  approximate solutions, 24

Capacitance (*continued*)
bridge, 39
cocylindrical plates, 23
concentric cylinders, 15
coplanar plates, 22
coplanar plates with shield, 23
cylinder and plane, 16
measuring, 49
multielectrode capacitors, 17
overlapped plates, 21
parallel cylinders, 15
parallel plates, 14, 48
reference capacitors, 17
single plate, 37
sketching field lines, 24
small gaps, 20
two cylinders and plane, 16
two strips and plane, 16
Capacitance bridge, 57
Capacitor dielectrics, 147–152
Capacitor measurement, 152
Capacitor models, 152
Carrier, 171–173, 219
frequency, 171
sine wave, 172
square wave, 173
Carrier; see also Excitation
Charge coupled device, 178
Charge images, 12
Charge injection, 188, 192–194
Charges, 7
Circuit
bandpass filter, 60, 240
bridge, 52, 57
capacitance bridge, 57
capacitance measurement, 49
limit switch, 80
lowpass filter, 59
micrometer, 62–65
proximity detector, 75
single-ended, 57, 58
synchronous demodulator, 54, 187, 193–196
Clinometer, 145
CMOS ASIC, 247
Component accuracy, 179
Conductive films, 115
Convolution, 92
2-D, 93, 97–98
integral, 92
inverse, 94, 94–97
Coulomb, 7
Crossover resistance, 167
Crosstalk, 31, 198, 219
Current noise, 167

D

DC restoration, 56
Debounce, 110, 110–112
Demodulator, 173–176, 193–196, 240, 246
180° drive, 173, 228, 244
90° drive, 175
Dielectric absorption, 148
Dielectric constant, 70, 283–291
Dielectric constant of air, 73
Dielectric models, 147
Dielectric substrate, 118
Digital signal processing, 177–178
Displacement current, 9
Dissipation factor, 148
Doppler, 128

E

Earth ground, 71
Edge effects, 61
Electret, 221–225
Electric, 8
Electric potential sensor, 87
Electrode configuration, 45
Electrostatic force, 62, 230
Electrostatics ,6–36
Encoder
absolute, 83
incremental, 83
optical stripe, 84
Equipotential surfaces, 24
ESD, 136, 138, 217
Excess charge, 149
Excess noise, 198, 199, 200
Excitation, 58, 219
pseudorandom carrier, 77
Excitation; see also Carrier

F

FET noise, 200
Field lines, 74
Finite element analysis, 27
Fringe, 29

G

Gage factor, 65, 241
Gauss, 10
Ghost keys, 137
Ground, 72, 209
ideal ground, 209
Guard, 42, 44, 52, 54, 56, 64, 101, 102, 214
Guard, bulk leakage, 215
Guard, surface leakage, 215

H

Hall effect, 68, 130
Heerens, 11, 20, 21, 22, 43, 127, 133
Humidity, 213, 217

I

IEEE Trans. on Dielectrics and Electrical Insulation, 147
Induced charge, 11
Inductive sensors, 67
Insulation resistance, 150
Integration, 2
Invar, 212

J

Jones and Richards, 61

K

Kelvin, 12
Keypad, 135

L

L. S. Starrett, 243
Laplace's equation, 10
Leakage, 214
Levelite Store, 140
Limit switch, 78, 78–82
Limiting displacement, 205
Linear encoder, 108
Linearity, 48, 53, 62, 91
Liquid level sense, 140–144
  conductive liquids, 141
  dielectric liquids, 140
Liquid level switch, 143
Loss tangent, 148, 150
Low-Z amplifier; see Amplifier
LVDT, 84

M

Magnetic sensors, 68
Market, 1
Maxwell's capacitor, 13
Metal-filled paint, 117
Micrometer, 45, 61–65
  limiting resolution, 62, 205
Micrometers, 61
Microphone, electret, 221
Miller capacitance, 224
MOS vs. bipolar, 179
Motion detect
  spacing variation, 61
Motion detect, *x-y*, 45
Motion sense, 38, 83–104
  area variation, 49
  linearity, 39
  moving shield, 40
  multiplate, 127, 244
  plate geometry, 99–101
  six axis, 144–145
  spacing change, 100
  spacing variation, 49
  vernier caliper, 243–249
Motion sense, *x-y*, 138–139
Motor commutator, 129
Moving shield, 34
Multiple plate systems, 105–121

N

NAMUR, 67
Neutralizing, 102–103
Neutralizing capacitor, 102
Noise, 46, 50, 76, 87, 197–211
  circuit, 168
  current, 167
  FET, 222–223
  high-Z amplifier, 204
  low-Z amplifier, 204
  proximity detector, 241
  thermal, 168
  transformer, 206
  transistor, 200–204
Noise resistance, 167
Noise, transistor, 202

O

Optical encoder, 109
Optical sensors, 68
Oscillator, 49, 51
  gated, 75
  LC, 51
  RC, 52

P

Parallel plates, 38, 61
Parasitic capacitance, 132, 133
Paschen's threshold, 217, 221
Phase detector, 76
Photopot, 85
Piezoresistive, 122, 228
Plastic plating, 117
Plate counting, 109
Poisson, 24
Poisson's equation, 10
Popcorn noise, 198
Position transducer, 86
Potentiometer, 85

Power factor, 148
Precision, 46–47
Pressure sensor, 122–124, 193
  silicon, 123
Pressure sensors
  absolute, 123
  differential, 122
  linearity, 124
Printed circuit board, 113–115, 244
  photoplot, 113
Proximity, 35, 37, 45
Proximity detector, 66–82, 236–242
  limit switch, 78
  limiting resolution, 72
  noise, 241
  target, 75
Pseudorandom number, 77
Puers, R., 279

Q

Quadrature, 110
Quadrature encoder, 109

R

Rectangular to polar conversion, 98
Resistive thick films, 116
Resistive thin films, 116
Resistor, 171
  high value, 171
Resistor noise, 199
Resolvers, 84
Ripple torque, 129
Rotary encoder, 106–108
  angle demodulation, 107
Rotary motion, 40
Rotary transducer, 89

S

Sampling, 181
Schering bridge, 153
Sensor, 3
Sensor bus
  Fieldbus, 3
  TC-9 committee, 3
Shield, 42, 54, 64, 76, 87, 101, 164, 207
Shot noise, 197, 200
Shunt resistance, 50, 81
Silicon
  accelerometer, 226–230
  crosstalk, 219
  pressure sensor, 123–124
Skin depth, 207
Spacing measurement, 139
Spacing variation, 38
Stability, 46, 211–213
Static charge, 219
Static discharge, 217
Stray capacitance, 44, 50, 55, 62, 87, 99, 101
Stray fields, 75
StudSensor, 231–234
Superposition, 11, 18
Surface micromachining, 226
Switched capacitor circuits, 177–196
  accuracy, 191
  balanced demodulator, 193
  components, 188
  demodulator, 187
  filter, 178, 182–185
  instrumentation ampilfier, 186
  integrator, 185
  operational amplifier, 189
Symbios/Scriptel, 138
Synaptics, 138
Synchronous demodulator, 54, 76

T

Teledeltos paper, 25
Thermal noise, 168, 197, 199
Thick films, 115
Thin films, 115
Three-phase drive, 113
Tilt, 88
Tiltmeter, 146
Tin oxide, 117
Touch switch, 134
Touchpad, 138
Transistor noise, 202
Turck, 70

U

Ultrasonic sensors, 68
Units, 7

V

Vernier caliper, 243–249
Von Hippel, 147, 148, 151, 283–291

W

Water, 151
Water/oil probe, 129
Westerlund, 150
Wheatstone bridge, 57
Wireless coupling, 103, 165