

# Index

*Note:* Page numbers followed by *f* indicate figures and *t* indicate tables.

## A

Acid-processing method, 25–26  
Adhesive bonding, 145  
ArmorLite™, 7  
As-spun fibers, 23–25  
Asymmetric supercapacitor, 70  
Atlas weave, 90, 91*f*  
Autocatalytic plating process, 37  
Automated grabbing systems, 148

## B

Bandgap energy, 157  
Base-processing method, 25  
Bedford cord, 11  
Body-worn textile antenna, 225–227  
Bulk CPYs  
    conductive fillers, 32–36  
    hybrid polymer–metal yarns, 27–30  
    ICPs, 22, 23–27

## C

Capacitance sensors, 85  
Carbon FRP (CFRP) layers, 150  
Carbon nanotubes (CNTs), 55  
    piezocomposites, 179  
    yarns (*see* CNT yarn)  
Catalogue classification, textile-based  
    sensors  
        access characteristics, 84*f*  
        benefits and conveniences, 82  
        classification and structure, 82–83  
        references, 81*f*, 83  
        solutions, 83, 84*f*  
        usability, 83–84  
Cellular communications, 225–227  
Chainsaw protection trousers, 149  
Chain-stitch embroidery (Ari), 91–93,  
    138, 138*f*  
Chemical polymerization, 44

CNT/CB coatings, 36–37  
CNT synthesis, 55–56  
CNT yarn  
    core-spun yarn, 59–60  
    electrical conductivity, 63–64  
    flyer spinning, 57–58  
    rub densification, 59  
    sensors, 65  
    structures and formation, 61–62  
    supercapacitors, 66–70  
    tensile properties, 62  
    textiles, 64–65  
    up-spinning, 58–59

Commonwealth Scientific and Industrial  
    Research Organisation (CSIRO),  
    57–58

Conductive fibres  
    carbon nanotubes, 12–13  
    in extrusion, 13  
    future aspects, 14–15  
    metal fibres, 5  
    metallized fibres, 9–10  
    plastic strips, 10–11  
    polyaniline (PANI), 11  
    substrates and conductive  
        elements, 6–7

Conductive fibre applications  
    biomedical sensors, 13  
    e-broidery, 13  
    embroidery, 13  
    fabric electrodes, 13  
    piezoelectric fibre, 13  
    PPy-coated Lycra, 13  
    steel threads, 13  
    transducers, 13

Conductive fibre developments, 6  
    in eighteenth century, 4  
    in nineteenth century, 5  
    in twentieth century, 5  
Conductive joints types, 146*f*

- Conductive polymer yarns (CPYs)  
 bulk, 23–36  
 chemical polymerization, 44  
 dipping-and-drying technique, 44  
 electrospinning technique, 42–43  
 fiber drawing technique, 43–44  
 melt spinning technique, 41–42  
 surface, 36–40
- Conductive textiles, 202–203, 203*f*  
 embroidery process, 204–205  
 losses, 207–211  
 polymer substrates, 205–207  
 radio frequency losses, 207–211  
 threads, 203
- Cross-polarized radiation, 224–225
- D**
- DARPA (Defence Advanced Research Projects Agency) funding, 246
- Dipping-and-drying technique, 44
- Distributed fibre optic sensors  
 intrinsic, 283–285  
 quasi, 285
- Dodecylbenzenesulfonic acid (DBSA), 35
- Double lock stitch, 94, 95*f*, 139*f*.  
*See also* Standard embroidery technique
- Drawability of CNT forests, 56–57
- 2D weaving  
 atlas weave, 90, 91*f*  
 plain weave, 89–90, 91*f*  
 stages, 89*f*  
 warp and weft yarns, 89, 90*f*
- Dye-sensitised solar cells (DSSCs), 160
- E**
- ECG/EMG monitoring systems, 259–260
- E-fiber textile surface, 214–216
- Electrical conductivity, 63–64
- Electrocardiogram (ECG), 258, 259–260
- Electromyogram (EMG), 258, 259–260
- Electronically active textiles (EATs), 110
- Electronically functional yarn (EFY),  
 112, 115*f*
- Electrospinning technique, 42–43, 180
- Embroidered textile antennas  
 conductive textiles, 202–203, 203*f*,  
 204–205  
 losses, 208–211  
 textile microstrip lines, 207–208  
 conformal applications, 227  
 future aspects, 234–236  
 GSM/PCS/WLAN communications,  
 221–227  
 insertion loss  
 E-fiber textile surface, 214–216  
 fiber density, 213–214  
 stitching density, 211–213  
 polymer substrates, 205–207  
 RF performance  
 textile antenna array, 216–219  
 textile patch antenna, 216  
 RF textile sensor, 228–230  
 threads, 203  
 tire tracking applications, 230–233  
 UHF communications, 219–221  
 wearable RF electronics, 201–202, 202*f*
- Embroidery  
 advantages, 141  
 chain-stitch embroidery (Ari), 91–93,  
 138, 138*f*  
 embroidery hoop dimensions, 142  
 joining technology, 140–141  
 kinds, 90–91  
 manufacturing of, 139–140  
 moss embroidery principle, 91–93, 92*f*  
 paths and circuit board (PCB), 144, 144*f*  
 standard embroidery technique, 93–94,  
 95*f*, 138, 139*f*  
 tailored fibre placement (TFP),  
 94–95, 139  
 technical challenges, 142–144  
 tubular embroidery machine, 92*f*, 143*f*
- Embroidery hoop dimensions, 142
- Emeraldine base (EB), 23
- Encapsulated Chip Area (ECA), 112
- Encapsulation technique  
 resin impregnated ECA process,  
 113–115  
 side-by-side thermal bonding  
 process, 113
- Environmental sensing, military textiles,  
 240–242  
 early warning systems, 245  
 health monitoring, 242–245
- Epoxy-based conductive adhesives, 146
- E-Thread<sup>r</sup>, 110–111

**F**

FabRoc<sup>®</sup> yarn, 12, 121–123  
 Ferroelectric materials, 173  
 Fiber density, 213–214  
 Fiber drawing technique, 43–44  
 Fibre Bragg gratings (FBGs) sensors, 286–287  
 Fibre-coated sensors, 102–103  
 Fibre electronics technology, 109, 111–115  
 Fibre-reinforced polymers (FRPs), 288  
 Fibres, textile-based sensors, 78  
 Flyer spinning, 57–58

**G**

Geotechnical and civil engineering  
   extrinsic optical fibre sensors, 281–282  
   fibre Bragg gratings sensors, 286–287  
   field trials and on-site tests  
     of railroad, Chemnitz (Germany), 294  
     of slope failure, Zimmersrode (Germany), 295–297  
     slope stability, Belchatow (Poland), 294–295  
   geotextiles, 280, 281*f*  
   intensity-based fibre optical sensors, 282  
   intrinsic distributed fibre optic sensors, 281–282, 283–285  
   non-crimp fabrics, 276–277  
   phase-modulated fibre optical sensors, 282  
   polarisation-modulated fibre optical sensors, 283  
   polymer optical fibre sensors, 285–286  
   retrofit strategy  
     full-coverage strategies, 276–277  
     reinforcing strips, 276–277  
   seismic reinforcement, masonry buildings at Eucentre (Italy), 291–292  
   at IIT (India), 293–294  
   sensing capability, 281  
   wavelength-modulated fibre optical sensors, 283  
   standardisation needs, 297–299  
 Glass FRP (GFRP) layers, 150  
 Global System for Mobile Communications (GSM), 221–223  
 Glueing, 148  
 GSM/PCS/WLAN communications  
   cellular communications, 225–227

  cross-polarized radiation, 224–225  
   multiband antenna design, 221–223  
   radiation pattern, 224  
   resonance frequency, detuning, 224

**H**

Heating theory, 119–120  
 Health monitoring  
   electrophysiological signals, 243–244  
   Sensatext, 244  
   SmartLife Technology, 244  
   sweat sensors, 244, 244*f*  
   weaving and knitting processes, 245  
 Humidity and moisture monitoring,  
   textile-based sensors, 96–100  
 Hybrid polymer–metal yarns  
   fiber drawing techniques, 30–31  
   metal-core yarns, 27–30, 27*f*, 28*t*  
   polymer-core yarns, 27*f*, 28*t*, 30  
   polymer–metal braided yarns, 27*f*, 28*t*, 30

**I**

ICP coatings, 37–38  
 Intelligent Knee Sleeve (IKS), 265–266, 266*f*  
 Intelligent Textiles, 173, 242–243, 242*f*  
   piezoelectric phenomenon  
     (see Piezoelectric energy)  
   PV (see Photovoltaic (PV) energy)  
 Intensity-based fibre optical sensors, 282  
 Intrinsically conductive polymers (ICPs), 33–36  
   PANI fibers, 23–26  
   PPy fibers, 26–27  
 IR-CNT yarn, 66–68  
 Isotropic conductive adhesive (ICA), 145, 147

**J**

Joining technology  
   adhesive bonding, 145  
   automated grabbing systems, 148  
   carbon FRP (CFRP) layers, 150  
   chainsaw protection trousers, 149  
   conductive joints types, 146*f*  
   continuous manufacturing, 135  
   conventional textiles, 134–135

## Joining technology (*Continued*)

- embroidery, 138–139.  
(*see also* Embroidery)
- epoxy-based conductive adhesives, 146
- glass FRP (GFRP) layers, 150
- glueing, 148
- isotropic conductive adhesive (ICA),  
145, 147
- LEDs, automated attachment, 136*f*
- non-conductive adhesive (NCA) bonding  
solutions, 135, 145–146
- positioning, 134*f*
- SensFloor<sup>®</sup> system modules, 137*f*
- standard adhesive application method, 148
- strategies and automatic approaches,  
145–148
- by textile processing, 137–144
- textile ribbon cables and connexion  
elements, 136*f*

## K

Knitting process, 123–125

## L

- LifeShirt<sup>®</sup>, 260, 263–264, 264*f*
- Light-emitting diode (LED), 11  
automated attachment, 136*f*
- Low-density polyethylene (LDPE), 31

## M

- Medical uses, piezoelectric energy, 190–191
- Melt spinning technique, 41–42
- Metal-based textile heaters, 118, 119*f*,  
120–121
- Metallic coatings, 36–37
- miCoach<sup>™</sup>, 266–267, 267*f*
- Military textiles, 240<sup>r</sup>
  - armoured vehicles, 248–249
  - camouflage uniforms, 247
  - design difficulties, 249–250
  - energy scavenging devices, 251
  - early warning systems, 245
  - environmental sensing, 240–242
  - future aspects, 253–254
  - health monitoring, 242–245
  - information systems, 246
  - maintenance, 252–253
  - mobility, 252

- PCNs, 246
- position detection, 248
- sensors, 240–242, 241*t*
- tactile comfort, 252
- textile antennae, 246
- thermal comfort, 252
- thermal regulation, 247–248
- WAN systems, 246
- with wearable computer and keyboard,  
242–243, 242*f*
- Military wireless uses, piezoelectric energy,  
190–191
- Moss embroidery principle, 91–93, 92*f*
- Motion sensors
  - accelerometer, 261, 262*t*
  - strain sensors, 262, 263*f*
- Multiband antenna design, 221–223
- Multifunctional geotextiles (MFGs), 280, 281*f*

## N

- Nanofibres/yarns, piezo fibres
  - manufacturing technique, 180
- Nanowires, piezocomposites, 179
- N-methyl-2-pyrrolidone (NMP), 23
- N,N'-dimethylpropylene urea (DMPU), 23
- Non-conductive adhesive (NCA) bonding  
solutions, 135, 145–146
- Non-crimp fabrics
  - advantages, 277
  - biaxial structure, 277, 278*f*
  - characteristics, 276–277
  - embedded fibre optic sensors,  
277–280, 279*f*
  - mechanical properties, 276–277
  - quadriaxial hybrid fabric, 277, 278*f*
  - quality check, 280, 280*f*
  - SENTEX 8300, 277–280, 279*f*
  - triaxial structure, 277, 278*f*
- Nuclear, biological and chemical (NBC)  
attacks, 245

## O

- Optical time-domain reflectometry (OTDR)  
principle, 283–284, 285–286, 290

## P

- PANI fibers
  - acid-processing method, 25–26

- as-spun fibers, 23–25
  - base-processing method, 25
  - DBSA, 35
  - emeraldine base, 23
  - solution-spinning process, 23
  - wet-spinning method, 26
  - Paths and circuit board (PCB), 144, 144f
  - PEDOT:PSS, 159f, 161
  - Personal Communications Service (PCS), 221–223
  - Phase-modulated fibre optical sensors, 282
  - Phenyl-C61-butyric acid methyl ester (PCBM), 158–160, 159f
  - Photovoltaic (PV) energy
    - advantages and requirements, flexible substrates, 160–161
    - applications, 167–168
    - cells operation mechanism, 156–157
    - electrical conductive textiles, 165–166
    - fabrics manufacture, 166–167
    - solar textile fabrics construction, 161–163
    - technological specifications, 166
    - textiles requirements, 163–165
    - types, 157–160
  - Piezoceramic fibres manufacturing, 181
  - Piezocomposites
    - carbon nanotubes, 179
    - copolymers, 179
    - fibres manufacturing, 182–183
    - nanowires, 179
  - Piezoelectric energy
    - applications, 188–191
    - charge formation and poling, 175
    - direct and converse effects, 176
    - energy requirements, 188
    - history of, 174–175
    - human-powered wearable devices
      - feasibility, 188–189
    - manufacturing of, 179–188
    - materials in, 173
    - mechanical energy conversion, 176–178
    - medical and military wireless uses, 190–191
    - piezoceramics, 178, 181
    - piezocomposites, 178–179, 182–183
    - piezo fabrics, 180–181, 183–185
    - piezopolymers, 178, 182
    - principles, 175–176
    - wearable energy harvesting, fabrication
      - optimisation, 185–186
  - Piezoelectric sensor, 261
  - Piezo fabrics
    - electro-spinning, 180
    - energy harvesting testing, 187–188
    - fibres manufacturing, 180–181
    - melt spinning, 181
    - nanofibres/yarns, 180
    - types, manufacturing techniques, 183–185
    - wrapping/twisting, 180
  - Piezo fibres manufacturing technique, 181
  - Piezopolymers, 178
    - fibres manufacturing, 182
  - Piezoresistive sensors, 13, 260
  - Plain weave, 89–90, 91f
  - Polarisation-modulated fibre optical sensors, 283
  - Polyaniline (PANI), 11
  - Polyethylene terephthalate (PET) fibres, 164
  - Poly-3-hexyl thiophene (P3HT), 158–160, 159f
  - Polymer-based textile heaters, 118, 119f
    - conductive yarn, 126–127
    - design, 125–126
    - FabRoc yarn, 121–123
    - heated fabrics, 129–130
    - heated gloves, 129
    - knitting process, 123–125
    - power supply system, 127–128
    - processing techniques, 128
  - Polymer optical fibre (POF) sensors, 285–286
  - Polymer yarns, conductive fillers
    - CB-filled polymer yarns, 32–33
    - CNT-filled polymer yarns, 33, 34r
    - ICPs, 33–36
  - POLYTECT project, 287–291
  - PPy-coated Lycra, 13
  - Pressure-mapping systems, textile-based sensors, 100–102
  - Printed circuit board (PCB), 7, 110
  - Printed sensors, 103
  - Pseudocapacitance, 66–68
  - PVDF copolymers, 179
- R**
- Radiation pattern, 224
  - Radio frequency identification (RFID), 110–111, 201
  - References, 81f, 83

Resin impregnated ECA process  
 fibre bonding, 113*f*  
 light-emitting yarn, 115, 115*f*  
 micro-pod, 114  
 objectives, 113–114  
 polymer resin, 113  
 RFID chips, 114  
 temperature-sensing yarn, 115  
 Resonance frequency, detuning, 224  
 Respiratory inductive plethysmography (RIP), 260, 260*f*  
 Respiratory sensors  
 capacitive displacement sensors, 261  
 piezoelectric sensor, 261  
 piezoresistive sensor, 260  
 respiratory inductive plethysmography, 260, 260*f*  
 RFID devices, 14  
 Rub densification, 59

**S**

SensFloor<sup>r</sup> system modules, 137*f*  
 Sensor-based monitoring systems, 80*f*, 81  
 Sensors, 65  
 SENTEX 410, 289–290, 290*f*  
 Shieldex<sup>®</sup>, 9  
 Silver-coated Amberstrand<sup>®</sup> fibers, 203  
 Small electronic device (SEW), 265  
 Smart 7-step tool  
 data analysis and evaluation, 81  
 limit value, 81  
 material and energy flow, 79–80  
 performance test, connecting electronic components, 80–81  
 physical parameters and measuring technique, 80  
 requirements, 79  
 textile prototype manufacture, 80  
 Smart textiles  
 described, 75  
 intelligence for textiles hierarchy, 97*t*  
 Sozni stitch, 93  
 Standard adhesive application method, 148  
 Standard embroidery technique, 93–94, 95*f*, 138, 139*f*  
 Steaming, 128  
 Stitching density, 211–213

Supercapacitors  
 asymmetric, 70  
 core-spun yarn, 70  
 IR-CNT yarn, 66–68  
 as substrate, 68–69  
 Surface CPYs, 36–40  
 CNT/CB coatings, 36–37  
 ICPs coatings, 37–38  
 metallic coatings, 36–37  
 Surface mount devices (SMD), 111

## T

Tailored fibre placement (TFP), 94–95, 139  
 Temperature sensors, 86–89  
 TenCate GeoDetect<sup>®</sup> System, 290–291  
 Textile antenna array, 216–219  
 Textile-based sensors  
 applications, 95–102  
 capacitance sensors, 85  
 catalogue classification, 82–84  
 definition, 76  
 development of, methodical approach to, 78–84  
 2D weaving, 89–90  
 embroidering, 90–95  
 fibre(s), 78  
 fibre-coated sensors, 102–103  
 in humidity and moisture monitoring, 96–100  
 integration levels, 75, 76*f*  
 manufacturing technologies, 89–95  
 in pressure-mapping systems, 100–102  
 printed sensors, 103  
 production methods, 77*f*  
 smart 7-step tool, 79–81  
 structure levels, 77*f*  
 in supporting textile, 77*f*  
 temperature sensors, 86–89  
 two- or three-dimensional textiles, 78  
 types, 85–89  
 uses, 75  
 variations, 76–77  
 yarns, 78  
 Textile fabrics  
 fibre electronics technology, 109, 111–115  
 knitted structure, 109, 110*f*  
 state of the art, 110–111  
 woven structure, 109, 110*f*

Textile heating systems  
  future aspects, 130–131  
  heating theory, 119–120  
  metal-based, 118, 119*f*, 120–121  
  performance-driven functionality, 117  
  polymer-based, 118, 119*f*  
  warmth conditions, 117  
Textile microstrip lines, 207–208  
Textile patch antenna, 216  
Textile ribbon cables and connexion  
  elements, 136*f*  
Tire tracking applications, 230–233  
Transducers, 13  
Tubular embroidery machine, 92*f*, 143*f*  
Two- or three-dimensional textiles, 78

## U

UHF body-worn communications, 219–221  
Ultra-high frequency (UHF), 219

## W

Wavelength-modulated fibre optical  
  sensors, 283  
Wearable energy harvesting, fabrication  
  optimisation, 185–186  
Wearable health monitoring systems,  
  athletes

  advantage, 257  
  ECG/EMG monitoring sensors, 259–260  
  IKS, 265–266, 266*f*  
  implantable sensing technology, 268*f*,  
    268*t*, 269  
  LifeShirt<sup>®</sup>, 263–264, 264*f*  
  miCoach<sup>™</sup>, 266–267, 267*f*  
  motion sensors, 261–262  
  portable technologies, 268–269, 268*f*, 268*t*  
  respiratory sensors, 260–261  
  schematic structure, 257, 258*f*  
  sensor module product specifications, 258*t*  
  wearable sensor module, 268–269,  
    268*f*, 268*t*  
  WWS, 264–265, 265*f*  
Wearable Wellness System (WWS),  
  264–265, 265*f*  
Wet-spinning method, 26  
Wireless Local Area Network (WLAN),  
  221–223  
Wrapping/twisting, 180

## Y

Yarns  
  textile-based sensors, 78  
  warp and weft, 89, 90*f*