



US007075412B1

(12) **United States Patent**  
**Reynolds et al.**

(10) **Patent No.:** **US 7,075,412 B1**  
(45) **Date of Patent:** **Jul. 11, 2006**

(54) **METHODS AND APPARATUS FOR  
OPERATING A RADIO DEVICE**

(75) Inventors: **Matthew S. Reynolds**, Cambridge, MA (US); **Joseph L. Richards**, Cambridge, MA (US); **Sumukh N. Pathare**, Waltham, MA (US); **E. Rehmatulla Post**, Somerville, MA (US); **Yael G. Maguire**, Cambridge, MA (US); **Harry F. Tsai**, Cambridge, MA (US); **Ravikanth S. Pappu**, Cambridge, MA (US); **Bernd Schoner**, Cambridge, MA (US)

(73) Assignee: **Thingmagic L.L.C.**, Cambridge, MA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 459 days.

(21) Appl. No.: **10/448,053**

(22) Filed: **May 29, 2003**

**Related U.S. Application Data**

(60) Provisional application No. 60/384,539, filed on May 30, 2002.

(51) **Int. Cl.**  
**H04Q 5/22** (2006.01)

(52) **U.S. Cl.** ..... **340/10.2; 340/10.3; 340/10.31**

(58) **Field of Classification Search** ..... **340/10.2, 340/10.3, 10.31**

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,924,210	A *	5/1990	Matsui et al. ....	340/10.41
5,425,032	A *	6/1995	Shloss et al. ....	340/10.2
5,537,398	A *	7/1996	Siwiak ....	370/468
5,604,486	A *	2/1997	Lauro et al. ....	340/10.3
6,172,609	B1 *	1/2001	Lu et al. ....	340/10.4
6,509,828	B1 *	1/2003	Bolavage et al. ....	340/10.2
6,529,488	B1 *	3/2003	Urs et al. ....	370/345
6,617,962	B1 *	9/2003	Horwitz et al. ....	340/10.4
6,735,426	B1 *	5/2004	Pau ....	455/255
2003/0104848	A1 *	6/2003	Brideglall ....	455/574

\* cited by examiner

*Primary Examiner*—Brian Zimmerman


*Assistant Examiner*—Clara Yang

(74) *Attorney, Agent, or Firm*—Chapin Intellectual Property Law, LLC; Barry W. Chapin, Esq.; Paul P. Kriz, Esq.

(57) **ABSTRACT**

A radio device such as a wireless tag reader communicates with multiple types of wireless identification tags in a monitored region. The radio device includes a network interface to receive messages transmitted over a network. In response to receiving a message indicating to reconfigure the radio device to support an additional wireless tag protocol, the radio is reconfigured to support communications with a corresponding new type of wireless identification tag in a monitored region. Based on this technique of reconfiguring the radio device via network messages, the radio device optionally supports additional, new or latest versions of wireless tag protocols without having to physically reprogram or replace the radio device.

**45 Claims, 12 Drawing Sheets**






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

1

## METHODS AND APPARATUS FOR OPERATING A RADIO DEVICE

### RELATED APPLICATION

This application is related to and claims the benefit of earlier filed U.S. Provisional Patent Application Ser. No. 60/384,539 entitled "RECONFIGURABLE IDENTIFICATION AND TRACKING SYSTEM," filed on May 30, 2002, the entire teachings of which are incorporated herein by this reference.

### BACKGROUND OF THE INVENTION

Wireless tag readers are commonly used in industrial plants to identify and track manufactured items. In such applications, a wireless identification tag such as an RFID (Radio Frequency Identification) tag is affixed to a monitored item such as a single packaged product or a bin or pallet containing multiple manufactured items. Typically, the wireless tag stores relevant data pertaining to and identifying the item to which it is affixed. As the wireless tag passes near a wireless tag reader, the tag reader communicates with the wireless tag to retrieve information pertaining to the tag itself and the tagged item.

Some wireless tags are 'active' in the sense that they include an antenna and transmitter capable of initiating wireless communication with a tag reader. Some active wireless tags contain only a radio transmitter, while others include a radio receiver. The transmitter may generate its own signal, or it may "backscatter" modulate the reader's transmitted signal. Active wireless tags include a power source such as a battery to power their internal electronic circuitry and generate a wireless communication signal. Typically, because of this on board power source, active tags exhibit longer transmission range (called "read range") than the passive tags described below.

In comparison to active tags, 'passive' wireless tags do not contain a power source and therefore they cannot independently generate a wireless signal to communicate with a tag reader or process digital information on their own. Instead, these passive devices rely on receiving power from an interrogating signal generated by a tag reader to power their internal circuitry. In the presence of the interrogation (or 'powering') signal, the passive tag devices are able to power themselves, retrieve data stored in their memory, and communicate the retrieved data to the tag reader. The amount of power that passive tags are able to recover from the reader's signal is generally small, so passive tags generally exhibit shorter transmission range (reduced "read range") than active tags.

Certain passive tags include a resonant circuit or antenna tuned to a particular interrogation frequency of the tag reader. In such devices, the characteristics of the resonant circuit are altered via switching (e.g., switching a resistor, inductor, or capacitor in and out) to modulate a signal to a tag reader according to a stored data string associated with the tag. A modulated signal produced by switching is then re-radiated to the tag reader. The tag reader, in turn, processes the received data string associated with the tag to identify characteristics of the item or tag itself. In certain applications, the tags can store information received from the tag reader in a memory located on the tag.

In practice, tag readers are typically mounted at strategic locations in manufacturing and/or retail facilities to monitor a presence of wireless identification tags. Mounting tag readers at locations throughout a facility enables tracking

2

movement of wireless tags and, thus, corresponding tagged items. The number of tag readers employed in a facility depends to some extent on the characteristics of the facility, as well as the operating characteristics of the tags (e.g., whether the tag is an active or passive tag, as well as on the tag's operating frequency). Specifically, applicable government radio regulations, tag type, and the size, shape and number of rooms and floors in a building are factors to consider when installing a tag monitoring system.

### SUMMARY

Unfortunately, there are deficiencies associated with conventional techniques of monitoring wireless identification tags. For example, outfitting a facility with tag readers is typically expensive. In addition to the cost of the tag readers themselves, a purchaser must pay for the cost of labor to install the tag readers. Because conventional tag readers are typically designed to communicate with only one type of wireless tag (e.g., certain conventional tag readers are statically configured to support communication with tags via use of a single tag communication protocol), installation sometimes must include installing multiple types of tag readers if it is necessary to communicate with different types of wireless tags in a monitored region.

In addition to high installation costs and the cost of tag readers themselves, wireless tag protocols continuously evolve over time. For example, today's wireless tag protocols include, e.g., ISO 15693, ISO 18000, Intellitag, iCode I, Tagit, Auto-ID Center EPC protocol, EPC (Electronic Product Code). In certain cases, the communication protocols themselves change over time. Also, new wireless tag protocols (and corresponding types of tags) are constantly being developed over time. As a consequence of evolving and ever-changing wireless tag protocols, operators of wireless tag monitoring systems are faced with paying for replacement of old wireless tag readers with corresponding retrofits to communicate with new types of wireless tags.

It is an advancement in the art to provide a radio device that addresses these and other deficiencies associated with conventional wireless tag readers.

One aspect of the present invention involves providing a radio device such as a tag reader that communicates with multiple types of wireless identification tags in a monitored region. The radio device is reprogrammable to support communications with different types of tag protocols. For example, a radio device in accordance with embodiments of the invention is re-programmable to allow the radio device to be configured to communicate using a plurality of different wireless tag protocols.

To support reprogrammability, the radio device includes a network interface to receive messages transmitted over a communication network to which the present type of wireless tag reader is connected. In response to receiving a message indicating to reconfigure (e.g., reprogram) the radio device to support an additional updated or new protocol, the radio device (or, more specifically, an internal electronic circuit of the radio device such as a digital signal processor) is reconfigured, for example by means of a dynamic software download, to support communications with a corresponding type of wireless identification tag in a monitored region. Based on this technique of reconfiguring the radio device via network messages, the radio device supports additional, new or latest versions of wireless tag protocols without having to replace the radio device. In this way, a

source sending the (reconfiguration) message over the network updates the radio device so that it supports a new protocol.

Although the origin of the (reconfiguration) message transmitted over the network can vary, the source is optionally an electronic device that automatically updates each of multiple radio devices by sending appropriate messages over the network. This relaxes a burden otherwise placed on an administrator that updates the radio device to support new or updated protocols.

In this manner, a single re-programmable radio device provided in accordance with embodiments of the invention can be remotely reconfigured and re-programmed to continually evolve and support new or changing radio frequency tag identification protocols as such protocols come into existence or as existing protocols change to include new features such as additional types of communication messages. Since embodiments of the invention are remotely re-programmable, no manual visitation and/or human modifications to the radio device are required to allow the radio device such as a tag reader to communicate using new or updated versions of tag identification protocols. Once programmed to communicate with a required set of protocols for any of the different types of tags that are within radio range of the radio device, the radio device described herein can operate each of the multiple tag protocols in a concurrent manner to communicate with all "visible" tags in a monitored region.

In operation, to increase efficiency of monitoring wireless tags in a particular region, the radio device at least occasionally performs a query to determine each type of wireless identification tag present in the monitored region. For the identified types of wireless identification tags detected in the monitored region, the radio device schedules additional radio communications directed to only those types of wireless identification tags detected in the monitored region.

In the course of communicating with the different types of wireless communication tags, the radio device collects relevant information about the tags and stores the information in a database at the radio device. The database in the radio device is optionally part of an overall hierarchical database distributed over the network.

In one application, the radio device generates wireless signals over multiple carrier frequencies to communicate with the different types of wireless identification tags. To increase throughput (and if supported), the radio device can simultaneously generate wireless signals from the radio device at different carrier frequencies to communicate with at least two different types of wireless identification tags at the same time. Even though different carrier frequencies are used to transmit information to different wireless identification tags, the radio device optionally uses a common baseband to receive data information from responding wireless identification tags. Use of a common baseband to modulate data onto different carrier frequencies reduces circuit complexity because a common circuit can be used to recapture information in the baseband signals.

Another aspect of the present invention is directed towards a wireless transceiver device that communicates with multiple types of wireless identification tags in a monitored region based on use of a corresponding set of radio communication protocols. The wireless transceiver device includes a scheduler to schedule radio communications associated with the corresponding set multiple of radio communication protocols and an interleaver that interleaves portions of the scheduled radio communications associated with the set of radio communication protocols.

Interleaving portions of (logical) transactions associated with multiple protocols increases efficiency of scheduling radio communications to different types of wireless identification tags. Thus, the rate of monitoring a region for wireless identification tags can be increased. Additionally, breaking down the protocols into portions or work units supports more efficient collection of data information associated with the wireless identification tags in the monitored region because the radio communications can be scheduled in many more ways than simply scheduling one entire radio communication protocol transaction after the other. That is, embodiments of the invention avoid having to perform an entire sequence of all messages associated with a particular tag protocol before executing another tag protocol.

In particular, when programming a radio device to support multiple specific tag reading protocols, the radio device is programmed with knowledge of how each protocol can be logically broken down into work units, portions or sub-portions. A portion of a protocol or work unit generally represents a subset of messages such as a single transmission message (e.g., a message generated by a tag reader to the tags) and its corresponding reply (e.g., received back from tags) as a result of executing the protocol. In other words, a work unit is a component or subset of one or more messages that collectively form the tag communication (e.g., reading) protocol. Each individual message is generally a predetermined wireless transmission generated by the radio device over one or more specific radio frequencies to communicate with tags that "speak" that protocol. Breaking each tag communication protocol into portions or work units, the radio device can interleave, overlap or otherwise multiplex execution of different work units associated with different types of tag protocols over time such that the radio device can concurrently or simultaneously carry out communication with multiple of multiple types of wireless tags.

As an example, the radio device can be programmed, as will be explained, to perform one or more work units or portions of a first protocol, followed by (or possibly at the same time as) one or more work units or portions of a second protocol, followed by one or more work units or portions of yet a third protocol, and so forth. Breaking down at least some of the protocols into work units enables interleaving of messages that support to communication with multiple types of wireless identification tags.

In certain embodiments of the invention, the process of selecting which portions of a protocol to interleave with other work units as well as how much time to allocate for each type of protocol depends on scheduling rules for the different protocols. Interleaving may include round-robin scheduling, random scheduling, or using other techniques explained herein. During the operation of interleaving multiple radio frequency tag identification protocols using a single programmable tag reader, a scheduler and interleaver in the radio device can thus keep track of which work units associated with each of different protocol have been executed and which work units need to be performed next.

The scheduler has flexibility when scheduling portions of the radio communications based on different protocols. For example, in one application, the scheduler randomly interleaves portions of the radio communications for each of the multiple types of wireless identification tags. In another application, the scheduler interleaves portions of the radio communications for each of different protocols in a round robin fashion. In yet another application, the scheduler selectively schedules the portions of radio communications to allocate more scheduling time for a particular type of protocol than another. In still another application, the sched-

5

uler identifies redundant portions of the radio communications and schedules only non-redundant portions of the radio communications. Further, in yet another application, the scheduler schedules portions of the radio communications based on priority to more frequently check a presence of a certain type of wireless identification tags in the monitored region. The scheduler also can employ any combination of the aforementioned techniques to schedule radio communications.

Such embodiments of the radio device can thus account for a variety of different physical environments in which the ability to read tagged items varies. For example, if a monitored region includes one type of tag associated with items that are relatively stationary (i.e., the tagged items do not move at all, or move very slowly, or move rather infrequently) while other types of tagged items associated with a different tag protocol move rapidly from one location to another (e.g. tagged items move quickly through a region on a conveyor belt in a manufacturing facility), embodiments of the invention can provide for proper scheduling of these two (or more) different types of tag protocols to account for the fact that it may be necessary to monitor one type of tag at a higher rate than another. Accordingly, the scheduler may use a priority scheduling technique to more frequently execute or schedule work units associated with the protocol used to communicate with the fast-moving tagged items.

Yet another aspect of the present invention is directed towards a radio device that monitors a presence of wireless identification tags in a region. The radio device (and potentially each of other similar radio devices that collectively form a distributed or hierarchical database) includes a network interface and a processor. The network interface receives a network message including an agent generated by a source at a remote location. The processor executes the agent and, in response to satisfying a condition of the agent, reports data information associated with the wireless identification tags back to the source (or another designated recipient) via the network interface. Based on this technique of executing the agent at the radio device such as a wireless identification tag reader, the remote sources control the collection of data at the radio device and reporting of the data back to the source or other recipient. In one application, the agent acts as a filter that selects which type of data to transmit back to the source or otherwise intended recipient.

#### BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects, features and advantages of the invention will be apparent from the following more particular description of preferred embodiments of the invention, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily drawn to scale, emphasis instead being placed upon illustrating the principles of the present invention.

FIG. 1 is a block diagram of a communication system for monitoring multiple types of wireless identification tags.

FIG. 2 is a block diagram of a reconfigurable wireless tag reader for monitoring multiple types of wireless identification tags.

FIG. 3 is a block diagram of a transceiver for use in a wireless tag reader.

FIG. 4 is a block diagram of a reconfigurable wireless tag reader for monitoring multiple types of wireless identification tags.

FIG. 5 is a detailed block diagram of a wireless identification tag and associated tag reader.

6

FIG. 6 is a block diagram of components associated with a tag reader.

FIG. 7 is a diagram of a monitoring system including multiple configurable radio devices.

FIG. 8 is a diagram of a software architecture associated with a programmable radio device.

FIG. 9 is a block diagram illustrating a system and method for interleaving portions of radio communications to communicate with different types of wireless identification tags.

FIG. 10 is a flow chart illustrating a method of reconfiguring a programmable radio device to support an additional wireless tag protocol.

FIG. 11 is a block diagram of hierarchical database including multiple wireless tag readers.

FIG. 12 is a flow chart illustrating a method of utilizing agents to execute tasks at wireless identification tag readers.

#### DETAILED DESCRIPTION

As discussed in the summary above, one aspect of the present invention is directed to a radio device such as a tag reader that communicates with multiple types of wireless identification tags in a monitored region. The radio device includes a network interface to receive messages transmitted over a network. In response to receiving a message indicating to reconfigure the radio device to support an additional protocol, the radio device is reconfigured to support communications with a corresponding additional type of wireless identification tag in a monitored region. In addition to a network interface, each radio device includes a database to manage and store information associated with multiple types of wireless identification tags.

As an example, radio devices can be multiple tag readers interconnected via a network to form a distributed system. Each tag reader in such a system is responsible for managing its local population of wireless identification tags. For example, each tag reader acts as a gateway between relatively 'dumb' tags and relatively 'smart' processing systems that enable users to make strategic business decisions depending on movement of tags (and corresponding tagged items) in a supply chain application. Each tag reader includes a database for managing its own local population of wireless tags. Thus, the network of tag readers itself can be managed as a distributed or hierarchical database system.

Although the techniques described herein are suitable for use in tag readers, and particularly to supply chain management applications, techniques discussed herein are also well-suited for other applications that employ techniques of monitoring wireless identification tags.

FIG. 1 is block diagram illustrating a technique of monitoring wireless identification tags in accordance with one embodiment of the present invention. As shown, wireless communication system 100 includes programmable radio device 160 including transducers 150, network 135, and different types of wireless identification tags 110, 120 and 130.

In the context of a wireless tag reader application, programmable device 160 is a network node that transmits and receives messages 141, 142, respectively. Messages 141, 142 include one or multiple data packets such as those encoded according to TCP/IP (Transmission Control Protocol/Internet Protocol).

One purpose of messages 141 and 142 is to maintain or update protocols that programmable radio device 160 uses to communicate with wireless identification tags 110, 120, and 130. For example, message 142 may indicate that a new or updated protocol shall be used by programmable radio



device **160** to monitor a corresponding local population of wireless identification tags **110**, **120** and **130**.

Programmable radio device **160** includes a network interface to receive message (or messages) **142** transmitted over network **135**. In response to receiving message **142** indicating to reconfigure programmable radio device **160** (to support an additional or updated protocol), programmable radio device **160** reconfigures itself to support communications with corresponding types of wireless identification tags **110**, **120**, **130** in a monitored region. Accordingly, message **142** transmitted over network **135** reconfigures programmable radio device **160** so that it supports additional or modified protocols.

As mentioned, message **142** includes one or more network data packets that individually or collectively form a command or commands to update, delete, or add a new protocol supported by programmable radio device **160**. In one application, message **142** includes specific parameters (such as frequency, modulation type, logic encoding scheme, bit duration, encryption, antenna type . . . ) associated with a new or updated wireless communication protocol. In another application, message **142** encapsulates a computer program in the form of source or object code which endows a reconfigurable radio device **160** with new communication capabilities, or new interface capabilities.

Another purpose of messages **141**, **142** is to enable remote sources to manage functional aspects of programmable radio device **160**. For example, message **142** is optionally an agent (generated by a remotely located source) that runs on programmable device **160** to filter, collect or generally maintain data and tag management tasks associated with radio device **160**. Accordingly, a source sending message **142** including an agent over network **135** can control collection of data at programmable radio device **160** and which, if any, of the collected data is transmitted back to the source or other designated recipient. Programmable radio device **160** optionally executes multiple agents received from one or multiple sources. Agents can be used to collect data at programmable device **160** and send it to a designated node of a network. This will be discussed in more detail later in this specification.

As will be discussed in more detail in the following text and associated figures, programmable radio device **160** such as a wireless tag reader can be viewed as a software-defined radio device. Communications received through a network gateway define operational characteristics of such a radio device **160**. This technique of supporting remote programmability is particularly beneficial in applications where a common tag reader must support communications on different frequency bands as may be required by different countries.

FIG. **2** is a block diagram of tag reader **102** for monitoring multiple types of wireless tags using multiple protocols. As shown, tag reader **102** includes one or more sensors **105**, transceiver **112**, network subsystem **115**, database server **136**, network processor **131**, communications port **120**, and memory device **125**. In general, tag reader **102** reads information provided by wireless identification tag **291** (or collectively, wireless identification tags **110**, **120**, **130**), stores the information in the memory device **125**, and generates messages in response to commands or queries received from remote networked clients.

In one application, tag reader **102** reads information associated with wireless tags **291** using one or more protocols, such as those associated with RFID (Radio Frequency Identification) tags. In addition to RFID tags, tag reader **102**

optionally supports communication with Electronic Product Code (EPC) tags and other types of identification tags.

Collective group of sensors **105** are coupled to transceiver **112**. During operation, one particular sensor **105** (or multiple sensors **105**) receives wireless signal **108-2** such as a Radio-Frequency (RF) signal from one or more wireless tags **291** at the same time. As previously discussed, wireless identification tags **291** are either active or passive devices. In the latter case, tag reader **102** generates an interrogation signal that wireless identification tag **291-1** uses to power its internal circuitry and generate a reply signal such as wireless signal **108-2**.

Sensor **105** converts received wireless signal **108-2** (from one or more tags **291**) to a corresponding electrical signal that drive inputs of transceiver **112**. Transceiver **112** processes the received electrical signal to remove any encoded information content impressed upon received wireless signal **108-2**. In one application, wireless signal **108-2** is a modulated RF signal, in which tag **291** has impressed information content upon an RF carrier signal via (e.g., amplitude, frequency, or phase) modulation.

Typically, the information impressed upon wireless signal **108-2** is a characteristic data string of binary information. The characteristic data string may include an address associated with a particular wireless identification tag **291** generating the character data string. In addition to a tag address, the characteristic data string may include information such as an article or item to which wireless identification tag **291** is affixed. Information associated with tags **291** are stored in a database to track, e.g., a certain type of product to which tag **291** is affixed. Tag information includes data such as a part number, lot number, date of manufacture, owner, temperature, humidity, associated with a particular item marked with wireless identification tag **291**.

Sensors **105** are generally selected for use depending on the type of wireless application of tag reader **102**. For example, in one application, wireless signal **108** is an electromagnetic signal such as a Radio Frequency (RF) signal. Sensors **105** are optionally antennas designed to support transmitting and receiving data at a particular frequency range. In one application, sensors **105** associated with tag reader **102** operate at multiple frequencies (or frequency bands) such as 13.56 megahertz, 869/915 megahertz, and 2.4 gigahertz, depending primarily on the radio regulations enforced by a particular government.

In one application, sensors **105** are linearly-polarized antennas such as wire loop antennas, microstrip patch antennas, wire antennas (e.g., half-wave dipoles, or quarter-wave whips over a ground plane), horn antennas, or combinations thereof. In other arrangements, sensors **105** are circularly-polarized antennas such as orthogonal pairs of linear antennas interconnected with a 90-degree phase shift or spiral antennas. In still other applications, sensors **105** are a switched, multiplexed, or phased array of subelement antennas of any of the preceding types.

In another application, sensors **105** are optionally pressure transducer devices (e.g., microphone, speaker or ultrasonic sensor) that transmit and receive encoded pressure signals. In such an application, the transducer devices generate and detect changes in air or water pressure. Additionally, sensors **105** are optionally optical devices that transmits or receives optical signals. In yet another application sensors **105** are wire loops that support inductive coupling.

Network subsystem **115** includes database server **136** and network processor **131**. Database server **136** communicates with both transceiver **112** and memory device **125**. Thus,

database server **136** supports retrieval of data stored in storage device **125** and queries generated by tag reader **102**.

Database server **136** receives an information signal from transceiver **112**, processes the received information, and stores the processed information (e.g., as objects) in a database residing in memory device **125**. Processing performed by the database server **136** includes, for example, parsing the received information into one or more sub-strings, and time-stamping the received information.

Database server **136** translates and executes queries on behalf of clients (e.g., other servers). Prior to generating a response to a client, database server **136** translates data into an appropriate format before returning the queried result to the requesting client. In one embodiment, the database residing in memory device **125** is configured according to a Structured Query Language (SQL), i.e., as an SQL database server. This database server may return data to the network client by means of multiple protocols including TCP/IP, SQL result strings, or markup language (e.g., the extensible markup language XML).

Database server **136** itself may be configured as multiple servers. In one embodiment, database server **136** includes a tag-reader server for handling communications between the database and wireless tags **291** (or collectively **110**, **120** and **130**) through transceiver **112**. Database server **136** further includes an applications server to handle requests for retrieving data from the database. Finally, database server **136** includes an administration server used by administrators and users to update the properties of objects in the database stored in memory device **125**.

Memory device **125** optionally includes volatile and/or nonvolatile media. Volatile media includes devices such as Random Access Memory (RAM). Non-volatile media includes devices such as Electronically-Erasable Programmable Read Only Memory (EEPROM), Flash memory, ferroelectric memory, battery-backup RAM, magnetic disks and tapes, and optical storage media.

Network processor **131** communicates tag query requests through transceiver **112** to receive characteristic data strings from remote tags **291**. Additionally, network processor **131** communicates via communications port **120** and with the database server **136**. Thus, network processor **131** supports communications between and among tag reader **102**, other networked clients, and wireless tags **291**.

Tag reader **102** optionally queries tags **291** in a structured manner to avoid interference between multiple tags responding simultaneously to a query. For example, tag reader **102** optionally uses different frequency ranges (e.g., 13.56 MHz, 869/915 MHz, and 2.4 GHz) and power levels to control the distance at which tags **291** are read. Generally, lower-frequency bands are used to detect nearby tags and higher-frequency bands are used to detect more distantly located tags **291**, depending on the characteristics of the tags **291**, the tag reader **102**, their respective antennas (**105**), and the materials present within the reader's electromagnetic field.

Host applications and wireless tag protocols associated with tag reader **102** can be remotely upgraded and/or reconfigured, thereby reducing the cost and complexity of maintaining such a device over its anticipated lifetime. Remote reconfiguration capability is particularly useful in applications supporting many tag readers **102** that are spread out over designated regions of a retail store.

Network subsystem **115** includes at least one processor selected from any of a number of available processors, such as one of Motorola's low-cost Dragonball family, or the Intel Xscale or StrongARM family. A Motorola processor can be scalable to 50 MIPS (Mega Instructions Per Second) using

ColdFire. Network subsystem **115** includes an on-board LINTUX-based kernel. Alternatively, network subsystem **115** includes software based on a Microsoft Windows-based architecture or any other networked operating system.

According to one arrangement, there are two modes of interfacing with network subsystem **115**. For example, standard Internet protocols, namely, Simple Network Management Protocol (SNMP) and, for real-time data exchange, an Unreliable Datagram Protocol (UDP) are used for communication purposes. Network subsystem **115** running Linux may host application software, such as a database system. For example, the Savant database system is optionally installed to run on tag reader **102** to maintain a database stored in memory device **125**.

Network subsystem **115** is optionally in communication with peripheral devices **140**. Peripheral devices **140** associated with tag reader **102** include input/output devices such as user-interface buttons, displays (such as LCD or LED displays), bar-code scanners, printers, etc.

FIG. **3** is a detailed block diagram of transceiver **112**. Transceiver **112** includes RF front end **200**, frequency converter **205**, and detector **212**. RF front end **200** is coupled to sensor **105** for receiving electrical signals from sensor **105** in a receive direction and sending electrical signals to sensor **105** in a transmit direction.

In one application, RF front end **200** combines electrical signals received on multiple sensors **105** into a common signal presented to frequency converter **205**. In one application, a triplexer is employed to separate (transmit) and combine (receive) the signals among each of multiple sensors **105**. RF front end **200** also provides appropriate amplification or gain, such as low-noise amplification to received signals, and power amplification to transmitted signals. RF front end **200** may include filters such as high-pass, low-pass, and band-pass filters. Filtering reduces interference from other RF sources (e.g., other tag readers **102**, or other electrical devices).

In a receive mode, RF front end **200** receives an electrical signal derived from wireless signal **108-2** as detected by sensor **105**. RF front end **200** amplifies and filters the signal and feeds it to frequency converter **205**. As its name suggests, frequency converter **205** converts the frequency of the received signal to an intermediate (or baseband) frequency. Generally, the frequency converter 'down-converts' the RF signal to a lower intermediate frequency or baseband signal.

Down-conversion may be performed in one step or in multiple steps in which the received RF signal is converted to multiple intermediate frequencies. Generally, down-converters (frequency converter **205**) utilize standard techniques of frequency synthesis using hardware such as local oscillators, mixers, amplifiers and filters to down-convert the signal.

Frequency converter **205** includes one or more filters that filter the intermediate frequency or baseband signal. In certain embodiments, frequency converter **205** includes an Analog to Digital Converter (ADC) to convert a received analog intermediate frequency or baseband signal into a representative digital signal fed to detector **212** or, in turn, network subsystem **115**. The representative digital signal can be encoded according to a common format associated with multiple types of wireless identification tags **291**.

Detector **212** (such as a digital signal processor) receives the intermediate frequency signal and detects the information impressed upon wireless signal **108**. Generally, detector **212** demodulates the intermediate frequency signal to obtain the characteristic data string associated with a responding wireless identification tag **291**.

## 11

A particular demodulation scheme employed by detector 212 to retrieve a characteristic data string depends upon a protocol (and modulation technique) associated with a particular type of wireless identification tag 110, 120, 130. Modulation employed by wireless tag 291 include, e.g., amplitude modulation, frequency modulation, phase modulation, and combinations thereof.

In one application, detector 212 includes digital signal processing functionality and receives a digital representation of the intermediate frequency signal from frequency converter 205 as mentioned. Under-sampling ADC is optionally implemented to allow detector 212 to operate at a much slower sampling rate while still digitizing at a relatively high intermediate frequency (IF). This technique reduces cost and complexity with detector 212.

In a transmit mode, detector 212 generates a signal that is communicated to wireless tag 291. For example, in a DSP configured detector 210, a transmit signal is generated using direct-digital synthesis (DDS) allowing AM, FM and PM control at a data rate lower than the RF carrier rate. Frequency converter 205 generates an RF carrier signal and transmits the carrier signal to RF front end 200. RF front end 200 optionally filters and amplifies the signal before driving it to the appropriate sensor 105 (e.g., as determined by the carrier frequency). Sensor 105, in turn, converts the electrical signal to a wireless signal intended for one or more wireless tags 110, 120, 130 in a monitored region.

FIG. 4 is block diagram of tag reader 260 in communication with peripheral devices 170 and network 135. As shown, tag reader 260 includes network interface 210, processor system 220, memory device (database) 230, digital signal processor 240, frequency converter 245, transducer interface 247, and transducers 250.

A basic task associated with tag reader 260 is the management and storage of data associated with wireless identification tags 110, 120, 130. To achieve this end, processor system 220 executes applications 222. One application involves managing data stored in memory device 230. Another application (such as a program of scheduled queries) involves monitoring a region for presence of wireless identification tags 110, 120, 130 by generating queries via transceiver 472.

Tag reader 260 includes network interface 210 to communicate with remote sources generating commands such as requests to update protocols associated with tag reader 260 for communicating with wireless identification tags 110, 120, 130. For example, one type of command received by tag reader 260 indicates to discontinue monitoring a region using a particular protocol associated with tags that are no longer used in a supply chain. Additionally, another type of command received by tag reader 260 indicates to start using a new protocol to communicate with wireless identification tags in a particular monitored region. Yet another type of command received by tag reader 260 indicates to modify an existing protocol used for communicating with wireless identification tags 110, 120, 130.

Message 142 such as a reconfiguration message optionally includes two distinct portions of data to update a protocol associated with digital signal processor 240. For example, a first portion of message 142 includes instructions to be executed by processor system 220 for reprogramming digital signal processor 240. A second portion of (a reconfiguration) message 142 includes specific data information or executable code to be executed by digital signal processor 240. Processor system 220 transfers the second portion of message 142 to digital signal processor 240 according to instructions in the first portion of message 142.

## 12

As previously discussed, messages 142 are generated by one or multiple remote sources over network 135 to manage functional aspects of tag reader 260. For example, message 142 such as an agent or daemon may include a set of tasks for execution by processor system 220. Attributes of an agent vary depending on the application but include tasks such as collection or retrieval of information stored in database 230, generation of specific queries that are performed by tag reader 260 to determine a presence of a particular type or address of wireless tags 110, 120, 130 in a monitored region, and detection of a particular event prompting generation of a reply message to a designated recipient.

In response to satisfying a condition of the agent such as detecting a certain wireless identification tag 110 in a monitored region, tag reader 260 reports data information associated with wireless identification tags 110, 120, 130 back to the source generating the agent (or another designated recipient) via messages 141. Based on this technique of executing the agent on processor system 220, the remote sources can control the collection of data associated with tag reader 260. In one application, the agent acts as a filter that selects which type of data to transmit back to the source so that it is not otherwise inundated with unwanted data from tag reader 260.

It should be noted that agents include any type of tasks to be executed by tag reader 260.

FIG. 5 is a block diagram of a wireless identification tag 291 and corresponding tag reader 260. As shown, wireless identification tag 291 includes transducer 370, power converter 310, receiver interface 320, transmitter interface 330, logic circuit 340 and memory device 350.

According to one embodiment, wireless identification tag 291 includes power converter 310 that converts power from wireless signal 108-1 received on transducer 370 to power wireless identification tag 291. In an alternate embodiment, power converter 310 includes a battery to power wireless identification tag 291 and associated circuitry.

When powered, logic circuit 340 processes a received query (wireless signal 108-1) generated by tag reader 260 through a combination of transducer 370 and receiver interface 320. In response to receiving a query directed to wireless identification tags 291, logic circuit 340 retrieves appropriate data (such as a characteristic data string associated with wireless identification tag 291) from memory device 350 for transmission to tag reader 260 over transmitter interface 330.

Wireless identification tag 291 optionally includes programmable memory 340. In such an application, tag reader 260 stores information in memory device 340 by generating an appropriate command to wireless identification tag 291 via wireless signal 108-1.

FIG. 6 is a block diagram of transceiver interface 472 associated with tag reader 260. As shown, transceiver interface 472 includes digital signal processor 240, protocol modules 480-1, 480-2, . . . , 480-n, frequency converter 245, transceivers 440-1, 440-2, . . . , 440-n, and corresponding antennas 450, 460.

Digital signal processor 240 includes protocol modules 480-1, . . . , 480-n to support communications with each of multiple types of wireless identification tags 10, 120, 130. While in a transmit mode, protocol module 480-1 generates corresponding baseband signal 410-1 such as a digitized signal including an encoded query or other data information. Baseband signal 410-1 is fed into frequency converter 245 that, in turn, uses the baseband signal 410-1 to modulate a carrier frequency. Frequency converter 245 generates modu-

13

lated carrier signal **420-1** that is fed to transmitter interface **435** of transceiver **440-1**. Transmitter interface **435** drives a selected one or multiple antennas **450-1**, . . . , **450-x** to generate wireless signal **108-1** from tag reader **260**.

In a reverse direction or receive mode, one or multiple antennas **450** associated with transceiver **440-1** receive wireless signal **108-2** generated by a wireless identification tag **291**. Receiver interface **436** appropriately amplifies and filters received wireless signal **108-2** for input to frequency converter **245**. Frequency converter **245** strips a corresponding carrier signal from received modulated signal **420-1** to produce baseband signal **410-1** such as a digitized signal of binary encoded information. Baseband signal **410-1** feeds the input of protocol module **480-1** of digital signal processor **240**.

FIG. 7 is a diagram of multiple tag readers **260** to monitor a region for a presence of wireless identification tags **110**, **120**, **130**. As shown, monitoring system **503** includes multiple tag readers **260** (such as programmable radio devices **160**), network **135**, and clients **510**.

Each tag reader **260** monitors a corresponding region **305** for wireless identification tags **110**, **120**, **130**. Clients **510** generate network messages (including protocol updates or agents) to one or multiple tag readers **260**.

In one application, each tag reader **260** includes a custom program for repeatedly monitoring a presence of wireless identification tags **110**, **120**, **130**. For example, tag readers **260** optionally include a program that is executed by processor system **220** to periodically interrogate respective regions **305** for wireless identification tags **110**, **120**, **130**. Tag readers **260** process received tag information (e.g., characteristic data strings) and store the processed information locally in corresponding database **230** of tag readers **260**. In one embodiment, tag readers **260** automatically coordinate scheduled interrogations to minimize interference with each other.

In addition to storing characteristic data strings associated with detected tags **110**, **120**, **130** tag readers **260** generate time stamp information for storage in database **230** to indicate a time of detecting a particular tag **110**, **120**, **130**. Consequently, monitoring system **503** functions as an historical (or temporal) database distributed over a monitored area or geographic region. Clients **510** access data information stored in corresponding databases **230** using a logical address of each tag reader **260**.

Network **135** (including connections to each tag reader **260**) is optionally a Local-Area Network (LAN) such as that based on Ethernet, wireless Ethernet (IEEE 802.11), token ring, and/or AppleTalk®. Also, network **135** is optionally a wide-area network (WAN) such as a Public-Switched Telephone Network (PSTN), a cellular communications network, the Internet, and/or the World-Wide Web.

Hardware associated with clients **510** include electronic communication equipment such as personal computers, personal digital assistants, mainframe computers, distributed networks, enterprise hardware and software, and network device in general.

Because monitoring system **503** potentially includes many distributed memory devices **230** for storing information, a considerable amount of distributed storage is available for tracking items associated with wireless identification tags **110**. Connectivity provided by network **135** enables multiple clients **510** to share resources associated with tag reader **260**.

Database queries to each tag reader **260** can be structured in numerous ways. For example, client **510** optionally queries the entire database (such as collective databases

14

associated with multiple tag readers **260**) to locate a whereabouts of one or more particular wireless identification tags **110**, **120**, **130**. In this instance, each tag reader **260** receives the client request message for information relating to the particular tag **110**.

In response to receiving the request for information, each tag reader **260** queries its corresponding database **230** or generates a new wireless identification tag query via wireless signal **108** to find a wireless identification tag **110**, **120**, **130**. Tag readers **260** having information associated with the request message then send appropriate information over network **135** to requesting clients **510**.

In another application, monitoring system **503** is queried to locate all tags **110**, **120**, **130** currently residing within a predetermined sub-area such as collective regions **305-1**, **305-2**, **305-4**, and **305-5**. In this instance, only tag readers **260** (**260-1**, **260-2**, **260-4** and **260-5**) search for the tags and respond to the query. A balance of tag readers do not needlessly reply to the query.

Monitoring system **503** also can be queried to track the progress of one or more tagged items as they travel through one or multiple regions **305**. For example, clients **510** optionally generate requests to tag readers **260** for information relating to particularly identified tags **110**, **120**, **130** at a specified time or interval of time. Based on reply information from tag readers **260**, clients **510** can track how long an item tagged with a wireless identification tag and corresponding item is present in a particular region **305**. Monitoring system **503** thus provides users with the ability to track inventory, identify bottlenecks, and identify lost, stolen, or outdated inventory.

FIG. 8 is a diagram of a potential software architecture associated with tag readers **260**. As shown, the software architecture includes web browser **610**, web server **620**, controller **630**, query client **612**, query server **622**, tag database **632**, protocol modules **480-1**, . . . , **480-N**, and device drives **650-1**, . . . , **650-N**.

In general, clients **510** execute software to manage tag readers **260** disposed over network **135**. Among other tasks, client software enables remotely located users to query tags **110**, **120**, **130** and reconfigure tag reader **260** (or multiple tag readers **260**) to support a different set of wireless communication protocols. For example, clients **510** reconfigure tag reader **260** to support an additional protocol to communicate with a new type of wireless identification tag. Clients **510** execute client software on web browser **610** or query client **612**. In one application, client software is embodied as web browser **610** such as a browser-based java query interface hosted by tag reader **260**. Alternatively, client software is embodied as query client **612** such as a higher-level data handling infrastructure (e.g., Savant) supporting SQL queries.

Software requests generated by web browser **610**, and query client **612** includes instructions such as search for tags, reconfigure tag reader, and retrieve tag information stored in database.

Communications between web browser **610** and web server **620** are supported via a protocol such as HTTP (Hypertext Transfer Protocol) and communications between query client **612** and query server **622** are supported by a protocol such as SQL (Structured Query Language).

Instructions processed by web server **620** are conveyed to controller **630** and tag database **632** via a general purpose interface bus such as the HPI (Host Processor Interface Bus) present on the digital signal processor. Requests for tag information are serviced by retrieving the appropriate infor-

15

mation from tag database 632 and sending it back to the requestor through query server 622 or web server 620.

In response to a reconfiguration request from either web browser 610 or query chart 612, controller 630 reconfigures digital signal processor 240 to support a new protocol module 480 for communicating with certain types of wireless identification tags 110, 120, 130.

Protocol modules 480 communicate with device drivers 650 that enable transmission and reception of radio signals to and from wireless identification tags 110, 120, 130. Results of a search are stored in tag database 632 and are sent back to a user at web browser 610 or query client 612.

Layering software in this way renders it easier to support additional protocols or modify existing protocols because adding support for protocols involves modifying software in protocol modules 480 and/or device drivers 650. Software in the rest of the system is minimally if at all changed.

FIG. 9 is a detailed block diagram of digital signal processor 240. As shown, digital signal processor 240 includes protocol modules 480-1, 480-2, . . . , 480-N, scheduler 750, and interleaver 760.

As mentioned, one aspect of the present invention is directed towards a tag reader 260 that interleaves portions of radio communications to communicate with multiple types of wireless identification tags 110, 120, 130. Scheduling logical sequences of radio communications (or protocols) one after the other, according to conventional methods, results in 'dead' time when hardware such as frequency converter 245, transceiver interfaces 440, and antennas 450, 460 are not used. For example, consider that most protocols for communicating with a type of wireless identification tag 110, 120, 130 include an interval of time when transceiver circuitry of tag reader 260 is neither transmitting nor receiving data information. This is an unnecessary waste of hardware resources. Thus, interleaving portions of radio communications (or protocols) reduces any dead time between transactions and, thus, a time it takes to otherwise monitor a region for wireless identification tags 110, 120, 130. Interleaving portions of radio communications also potentially reduces an amount of power consumed by tag reader 260.

Protocol modules 480 generate different protocols 740 (such as unique bit sequences) to communicate with different types of wireless identification tags 110, 120, 130. Protocols 740 associated with a particular type of tag are parsed into work units to support flexible scheduling. For example, protocol 740-2 from protocol module 480-1 is divided into work units (portions) A1, A2, . . . , Ak. Likewise, protocol 740-2 from protocol module 480-2 is divided into work units (portions) B1, B2, and B3; protocol 740-N 2 from protocol module 480-N is divided into work units (portions) C1, C2, C3, and C4. Collectively, work units of a corresponding protocol 740 form a logical transaction or radio communication such as a query (read) or write command associated with a particular type of wireless tag 291. In one application, a logical transaction includes a series of address query commands to identify address of each tag in the monitored region.

In one application, protocol module 480 employs a specific protocol to identify an address of each tag 291 in a monitored region. For example, a first portion of the specific protocol involves generating a universal message to determine if any wireless tags 291 of a particular type are located in the monitored region. Multiple tags 291 may respond simultaneously to indicate that they are present. If so, tag reader 260 generates successively narrower queries (additional portions of the protocol) to potential sets of wireless

16

tags 291 to identify tags in a given monitored area. Eventually, tag reader 260 narrows the queries enough to identify each and every address of tags 291 in the monitored region. Interleaving protocols enables tag reader 260 to monitor an area at least a minimum rate so that tag reader 260 can identify even fast-moving tags 291 such as those on conveyor belts that would otherwise be missed.

Based on input provided from scheduler 750 (such as a real-time scheduler) indicating an order for interleaving radio communications (protocols 740), interleaver 760 generates output signal 782 including interleaved work units (such as sequence of work units B1, A1, B2, A2, C1, C2 . . . ) from multiple protocols to communicate with different types of wireless identification tags 110, 120, 130.

Protocols 740 may each have an associated set of rules for scheduling work units associated with a particular radio communication protocol 740. For example, certain work units associated with a protocol 740 may need to be executed within a specified period of time. Other work units and protocols 740 may have no restrictions on when work instructions must be executed. Based on the set of rules for scheduling protocols 740, scheduler 750 identifies how to schedule and interleave the radio communications.

Scheduler 750 can not perform work units at certain times such as time period 775 because it may cause corruption of data associated with certain tags 291.

Breaking down the protocols into portions supports more efficient collection of data information associated with the wireless identification tags in the monitored region because protocols 740 (radio communications) can be scheduled in many more ways than simply scheduling one entire radio communication transaction after the other. For example, in one application, scheduler 750 randomly interleaves portions of radio communications with no particular preference given to each of the multiple types of wireless identification tags 110, 120, 130.

In another application, scheduler 750 interleaves portions of radio communications for each of different protocols 740 in a round robin fashion. In yet another application, scheduler 750 selectively schedules the portions of radio communications by allocating more scheduling time for one particular type of protocol 740 over another. In still another application, scheduler 750 identifies redundant portions of the radio communications and schedules only non-redundant portions of the radio communications. Further, in yet another application, scheduler 750 schedules and interleaves portions of the radio communications based on priority to more frequently check a presence of a certain type of wireless identification tags in the monitored region. Scheduler 750 also employs any combination of the aforementioned techniques to schedule radio communications.

In a further application, scheduler 750 interleaves portions of wireless communications, or intentionally incorporates "dead time" in response to wireless signals received by the transceiver. This may take the form of a simple channel occupancy measurement, or a more complex interception of another communication between a wireless tag reader and a tag, between two wireless tag readers, or between any other systems occupying the same frequency range. This operation can be treated as a special case of a scheduled wireless transmission event to improve the interoperability of a plurality of wireless tag readers in the case where they may mutually interfere, or to improve interoperability between wireless tag readers and any other wireless communication system in the case where the wireless tag readers cause or receive interference to or from said other wireless communication system.

17

Scheduler **750** may also affect the modulation type, operating frequency, or any other parameter of the wireless communication to achieve any of these goals.

Additional aspects of scheduler **750** and related hardware and software functions may include: introducing a period of time including no wireless transmissions from the radio device to wireless identification tags in the monitored region, changing an operating frequency to improve interoperability among multiple wireless devices simultaneously communicating in a common area, identifying redundant portions of radio communications and optimizing by scheduling only non-redundant portions of the radio communications, identifying otherwise interfering portions of the radio communications and optimizing by scheduling only non-interfering portions of the radio communications, and monitoring wireless signal characteristics (such as channel occupancy) to reduce interference with other wireless communication devices sharing a common area.

Distributing tag readers **260** over a network enables the establishment of a Tag Services Provider (TSP) such as a management entity that handles maintenance of tag readers **260** as well as processing of tag information. For example, a small retail business may purchase or lease a tag reader but rely on the TSP to enable different applications (via agents) such as those associated with a particular retail store. Accordingly, the TSPs assist everyday users in maintaining a personal inventory of their tagged objects on a remote server, similar to the manner in which Hotmail™ manages a user's inventory of e-mail.

TSPs can assist during situations when network connectivity is intermittent or non-existent due to network failures. For example, tag reader **260** may continue to store tag transactions within its internal database even without a network connection. Configured according to an offline (proxy server) processing model, the tag reader (having stored the tag transactions) forwards them to the TSP when connectivity is re-established.

Tag readers **260** can be used in many ways. For example in one application, a networked tag reader **260** is configured to automatically notify a user when an article bearing a specific tag registered by a reader or by a class of readers is in physical location monitored by a particular tag reader **260**. For example, a filing cabinet can be configured with a networked tag reader **260** to notify an administrator when a specific document has been filed in the filing cabinet.

In another application, a book collector may generate a request for a specific book along with an offer to purchase it for a specified amount of money. When an owner of the book passes by tag reader **260**, the tag reader **260** notifies the owner of the offer.

In yet another application, a librarian can utilize a handheld tag reader **260** that is pre-configured to include tag IDs of books potentially being sought. The librarian can be notified when the tag reader **260** detects a particular wireless tag **291** associated with a sought-after book within the vicinity of tag reader **260**. In still another example, a web application can issue a search command for a class of items or specific items themselves. Tag reader **260** will respond with location information associated with a specific tagged item.

FIG. **10** is a flow chart illustrating a method of operating a tag reader **260** that communicates with wireless identification tags **110**, **120**, **130**.

In step **710**, tag reader **260** monitors multiple types of wireless identification tags **110**, **120**, **130** based on utilization of a corresponding set of protocols. In step **715**, tag reader **260** receives network message **142** (FIG. **1**) to

18

reprogram tag reader **260** such as reconfiguring its associated transceiver interface **472** for communicating with an additional protocol. In step **720**, tag reader **260** reconfigures its transceiver interface **472** to support radio communications based on the additional protocol.

FIG. **11** is a block diagram of a network of tag readers forming part of a hierarchical database. As shown, hierarchical level one includes, network interface **815**, level one database manager **820**, and memory device **825**. Hierarchical level two includes source **810-2**, network interface **840-1**, level two database manager **850-1**, memory device **830-1**, source **810-3**, network interface **840-N**, level two database manager **850-M**, and memory device **830-M**. Hierarchical level three includes tag readers **260-1**, . . . , **260-k** and **260-i**, . . . , **260-j**. The system as shown is easily scalable by adding hardware and software at different levels.

Collectively, hierarchical level one, two and three form a hierarchical database. Tag readers **260** monitor local populations of wireless identification tags **110**, **120**, **130**. Level two database managers **850** manage multiple tag readers and create their own database for storage in corresponding memory device **830**. At yet a higher level, level one database manager **820** manages hierarchical level two and level three as well as its own database stored in memory device **825**.

In the context of a supply chain, sets of tag readers **260** in hierarchical level 3 are employed to monitor different sites. For example one set of tag readers **260** monitors wireless tags **110**, **120**, **130** (FIG. **7**) in a manufacturing facility. Another set of tag readers **260** monitors wireless tags **110**, **120**, **130** in a warehouse. Yet another set of tag readers **260** monitors a shipping container that delivers tagged items to a retailer. Still another set of tag readers **260** monitors wireless tags **110**, **120**, **130** at a consumer outlet such as a retail store. Based on this topology, wireless identification tags **110**, **120**, **130** and corresponding retail items can be tracked from manufacturing to actual sale at a cashier in a retail store.

Each site including networked tag readers **260** optionally includes a local monitor system **865** (hierarchical level 2) to track a movement of wireless identification tags **110**, **120**, **130** and corresponding products. For example, level two database managers **850** retrieve relevant information from tag readers **260** for storage in memory devices **830**. Based on information collected from tag readers **260** at a particular site, appropriate corrective action can be taken to rectify, for example, a bottleneck or other corresponding problems at the monitored site.

At a higher level (namely, hierarchical level one), monitor system **862** oversees a whole supply chain including tag readers **260** and level two monitor systems **865**. In one application, monitor systems **862** is located at headquarters of a company that monitors the supply chain. In this way, wireless tags **110**, **120**, **130** can be automatically monitored from remote locations.

Disposing tag readers **260** (including memory device **230**) to form a hierarchical database reduces a burden of having to continuously transmit and process data information from tag readers **260**. For example, tag reader **260** stores collected information in corresponding memory device **230** instead of sending all raw data to a centralized storage device such as memory device **830**. As information is needed, monitor systems **862**, **865** generate requests to tag reader **260** for such data. Also, tag readers **260** compile, process and generate reports that are sent to monitor system **862**, **865**. Processing raw collected data at tag readers **260** reduces an amount of processing required at other hierarchical levels.

As previously discussed, tag readers **260** are reconfigurable via network messages. In the hierarchical system in FIG. **11**, sources **810** transmit messages **805** to reconfigure tag readers **260** so they support a new set of wireless identification tag protocols. Confirmation of changes to tag reader **260** can be received via messages **806**.

Tag readers **260** can be reconfigured by proactively 'pulling' software or protocol information from a remote location. For example, tag reader **260** may periodically poll a remote source such as source **810-1** for updates software. Additionally, tag reader **260** may proactively retrieve updates from a remote source such as **810-2** after receiving an update command received from source **810-1**.

In addition to generating reconfiguration instructions, messages **806** support transmission of agents to tag readers **260**. The agents are executed at tag readers **260** and, in response to satisfying a condition of the agent, report appropriate information back to source **810** via messages **806**. Conditions associated with an agent include detecting events such as sensing that multiple tags **291** are no longer in a particular monitored region such as a store shelf of a retail store.

In one application, agents are generated by different functional groups of an organization and each group monitors different aspects of a supply chain. For example, a marketing group may generate an agent that reports information regarding how long a certain type of product sits on a shelf at a particular retail store. An operations group may generate agents to identify bottlenecks in the supply chain being monitored. Based on information reported by the agents, the functional groups of a corporation managing different aspects of a supply chain can make appropriate business decisions.

It should be noted that agents are not merely limited executed to report data information back to a corresponding source **810**. They are optionally employed to perform any type of processing task at a tag reader **260**. For example, agents can be used to program tag readers **260** with application software.

As mentioned, tag reader **260** optionally executes multiple agents, each of which includes its own set of instructions for retrieving wireless tag **291** information. To optimize use of a wireless spectrum, scheduler **750** identifies a minimum superset of transactions to perform the functional tasks associated with multiple agents. Without optimizing, tag reader **260** may otherwise perform needless tasks such as redundant tag queries.

FIG. **12** is a flow chart **900** including a method of utilizing agents to execute tasks at tag readers **260**.

In step **910**, tag reader **260** monitors a presence of wireless identification tags **110**, **120**, **130** based on a use of at least one radio communication protocol.

In step **920**, tag reader **260** receives a network message including an agent generated by a source at a remote location.

In step **930**, tag reader **260** executes the agent by performing tasks specified therein.

In step **940**, tag reader **260** transmits reporting messages including data information associated with the tag reader **260** in response to satisfying a condition of the agent.

While this invention has been particularly shown and described with references to preferred embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

**1.** A method of operating a wireless transceiver device that communicates with wireless identification tags, the method comprising:

communicating with multiple types of wireless identification tags in a monitored region based on use of a corresponding set of wireless communication protocols;

at the wireless transceiver device, receiving a message transmitted over a network;

in response to receiving the message, reconfiguring the wireless transceiver device to support a new protocol for communicating with a corresponding type of wireless identification tag in the monitored region;

partitioning at least two of the multiple types of wireless communication protocols that are used to communicate with wireless identification tags; and

interleaving portions of the partitioned protocols to communicate with multiple types of wireless identification tags.

**2.** A method as in claim **1** further comprising:

at the wireless transceiver device, at least occasionally performing a query to determine a presence of each type of wireless identification tag in the monitored region; and

for the identified types of wireless identification tags in the monitored region, scheduling additional wireless communications directed to detected types of wireless identification tags in the monitored region.

**3.** A method as in claim **1** further comprising:

at the wireless transceiver device, collecting information related to the wireless identification tags; and

storing the information in a database at the wireless transceiver device, the database of the wireless transceiver device forming part of an overall hierarchical database distributed over the network.

**4.** A method as in claim **1**, wherein communicating with multiple types of wireless identification tags includes:

generating wireless signals over multiple carrier frequencies.

**5.** A method as in claim **4**, wherein generating wireless signals includes:

generating wireless signals from the wireless device at different carrier frequencies but utilizing a common baseband to receive data information from the wireless identification tags.

**6.** A method as in claim **4**, wherein generating wireless signals includes:

generating wireless signals from the wireless device at different carrier frequencies but utilizing a common intermediate frequency to receive data information from the wireless identification tags.

**7.** A method as in claim **1**, wherein generating wireless signals includes:

simultaneously generating wireless signals from the wireless transceiver device at different carrier frequencies to communicate with at least two different types of wireless identification tags at the same time.

**8.** A method as in claim **1**, wherein communicating with multiple types of wireless identification tags includes:

powering the different types of wireless identification tags via wireless signals generated by the wireless transceiver device.

**9.** A method as in claim **1** further comprising:

processing the message received over the network and reprogramming a digital signal processor of the wire-



## 21

less transceiver device to support wireless communications with the new protocol.

10. A method of operating a radio device that communicates with wireless identification tags, the method comprising:

communicating with multiple types of wireless identification tags in a monitored region based on use of a corresponding set of radio communication protocols; interleaving portions of the radio communications associated with the multiple types of protocols to communicate with the multiple types of wireless identification tags.

11. A method as in claim 10, wherein interleaving portions of the radio communications includes:

randomly scheduling portions of the radio communications for each of different protocols.

12. A method as in claim 10, wherein interleaving portions of the radio communications includes:

scheduling portions of the radio communications for each of different protocols in a round robin fashion.

13. A method as in claim 10, wherein interleaving portions of the radio communications includes:

selectively scheduling portions of the radio communications to allocate more time for servicing one protocol over another.

14. A method as in claim 10, wherein interleaving portions of the radio communications includes:

introducing a period of time including no wireless transmissions from the radio device to wireless identification tags in the monitored region.

15. A method as in claim 10, wherein interleaving portions of the radio communications includes:

changing an operating frequency to improve interoperability among multiple wireless devices simultaneously communicating in a common area.

16. A method as in claim 10, wherein interleaving portions of the radio communications from the radio device includes:

identifying redundant portions of the radio communications; and

scheduling non-redundant portions of the radio communications to communicate with multiple types of wireless identification tags.

17. A method as in claim 10, wherein interleaving portions of the radio communications from the radio device includes:

based on a set of scheduling rules, identifying an acceptable order of scheduling the portions of radio communications associated with the set of radio protocols; and scheduling the portions of radio communications according to the acceptable order.

18. A method as in claim 10 further comprising:

at the radio device, collecting information related to the wireless identification tags; and

storing the information in a database at the radio device, the database of the radio device forming part of a hierarchical database distributed over the network.

19. A method as in claim 10, wherein interleaving portions of the radio communications from the radio device includes:

scheduling portions of the radio communications based on priority to more frequently check a presence of a certain type of wireless identification tags in the monitored region.

20. A method of selectively providing data information associated with a radio device that monitors a presence of wireless identification tags, the method comprising:

## 22

monitoring the presence of wireless identification tags based on utilization of multiple types of wireless communication protocols;

at the radio device, receiving a network message including an agent generated by a source at a remote location; executing the agent at the radio device; and

in response to satisfying a condition of the agent, transmitting messages over the network to report data information associated with the radio device back to the source; and

wherein monitoring the presence of the wireless identification tags includes: i) partitioning at least two of the multiple types of wireless communication protocols that are used to communicate with wireless identification tags, and ii) interleaving portions of the partitioned protocols to communicate with multiple types of wireless identification tags.

21. A method as in claim 20 further comprising:

executing multiple agents received from multiple sources at different remote locations relative to the radio device, each of the multiple agents having an associated function for retrieving particular information from a database associated with the radio device that stores wireless identification tag information.

22. A method as in claim 20 further comprising:

as a result of executing the agent at the radio device, filtering data information associated with the wireless identification tags that would otherwise be sent back to the source.

23. A system to communicate with wireless identification tags, the system comprising:

a wireless transceiver device to communicate with multiple types of wireless identification tags in a region based on use of a corresponding set of radio communication protocols;

a network interface to receive a message transmitted over a network;

a processor that, in response to receiving the message over the network, reconfigures the wireless transceiver device to support a new protocol for communicating with a corresponding type of wireless identification tag in a monitored region; and

an interleaver that interleaves portions of the radio communication protocols to communicate with the multiple types of wireless identification tags in the monitored region.

24. A system as in claim 23, wherein the wireless transceiver device includes a scheduler that at least occasionally performs a query to determine a presence of each type of wireless identification tag in the monitored region, the scheduler scheduling radio communications to further identify particular data about the types of wireless identification tags detected in the monitored region.

25. A system as in claim 23, further comprising:

a database to store information collected as a result of communicating with the corresponding set of radio communication protocols, the database being part of an overall hierarchical database distributed over the network.

26. A system as in claim 23, wherein the wireless transceiver device communicates with multiple types of wireless identification tags by generating wireless signals over multiple carrier frequencies.

27. A system as in claim 26, wherein the transceiver device generates wireless signals at different carrier frequencies to simultaneously communicate with at least two different types of wireless identification tags at the same time.



## 23

28. A system as in claim 26, wherein transceiver device generates wireless signals at different carrier frequencies but receives data from multiple type of wireless identification tags based on a common baseband frequency.

29. A system as in claim 28, wherein transceiver device generates wireless signals at different carrier frequencies but receives data from multiple type of wireless identification tags based on a common intermediate frequency.

30. A system to communicate with wireless identification tags, the system comprising:

- a wireless transceiver device that communicates with multiple types of wireless identification tags in a region based on use of a corresponding set of radio communication protocols, the wireless transceiver including: a scheduler to schedule radio communications associated with the corresponding set of radio communication protocols; and
- an interleaver that interleaves portions of scheduled radio communications associated with the set of radio communication protocols to communicate with the multiple types of wireless identification tags.

31. A system as in claim 30, wherein the scheduler randomly interleaves portions of the radio communications for each of the multiple types of wireless identification tags.

32. A system as in claim 30, wherein the scheduler interleaves portions of the radio communications for each of different protocols in a round robin fashion.

33. A system as in claim 30, wherein the scheduler, under direct user control, selectively schedules the portions of radio communications to allocate more scheduling time for one particular type of protocol than another.

34. A system as in claim 30, wherein the scheduler, under control of a software agent, selectively schedules the portions of radio communications to allocate more scheduling time for one particular type of protocol than another.

35. A system as in claim 30, wherein the scheduler identifies redundant portions of the radio communications and optimizes by scheduling only non-redundant portions of the radio communications.

36. A system as in claim 30, wherein the scheduler identifies interfering portions of the radio communications and optimizes by scheduling only non-interfering portions of the radio communications.

37. A system as in claim 30, wherein operations by the scheduler include monitoring wireless signal characteristics to reduce interference with other wireless communication devices sharing a common area.

38. A system as in claim 37, wherein the monitored wireless signal characteristics include channel occupancy.

39. A system as in claim 30 further comprising:

- a database that stores collected information related to the wireless identification tags in the monitored region, wherein the database is part of a hierarchical database distributed over the network.

40. A system as in claim 30, wherein the scheduler schedules portions of the radio communications based on priority to more frequently check a presence of a certain type of wireless identification tags in the monitored region.

41. A radio device to monitor the presence of wireless identification tags in a region, the radio device comprising: a network interface to receive an agent generated by a source at a remote location;

## 24

a processor to execute the agent, the processor reporting data information associated with the wireless identification tags back to the source in response to executing instructions associated with the agent; and

an interleaver that interleaves portions of multiple different types of radio communication protocols to communicate with corresponding different types of wireless identification tags in the region.

42. A radio device as in claim 41, wherein the processor executes multiple agents received from multiple sources at different remote locations relative to the radio device, each of the multiple agents having an associated function for retrieving particular information from a database associated with the radio device that stores wireless identification tag information.

43. A radio device as in claim 41, wherein the processor, in response to executing an agent, filters data information associated with the wireless identification tags that would be otherwise transmitted back to the source.

44. A system to communicate with wireless identification tags, the system comprising:

- means for communicating with multiple types of wireless identification tags in a region based on use of a corresponding set of radio communication protocols;
- a network interface to receive a message transmitted over a network;
- means for supporting at least one additional protocol for communicating with a corresponding type of wireless identification tag in a monitored region in response to receiving the message over the network;
- means for partitioning at least two of the multiple types of wireless communication protocols that are used to communicate with wireless identification tags; and
- means for interleaving portions of the partitioned protocols to communicate with multiple types of wireless identification tags.

45. A computer program product including a computer-readable medium having instructions stored thereon for processing data information, such that the instructions, when carried out by a processing device, enable the processing device to perform the steps of:

- communicating with multiple types of wireless identification tags in a monitored region based on use of a corresponding set of wireless communication protocols;
- at the wireless transceiver device, receiving a message transmitted over a network;
- in response to receiving the message, reconfiguring the wireless transceiver device to support at least one additional protocol for communicating with a corresponding type of wireless identification tag in the monitored region;
- partitioning at least two of the multiple types of wireless communication protocols that are used to communicate with wireless identification tags; and
- interleaving portions of the partitioned protocols to communicate with multiple types of wireless identification tags.

\* \* \* \* \*