

# Index

---

*Note:* Page numbers followed by “f,” “t,” and “b” refer to figures, tables, and boxes, respectively.

## 0-9 and symbols

1/f noise. *See* Flicker noise

1-nearest-neighbor (1-NN) approach, 387

1-Rule (1R), 386

4-cole-cole model, 258

## A

Absorption and molar extinction coefficients, of  
biological tissue constituents, 111, 111f

Accelerometers, 11, 86–88, 93, 136, 597

angular, 498

-based devices, 136–137

linear, 498

miniature, 599

piezoelectric, 87

tri-axial, 389–390

Accuracy, 494

AC-DC converters, 251–253

Actigraph, 136–137

Active interactions, with wearable system, 33

Active matrix for organic light emitting diodes  
(AMOLED) technology, 204

Active power, 235–236

Active sensory test, 58–59

Active/passive wearables, 8–9

ActiveBelt, 48–49

Activity monitoring, 412, 549–552

for epilepsy patients, 553–554

physical capabilities, 409–411

Activity of daily life (ADL) score, 95–96

Adaptive behavioral interventions, 411

ADC. *See* Analog-to-digital converter

Additional power loss, 306

Adenosine triphosphate (ATP) consumption, 133

Aerobic energy, 413

Aesthetics, 7

changes

adoption of innovation and, 30–32

fashion cycle, 30–32

individual and group identity, visual expression of,  
29–30

social interpretation of, 26–30

visual processing of, 26–28, 29f

Affinity propagation (AP), 605

Agglomerative hierarchical clustering (AHC), 605

Agilent Advanced Design System, 444

AHLoS (ad-hoc localization system), 509–510

a-IGZO, 204–215

analog circuits based on, 214–215

digital circuits based on, 211–213

Akaike's information criterion (AIC), 393

Algorithms, need for, 356–364

battery selection, 356–358

effective capacity and lifetime, 357–358

maximum continuous current, 357

maximum pulse current capability, 357

supplied voltage, 357

hardware platform, 358–359

data acquisition, 359

wireless transmission controller, 359

practical example and impact of data compression,  
361–364

node design, 361–362

optional data compression, 362

power performance results, 362–364

wireless transmitter, 359–361

air data rate vs. effective data rate, 360–361

hardware overhead, 360

quality of packet transmission, 360

Ambient assisted living (AAL), 493

Amorphous materials, 91

Amorphous oxide semiconductors, electronics based on,  
199–200

improvements and limitations, 215–223

double-gate architecture, 218–219

flexible a-IGZO TFTs with vertical channel,  
219–223

TFTs by self-aligned lithography, 216–217

plastic electronics for smart textiles, 223–229

textile e-nose, 224–226

textile integrated near-infrared spectroscopy,  
226–229

- Amorphous oxide semiconductors, electronics based on  
     (Continued)  
     semiconductors employed in, 202–204  
     thin-film transistors (TFTs), 200–202  
         analog and digital circuits, 211–215  
         based on A-IGZO, 204–215  
         fabrication and characterization, 205–207  
         influence of mechanical strain, 207–211
- Amorphous silicon, 204
- Amplifier design techniques, 332–335  
      $g_m/I_D$  design methodology, 334  
     noise and power perspective, 333–334  
     stability perspective, 334–335
- Anaerobic energy, 413
- Analog front-end for human body communication,  
     440–448  
     design of, 441–445  
     operation of CDR, 445–448  
     performance of, 448–449  
     received signal, 441
- Analog signal processing, 372–373, 377–378
- Analog-to-digital-converter (ADC), 359, 438  
     low-power design for, 340–342  
     sigma-delta ADCs, 341–342, 342f, 343f  
     successive-approximation-register (SAR),  
         340
- Angle of arrival (AOA), 500
- Anisotropic magneto-resistance (AMR)  
     HMC1043 sensors, 574  
     sensors, 92
- Anorexia nervosa, 592
- Antenna effective area, 300–301
- Antenna equivalent circuit elements, 303f
- Antenna-rectifier co-design, 317–320
- Antenna-rectifier interface  
     with impedance matching network,  
         302f  
     with passive voltage boosting, 304f  
     voltage, 302–305
- Aoyagi et al. model, 456  
     power delay profile model, 461
- APIT, 502
- Apparel manufacturing, 18
- Apparel-body-construct, 26–27, 29f  
     characteristics of, 27
- Application specific integrated circuit (ASIC),  
     278  
     design and demonstrator, 278–279
- ASK-BAN, 483–484
- Assistive technology (AT), 563
- Astrin model, 459–460
- Atrial fibrillation (AF), 545–546
- Attribute-based encryption (ABE), 478
- Authenticated secret key establishment in WBAN,  
     483–484  
     ASK-BAN, 483–484  
     challenges, 483
- Authentication  
     biometric-based, 479  
     channel-based, 479  
     methods, 480–481  
     proximity-based, 480  
     public key-based, 478  
     schemes, 480  
     symmetric key-based, 477  
     WBAN device authentication techniques,  
         476–481
- Autocorrelation function, 94
- Automatic Ingestion Monitor (AIM), 610–611, 610f
- Automatic signal processing and pattern-recognition  
     methods for food intake detection, 600–604  
     from chewing, 602–603  
     from hand gestures, 601–602  
     from imagery, 601  
     from swallowing, 603–604
- Autozeroing techniques, 329, 336
- Available power, 300–301
- B**
- Ballistocardiogram, 530
- Banister impulse response (IR) model, 413–414
- Battery selection, 356–358  
     effective capacity and lifetime, 357–358  
     maximum continuous current, 357  
     maximum pulse current capability, 357  
     supplied voltage, 357
- Bayesian information criterion (BIC), 386–387, 393
- Beam-type accelerometers, 86
- Beer-Lambert law, 108–109
- Behavior change, physical activity. *See* Physical activity  
     behavior change
- Berg Balance Scale (BBS), 97
- Bessel filter, 444
- Big data concept, wearable role in relationship to, 4–5
- Big Data* performance testing, 366–369
- Bimorph configuration, 87, 87f
- Binge eating, 592
- Bio and chemical sensors. *See* Chemical and  
     biochemical sensors
- Biomechanical sensing, 161–163
- Biometric-based authentication, 479
- Biometrics/motion, 482
- Biopotential sensors, 160  
     low-power analog circuit design techniques for,  
         327–340
- Biopotential signals and characteristics, 324–325

- Biostamp technology, 76
  - Bit error rate (BER) performance, 431–432, 472
  - Bland-Altman plot, comparing ECG- and PPG-derived heartbeat intervals, 122, 124f
  - Blood pressure measurement, 523–526
  - Bluetooth, 497–498
  - Body area networks (BAN), 425
  - Body location and handedness, 34–35
  - Body sensor networks (BSNs)
    - classification accuracy, 399–400
      - GMM, 399
      - k-means, 399
    - movement template evaluation, 402–404
    - parameter trade-offs, 400–402
  - classifier, 396–397
  - comparison metric, 394–396
    - N-gram selection, 395–396
  - data-mining model, 397–398
  - query processing, 397–398
  - training, 397
  - data representation, 391–394
    - motion transcripts, 394
    - primitive construction, 391–393
  - desirable solution properties, 390
  - experimental results, 398–404
  - machine learning approaches, 385–388
    - mining techniques, 386–387
    - structural recognition in BSN, 387–388
  - mining techniques for, 383–385, 389
  - pilot application, 390
  - recommendations, 404
  - wearable sensor hardware, 389–390
- Body sensors, 409, 411
- Body temperature measurement, 528–529
- Body-attached sensors, 595–600
  - chewing monitoring, 597–599
  - hand gestures monitoring, 596–597
  - swallowing monitoring, 599–600
- Bodygem, 137
- Body-worn heat-flow sensors, 131–132
  - body media, 141
  - design considerations, 142–144
- direct calorimeters, 137–141
  - historical heat-flow gauges, 138–141
  - historical water-cooled suits, 138
- indirect calorimeters, 137
  - Cosmed K4 b<sup>2</sup>, 137
  - MicroLife Bodygem, 137
- MetaLogics Personal Calorie Monitor (PCM), 141
- motion-based estimation of energy expenditure, 136–137
- performance, 144–146
- validations, 146–149
  - comparison to metabolic cart, 146–147
  - comparison to room calorimeter, 147–149
- Brain-computer interfaces (BCIs), 568, 569f
- Bravo™, 555
- Breath analysis, 67, 72
- Bulimia nervosa, 592
- Bus, 13–14
- ## C
- Cadence, 94
  - Caloric density (CD), 608
  - Capacitive contact electrodes, 326
  - Capacitive wireless energy transfer in the near field, 254–255
  - Capacitively coupled communication through human body, 425–426
  - Capacitively coupled electrodes, 518–519, 519t
  - Carbon dioxide (CO<sub>2</sub>) sensors, 79, 80f
  - Carbon monoxide (CO) sensors, 79, 80f
  - Carbon nanotubes (CNTs), 203–204
  - Carbopol 971 P, 558–559
  - Cardiovascular diseases (CVDs)
    - diagnosis of, 545–547
    - future development of, 547–548
    - monitoring risk factors of, 544–545
    - wearing sensors for, 544–548
  - Cardiovascular system
    - monitoring, biosignal sensors for, 522–529
      - blood pressure measurement, 523–526
      - body temperature measurement, 528–529
      - plethysmogram and oximeter, 526–527
      - respirometry, 527–528
  - CC2500, 361–362
  - Centre of Wireless Communications (CWC)
    - Oulu University model, 465–468
  - Centroid, 501
  - Channel impulse response (CIR), 479
  - Channel model for human body communication, 432–434
  - Channel properties of human body, 427
  - Channel-based authentication, 479
  - Channel-length scaling, 202
  - Characterization methods for food intake, 604–609
    - ingested mass and energy intake
      - from counts of chews, swallows and hand gestures, 607–609
      - from imagery estimation of, 606–607
    - number of foods in a meal recognition, 604–606
  - Charge pump rectifier (CPR) topologies, 309–313
  - Charged amplifier, 87f
  - Chemical and biochemical sensors, 65–66
    - application areas, 78–79
    - personal health, 78

- Chemical and biochemical sensors (*Continued*)  
 safety and security, 79  
 sports performance, 78–79  
 challenges, 74–78  
 interface with body, 75–76  
 power requirements, 77–78  
 sensor stability, 74–75  
 textile integration, 76–77  
 colorimetric sensors, 72–73  
 components of, 68  
 electrochemical sensors, 73–74  
 sample handling, 68–72  
 microneedle technology, 70–72  
 sampling gases, 72  
 transport of fluids in textile, 68–70  
 sensors types, 72–74  
 system design, 68–74  
 working principle of, 66f
- Chemiresistors, 224–225
- Chest-strap wearable HR monitor, 118–119
- Chewing  
 estimation of ingested mass and energy intake from, 607–609  
 food-intake detection from, 602–603  
 monitoring, 597–599
- Chews preceding a swallow (CPS), 605
- Chopper stabilization techniques, 336–337
- “Chorus” 486–488
- Ciphertext, 478
- Circular knitting machine, 156–158
- Classification accuracy, 399–400
- Classifier, 396–397
- Clinical assessment, 582–586  
 command definition, 583  
 magnet attachment, 583  
 response time measurement, 583–586  
 powered wheelchair navigation, 584–585  
 results, 585–586  
 subjects, 583  
 training session, 583
- Clock and data recovery (CDR) circuit, 441–442, 444–448
- Clustering algorithms, 387
- CMRR enhancement techniques, 338–340  
 DRL technique, 339–340  
 input impedance boosting techniques, 340
- Co-designing antenna–rectifier, 317–320
- Colorimetric sensors, 72
- Command classification, 577–578
- Commercialization of human body communication, 449–450
- Common-mode rejection ratio (CMRR). *See* CMRR enhancement techniques
- Communication functions of dress, 26–27, 29–30
- Complementary metal-oxide-semiconductor (CMOS)  
 digital logic, 201  
 transistor, 303, 306–307
- Computers, wearable, 9
- Conduction loss resistance, 302
- Conductive bicomponent fibers yarn, 158
- Conductive elastic yarns, 155
- Conductive fabrics, 153–154, 154f, 160
- Conductive polymers (CPs), 224–225
- Conductive textile, 160
- Conductive yarns, 153–154, 154f, 177–178
- Conductivity sensor, 165–166
- Conspicuity and social weight, 33–34
- Constrained least square technique (CTLS), 509–510
- Consumer spectrum, for fashion trends, 31f
- Contact area  
 deformation of, 50–51  
 separation of, 51, 51f
- Continuous feedback, 47–48
- Continuous wavelet transform (CWT), 378
- Continuous-time latent Markov (CT-LM) model, 420
- Control loop optimization, 316f
- Convergence and interactive textiles, 14–15
- Core spun elastomeric yarn, 155
- Coriolis effect, 89
- Coronary heart disease (CHD), 547
- Cosmed K4 b<sup>2</sup>, 137, 138f
- Cramér-Rao lower bound (CRLB), 509–511
- Critical power (CP), 413  
 model, 413–414
- Cryptographic authentication mechanisms in WBAN, 477–478  
 public key-based authentication, 478  
 symmetric key-based authentication, 477
- Cuff-less blood-pressure, 545f
- Cultural norms, 35–36
- Cymbet thin-film batteries, 269
- Cystic fibrosis diagnosis  
 gold-standard technique for, 67
- ## D
- Daily life  
 HR monitoring during, 121–122  
 monitoring, 517
- Data clustering, 392–393
- Data compression and sensor fusion, 587
- Data fusion, 499–500  
 techniques, 499
- Data-information-knowledge-value paradigm, 4–5, 4f  
 big data, emerging concept of, 4–5  
 medical loss ratio and wearables, 5

- Data-mining model, 397–398
  - query processing, 397–398, 399*f*
  - training, 397, 398*f*
- DC-DC converter, 265–267
  - design for ultra-low input voltages, 241–245
    - maximum-powerpoint tracking for impedance matching, 244–245
  - topologies, 240–241
- Deformation of the contact area, 50–51
- DELTA-4, 46
- Deoxyhemoglobin, 527
- Device authentication techniques, of WBAN, 476–481
- Device-free localization, 499
  - data fusion, 499–500
  - hybrid techniques, 499–500
  - SLAM (simultaneous location and mapping), 500
  - wearable radios, 500–513
- Diffie–Hellman key exchange, 480
- Digital circuits, low-power, 342–345
- Digital life
  - ecosystem enabling, 5–6
  - world of variables (WOW), 2*f*
- Digital-to-analog converter (DAC), 438
- Direct calorimeters, 132, 135–141
  - historical heat-flow gauges, 138–141
  - historical water-cooled suits, 138
- Direction cosine matrix (DCM), 384
- Distribution of harvested power in a realistic environment, 308–309
  - ambient RF power, 309
- Dobby loom, 182–183
- Dolmans, G. and Fort, A.
  - model suggested by, 456–458
  - wideband model, 461–462
- Drain current, in weak inversion, 328
- Dress, communication functions of, 26–27, 29–30
- Driven right leg (DRL) technique, 339–340
- Dry electrodes, 71, 167–168, 326–327, 340, 518–520, 519*t*, 568
- Dual-mode Tongue Drive System (dTDS), 578–581
  - advantages of multi-modal system, 578
  - block diagram of, 579*f*
  - hardware specifications, 582*t*
  - major components of, 580*f*
  - wearable dTDS prototype, 580–581
    - wireless headset, 580–581
    - wireless USB transceiver, 581
- Dynamic voltage scaling, 378
- E**
- Eating disorders, 592
- Eccentricity, 50–51
  - desired and measured, 54*f*
  - weight and friction changes, 52*f*
- Echocardiography, 107
- Ecological Momentary Assessment, 419
- Ecosystem
  - to enabling digital life, 5–6
  - smart mobile communication devices, 6
  - social media tools, 6
- Electric field, 428–430
- Electrical conductivity, 153
- Electrocardiogram (ECG), 324, 543–544
  - monitoring by non-contact electrodes, 518–522
  - technique, 106
- Electrochemical sensors, 73
- Electrode noise, 326–327
- Electrode's structure, effects of, 428–434
  - channel model for human body communication, 432–434
  - electromagnetic environment effects outside the human body, 430–432
- Electrode-body interface, 325–327
- Electrodes
  - dry, 71, 167–168, 326–327, 340, 518–520, 568
  - and ECG monitoring by non-contact electrodes, 518–522
  - textile, 190
  - types of, 519*t*
  - wet, 71, 167–168, 325–327
- Electroencephalogram (EEG), 324, 353
- Electroglottograph (EGG) device, 600
- Electromagnetic environment effects outside the human body, 430–432
- Electromagnetic interference (EMI), 347
- Electromagnetic wireless energy transmission in the far field, 255–256
- Electromyography (EMG), 324
  - based controllers, 567
  - for swallowing, 599
- Electronic aids to daily life (EADLs), 587–588
- Electronic load consumption, 270
- Electronic medical records (EMRs), 478
- Electronic textiles (e-textiles), 175–198
  - applications, 186–195
    - RFID Textiles, 191–195
    - textile electrodes, 190
    - textile switch, 189–190
    - touchpad, 186–188
  - equivalent pattern for, 181*f*
  - textiles, 177–185

- Electronic textiles (e-textiles) (*Continued*)  
   looms, 182–185  
   yarn, 177–179
- Electronics  
   and communications, 18  
   flexible, 10  
   and textiles, 14–15, 18
- Electro-oculograms (EOG), 565–567
- Electro-tactile feedback devices, 46, 48
- Elliptic curve cryptography (ECC), 478
- Embedded signal-processing, 366
- Embroidery, 175
- Emotional state assessment, systems for,  
   171–172
- Energy consumption  
   active, leakage, and total, 344  
   of digital circuit, 344f  
   and power consumption issues, 267–270
- Energy expenditure (EE), 131–132  
   background, 132–136  
   motion-based estimation of, 136–137
- Energy expenditure of the activity (EEact),  
   100–101
- Energy harvesting  
   from human body, 235  
     AC-DC converters, 251–253  
     AC-DC linear rectifiers, 285–290  
     AC-DC nonlinear rectifiers, 290–292  
     energy and power consumption issues,  
       267–270  
     from foot motion, 245–253, 285–292  
     physical principles, 245–251  
   from light, 259–267  
     DC-DC converter, 265–267  
     MPPT algorithms, 292–296  
     physical principles, 260–265  
   radio frequency identification (RFID) technology,  
     256–257  
   systems  
     block diagram of, 236f  
     introduction to, 235–237  
   from temperature gradient, 237–245, 275–285  
     ASIC design and demonstrator, 278–279  
     bipolar DC-DC converter design, 277  
     DC-DC converter design for ultra-low input  
       voltages, 241–245  
     DC-DC converter topologies, 240–241  
     maximum-powerpoint tracking for impedance  
       matching, 279–285  
     thermoelectric generators, 237–240  
   wireless energy transmission, 253–259  
     capacitive wireless energy transfer in the near  
       field, 254–255  
     electromagnetic wireless energy transmission in  
       the far field, 255–256  
     inductive wireless energy transfer in the near  
       field, 254  
     wireless power transmission regulations, 257–258  
     wireless system, influence of the body on, 258–259
- Energy intake and ingested mass  
   from counts of chews, swallows and hand gestures,  
     607–609  
   from imagery estimation of, 606–607
- Energy transducer, 236
- E-noses, 224–226
- Entertainment application, of wearables, 16t
- Environmental control units (EDUs), 587–588
- Epidermal electronics system (EES), 555–556
- Equivalent isotropic radiated power (EIRP), 300–301
- Ergonomics, 27
- E-Sponder, 168
- E-textiles. *See* Electronic textiles
- EU BIOTEX project, 68–69
- EvAAL (Evaluating AAL Systems through  
   Competitive Benchmarking), 494
- Evaluation metrics, of localization systems, 494–495
- Evaporative heat flow, 142–144
- Exhaustion, 413
- ExoPhalanx, 47
- Exoskeletons, 46–47
- Expectation-maximization (EM) estimator, 509–510
- Explorer program, 38–39
- Expressive characteristics, of apparel-body-construct,  
   27
- ExpWear*, 20
- Extended Kalman filter, 499
- External magnetic interference (EMI) attenuation,  
   576–577
- External Tongue Drive System (eTDS) headsets, 573f,  
   575–576  
   block diagram of, 574f
- Eye-tracking systems, 565–567, 566f
- F**
- Fabric, 5–6, 9, 12–13, 17, 153  
   touchpad, 187f
- Fabricated antenna, 317f
- Fading, 458, 459t
- Fall detection, 98–99
- Fall risk assessment with rehabilitation battery, 97–98
- Fashion  
   aesthetic change in, 30–32  
   social leadership in, 32
- Feature extraction (FE), 577
- Fick's first law of diffusion, 164–165
- Field-programmable gate array (FPGA), 441

- Fill factor (FF), 263  
 Fingercap-type wearable sensorimotor enhancer, 56  
 Fingerprinting, 504–507  
 Fingertip-mounted devices, 46–47  
 Fisher information, 512  
 Fixed sensors, 500  
 Flat knitting, 156–158  
 Flexible electronics, 10, 554–556  
   circuits, 199–200  
 Flexible goniometer for articular motion, 537–538  
 Flicker noise, 329  
 Food intake  
   applications, 609–611  
     laboratory vs. free-living monitoring, 609–610  
     wearable devices for free-living monitoring, 610–611  
   automatic detection, signal processing and pattern-recognition methods for, 600–604  
   from chewing, 602–603  
   from hand gestures, 601–602  
   from imagery, 601  
   from swallowing, 603–604  
   characterization, methods for, 604–609  
   ingested mass and energy intake from counts of chews, swallows and hand gestures, 607–609  
   ingested mass and energy intake from imagery estimation of, 606–607  
   number of foods in a meal recognition, 604–606  
   detection by wearable sensors, 594–600  
   body-attached sensors, 595–600  
   handheld devices, 594–595  
 Food-related hand gestures, 602  
 Foot motion, energy harvesting from, 245–253  
   AC-DC converters, 251–253  
   physical principles, 245–251  
 Force feedback devices, 46–47  
 Force monitoring during walking, 540–541  
 Fractional open circuit voltage algorithm, flowchart of, 294f  
 Free space path loss, 301  
 Frequency domain HR approaches, 117–118  
 Frequency selective code (FSC), 434–436  
 Frequency-modulation-based vibrotactile (FMBV) feedback, 47–48  
 Frequency-selective (FS) spreader, 434–436  
 Frequency-selective digital transmission (FSDT), 434–440, 448  
 Friction and weight illusion display, 52–54  
   based on fingertip manipulation, 48–54  
   deformation of the contact area, 50–51  
   haptic sensation creation, 48–50  
   weight and friction illusion display, 52–54  
 Friis' transmission equation, 300–301  
 Fully custom hardware, 373–374  
 Fully hardware electronics, 378  
 Functional attributes, of wearables, 7–11  
 Functional electrical stimulation (FES), 169–170  
  
**G**  
 Gait cycle characteristics, 95f  
 Gamer, immersive, 1–2  
 Gas sensors, 72  
 Gastroesophageal reflux disease (GERD), 555  
 Gastrointestinal diseases  
   device-transferring technique, 558  
   high-performance flexible sensory system, design of, 557  
   in-body chemical and biological flexible sensors and systems, 556–557  
   fabricating flexible sensory system, technical challenges for, 557  
   on-body wearable sensors designed based on flexible electronics, 555–556  
   wearing sensors for, 555–559  
 Gaussian mixture models (GMM), 392–393, 399  
 Gaussian noise, 434  
 Generalized tonic-clonic seizures (GTCS), 553  
 Generic processors, 377  
   with accelerators, 377  
 Gesture  
   body location and handedness, 34–35  
   conspicuity and social weight, 33–34  
   cultural norms, 35–36  
   passive and active, differentiation of, 37–38  
   social acceptance of, 33–38  
   vocabulary of, 36–37  
 Giant magnetoresistance (GMR) sensors, 92–93  
 Glass, design of, 39  
 GlucoDay® S, 78  
 Glucose, 67, 70–71  
 GNSS (global navigation satellite systems), 493  
 Google Glass, 10–11  
   case study, 38–41  
 Gradient layer calorimetry, 135–136  
 Graphene, 203–204  
 Graphical user interface (GUI), 576  
 Gregory Abowd, 38  
 Grounded haptic devices, 46  
 Group identity, visual expression of, 29–30  
 Gyroscopic sensors, 88–90  
  
**H**  
 H2 heart rate sensor, 155  
 Hadamard code, 436  
 Hall effect, 90



- Hand gestures
    - detection of, 601–602
    - estimation of ingested mass and energy intake from, 607–609
    - monitoring, 596–597
  - Handedness, body location and, 34–35
  - Handheld devices, 594–595
  - Handshaking mode
    - in wireless USB transceiver, 581
  - HapticGEAR, 47
  - Haptics
    - meaning of, 45
    - sensation creation, based on finger pulp manipulation, 48–50
    - and tactile sensory capability improvement, for enhanced motor performance, 54–56
  - Hardware platform, 358–359, 372–374
    - data acquisition, 359
    - wireless transmission controller, 359
  - Harvested energy, 269–270
  - HBC AFE block, 438
  - HBC IF block, 438
  - HBC PHY, 434–436, 439, 449–450
  - HBC RX block, 438
  - HBC TX block, 438
  - Head controllers, 565, 566*f*
  - Head-pointers, 565
  - Health, wearables and, 5, 8–9, 17
  - Health coaches, 416–417, 417*f*, 418*f*, 421–422
  - Health informatics, 543, 559
  - Healthcare
    - wearable chemical and biochemical sensors in, 78
  - Heart rate (HR) monitoring, 105
    - applications
      - daily life, 121–122
      - HRV, 122–125
      - sport and fitness, 118–120
    - PPG. *See* Photoplethysmography (PPG) technology
  - Heat-flow gauges (HFG), 138–141, 142*f*
  - Hemoglobin, 527
  - Hertzian contact, 50
  - High-pass cut-off frequency, for biomedical signals, 337
  - Holter, Norman, 105
  - Holter systems, 107
  - Holy Grail, 6*b*, 21
  - Horizontal flow theory, 32
  - Human body
    - gastrointestinal diseases, 555–559
    - neurological diseases, 549–555
    - wearing sensors for early detection of diseases, 543–562
      - cardiovascular diseases (CVDs), 544–548
  - Human body communication (HBC), 425
    - analog front-end for, 440–448
      - design of an analog front-end, 441–445
      - operation of CDR, 445–448
      - performance of, 448–449
      - received signal, 441
    - capacitive-coupling communication, 425–426
    - channel model for, 432–434
    - channel properties of human body, 427
    - commercialization of, 449–450
    - effects of the electromagnetic environment outside human body, 430–432
    - electrode's structure, effects of, 428–434
    - transmission scheme of, 434–440
      - frequency-selective digital transmission, 437–440
      - Walsh code, 436–437
  - Human skin, as ultimate sensor, 6*b*
  - Hunger, 591
  - Hydrogel membrane, 160, 161*f*
  - Hypertension, 523
- ## I
- IBGStar, 75–76
  - Identity-based encryption (IBE), 478
  - IEEE 802.15 working group, 434–436
  - IEEE 802.15.6 TG6 standard models, 455–464
  - IGZO TFT, 205–206, 205*f*, 206*f*
    - electrical stability of, 207*f*
  - Impedance cardiography (ICG) technique, 107
  - Impedance matching, maximum-powerpoint tracking for, 244–245
  - Impedance mismatch, losses and efficiency, 306–308
    - available components and technology, 306–307
    - regulations and maximum achievable distance, 307–308
  - Implantable sensors, 8
  - Incremental conductance (IC)
    - algorithm, flowchart of, 296*f*
    - method, 295
  - Indirect calorimeters, 131–132, 137
    - Cosmed K4 b<sup>2</sup>, 137
    - MicroLife Bodygem, 137
  - Individual and group identity, visual expression of, 29–30
  - Individual networks, 9–10
  - Indoor localization systems, 494
  - Indoor signal propagation model, 508–509
  - Inductive wireless energy transfer in the near field, 254
  - Industrial, scientific and medical (ISM) radio frequency bands, 257
  - Inertial sensors. *See* Wearable inertial sensors
  - Infinity-norm, 506*t*
  - Influence of the body on the wireless system, 258–259



“Information Anywhere, Anytime, Anyone”  
paradigm, 19

Information gain (IG), 395

Information processing, 8–9  
structure, 14–15

Information transfer rate (ITR), 583–584

Ingested mass and energy intake  
from counts of chews, swallows and hand gestures,  
607–609  
from imagery estimation of, 606–607

Ingestive behavior, 591–592, 604

Inkjet printing, 74

Innovation, adoption in wearable products, 30–32

Input impedance boosting techniques, 340

Input-referred noise, 332–333, 336

Instance-based learning, 387

Instantaneous swallowing frequency (ISF), 603

Instrumentation amplifiers (IAs)  
basic, 330–332  
implementation, 330

Integra-Mouse, 568–569, 570f

Interactions, between user and device, 33

Interconnection technology, 13

InterfaceSuit, 47–48

Interference signals, 431–432

Interoperability, 495

Interuniversity Microelectronics Center (IMEC), 239

Intraoral version of the TDS (iTDS), 586–587

Invasive wearables, 8

Ion selective electrode (ISE) sensors, 73–74

Isotropic available power, 319

## J

Jacquard loom, 183–184

Joint motion measurement, using two accelerometers  
set near both sides of joint, 538–540

Joule heating effect, 237

## K

Kalman filters, 384, 499

Kang et al. model, 463

Kapton film, 76–77

Katz ADL score, 96

Kim et al. model, 464

Kinect technologies, 412

K-means, 387, 392–393, 399

K-nearest neighbor method (KNN), 505  
approach, 387  
classifier, 577

Knitted electronic textiles, 153

biomechanical sensing, 161–163  
circular knitting machine, 156–158  
emotional state assessment, systems for, 171–172

flat knitting, 156–158

interlaced network, 155–159

non-invasive sweat monitoring by textile sensors,  
163–166

physiological state monitoring, textile sensors for,  
159–161

plated knitting, 157f

remote rehabilitation, system for, 168–170

smart fabrics and interactive textile platforms for  
remote monitoring, 166–168

Knitted piezoresistive fabric (KPF) sensors, 161–163

P\_KPF sensor, 161–162

T\_KPF sensor, 161–162

## L

Laboratory vs. free-living monitoring, 609–610

Laggards, fashion, 32

Lapka™ breath alcohol monitor, 72

Laser-based systems, 499

Lawton Instrumental ADL (IADL) scale,  
96

Lead zirconium titanate (PZT), 245

Levenstein distance, value of, 387–388

Lifetime of battery, 358

Light emitting diodes (LEDs), 226–227

Linear regression, 387

Line-of-sight (LOS), 455

Lithographic technique, 159

Litmus test, for wearables, 18–19

Load and source variations, effect of, 313–316  
antenna-rectifier co-design, 317–320  
measurements and verification, 318–320  
optimum power transfer techniques, 314–316

Localization, in wireless body area networks,  
493–516

device-free localization, 499

data fusion, 499–500

hybrid techniques, 499–500

SLAM (simultaneous location and mapping),  
500

wearable radios, 500–513

evaluation metrics, 494–495

indoor signal propagation model, 508–509

multi-lateration algorithm, 509–511

maximum-likelihood distance estimator and  
cramér-rao bounds, 511–513

RSS information, 511–512

range-based, 503–513

deterministic approaches, 505

fingerprinting, 504–507

probabilistic approaches, 505–507

propagation model, 507–513

radio map, 504

## Localization, in wireless body area networks

(Continued)

- range-free, 501–503
  - APIT, 502
  - centroid, 501
  - SeRLoc, 502–503
- technologies, 495–500
  - RFID tags, 496–497
  - ultrasound systems, 496
  - ultra-wide band systems, 497
  - wearable active transducers, 496–497
- Log-likelihood formulation, 421
- Lognormal distribution, 466*t*
- Looms, 182–185
- Loss-free resistor, 302
- Low-dropout regulator (LDO), 316
- Low-power analog circuit design techniques
  - amplifier design techniques, 332–335
    - $g_m/I_D$  design methodology, 334
    - noise and power perspective, 333–334
    - stability perspective, 334–335
  - for biopotential sensors, 327–340
  - chopper stabilization techniques, 336–337
  - CMRR enhancement techniques, 338–340
    - DRL technique, 339–340
    - input impedance boosting techniques, 340
  - instrumentation amplifiers
    - basic, 330–332
    - implementation, 330
  - noise across sampling capacitor, 335–336
  - pseudoresistors for sub-Hz high-pass cut-off, 337–338
  - subthreshold weak inversion operation of MOS transistors, 327–329
- Low-power biopotential acquisition
  - architectural design strategies, 345–346
  - power domain design, 347
- Low-power design for ADCs, 340–342
- Low-power digital circuit design techniques, 342–345

**M**

- Machine learning approaches to data mining, 385–388
  - mining techniques, 386–387
  - structural recognition in BSN, 387–388
- Magnetic sensors, 90–93, 571–573, 579, 581
  - giant magnetoresistance sensors, 92–93
  - magnetoimpedance sensors, 91–92
  - magnetoresistance sensors, 92
  - parameters for, 96*t*
- Magnetic tracer, 571–572, 574
- Magnetoimpedance sensors, 91–92
- Magnetoresistance sensors, 92
- Mahalanobis-norm, 506*t*
- Manchester-coded preamble, 438, 441, 444–445
- Market, wearables in, 18–19
- Markov model, 420
- Mass-market consumer, 31
- Material conductivity, 258
- Maximum power point tracking (MPPT) algorithms, 265, 283, 292–296, 314–315
  - flowchart of, 266*f*
- Maximum-a-posterior (MAP) estimate, 506–507
- Maximum-likelihood (ML) estimate, 506–507
- Maximum-likelihood distance estimator
  - and cramer-rao bounds, 511–513
- Maximum-likelihood estimators (MLEs), 511
- Maximum-powerpoint-tracker, analog implementation of, 284*f*
- Mean body temperature, 135*f*
- Mechanoreceptors, 45
- Medgem, 137
- Medical Loss Ratio (MLR), 5
- Meissner oscillator based converter, 276*f*, 277*f*
- MetaLogics Personal Calorie Monitor, 141, 148–150
- Metal-oxide-semiconductor (MOS) transistors, weak inversion operation of, 327–329
- Metal-plated yarns, 177–178
- Meta-wearables
  - applications of, 15–16, 16*t*
  - attributes of, 12–13
  - realization of, 13–15
  - textiles and clothing, 11–16, 20
- Micro-controller unit (MCU), 574–575, 581
- Micro-fluidic systems, 68
- MicroLife Bodygem, 137
- Microneedle technology, 70–72
- Microsoft Kinect, 412
- “Midas touch” problem, 567
- Minimal-force grasping, 59–60
- Minimum energy point (MEP), 344
- Miniutti et al. model, 458
- Mio’s Alpha device, 119, 120*f*
- Mobile sensors, 500, 503–504
- Modified p-norm, 506*t*
- Moore’s law, 199–200
- MOSFET operation, 327
- Motion artifact processing
  - changes in pressure between optical probe and skin, 115
  - in HR monitoring, 114–115
  - relative motion of sensor-skin interface, 115
  - tissue modifications due to movements, 114
- Motion artifacts, 115–117, 160, 228–229
  - minimization and removal, 114–115
- Motion transcripts, 394
- Motion-based devices, 136

- Motion-based sensors, 131  
 Motivational interviewing, 416, 417f  
 Motor skill test, 59–60  
 MPPT algorithms. *See* Maximum power point tracking (MPPT) algorithms  
 MSP430, 354, 362, 369–370, 377  
 Multi-lateration algorithm, 509–511  
     maximum-likelihood distance estimator and cramer-rao bounds, 511–513  
     RSS information, 511–512  
     multiple samples case, 512–513  
     single sample case, 511–512  
 Multi-layered textile, 180f, 181f  
 Multi-modal system, advantages of, 578  
 Multi-modal TDS, 587  
 Myocardial infarction (MI), 547
- N**
- Naive Bayes, 386  
 Narrowband communications, 455  
 Near-infrared spectroscopy, 107, 226–227  
 Needle electrodes, 518–519, 519t  
 Nelder-Mead, 572–573  
 Neurological diseases  
     future development, 554–555  
     motor activity monitoring intervention for neurological rehabilitation, 549–552  
     seizure activity monitoring for epilepsy patients, 553–554  
     wearing sensors for, 549–555  
 Neurological rehabilitation system (NRS), 168–169, 169f  
 Neutral command, 576, 578  
 Newton iterative algorithm, 509–510  
 N-grams, 387–388  
     selection, 395–396  
 NMOS and PMOS field-effect transistors, in CMOS process, 327, 328f  
 Noise  
     across sampling capacitor, 335–336  
     and power perspective, 333–334  
 Noise efficiency factor (NEF), 332  
 Nominal operating cell temperature (NOCT) parameter, 263  
 Non-contact electrodes, 326–327  
 Non-cryptographic authentication mechanisms, in WBAN, 478–480  
     authentication  
         methods, 480–481  
         schemes, 480  
     biometric-based authentication, 479  
     channel-based authentication, 479  
     proximity-based authentication, 480  
     Non-food-related hand gestures, 602  
     Non-grounded haptic devices, 46  
     Non-invasive sweat monitoring by textile sensors, 163–166  
     Non-invasive wearables, 8  
     Non-line-of-sight (NLOS), 455  
     Non-restrictive heart-rate measurement, 530–532  
     Nyquist-Johnson noise, 335
- O**
- Obesity, defined, 591  
 “OK Glass,” verbal activation command, 37, 40–41  
 Olsson, Isabelle, 39  
 On-body communications  
     analytical models, 453  
     channel models for, 453–474  
     empirical models, 453  
     IEEE 802.15.6 TG6 standard models, 455–464  
         Aoyagi et al., power delay profile model, 461  
         Aoyagi et al. model, 456  
         Astrin model, 459–460  
         Dolmans and Fort model, 456–458  
         Dolmans and Fort Wideband model, 461–462  
         Kang et al. model, 463  
         Kim et al. model, 464  
         Miniutti et al. model, 458  
     independent studies, 464–471  
         CWC Oulu University model, 465–468  
         Queen’s University of Belfast models, 470–471  
         Reusens et al. model, 469–470  
         University of Birmingham and Queen Mary University models, 471  
         Wang et al. model, 468–469  
 On-body interactions, 33–38  
 On-chip pseudoresistor implementations, 338f  
 One-point touch test, 58  
 Opamp IA, 330  
 Open-circuit voltage, 260  
 Open-loop Bode plot, for amplifiers, 334–335, 335f  
 Operational transconductance amplifier (OTA), 332, 333f, 339  
 Optical shunting effect, 113–114  
 Optimum duty cycle, 289  
 Optimum power transfer techniques, 314–316  
 Optomechanical design, 115–116  
 Organic electrochemical transistor (OECT), 73–74  
 Organic semiconductors, 202–203  
 Output power, 236  
 Oximeter, 526–527  
 Oxyhemoglobin, 527

## P

- Packet radio systems, 497–498
- Paralysis, assistive devices for individuals with, 563–570
  - brain-computer interfaces (BCIs), 568, 569*f*
  - electromyography (EMG) based controllers, 567
  - eye-tracking systems, 565–567, 566*f*
  - head controllers, 565, 566*f*
  - sip-n-puff, 564–565, 565*f*
  - tongue-operated devices, 568–570
  - voice controllers, 567–568
- Paralysis, causes of
  - in the U.S., 564*f*
- Parkinson's disease, 384–385, 549
  - inertial sensors and, 99–100
- Particle filters, 499–500
- Passive and active gestures, differentiating between, 37–38
- Passive interactions, with wearable system, 33
- Passive power, 235–236
- Passive voltage boosting, 303–304, 304*f*
  - antenna-rectifier interface equivalent circuit model with, 304*f*
- Path loss models, 457–458, 462*t*
  - vs. distance, 469*t*
- Patient Protection and Affordable Care Act of 2010, 5
- Patricia tree, 396–397
- Pattern matching, 503–504
- Payer, 18–19
- PDR (pedestrian dead reckoning), 498–500
- Peltier effect, 237
- Peripheral arteries disease (PAD), 547
- Permanent magnetic tracer, 574
- Personal Calorie Monitor (PCM), 132*f*, 141
- Personal networks, 9–10
- Personalized behavior-change interventions, sensors and, 410–411
- Personalized intervention plans, 410–411, 417*f*
- Personalized mobile information processing, 3–4
- Perturb and observe (P&O) algorithm, 292, 294–295
  - flowchart of, 295*f*
- Peyton Manning's Smart Jersey, 20
- PHANToM, 46
- Philips Lighting project, 16*t*
- Phonocardiography (PCG) technology, 107
- Photodiodes, 260
- Photoplethysmograph fingernail sensor, 55–56
- Photoplethysmography (PPG) technology, 107–118
  - factors affecting quality of signal, 113–114
  - history, 108
  - measurement principles, 108–112
  - measurement sites, 112–113
  - motion artifact minimization and removal, 114–115
  - changes in pressure between optical probe and skin, 115
  - relative motion of sensor-skin interface, 115
  - tissue modifications due to movements, 114
- optomechanical design, 115–116
- signal processing algorithm, 117–118
- Phototransistors, 260
- Photovoltaic (PV) cell, 259
- Physical activity behavior change, 409–424
  - framework for quantitative modeling of, 416–418
  - to guide intervention programs, 420–422
  - modeling physical activity, 413–414
    - Banister impulse response (IR) model, 414
    - critical power (CP) model, 413–414
  - physical activity body sensor technology, 411–412
  - physical activity monitoring capabilities, 409–411
    - sensors and personalized behavior-change interventions, 410–411
  - stages of change, assessing, 419
- Physical activity measurement, wearable sensors for, 536–541
  - flexible goniometer for articular motion, 537–538
  - force monitoring during walking, 540–541
  - joint motion measurement, using two accelerometers
    - set near both sides of joint, 538–540
- Physical attributes, of wearables, 7–11
- Physical layer (PHY), 426
- Physical sensor, 517
- Physiological sensor, 517
- Physiological signal measurement, wearable sensors for, 518–541
  - cardiovascular system monitoring, biosignal sensors for, 522–529
    - blood pressure measurement, 523–526
    - body temperature measurement, 528–529
    - plethysmogram and oximeter, 526–527
    - respirometry, 527–528
  - electrodes, types of, 519*t*
    - and ECG monitoring by non-contact electrodes, 518–522
- physical activity measurement, wearable sensors for, 536–541
  - flexible goniometer for articular motion, 537–538
  - force monitoring during walking, 540–541
  - joint motion measurement using two
    - accelerometers set near both sides of joint, 538–540
- sleep monitoring, biosignal sensors for, 530–536
  - ballistic cardiogram, 530
  - non-restrictive heart-rate measurement, 530–532
  - sheet type respiratory and body motion sensor, 533
  - video camera, 533–536

- Physiological state monitoring, textile sensors for, 159–161
- Piezoelectric accelerometers, 87
- Piezoelectric constants, definition of, 247*t*
- Piezoelectric materials, 245–246, 248
- Piezoresistive fabric sensors, 158
- Piezoresistive sensors, 160
- Piezoresistive textile sensors, 162
- Pink noise. *See* Flicker noise
- Pinstripe e-textile interface, 37–38
- PIR (presence infra-red) sensors, 499
- P\_KPF sensor, 161–162
- Plain weave, 179, 180*f*
- Plated knitting, 157, 157*f*
- Plethysmogram, 526–527
- photoelectric, 526*f*
- PMOS-based MOS-bipolar pseudoresistors, 337–338
- P-norm, 506*t*
- Point-in-triangulation test (PIT), 502
- Polydimethylsiloxane (PMDs), 557
- Polyvinylidene fluoride (PVDF) film, 245, 251
- Poma Wearable PC, 9
- PossessedHand, 48
- Power consumption, 267–270
- Power conversion efficiency (PCE), 306–308, 310
- Power delay profile (PDP) model, 461
- Power density, 300–301
- Power density values for different lighting conditions, 260*t*
- Power dissipation, in digital circuits, 343–344
- Power domain design, 347
- Power output, 413
- Power transmission limits, 257*t*
- Powercast P2110-EVAL-02 RF energy harvesting development kit, 308–309
- Powered wheelchair (PWC), 564–565, 571
- navigation, 584–585
- Power–lifetime trade-off, 364–366
- Primitives, 391–393
- data clustering, 392–393
- Principal component analysis (PCA), 225–226, 577, 603
- Probabilistic approaches, 505–507
- Probability of correct choices (PCC), 584
- “Processes of change” 415–416
- Prochaska’s transtheoretical model (TTM), 414–415
- Propagation model, 507–513
- indoor signal, 508–509
- Prototype touchpad, 188, 189*f*
- Proximity-based authentication, 480
- Pseudoresistors, for sub-Hz high-pass cut-off frequency, 337–338
- Psyche multi-sensing platform, 171–172, 171*f*
- Public key-based (PKC) authentication, 478
- Public policy, 18–19
- Public safety (protection) application, of wearables, 16*t*
- Pulse oximetry, 108, 527*f*
- Pulse transit time, 544–545
- Push-to-gesture interaction, 37
- ## Q
- Queen’s University of Belfast models, 470–471
- ## R
- Racecar drivers, monitoring, 2–3
- Radiation efficiency, 306
- Radiation resistance, 302
- Radio frequency identification (RFID) technology, 256–257
- frequencies and characteristics, 256*t*
- Radio map, 504
- location estimation, 505–507
- Radio tomographic imaging (RTI), 499
- Range-based localization, 503–513
- deterministic approaches, 505
- fingerprinting, 504–507
- probabilistic approaches, 505–507
- propagation model, 507–513
- radio map, 504
- location estimation, 505–507
- Range-free localization, 501–503
- APIT, 502
- centroid, 501
- SeRLoc, 502–503
- Rapidly adapting (RA) receptor, 45
- Rapier loom, 185
- Rare-earth permanent magnet, 574
- Received signal strength (RSS), 479, 500
- information, 511–512
- multiple samples case, 512–513
- single sample case, 511–512
- Referential characteristics, of apparel-body-construct, 27
- Relative noise, 328–329
- Remote monitoring, smart fabrics and interactive textile platforms for, 166–168
- Remote rehabilitation, system for, 168–170
- Resonance control loop optimization, 316
- Resonant transducers, 271
- Respiratory exchange ratio (RER), 134
- Respiratory quotient (RQ), 133–134
- Respirometry, 527–528
- Resting metabolic rate (RMR), 137
- Reusens et al. model, 469–470

- RF energy harvesting (RFEH), 299–322
  - antenna effective area, 300–301
  - antenna-rectifier interface voltage, 302–305
  - available power, 300–301
  - charge pump rectifier topologies, 309–313
  - distribution of harvested power in a realistic environment, 308–309
    - ambient RF power, 309
  - effect of load and source variations, 313–316
    - antenna-rectifier co-design, 317–320
    - measurements and verification, 318–320
    - optimum power transfer techniques, 314–316
  - impedance mismatch, losses and efficiency, 306–308
    - available components and technology, 306–307
    - regulations and maximum achievable distance, 307–308
  - practical limitations, 306
  - wave propagation, 300–301
- RF-DC power conversion efficiency, 318–319
- RFID fiber, 178*f*, 179*f*
- RFID tags, 77–78, 496–497
- RFID textiles, 191–195
- Riva-Rocci cuff, 523–524
- Role theory of social organization, 30
- Root mean square (RMS) values, 94–95
- Rutgers Master II, 47
- S**
- Safety and security, use of wearable sensors, 79
- Saleh-Valenzuela model, 469
- Saliva analysis, 67
- Sartorial morality, 27
- Schottky diodes, 251, 310, 321
- Scosche's RHYTHM device, 119, 120*f*
- SDNN and SDSD, 122–123, 124*f*
- Secret key establishment in WBAN, 481–488
  - based on biometrics/motion, 482
  - based on wireless channel characteristics, 482
- Seebeck coefficient, 237
- Self-aligned transistors, 215–216
- Semiconductors in flexible electronics, 202–204
- Semi-definite programming (SDP) algorithms, 509–510
- Sensor, defined, 7
- Sensor signal-processing (SSP) algorithm, 571–572, 576–578
  - command classification, 577–578
  - external magnetic interference (EMI) attenuation, 576–577
  - feature extraction (FE), 577
  - improvement, 587
- Sensor system, 11–12
- Sensorimotor enhancer, 56
- Sensors and personalized behavior-change interventions, 410–411
- Serial-to-parallel (S2P) converter, 434–436, 438
- SeRLoc, 502–503
- Shadowing, 454
- Sheet type respiratory and body motion sensor, 533
- Short circuit current density, 260–263
- Short-circuit current, 260
- Shuttle loom, 184–185
- Signal-processing algorithms, 117–118, 370–372
- Signal-to-noise ratio, 329
- Silicon Schottky diode BAT60A, 277
- Silicon wafer technology, 199–200
- SimpliciTI protocol, 361–362
- Single-walled carbon nanotubes (SWCNTs), 73–74
- Sip-n-puff, 564–565, 565*f*
- SiSonic MEMS microphone, 581
- Situational awareness data, 3–4
- Skin electrode, 518–519, 519*t*, 520*f*
- Skin stretch method, 49
- SLAM (simultaneous location and mapping), 500
- Sleep monitoring, biosignal sensors for, 530–536
  - ballistic cardiogram, 530
  - non-restrictive heart-rate measurement, 530–532
  - sheet type respiratory and body motion sensor, 533
  - video camera, 533–536
- SlipGlove, 55–56
- Slowly adapting (SA) receptor, 45
- Smart fabric and interactive textile (SFIT) systems, 171–173
  - for remote monitoring, 166–168
- Smart Jersey, 20
- Smart mobile communication devices, 6
- Smart Shirt, 10, 13–14, 546*f*
- Smart textiles, 9–10, 175
  - plastic electronics for, 223–229
  - textile e-nose, 224–226
  - textile integrated near-infrared spectroscopy, 226–229
- Smartphones, 126, 514, 517–518
- Smartwatches, 10–11, 126
- Social leadership, in fashion, 32
- Social media tools, 6
- Social wearability, 26, 30, 41–42
- Social weight, conspicuity and, 33–34
- Sodium sensor, 165
- Solar cell, 259–260, 265, 271
  - equivalent electrical circuit of, 263*f*
- Solar radiation, 259
- Solid contact ISE (scISE) sensors, 73–74
- Sony Walkman, 38, 41
- Specific absorption rate (SAR), 258
- Speech recognition software, 567–568

- SPIDAR series, 46  
 SPIDAR-8, 47  
 Spinal cord injuries (SCI), 563  
 Sportainment, 20, 20f  
 Sports applications, 16*t*, 118–120  
 Sports performance, 78–79  
 Spread spectrum, 438  
 Stage of Exercise Behavior Change (SEBC)  
     questionnaire, 419  
 Stage of Exercise Scale (SOES), 419  
 Stages of change, 415  
 Stakeholders  
     and metrics, 19*f*  
     and wearables, 18–19  
 Starner, Thad, 39*f*, 40–41  
 Statistical modeling, 386  
 Step and stride lengths, 91*f*, 94, 95*f*  
 Stochastic resonance (SR), 56–60  
 Stretch fabrics, 155  
 Stroke rehabilitation, wearable system for, 170, 549  
 Subthreshold weak inversion operation, of MOS  
     transistors, 327–329  
 Successive-approximation-register (SAR) ADC,  
     340–341  
 Suit calorimeter, 140  
     from Web, 139*f*  
 Suit direct calorimeters, 132  
 Super Bowl 2014, 20  
 SuperNova Seamless Glide bra, 155  
 Supervised machine learning technique, 603–604  
 Support vector machines (SVM), 371–372, 377, 587, 602  
 Surface electromyography (EMG), 597  
 Swallowing  
     estimation of ingested mass and energy intake from,  
         607–609  
     food-intake detection from, 603–604  
     monitoring, 599–600  
 Swamp Particle, 572–573  
 Sweat analysis, 67, 75, 79, 163–164  
 Switched-capacitor pseudo-resistor, 338  
 Symmetric key-based (SKC) authentication, 477  
 Synchronization signal, 433–434
- T**
- Tactile display and wearable haptic development,  
     46–48  
 Tactile nail chip, 55–56  
 Tactile sense, 45  
 Tattoo papers, 558  
 Tattoo technology, 73–74, 76  
 T-connectors, 17  
 Tear glucose-sensing device, 73*f*  
 Tears, analysis of, 67
- Technologies, for localization systems, 495–500  
 Telexistence cockpit system, 47  
 Temperature gradient, energy harvesting from,  
     237–245  
     DC-DC converter design for ultra-low input  
         voltages, 241–245  
         maximum-powerpoint tracking for impedance  
             matching, 244–245  
     DC-DC converter topologies, 240–241  
     thermoelectric generators, 237–240  
 Textile electrode, 160, 190  
     for EMG detection, 168  
     with hydrogel membrane, 161*f*  
 Textile e-nose, 224–226  
 Textile integrated near-infrared spectroscopy (NIRS)  
     system, 226–229  
 Textile sensors  
     non-invasive sweat monitoring by, 163–166  
     for physiological state monitoring, 159–161  
 Textile switch, 189–190  
 Textile weave, 179  
 Textiles, 177–185  
     battery, 17–18  
     and clothing, meta-wearables, 11–16  
     integration, 76–77  
     looms, 182–185  
     transport of fluids in, 68–70  
     yarn, 177–179  
 Textillography, 17  
 Texture discrimination, 58–59  
 Thermal balance, 135*f*  
 Thermal noise, 328–329  
     in resistor, 335  
 Thermal resistance, 237, 239  
 Thermocouples (TCs), 138–140, 529*f*  
 Thermoelectric generators (TEGs), 237–240, 244–245,  
     271  
 Thermopile, 139–140, 529*f*  
 Thévenin equivalent circuit, 304  
 ThinEnergy thin-film batteries, 269  
 Thin-film transistors (TFTs), 200–202  
     based on A-IGZO, 204–215  
         analog and digital circuits, 211–215  
         analog circuits, 214–215  
         digital circuits, 211–213  
         fabrication and characterization, 205–207  
         influence of mechanical strain, 207–211  
     flexible a-IGZO TFTs with vertical channel, 219–223  
     flexible double-gate, 218–219  
     parameters in, 202*t*  
     by self-aligned lithography, 216–217  
 Think-A-Move, 568–569, 570*f*  
 Time difference of arrival (TDOA), 500



Time domain HR approaches, 117–118  
 Time of arrival (TOA), 500  
 Time to preceding swallow (TPS), 605  
 Timed up and go (TUG) test, 97  
 T\_KPF sensor, 161–162  
 Tongue, using  
   for wearable technology, 570–571  
 Tongue drive system (TDS), 571, 572*f*  
   advantage of, 573  
   dual-mode. *See* Dual-mode Tongue Drive System (dTDS)  
   external. *See* External Tongue Drive System (eTDS) headsets  
   wearable. *See* Wearable tongue drive system  
 Tongue motion, wireless tracking of, 571–573  
 Tongue-Mouse, 568–569, 570*f*  
 Tongue-operated devices, 568–570  
 Tongue-Point, 568–569, 570*f*  
 Tongue-Touch-Keypad (TTK), 568–569, 570*f*  
 Touchpad, 186–188  
 Tracmor, 136–137  
 Transconductance  
   efficiency, 334, 334*f*  
   in weak inversion, 328  
 Transimpedance amplifier (TIA), 214, 228*f*  
 Transition metal dichalcogenides (TMDCs), 203–204  
 Transition probabilities, 420  
 Transmission scheme of human body communication, 434–440  
 Transmission versus reflectance light modes, 110, 110*f*  
 Transmitter device, block diagram of, 280*f*  
 Transmitters, 365  
 Transtheoretical model (TTM), 414–415  
 Triaxial accelerometers, 86, 86*f*  
 Triaxial devices, 136–137  
 Trickle-down theory, 32  
 Turning fork gyroscopic sensor, 89, 89*f*  
 Two-point discrimination test, 57–58

**U**

Ultrasound systems, 496  
 Ultra-wide band systems, 497  
   packet radio systems, 497–498  
   wearable passive systems, 498  
 Ultrawideband (UWB) communications, 455  
 Uncoordinated frequency hopping (UFH), 487  
 Uniaxial accelerometer, 86*f*  
 Uniaxial Biotrainer, 136–137  
 Unified Parkinson's Disease Rating Scale (UPDRS) III, 99–100  
 Unity-gain frequency, in weak inversion, 328  
 University of Birmingham and Queen Mary University models, 471

Unreliable devices, 412  
 Unscented Kalman filters, 499  
 US healthcare system, 4–5

**V**

*Vanis  technique*, 157  
 VCXO control voltage, 445–447  
 Vertical thin-film transistors (VTFTs), 219–223, 447–448  
 Vibro-tactile feedback devices, 46–48  
 Video camera, 499, 533–536  
 Videofluoroscopy, for swallowing, 599  
 Virtual calibration, 507–508  
 Visible Human Project, 258  
 Visual processing of aesthetics, 26–28, 29*f*  
 Vittoz, Eric, 372  
 Vocabulary, of gesture, 36–37  
 Vocal Joystick, 567–568  
*Vogue Magazine*, 41  
 Voice controllers, 567–568  
 Voltage difference, 428  
 Voltage-controlled oscillator (VCO), 444–445  
 Volume compensation method, 524

## W

Walking speed, estimation of, 93–94, 97, 99  
 Walsh code, 434–437, 444–445  
 Walsh–Hadamard code, 436  
 Wang et al. model, 468–469  
 Water-cooled suits, 138  
 Wave propagation, 300–301  
 Weak inversion (subthreshold) operation, of MOS transistors, 327–329  
 Wealthy textile system, 166–167, 167*f*  
 Wearability, social aspects and interaction, 25–44  
 Wearable active transducers, 496–497  
 Wearable algorithms, 353–355, 364–369  
   *Big Data* performance testing, 366–369  
   classification engines, 371–372  
   examples from literature, 374–378  
   feature extraction, 371  
   fully custom hardware, 373–374  
   hardware platform, 372–374  
   making signal-processing algorithm, 370–372  
   need for, 356–364  
     battery selection, 356–358  
     hardware platform, 358–359  
     practical example and impact of data compression, 361–364  
     wireless transmitter, 359–361  
       *Big Data* performance testing, 366–369  
       classification engines, 371–372  
       examples from literature, 374–378

- feature extraction, 371
- fully custom hardware, 373–374
- hardware platform, 372–374
- making signal-processing algorithm, 370–372
- performance–power trade-off, 369
- power–lifetime trade-off, 364–366
- performance–power trade-off, 369
- power–lifetime trade-off, 364–366
- Wearable chemical and biochemical sensor system.
  - See* Chemical and biochemical sensors
- Wearable computers, 9
- Wearable devices, 26–27, 37–38, 356, 385, 513, 549, 553–554
  - for free-living monitoring, 610–611
  - worn inside the body, 8, 543–544
  - worn under and on top of clothing, 27, 28*f*
- Wearable dTDS prototype, 580–581
  - wireless headset, 580–581
  - wireless USB transceiver, 581
- Wearable haptic devices, 46
- Wearable haptics
  - categories, 46–48
  - devices, 45–46
  - friction and weight illusion display
    - based on fingertip manipulation, 48–54
  - wearable sensorimotor enhancer, 54–60
- Wearable inertial sensors, 85–93
  - accelerometers, 86–88
  - energy expenditure, 100–101
  - fall detection, 98–99
  - fall risk assessment with rehabilitation battery, 97–98
  - gyroscopic sensors, 88–90
  - hemiplegic patients, quantitative evaluation of, 99
  - magnetic sensors, 90–93
  - mathematical analyses, 93–95
  - Parkinson’s disease, clinical assessment for, 99–100
  - practical considerations for, in clinical applications, 101
  - principles of, 85–86
  - rehabilitation score and acceleration, comparison between, 95–96
- Wearable motherboard, 9–10
  - architecture, 13–14
  - realization of meta-wearable, 13–15
- Wearable passive systems, 498
- Wearable radios, 500–513
- Wearable robotic exoskeleton for orthotic tremor suppression (WOTAS), 550–551
- Wearable sensorimotor enhancer
  - active sensory test, 58–59
  - based on stochastic resonance effect, 56–60
  - motor skill test, 59–60
  - one-point touch test, 58
  - two-point discrimination test, 57–58
- Wearable systems, 235–236, 271, 503, 547, 550–551
  - with PPG sensors, 548*f*
  - for stroke rehabilitation, 170
- Wearable tongue drive system, 573–576
  - graphical user interface (GUI), 576
  - permanent magnetic tracer, 574
  - wireless headset, 574–575
  - wireless USB receiver, 575–576
- Wearable Wellness System (WWS), 167–168, 171–172
- Wearables. *See also* Meta-wearables
  - advancements in, 9–11
  - attributes of, 7–11
  - challenges and opportunities, 16–19
  - data-information-knowledge-value paradigm, 4–5
  - ecosystem to enabling digital life, 5–6
  - emerging set of, 10*f*
  - flexible electronics, 10
  - future of, 19–21
  - in healthcare domain, 5
  - in relationship to big data, 4–5
  - in twin continuum of life and activities, 15*f*
  - latest trends in, 10–11
  - making a business case, 18–19
  - meaning of, 1–2
  - Medical Loss Ratio (MLR) and, 5
  - research roadmap, need for transdisciplinary approach, 21
  - role of, 3–4
  - taxonomy for, 8–9
  - technical challenges in, 17–18
  - textiles and clothing, 11–16, 20
  - unit operations in obtaining situational awareness, 3*f*
  - wearable motherboard, 9–10
  - WOW, 1–6
- Weave repeat, 179
- Weaving, 126, 155–156, 175–176, 196
- Weibull distribution, 464, 466*t*
- Weight and friction illusion display, 52–54
- Weighted K-nearest neighbor method (WKNN), 505
- Wet electrodes, 71, 167–168, 325–327
- Wired/wireless wearables, 8–9
- Wireless biopotential acquisition, architecture for, 345*f*
- Wireless body area networks (WBAN) technology, 475–476
  - authenticated secret key establishment in, 453, 483–484
  - ASK-BAN, 483–484
  - challenges, 483
  - cryptographic authentication mechanisms in, 477–478
  - public key-based authentication, 478
  - symmetric key-based authentication, 477

- Wireless body area networks (WBAN) technology  
     *(Continued)*  
     device authentication techniques, 476–481  
     localization in, 493–516  
     non-cryptographic authentication mechanisms in,  
         478–480  
         authentication methods, 480–481  
         authentication schemes, 480  
         biometric-based authentication, 479  
         channel-based authentication, 479  
         proximity-based authentication, 480  
     secret key establishment in, 481–488  
         based on biometrics/motion, 482  
         based on wireless channel characteristics, 482  
     wireless in-band trust establishment in, 484–488  
         “chorus” 486–488  
         related work, 485–486  
     Wireless channel characteristics, 482  
 Wireless energy transmission systems, 253–259  
     capacitive wireless energy transfer in the near field,  
         254–255  
     electromagnetic wireless energy transmission in the  
         far field, 255–256  
     inductive wireless energy transfer in the near field,  
         254  
 Wireless headset, 574–575, 580–581  
 Wireless power transmission (WPT), 270–271  
     regulations, 257–258  
 Wireless sensor networks (WSNs), 65, 476  
 Wireless tracking of tongue motion, 571–573  
 Wireless transmission controller, 359  
 Wireless transmitter, 359–361  
     air data rate vs. effective data rate, 360–361  
     hardware overhead, 360  
     quality of packet transmission, 360  
 Wireless USB receiver, 575–576  
 Wireless USB transceiver, 581  
 World of wearables (WOW), 1–6  
     enabling digital lives, 2*f*  
 Woven electronic textiles. *See* Electronic textiles  
 WrisTAS™ (Wrist Transdermal Alcohol Sensor),  
     76  
 Wrist-worn accelerometry device, 553*f*
- X**  
 Xybernaut, 9
- Y**  
 Yarn, 177–179  
     defined, 153–154