

NoCK

Computing obstruction for compact Clifford-Klein form

Version 1.1

July 2018

**Maciej Bocheński
Piotr Jastrzębski
Anna Szczepkowska
Aleksy Tralle
Artur Woike**

Maciej Bocheński Email: mabo@matman.uwm.edu.pl

Address: Faculty of Mathematics and Computer Science,
University of Warmia and Mazury in Olsztyn
Słoneczna 54 Street,
10-710 Olsztyn, Poland

Piotr Jastrzębski Email: piojas@matman.uwm.edu.pl

Homepage: <http://wmii.uwm.edu.pl/~piojas/>

Address: Faculty of Mathematics and Computer Science,
University of Warmia and Mazury in Olsztyn
Słoneczna 54 Street,
10-710 Olsztyn, Poland

Anna Szczepkowska Email: anna.szczepkowska@matman.uwm.edu.pl

Address: Faculty of Mathematics and Computer Science,
University of Warmia and Mazury in Olsztyn
Słoneczna 54 Street,
10-710 Olsztyn, Poland

Aleksy Tralle Email: tralle@matman.uwm.edu.pl

Homepage: <http://wmii.uwm.edu.pl/~tralle/>

Address: Faculty of Mathematics and Computer Science,
University of Warmia and Mazury in Olsztyn
Słoneczna 54 Street,
10-710 Olsztyn, Poland

Artur Woike Email: awoike@matman.uwm.edu.pl

Homepage: <http://wmii.uwm.edu.pl/~awoike/>

Address: Faculty of Mathematics and Computer Science,
University of Warmia and Mazury in Olsztyn
Słoneczna 54 Street,
10-710 Olsztyn, Poland

Abstract

In this package we develop functions for algorithms of finding homogeneous spaces of semisimple non-compact Lie groups which do not admit compact Clifford-Klein forms.

Copyright

NoCK Package is free software; you can redistribute it and/or modify it under the terms of the [GNU General Public License](#) as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

Acknowledgements

We thank Willem de Graaf for his help in getting some literature sources.

Contents

1	Notation	4
2	Obstruction for compact Clifford-Klein form	5
2.1	Technical functions	5
	References	7
	Index	8

Chapter 1

Notation

Notation for real Lie algebra is from CoReLG Package, [DFdG14]. Notice: we found some misspellings:

- "D",4,5 is $\mathfrak{so}(1,7)$
- "D",4,4 is $\mathfrak{so}(3,5)$
- "E",7,3 is $\mathfrak{e}_{7(-25)} = EVII$
- "E",7,4 is $\mathfrak{e}_{7(-5)} = EVI$

To be sure, check the rank or the dimension and check the result with the table in [OV90].

Example

```
gap> G:=RealFormById( "E", 7,3);
<Lie algebra of dimension 133 over SqrtField>
gap> rankG:=Dimension(CartanSubalgebra(G));
7
gap> rankRG:=Dimension(CartanSubspace(G));
3
gap> dimG:=Dimension(G);
133
gap> P:=CartanDecomposition( G ).P;
<vector space over SqrtField, with 54 generators>
gap> dimPforG:=Dimension(P);
54
gap> K:=CartanDecomposition( G ).K;
<Lie algebra of dimension 79 over SqrtField>
gap> rankK:= Dimension(CartanSubalgebra(K));
7
gap> dimK:= Dimension(K);
79
```

Chapter 2

Obstruction for compact Clifford-Klein form

In this chapter we describe functions for algorithms from [BJS⁺].

2.1 Technical functions

2.1.1 NonCompactDimension

▷ NonCompactDimension(G) (function)

For a real Lie algebra G constructed by the function *RealFormById* (from [DFdG14]), this function returns the non-compact dimension of G .

Example

```
gap> G:=RealFormById("E",6,2); # E6(6)
<Lie algebra of dimension 78 over SqrtField>
gap> dG:=NonCompactDimension(G);
42
```

2.1.2 PCoefficients

▷ PCoefficients($type$, $rank$) (function)

Let G be the compact connected Lie group of the type $type$ and the rank $rank$. Let $\Lambda P_G = \Lambda(y_1, \dots, y_l)$ be the exterior algebras over the spaces P_G of the primitive elements in $H^*(G)$. Denote the degrees as follows $|y_j| = 2p_j - 1, j = 1, \dots, l$. This function returns coefficients $p_1, \dots, p_l, j = 1, \dots, l$.

Example

```
gap> PCoefficients("D",5);
[ 2, 4, 6, 8, 5 ]
```

2.1.3 PCalculate

▷ PCalculate(pi , qi) (function)

Here $pi = \{p_1, \dots, p_l\}$ and $qi = \{q_1, \dots, q_m\}$ are sets of coefficients ($l \geq m$). This function returns the polynomial: $P(t) = \prod_{j=m+1}^l (1 + t^{2p_j-1}) \prod_{i=1}^m (1 - t^{2p_i}) / (1 - t^{2q_i})$.

Example

```
gap> PCalculate([4,2,3],[2,2]);
t^9+t^5+t^4+1
```

2.1.4 AllZeroDH

▷ AllZeroDH(*type*, *rank*, *id*)

(function)

Let G^C be the complex Lie algebra of the type *type* and the rank *rank*. Let G be the real form of G^C with the index *id* (see *RealFormsInformation*, [DFdG14]). This function returns the set of degrees of $P(t)$ that have zero coefficients over all permutation (see Section 7 in [BJS⁺]).

Example

```
gap> AllZeroDH("F",4,2);
[ 1, 2, 3, 5, 6, 7, 9, 10, 11, 13, 14, 15, 17, 18, 19, 21, 22, 23, 25, 26, 27 ]
```

References

- [BJS⁺] M. Bocheński, P. Jastrzębski, A. Szczepkowska, A. Tralle, and A. Woike. Semisimple subalgebras in simple lie algebras and a computational approach to the compact clifford-klein forms problem. <https://arxiv.org/abs/1804.03484>. 5, 6
- [DFdG14] H. Dietrich, P. Faccin, and W. A. de Graaf. Corelg, computation with real lie groups, version 1.20. <http://users.monash.edu/~heikod/corelg/>, Dec 2014. Refereed GAP package. 4, 5, 6
- [OV90] A. Onishchik and E. Vinberg. *Lie Groups and Algebraic Groups*. Springer Series in Soviet Mathematics. Springer-Verlag Berlin Heidelberg, first edition, 1990. Original Russian edition published by Nauka, Moscow 1988. 4

Index

AllZeroDH, [6](#)

NonCompactDimension, [5](#)

PCalculate, [5](#)

PCoefficients, [5](#)