

higher level standard rate generator					inductive transducer	
m	n	U	n(r60)	n®	m(i)	n(i)
0	0	0	0	0	0	0
70	3.5	0.05	100	1.6667	21.3	3.55
205.5	10.275	3.99	500	8.3333	61.7	10.283
302	15.1	6.03	750	12.5	90.5	15.083
404	20.2	8.12	1100	18.333	121.4	20.233
505	25.25	10.15	1400	23.333	151.5	25.25
602	30.1	12.08	1700	28.333	180.5	30.083
757	37.85	15.2	2100	35	227	37.833
917.5	45.875	18.4	2600	43.333	275.3	45.883
766	38.3	15.35	2200	36.667	230	38.333
627.5	31.375	12.56	1750	29.167	188.3	31.383
489.4	24.47	9.8	1400	23.333	146.8	24.467
341	17.05	6.85	900	15	102.3	17.05
223.5	11.175	4.4	550	9.1667	67	11.167
145	7.25	2.35	320	5.3333	43.5	7.25
68	3.4	0.04	120	2	20.5	3.4167
0	0	0	0	0	0	0

pneumatic I			pneumatic II		
I	dl	p	I1	I2	dl
-4.3	0		0.1	0.1	0
-4.1	0.2		10	-9	19
-3.5	0.8		28	-26	54
-2.7	1.6		39	-38	77
-1.5	2.8		39	-38	77
0	4.3		48	-47	95
2.3	6.6		59	-57	116
6.1	10.4		75	-72	147
11	15.3		90	-88	178
6.5	10.8		76	-74	150
3	7.3		61	-60	121
0.5	4.8		48	-46	94
-2	2.3		34	-32	66
-3	1.3		22	-21	43
-3.5	0.8		19	-18	37
-4	0.3		10	-8	18
-4	0.3		0.1	0.1	0

