

List of Changes and Why they were done:

Node class:

1. HashSet<String> childrenList added to keep track of all children of said node
2. Variables int hashCode and String name were changed to private to prevent data breaches, and a String getName() method was added to give necessary access to the name variable.
3. An addChild(Node child, String label) method was added allow children to be added to the childrenList by external means due to the childrenList being made private to prevent data breaches

Edge class:

1. The destination node is added to the source node's childrenList via the addChild method. This was done due to the childrenList being made private to prevent data breaches
2. Checkrep() commented out in the constructor due to it making the program slower
3. Methods getLabel(), getSourceNodeName(), getDestNodeName(), getSourceNode, and getDestNode(), all created to give access to the variables when needed outside the class. This was to replace the previously public access to each of the variables, which was changed to prevent data breaches.

Graph class:

1. checkRep in the constructor, addNode() method, and addEdge() methods is commented out due to it slowing down the program
2. listChildren implementation changed to be simpler due to the new access and information provided by the getChildrenList() method.
3. Two new methods of getEdgeCollection() and getNodeCollection() were created to accommodate the need to access the 2 hashset collections after they were made private to prevent data breaches.

GraphWrapper class:

1. A "findNode(String node)" method was created to help located pre existing nodes within the graph of graphWrapper. This change was made because there was a bug where new nodes would be made in place of old ones and information would be lost.
2. Methods "addNode(String nodeData)", "addEdge(String parentNode, String childNode, String edgeLabel)", and "listChildren(String parentNode" utilize the new "findNode(String node)" method to prevent loss of information on existing nodes