

4103026_01 多媒體技術概論

Assignment #2

Due: 11:59pm, 2021/12/15 (Wed)

Image Convolution

Implement the image convolution by Gaussian filter for image smoothing. Assume that there are zero-valued pixels around the edges to ensure the same-size image after image convolution. The following Matlab code creates a Gaussian filter with hsize = [3 3] and sigma = 1. $G = fspecial('gaussian', [3\ 3], 1);$



- (a) Creates the Gaussian filter with hsize = 3x3, 7x7 and 13x13. Apply image convolution to image 柴犬飛飛.jpg by three Gaussian filters, and compute the PSNR with the original image. [3 image]
- (b) Creates the Gaussian filter with sigma = 1, 30 and 100 with hsize = 3x3. Apply image convolution to image 柴犬飛飛.jpg by three Gaussian filters, and compute the PSNR with the original image. [3 image]
- (c) Compare and discuss the results from the above three methods and give the meaning of PSNR values to these results.
- (d) Apply Unsharp mask 、Edge detection mask to the 柴犬飛飛.jpg and show the results.

$$\begin{bmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{bmatrix}$$

Note:

You should not use the MATLAB built-in functions, such as `imfilter`, `conv2`, `filter2`, `convn`, etc. You are allowed to use 'psnr' provided by Matlab.

Reminder

- MATLAB built-in functions listed in problem description are prohibited.
- Your code should work correctly and the generated results (display or output files) must be consistent to your results in report.
- Report format can be in Word, PowerPoint or others that can clearly describe your work and results. You should convert your report to a PDF file.
- Your report should contain how you implement the methods and discussion about the output results.
- **Pack {student_ID}_report.pdf, the output result images, and codes in {student_ID}.zip. Your package should also contain a README file about how to execute your program.**

Mean Square Error and Standard Deviation Between Two Images

- For two $N \times M$ digital images A and B the **mean square error (deviation) (MSE)** is defined as follows:

$$MSE = \frac{1}{NM} \sum_{i=0}^{N-1} \sum_{j=0}^{M-1} (A(i, j) - B(i, j))^2$$

- For two $N \times M$ digital images A and B the **standard deviation (the root mean square error - RMSE)** is defined as follows:

$$RMSE = \sqrt{MSE} = \sqrt{\frac{1}{NM} \sum_{i=0}^{N-1} \sum_{j=0}^{M-1} (A(i, j) - B(i, j))^2}$$

Peak Signal-to-Noise Ratio (PSNR)

$$PSNR = 10 \log_{10} \left(\frac{(L-1)^2}{MSE} \right) = 20 \log_{10} \left(\frac{L-1}{RMSE} \right)$$

- where L is the number of maximum possible intensity levels (the minimum intensity level suppose to be 0) in an image, **MSE** is the mean square error, **RMSE** is the root mean square error between a tested image and an “ideal” image