



MASSEY UNIVERSITY
ENGINEERING

SCHOOL OF ENGINEERING AND ADVANCED TECHNOLOGY

LITERATURE REVIEW SUPPORTING THE
Engineering Project
Submitted as part requirement for B.Eng (Hons).

Prosthetic Tactile Sensor With Force Feedback

Marc Alexander Sferrazza
2017

SUPERVISORS
a. Chris Chitty
b. Steven Dirven

Literature Review

Prosthetic Tactile Sensor With Force Feedback

Marc Alexander Sferrazza^{*}

Abstract

The focus of this research is in the area of tactile sensors, and their application in the field of prosthetics. Such a study is important in order to further develop practical implementations for a forced feedback analysis, to give the sense of touch back to those whom have lost limbs. The research approach adopted in this dissertation is due to the high impact on amputees lives without the ability to feel what they are doing.

The findings from this research provide evidence that tactile sensory is a viable force measure tool, while the range of dynamic sensory (temperature, stroking) is still limited. There are processes currently being specifically targeted in capturing this data and relaying it correctly.

The main conclusions drawn from the study are that tactile's are a largely accepted means of measurement for prosthetics, and the methods of implementation of these sensors range immensely for applications not limited to that of this condition. It is found that the use of durable tactile's in an array provides a reasonable level of ranged force feedback, which in turn can be passed as output to a user to distinguish differences of sharp and smooth objects relative to this application.

This dissertation recommends that a viable sensor for use with prosthetics will be that of a durable and high-resolution force measurement tactile which is closely meet with by E-Skin (Tokyo University Professor Takao Someya), and PRINTSKIN (Dr. Ravinder S. Dahiya, University of Glasgow Scotland).

1. INTRODUCTION

Tactile sensors have a wide range of applications from medical instruments, manufacturing line, sorting tasks, and much more. Over the last decade tactile sensors have been refined from their more rudimentary predecessors; which in turn provides far more variety of applications. One opportunity opened when durable tactile's with moderate usable resolution presented itself is the task or implementation in prosthetics.

Doctors are now successfully experimenting with a surgery called TMR (targeted muscle reinnervation) also known as TSR (targeted sensor reinnervation) with slight variances.

This surgery unbundles the main already severed nerves (touch and muscle control) and maps them to a patient's skin nerves; which allow devices such as electrodes to be used to measure the patterns and run algorithms to determine process's of movement currently up to 10 degrees of freedom [John Hopkins APL, DARPA] As a bonus to this nerve mapping the stimulation of the mapped skin area could be used to give sensation back to the user of feeling in their missing limb down to the stroke on the pinky.

As an additional side effect which surprised everyone at the time is that the mapped nerves could also sense all the ranges regular appendages could with a range of temperature and sharpness.

This remarkable procedure not only provides the task to give users back control of a once lost limb, it also means a response can be issued back dynamically none the less from a stimulated force feedback, to simulated temperature control.

The focus of this research being that more second step in which a force is to be measured, in turn giving an output to which can be applied to the user in a number of ways. The frame of tactile's today has come along

^{*}*This work was not supported by any organisation

[†]Faculty of Mechatronics Engineering, Massey University, Albany, Auckland, New Zealand Progress of project: alex1v1a.github.io /Prosthetic-Tactile-Research/

way in the last 10 years for robotics, and can now successfully be utilised for this application.

A number of methods have already been implemented in order to achieve this task, however there is more than one correct answer and development will only improve. Currently there are several limitations at hand (no pun intended) including size, durability and deformation, types of sensors, and other aesthetic and ethic aspects to be praised.




Figure 1. Understanding the fundamentals; simplified diagram of communication from the brain to fingertips

The main aspect to focus for this prosthetic tactile research (as there are so many focus segments) is to apply an array of tactile's to a wearable device; in which a user output can be given such that a high enough resolution is available to determine the difference between smooth distribution and sharp surfaces e.g. a sea egg (urchin) and a chicken egg.

This is a critical move in applying using a tactile device to output in micro volts and stimulate the nerve sense with the TMR mapping. It is hoped to re-obtain some of the lost sense back; this could be applied for machines, and patients with nerve damage not just amputees.

It also open the possibility in assistive touch for those suffering from muscle diseases such as ALS, in the respect that in collaboration with another device a computer is able to assist the user in not over-gripping/under-gripping of objects etc.

2. Review of Literature

Tactile force feedback is a new way to make machines aware of their surroundings and safely deform around them. They have been developed for over 30 years with the idea of first measuring pressure over a cylinders surface for LPG tanks and water cylinders.

Since then the design has passed from capacitance and resistive measurements with simple implementations in use such as bendable resistors, surface pads, midi control tiles, pushing for smaller and smaller device applications.

The technology has lead to developments in more sophisticated instruments, which now take advantage of more intricate designs of MOSFET's and other types of transistors, more commonly used today are POSFET's (piezoelectric polymers)

These POSFET designs are already being used in many manufacturing devices today, and are being further developed with even smaller elements, in more durable and ductile ways; also beginning to explore the potential to simultaneously act as PV cells absorbing light efficiently.

There is a performance criteria still to be met, of which can be done with organic compounds in substitute of the current inorganic's favoured in todays POSFET's. These inorganic materials are favoured for stability but are overwhelmed by the organics in accuracy and ductility. The features of organic's are highly appealing in the task at hand however unfortunately due to the infancy of the research at this stage organics are unfeasible due to their instability.

2.1. Technique

This development provides wide range of innovative applications. To find more about the current technology available, checks at each point have been carefully recognised. With further reading analysis, breaking down the main research task into blocks and analysing each component; then further exploring the advancements in the components, and cross examining the research recording the most relevant information.

This process is repeated until the most relevant data is recognised, which can then be assessed for the points that are missing or needed to be connected together.

The study when looking at old sensors from the 90's, and the development of durable sensors, lead to finding some of the more intricate designs using graphene and POSFET's in array of tiles being researched today.

3. Methodology

Several types of tactile have been developed over the last 30 years from large resistors, and narrowing to smaller more compact transistors. The focus over the last 10 years has been to form a more durable and robust tactile, capable of being bent and stretched in order to deform in a manner respect to its environment [14]

The importance of this research enables implementations in applications such as the medical and manufacturing fields; and more specifically to address the manner of wearable touch sensitive devices, to distinguish the nature of foreign objects.

3.1. Materials

Traditionally inorganic materials have been used due to their favourable fabrication and electronic performance; however for the nature of this application, and the specific parameters required, a smart ductile, stretchable, electronic material, is required to match properties that like of skin [1] [17] Therefore a balance must be found on which the properties are met for all required conditions.




Figure 2. Traditional arrangements of a durable tactile

The current materials being implemented are P(VDF-TrFE) soft piezoelectric polymer films [2] [13]

These polymers demonstrate viscoelastic, and dielectric losses, which are used as an advantage to the substrate [1]

Stretchable polymers are a great means for rigidity and deformation, however its materials lack in the ability to conduct electrical signals efficiently [3] Therefore conductive fillers were introduced to aid the conductivity of layers.

This is a trade-off of course as the higher ratio of filler added, the less ductile the material, the more brittle the nano-wires [2] which of course is reliant for the system.

3.2. Social, Economical and Environmental impact

The way in which fundamental interactions with the environment can be defined is limited. This interaction can be assessed in any necessary way in respect to a touch sense but without scientific method remains critique. The definitive method is the effects with peoples social interaction and ethics which is something to be further developed however is been found accepted in a general sense [3]

The manufacturing process of the lamination is low cost which leads higher margins for profit gain and potentially affordable for a largely accepted market. As the research is applicable in more than several key developing areas the investment strategy and target market is fairly open for the picking, which gives much room for investor opportunity.

3.3. Printable Materials

The process of which a printable tactile can be established involves first moulding a cast with lithography, then inking by spin coating a wafer with composite ink and transferring that via the mould to another substrate, passing that substrate to polydimethylsiloxane (PDMS) cast and cure, and finally resulting with a patterned composite PDMS block. [3] [4]

Organic semiconductors are capable of meeting high-performance standards, however are such unstable [5] As a result they can often be slower than inorganic components. Further investigation for single crystal Si ultra graphene chips are in the early stages but hold promise [3]




Figure 3. A general process of manufacturing



Figure 4. Process equipment for a MOSFET tactile

3.4. Sensor Arrays

In a standard manufacturing process, arrays of tactile's are printed in layers. These wafer thin layers (700 m - 50 m) form together in a combination of patterns of which a lining process envelopes a lamination [3] that similar to skin but rather comprised of several parts silicon.

Although silicon has become a popular and widely used material for tactile's in many research development centres around the world [5]; Dr. Ravinder S. Dahiya has applied graphene in substitute as a filler for several prototypes in 2104.

While this method is not relatively new, it has been avoided in more of the films designs from methods produced by Rodolfo Zunino, and Maurizio Valle. The argument is that introducing graphene in the substrate is adding limitations on future development, but its im-




Figure 5. Composite PDMS block

portant to note that the Si compounds widely used are mostly artificial, and therefore cost effective [7]

In order to produce a feasible method without the graphene, organic materials must first be further explored, to provide a more stable and cost effective approach [6] Currently the organic materials although highly accurate, are highly unstable.

The ultra thin layers of each transistor are grown even smaller then other silicone-based types, Down to the macro scale for each piezoelectric oxide semiconductor field effect transistor (POSFET) [3] Each element in the array generates a charge voltage, as per design of the MOSFET the signal is then amplified to be analysed by computational intelligence.




Figure 6. Single element diagram of a POSFET tactile




Figure 7. Sensor process diagram

The CMOS Sensor Array consists of elements in the 32 micro electrode gates and are layered between 15 m and 100 m piezoelectric films [4] [13] [18]

These films use an epoxy where higher filler of graphene is found [6]. The advantage is that each piezoelectric block has a higher control gain over the individual sensors and therefore simulated response when passed through as RAW data to the computational intelligence it's far more accurate [7]

Articles of Dr. Dahiya's more recent work discuss how the nano fabricated arrays are now using some of the graphene layers as conductive solar cells which are sufficient in self powering, they are also surprisingly stable even in low light conditions (greater than 30%). However the power is not enough for any computational processing.




Figure 8. Simulated response comparison in CMOS 32 array




Figure 9. POSFET Touch Sensor

While the arrays are fundamentally sound and produce a good response, they are not great and there is a long way to go as far as high definition in the resolution for the sense.

3.5. Computational Intelligence

As a general rule the piezoelectric polymer transducer is influenced by types of materials on all sides. This is important to note when handling the RAW data. Computational intelligence introduces different approaches on how to deal with such information as well as how to deal with roughness, angled contact, also texture pattern recognition, and other object detection [8]

Classifiers are used for the platform to address the dynamic range of forces [9]. To calibrate this range, an instance of neural networks are stabilised using a learning machine; this uses probes of different materials and forces to generate a dynamic force range. The RAW data is passed to check the phase difference between each sensor on a difference deformation level, which is then used to average the force on the entire measurable area; a bit like mapping how skin ranges from tight and stretchy, to hard and wrinkly [13]

Piezoelectric polymer properties offer a great range of positive aspects; however there are some drawbacks with factors to take account for, such as viscoelastic, dielectric losses. To compensate for these losses complex constants are in place for the elastic region, and often the phase of the signal must be classified with the dynamic forces [10]




Figure 10. Phase and Gain plots at 3 different applied forces for MEA film

3.6. Objects Orientation and Deformation

Simultaneous localisation and mapping (SLAM) provides tactile arrays to demonstrate how the sensors can work in neural networks in order to use combine and predict algorithms, such that a 3D map of force over an object can be achieved [14] This technique relies on the stretchable surfaces and the inductance of the transducers being constant over a dynamic scale, and is therefore calculated using three formulas relating to the force over the array in simultaneous directions at any given time [11]

This technology is in its infancy stage and will be a few more years before implemented in the POSFET tactile system. The advantage of this is that with integration the signal elements can process sensing in live time, with predictions as to where applied forces will occur in advanced when clasping different objects. When a bottle or cup is picked up, majority of forces




Figure 11. Simulation of POSFET type sensors over objects

occur in four places; the bottom of the hand, the thumb, the fore-thumb and along the finger tips [5] By using SLAM with the tactile's, predictions can be made as to what object is about to be obtained and what forces to expect. Further advantage of using this process is that while a large dynamic range may not be available in one calibrated setting; the array gives opportunity to adjust the calibration dependent on the predicted forces expected. [12]

4. CONCLUSIONS

The results are highly influenced by real-world factors. How it feels when touched to a surface can be dependent on a number of considered reasons; these include interaction behaviours when the tactile's are deformed [15] Contact to objects and other external forces are not exempt to the noise of motion; meaning that not only the weight of an object and its deformation to the sensors must be compensated, but also how the motion and movements change this dynamic measurement.

If the array were to sense a spiky ball being held in place, then squeezed the ball, and lastly push and roll the ball on a 3rd surface; the sensitivity of forces are calibrated such that an array can concise of 25 to 256 elements, thus providing a comparable use of range [6]

It is found that with the current range of research

POSFET element, CMOS arrays are at a strong point and have future development underway with 3D mapping and force prediction [9] The POSFET tactile's are to a high enough resolution, and the durable, ductile material allows to be fitted to a specific or wide range of applications.

The properties of the piezoelectric blocks are stable enough and provide an accurate dynamic range of feedback, which when using correct classification and accounting for the phase and gain with deformation, will provide a close to life like sense similar to that of a human hand [16]

The material is also 98.78% translucent and remarkably thin allowing the application to be used as a medicine glove, or other low profile device for a wide range of applications [3] The limitations at this stage are that its not yet an everyday usable device, and may not be available for commercial application for some time.

The major setback is if a single element becomes offline the series will fail, and due to the inability to change individual components the entire unit would need to be replaced; however the cost per unit is considerably cheap to manufacture which will hopefully show on the retail side [2]

For the purpose of this task, the piezoelectric array tactile's, PRINTSKIN (Dr. Ravinder S. Dahiya, University of Glasgow Scotland) or E-Skin (Tokyo University Professor Takao Someya) is optimal for measuring the variety of difference between a sea egg or chicken egg.

References

- [1] S. Tinku, *Micro fabrication technologies for tear fluid sensors for functional contact lens applications*. PhD thesis, University of Trento, 2016.
- [2] A. Billard, A. Bonfiglio, G. Cannata, P. Cosseddu, T. Dahl, K. Dautenhahn, F. Mastrogiovanni, G. Metta, L. Natale, B. Robins, *et al.*, “The roboSkin project: Challenges and results,” in *Romansy 19-Robot Design, Dynamics and Control*, pp. 351–358, Springer Vienna, 2013.
- [3] N. Yogeswaran, W. Dang, W. T. Navaraj, D. Shakthivel, S. Khan, E. O. Polat, S. Gupta, H. Heidari, M. Kaboli, L. Lorenzelli, *et al.*, “New materials and advances in making electronic skin for interactive robots,” *Advanced Robotics*, vol. 29, no. 21, pp. 1359–1373, 2015.
- [4] S. Khan, L. Lorenzelli, and R. Dahiya, “Technologies for printing sensors and electronics over large flexible substrates: a review,” *IEEE Sensors Journal*, vol. 15, no. 6, pp. 3164–3185, 2015.
- [5] R. S. Dahiya and S. Gennaro, “Bendable ultra-thin chips on flexible foils,” *IEEE Sensors Journal*, vol. 13, no. 10, pp. 4030–4037, 2013.
- [6] R. Dahiya, A. Adami, C. Collini, and L. Lorenzelli, “Posfet tactile sensing arrays using cmos technology,” *Sensors and Actuators A: Physical*, vol. 202, pp. 226–232, 2013.
- [7] R. S. Dahiya, M. Valle, G. Metta, and L. Lorenzelli, “Posfet based tactile sensor arrays,” in *Electronics, Circuits and Systems, 2007. ICECS 2007. 14th IEEE International Conference on*, pp. 1075–1078, IEEE, 2007.
- [8] S. Decherchi, P. Gastaldo, R. S. Dahiya, M. Valle, and R. Zunino, “Tactile-data classification of contact materials using computational intelligence,” *IEEE Transactions on Robotics*, vol. 27, no. 3, pp. 635–639, 2011.
- [9] G. Cannata, S. Denei, and F. Mastrogiovanni, “Tactile sensing: Steps to artificial somatosensory maps,” in *ROMAN, 2010 IEEE*, pp. 576–581, IEEE, 2010.
- [10] M. Kaboli and G. Cheng, “Novel tactile descriptors and a tactile transfer learning technique for active in-hand object recognition via texture properties,” in *IEEE-RAS International Conference on Humanoid Robots (Humanoids)-workshop on tactile sensing for manipulation: new progress and challenges*, 2016.
- [11] M. Kaboli, K. Yao, and G. Cheng, “Tactile-based manipulation of deformable objects with dynamic center of mass,” in *Humanoid Robots (Humanoids), 2016 IEEE-RAS 16th International Conference on*, pp. 752–757, IEEE, 2016.
- [12] M. Kaboli, T. De La Rosa, R. Walker, and G. Cheng, “In-hand object recognition via texture properties with robotic hands, artificial skin, and novel tactile descriptors,” in *IEEE-RAS 15th International Conference on Humanoid Robots (Humanoids)*, pp. 1155–1160, IEEE, 2015.
- [13] R. S. Dahiya, G. Metta, M. Valle, and G. Sandini, “Tactile sensing?from humans to humanoids,” *IEEE Transactions on Robotics*, vol. 26, no. 1, pp. 1–20, 2010.
- [14] R. S. Dahiya, P. Mittendorfer, M. Valle, G. Cheng, and V. Lumelsky, “Directions towards effective utilization of tactile skin-a review,” *IEEE Sensors Journal*, vol. 13, no. 11, pp. 4121–4138, 2013.
- [15] G. Cannata, R. S. Dahiya, M. Maggiali, F. Mastrogiovanni, G. Metta, and M. Valle, “Modular skin for humanoid robot systems,” in *4th Int. Conf. on Cognitive Systems*, 2010.
- [16] R. S. Dahiya, G. Metta, and M. Valle, “Development of fingertip tactile sensing chips for humanoid robots,” in *IEEE International Conference on Mechatronics (ICM 2009)*, pp. 1–6, IEEE, 2009.
- [17] R. S. Dahiya, M. Valle, G. Metta, L. Lorenzelli, and C. Collini, “Tactile sensing arrays for humanoid robots,” in *Research in Microelectronics and Electronics Conference, 2007. PRIME 2007. Ph. D.*, pp. 201–204, IEEE, 2007.
- [18] R. S. Dahiya and M. Valle, “Tactile sensing for robotic applications,” 2008.