

# BONTON CABLES (INDIA) PVT. LTD.

ISO:9001:2015, IATF:16949:2016  
ISO:14001:2015, ISO:45001:2018,  
ISO:50001:2011, RoHS2 Compliant,  
Sedex/Smeta, G.C. Mark, Trusted Product,  
TUV For Fire Survival Cable

Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

## Bonton Single Core Copper Conductor PVC Cables (Unsheathed)-HRFR

1100V Grade Conforming to IS:694

Nominal Area of Conductor sq.mm	HRFR PVC		Std. Pkg. of Coil in Master Carton	HRFR PVC In Project Packing	
	PartNo.	MRP (90 Mtr. Box)		PartNo.	MRP (180 Mtr. Coil)
0.75	110266N	1570	20	110266P	3995
1	110267N	2020	20	110267P	4795
1.5	110268N	2985	16	110268P	7030
2.5	110269N	4795	12	110269P	11425
4	110270N	7045	8	110270P	17350
6	110271N	10635	4	110271P	25930

Standard Packing : 90mtr. In Carton\* Project Packing: 180 mtrs. Polywrapped

Colour Available : Red, Yellow, Blue, Black, White, Green & Grey

## Bonton Single Core Copper Conductor PVC Insulated Cables (Unsheathed) - FRLS(H)

1100V Grade Conforming to IS:694

Nominal Area of Conductor sq.mm	FRLS(H) PVC		Std. Pkg. of Coil in Master Carton	FRLS(H) PVC in Project Packing	
	Part No.	MRP (90 Mtr. Box)		Part No.	MRP (180 Mtr. Coil)
0.75	110266NLS	1650	20	110266PLS	4195
1	110267NLS	2120	20	110267PLS	5035
1.5	110268NLS	3135	16	110268PLS	7380
2.5	110269NLS	5035	12	110269PLS	11995
4	110270NLS	7395	4	110270PLS	18215
6	110271NLS	11165	4	110271PLS	27225

Standard Packing : 90mtr. In Carton \* Project Packing : 180 mtrs. Polywrapped

Colour Available : Red, Yellow, Blue, Black, White, Green & Grey

## Bonton Single Core Copper Conductor ZHFR Insulated Cables - ZHFR

1100V Grade Conforming to IS:17048 (Unsheathed)

Nominal Area of Conductor sq.mm	ZHFR		Std. Pkg. of Coil in Master Carton	ZHFR in Project Packing	
	Part No.	MRP (90 Mtr. Box)		Part No.	MRP (180 Mtr. Coil)
0.75	110267NZ	2030	20	110267PZ	4470
1	110267NZ	2645	20	110267PZ	5355
1.5	110268NZ	3875	16	110268PZ	7880
2.5	110269NZ	6255	12	110269PZ	12810
4	110270NZ	9135	4	110270PZ	19430
6	110271NZ	13840	4	110271PZ	29035

Standard Packing for ZHFR : 90mtr. In Carton \* Project Packing : 180 mtrs. Polywrapped

Colour Available : Red, Yellow, Blue, Black & Green

## Bonton Single Core Copper Conductor PVC Cables (Unsheathed) - HRFR

1100V Grade Conforming to IS:694

Nominal Area of Conductor sq.mm	HRFR PVC		Nominal area of Conductor sq.mm	HRFR PVC	
	Part No.	MRP (100 mtr.)		Part No.	MRP (100 mtr.)
10	110272H	25330	120	110279H	297535
16	110273H	39420	150	110280H	372435
25	110274H	62020	185	110281H	463395
35	110275H	86800	240	110282H	604905
50	110276H	123820	300	110283H	756775
70	110277H	174920	400	110284H	1008345
95	110278H	230815	500	110285H	1261440

Standard Packing : 100 mtrs. Coils

Colour available : Red, Yellow, Blue, Black & Green

\* FRLS(H) insulation: 5% Extra

\* HFLS (Halogen Free Insulation) : 12% Extra

# BONTON CABLES (INDIA) PVT. LTD.

ISO:9001:2015, IATF:16949:2016  
ISO:14001:2015, ISO:45001:2018,  
ISO:50001:2011, RoHS2 Compliant,  
Sedex/Smeta, G.C. Mark, Trusted Product,  
TUV For Fire Survival Cable

**Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)**

**Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)**

**E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001**

## Bonton Single Core Copper Conductor PVC Cables (Unsheathed) - HRFR & FRLSH

### 1100V Grade Conforming to IS : 694

Nominal Area of Conductor sq.mm	HRFR PVC in Project Packing		FRLSH PVC in Project Packing	
	Part No.	MRP (200 mtr. Coil)	Part No.	MRP (200 Mtr. Coil)
0.5	110265 T	3030	110265 TLS	3180
0.75	110266 T	3950	110266 TLS	4150
1	110267 T	5210	110267 TLS	5470
1.5	110268 T	7635	110268 TLS	8015
2.5	110269 T	12410	110269 TLS	13030
4	110270 T	18820	110270 TLS	19760
6	110271 T	28125	110271 TLS	29530

Colour available : Red, Yellow, Blue, Black, White, Green & Grey

## Bonton Jelly Flooded Aluminium Foil & Aluminium Wire Braided Co-Axial Cables

Size	Part No.	100 Meter Unarmoured	305 Meter Unarmoured	1000 Meter Armoured
RG 59	110086	3650	10935	
RG 6	110087	4585	13740	130470
RG 11	110088	9960	30145	199310

## Bonton PVC insulated Telephone Cables for Indoor application conforming to TEC Specification G/WIR06/02

No. of Pair (0.40mm)	Part No.	MRP - 100 Mtr. (0.40 mm)	No. of Pair (0.50 mm)	Part No.	MRP - 100 Mtr. (0.50 mm)	No. of Pair (0.61 mm)	Part No.	MRP - 100 Mtr. (0.61 mm)
1	110082	1255	1	110091	1655	1	110101	2435
2	110083	2175	2	110092	2755	2	110102	4635
3	110084	2810	3	110093	4150	3	110103	6920
4	110085	3605	4	110094	5490	4	110104	9335
5	110086	4665	5	110095	6530	5	110105	11595
10	110087	9435	10	110096	13330	10	110106	24025
20	110088	18850	20	110097	26520	20	110107	46995
50	110089	-	50	110098	64685	50	110108	114745
100	110090	-	100	110099	136065	100	110109	229570

## Bonton Multi Core Copper Conductor PVC Cables (Sheathed) - FR

### 1100V Grade Conforming to IS : 694

Nominal Area of Conductor sq.mm	Part No.	2 Core	Part No.	3 Core	Part No.	4 Core	Part No.	5 Core
0.5	110308 2C	3785	110308 3C	5190	110308 4C	6640	110308 5C	8335
0.75	110309 2C	5060	110309 3C	7020	110309 4C	9030	110309 5C	11815
1	110310 2C	6425	110310 3C	8935	110310 4C	11555	110310 5C	15295
1.5	110311 2C	8750	110311 3C	12555	110311 4C	16265	110311 5C	20740
2.5	110312 2C	14405	110312 3C	19870	110312 4C	26850	110312 5C	34065
4	110313 2C	21180	110313 3C	30575	110313 4C	40615	110313 5C	53610
6	110314 2C	31235	110314 3C	44980	110314 4C	59730	110314 5C	78945
10	110315 2C	53280	110315 3C	78400	110315 4C	103625	110315 5C	136155
16	110316 2C	84295	110316 3C	123160	110316 4C	162690	110316 5C	208875
25	110317 2C	140415	110317 3C	204395	110317 4C	266960	110317 5C	379755
35	110318 2C	195550	110318 3C	284000	110318 4C	373205	110318 5C	520275
50	110319 2C	277560	110319 3C	404545	110319 4C	534145	110319 5C	752955
70	110320 2C	394380	110320 3C	561120	110320 4C	741710	110320 5C	1029530

Standard Packing : 100 mtrs. Coil

\* FRLS(H) insulation : 5% Extra

\* HFLS (Halogen Free Insulation) : 12% Extra

# BONTON CABLES (INDIA) PVT. LTD.

ISO:9001:2015, IATF:16949:2016  
ISO:14001:2015, ISO:45001:2018,  
ISO:50001:2011, RoHS2 Compliant,  
Sedex/Smeta, G.C. Mark, Trusted Product,  
TUV For Fire Survival Cable

Plant-1 : A 115 RIICO Industrial Area, Phase-1, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

Plant-2 : A 6A, Kaharani Industrial Area, Bhiwadi - 301019, Distt.- Alwar, Rajasthan (INDIA)

E Mail : marketing@bontoncablesindia.com, Phone No. - 8130299001

## Bonton PVC Insulated and Sheathed 3 Core Flat Submersible Cable

1100V grade conforming to IS : 694/1990

Nominal area of Conductor sq.mm	Part Number	MRP - Per 100 Mtrs.
1.5	110311 3C FT	13775
2.5	110312 3C FT	22915
4	110313 3C FT	32805
6	110314 3C FT	47685
10	110315 3C FT	80480
16	110316 3C FT	124595
25	110317 3C FT	200625
35	110318 3C FT	279240

## Bonton PVC Insulated and sheathed 4 Pair Twisted LAN Cable

Size	MRP 305 Meter
CAT 6	17105

## Flexible Bare Copper Conductor PVC Insulated Overall Aluminium Mylar Tape Shielded along with ATC Drain wire PVC Outer Sheath Aluminium Mylar Tape Wires / Cables (100 Mtr Coil)

Core	0.5 sq.mm	0.75 sq.mm	1.0 sq.mm	1.5 sq.mm	2.5 sq.mm
2	6335	8110	9725	12675	19820
3	7850	10675	12880	17145	27405
4	9720	12880	16510	23150	34615
5	12005	16055	19545	26755	43780
6	13870	18230	22815	32205	52410
7	15070	21395	26530	36245	62020
8	17145	23150	29485	40505	69220
10	20305	28605	36245	50115	84615
12	24025	33520	42800	59400	103840
14	27950	39200	49455	68355	
16	31665	43995	55685	78825	
19	36250	52405	65835	91715	
24	44980	64315	81450	117155	

Note : 3% Extra Charges for Drum packing

## FIRE SURVIVAL CABLE

### Bonton Multicore High Proformance Silicon Rubber (HPSR) Insulated LSZH Sheathed Fire Survival Cable - TUV Certified Cable

Test as per BS:6387 C.W.Z.

Size	Part No.	MRP - Per Mtr (Un-armoured)	MRP - Per Mtr (Armoured)
2 Core x 1.5 sq.mm	110331	355	420
3 Core x 1.5 sq.mm	110332	440	500
2 Core x 2.5 sq.mm	110333	485	525
3 Core x 2.5 sq.mm	110334	575	650

### Bonton MICA Tape Multicore XLPE Insulated LSZH sheathed Copper Armoured Fire Survival Cable - TUV Certified Cable

Test as per BS6387 C.W.Z.

Size	Part No.	MRP- Per Mtr.
2 Core x 1.5 sq.mm	110341	315
3 Core x 1.5 sq.mm	110342	390
2 Core x 2.5 sq.mm	110343	440
3 Core x 2.5 sq.mm	110344	545

#### Terms & Conditions : -

1. GST @ 18% Extra on Copper Flexible PVC Insulated Wire & PVC Insulated/Sheathed Cable (HSN Code 85446020)
2. Order are accepted subject to availability of stocks.
3. Conductor Resistance as per IS 694 is the governing criteria.