

Django

urls.py

```
from django.urls import path
from . import views

urlpatterns = [
    path('results/', views.index, name='index'),
    path('upload/', views.upload_file, name='upload_file'),
]
```

views.py

```
from django.shortcuts import render, redirect
from django.http import HttpResponse
from django.views.decorators.http import require_POST
import json

def index(request):
    return render(request, 'upload.html')

@require_POST
def upload_file(request):
    if 'file' not in request.FILES:
        return redirect('index')
    file = request.FILES['file']
    if file.name == '':
        return redirect('index')
    if file:
        content = file.read().decode('utf-8')
        data = [json.loads(line) for line in
content.strip().split('\n')]

        for item in data:
```

```
        item['details_sex'] = item.get('details',
    {}).get('sex', 'Unknown')

    passes_over_50 = sum(1 for d in data if d['result'] >
50)

    return render(request, 'dashboard.html', {'data':
data, 'passes_over_50': passes_over_50})
```

upload.html

```
<!DOCTYPE html>
<html>
<head>
    <title>Upload File</title>
</head>
<body>
    <h1>Upload your file</h1>
    <form action="/upload/" method="post"
enctype="multipart/form-data">
        {% csrf_token %}
        <input type="file" name="file">
        <input type="submit" value="Upload">
    </form>
</body>
</html>
```

dashboard.html

```
<!DOCTYPE html>
<html>
<head>
    <title>Dashboard</title>
    <style>
        table {
            width: 100%;
            border-collapse: collapse;
```

```

    }
    th, td {
        text-align: left;
        padding: 8px;
    }
    th {
        background-color: #f2f2f2;
    }
</style>
</head>
<body>
    <h1>Dashboard</h1>
    <p>Number of people who passed over 50: {{ passes_over_50
}}</p>
    <table border="1">
        <tr>
            <th>Name</th>
            <th>Result</th>
            <th>Location</th>
            <th>Sex</th>
        </tr>
        {% for item in data %}
        <tr>
            <td>{{ item.name }}</td>
            <td>{{ item.result }}</td>
            <td>{{ item.location }}</td>
            <td>{{ item.details_sex }}</td>
        </tr>
        {% endfor %}
    </table>
</body>
</html>

```

urls.py (main project)

```

from django.urls import path, include # Use include for app
URLs

```

```
urlpatterns = [
    path('', include('myapp.urls')), # Adjust 'myapp' to
    your app's name
]
```

settings.py

```
"""
Django settings for web_app project.

Generated by 'django-admin startproject' using Django 3.2.20.

For more information on this file, see
https://docs.djangoproject.com/en/3.2/topics/settings/

For the full list of settings and their values, see
https://docs.djangoproject.com/en/3.2/ref/settings/
"""

from pathlib import Path

# Build paths inside the project like this: BASE_DIR /
# 'subdir'.
BASE_DIR = Path(__file__).resolve().parent.parent

# Quick-start development settings - unsuitable for
# production
# See
https://docs.djangoproject.com/en/3.2/howto/deployment/checklist/

# SECURITY WARNING: keep the secret key used in production
# secret!
SECRET_KEY = 'django-insecure-=l*n1_4#ikxbamd4xrr6(eas@353_#-
b_k&=5l@^9n*r4r&9+$'
```

```
# SECURITY WARNING: don't run with debug turned on in
production!
DEBUG = True

ALLOWED_HOSTS = []

# Application definition

INSTALLED_APPS = [
    'django.contrib.admin',
    'django.contrib.auth',
    'django.contrib.contenttypes',
    'django.contrib.sessions',
    'django.contrib.messages',
    'django.contrib.staticfiles',
    'myapp',
]

MIDDLEWARE = [
    'django.middleware.security.SecurityMiddleware',
    'django.contrib.sessions.middleware.SessionMiddleware',
    'django.middleware.common.CommonMiddleware',
    'django.middleware.csrf.CsrfViewMiddleware',

    'django.contrib.auth.middleware.AuthenticationMiddleware',
    'django.contrib.messages.middleware.MessageMiddleware',
    'django.middleware.clickjacking.XFrameOptionsMiddleware',
]

ROOT_URLCONF = 'web_app.urls'

TEMPLATES = [
    {
        'BACKEND':
'django.template.backends.django.DjangoTemplates',
        'DIRS': [],
    },
]
```

```
    'APP_DIRS': True,
    'OPTIONS': {
        'context_processors': [
            'django.template.context_processors.debug',
            'django.template.context_processors.request',

            'django.contrib.auth.context_processors.auth',

            'django.contrib.messages.context_processors.messages',
        ],
    },
]
```

```
WSGI_APPLICATION = 'web_app.wsgi.application'
```

```
# Database
```

```
#
```

```
https://docs.djangoproject.com/en/3.2/ref/settings/#databases
```

```
DATABASES = {
    'default': {
        'ENGINE': 'django.db.backends.sqlite3',
        'NAME': BASE_DIR / 'db.sqlite3',
    }
}
```