NARUTO API: COMMAND & SETUP GUIDE

Comprehensive Reference for .NET 10, Docker, and EF Core

1. Infrastructure (Docker)

Before the API can store data, the SQL Server environment must be active. These commands manage the "Hardware" layer of your project.

Command	Purpose
`docker-compose up -d`	Starts the SQL Server container in the background (detached mode).
`docker ps`	Lists running containers. Used to verify **narutoapp-db-1** is active.
`docker-compose down`	Stops and removes the containers. Use this when finished for the day.

2. Database Schema (EF Core Migrations)

Migrations translate your C# Classes into SQL Tables. They are essential for versioning the database.

Command	Purpose
`dotnet ef migrations add [Name]`	Scans your code for changes and creates a new "Instruction File" in the Migrations folder.
`dotnet ef database update`	Executes the pending migrations against the live SQL Server in Docker.
`dotnet ef migrations remove`	Deletes the last migration if it hasn't been applied yet (useful for fixing typos).

> **Pro Tip:** If `database update` fails, ensure the API isn't currently running, as it might lock the database file.

3. Development Workflow

Commands used during the daily coding cycle to build and test the application.

Command	Purpose
`dotnet build`	Compiles the code. Essential to catch syntax errors like **CS1061** before running.
`dotnet run`	Starts the web server. This makes your API listen for requests at **localhost:5084**.
`dotnet clean`	Deletes previous build artifacts. Helps resolve "File in use" errors (MSB3021).

4. Frontend Preparation (Upcoming)

Once the API is ready, you will pivot to Angular using these commands.

Command	Purpose
`ng new NarutoFrontend`	Initializes a new Angular workspace.
`ng serve -o`	Starts the Angular development server and opens the browser.