June 27, 2025

Vulnerability Scan
Report

Prepared By

HostedScan Security



hostedscan.com

Overview

1 Executive Summary 3

2 Trends 4

3 Vulnerabilities By Target 5

4 Passive Web Application Vulnerabilities 7

5 Glossary 14

1 Executive Summary

Vulnerability scans were conducted on select servers, networks, websites, and applications. This report contains the discovered potential vulnerabilities from these scans. Vulnerabilities have been classified by severity. Higher severity indicates a greater risk of a data breach, loss of integrity, or availability of the targets.

1.1 Total Vulnerabilities

Below are the total number of vulnerabilities found by severity. Critical vulnerabilities are the most severe and should be evaluated first. An accepted vulnerability is one which has been manually reviewed and classified as acceptable to not fix at this time, such as a false positive detection or an intentional part of the system's architecture.

Critical	High	Medium	Low	Accepted
0	0	3	3	0

1.2 Report Coverage

This report includes findings for 1 target scanned. Each target is a single URL, IP address, or fully qualified domain name (FQDN).

Vulnerability Categories

6

Passive Web Application Vulnerabilities

2 Trends

2.1 Open Risks

Total number of vulnerabilities grouped by severity level.



2.2 Exposure Window

Total number of unresolved vulnerabilities grouped by age (time since first detection).



3 Vulnerabilities By Target

This section contains the vulnerability findings for each scanned target. Prioritization should be given to the targets with the highest severity vulnerabilities. However, it is important to take into account the purpose of each system and consider the potential impact a breach or an outage would have for the particular target.

3.1 Targets Summary

The number of potential vulnerabilities found for each target by severity.

Target	Critical	High	Medium	Low	Accepted
test new site	0	0	3	3	0

3.2 Target Breakdowns

Details for the potential vulnerabilities found for each target by scan type.

test new site

Target - https://casa-gotten-nasa-participants.trycloudflare.com/

Total Risks

0	0	3	3	0

50% 50%

Passive Web Application Vulnerabilities	Severity	First Detected	Last Detected
Cross-Domain Misconfiguration	Medium	0 days ago	0 days ago
Missing Anti-clickjacking Header	Medium	0 days ago	0 days ago
Content Security Policy (CSP) Header Not Set	Medium	0 days ago	0 days ago
X-Content-Type-Options Header Missing	Low	0 days ago	0 days ago
Cross-Domain JavaScript Source File Inclusion	Low	0 days ago	0 days ago
Strict-Transport-Security Header Not Set	Low	0 days ago	0 days ago

4 Passive Web Application Vulnerabilities

The OWASP ZAP Passive Web Application scan crawls the pages of a website or web application. The passive scan inspects each page as well as the requests and responses sent between the server. The passive scan checks for vulnerabilities such as cross-domain misconfigurations, insecure cookies, vulnerable Javascript dependencies, and more.

4.1 Total Vulnerabilities

Total number of vulnerabilities found by severity.

Critical	High	Medium	Low	Accepted
0	0	3	3	0

4.2 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	Open	Accepted
Cross-Domain Misconfiguration	Medium	1	0
Missing Anti-clickjacking Header	Medium	1	0
Content Security Policy (CSP) Header Not Set	Medium	1	0
X-Content-Type-Options Header Missing	Low	1	0
Cross-Domain JavaScript Source File Inclusion	Low	1	0
Strict-Transport-Security Header Not Set	Low	1	0

4.3 Vulnerability Details

Detailed information about each potential vulnerability found by the scan.

Cross-Domain Misconfiguration

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	0 days ago

Description

Web browser data loading may be possible, due to a Cross Origin Resource Sharing (CORS) misconfiguration on the web server.

Solution

Ensure that sensitive data is not available in an unauthenticated manner (using IP address white-listing, for instance).

Configure the "Access-Control-Allow-Origin" HTTP header to a more restrictive set of domains, or remove all CORS headers entirely, to allow the web browser to enforce the Same Origin Policy (SOP) in a more restrictive manner.

Instances (1 of 1)

uri: https://casa-gotten-nasa-participants.trycloudflare.com/api/linkedin-news.json
method: GET
evidence: Access-Control-Allow-Origin: *
otherinfo: The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.

References

https://vulncat.fortify.com/en/detail?id=desc.config.dotnet.html5_overly_permissive_cors_policy

Vulnerable Target	First Detected	Last Detected
https://casa-gotten-nasa-participants.trycloudflare.com/ test new site	0 days ago	0 days ago

Missing Anti-clickjacking Header

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	0 days ago

Description

The response does not protect against 'ClickJacking' attacks. It should include either Content-Security-Policy with 'frame-ancestors' directive or X-Frame-Options.

Solution

Modern Web browsers support the Content-Security-Policy and X-Frame-Options HTTP headers. Ensure one of them is set on all web pages returned by your site/app.

If you expect the page to be framed only by pages on your server (e.g. it's part of a FRAMESET) then you'll want to use SAMEORIGIN, otherwise if you never expect the page to be framed, you should use DENY. Alternatively consider implementing Content Security Policy's "frame-ancestors" directive.

Instances (1 of 10)

uri: https://casa-gotten-nasa-participants.trycloudflare.com/
method: GET
param: x-frame-options

References

https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Frame-Options

Vulnerable Target	First Detected	Last Detected
https://casa-gotten-nasa-participants.trycloudflare.com/ test new site	0 days ago	0 days ago

Content Security Policy (CSP) Header Not Set

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	0 days ago

Description

Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks, including Cross Site Scripting (XSS) and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.

Solution

Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header.

Instances (1 of 13)

uri: https://casa-gotten-nasa-participants.trycloudflare.com/
method: GET

References

https://developer.mozilla.org/en-US/docs/Web/Security/CSP/Introducing_Content_Security_Policy
https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html
https://www.w3.org/TR/CSP/
https://w3c.github.io/webappsec-csp/
https://web.dev/articles/csp
https://caniuse.com/#feat=contentsecuritypolicy
https://content-security-policy.com/

Vulnerable Target	First Detected	Last Detected
https://casa-gotten-nasa-participants.trycloudflare.com/ test new site	0 days ago	0 days ago

X-Content-Type-Options Header Missing

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	0 days ago

Description

The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.

Solution

Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages.

If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application/web server to not perform MIME-sniffing.

Instances (1 of 96)

uri: https://casa-gotten-nasa-participants.trycloudflare.com/
method: GET
param: x-content-type-options
otherinfo: This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.

References

https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85)
https://owasp.org/www-community/Security_Headers

Vulnerable Target	First Detected	Last Detected
https://casa-gotten-nasa-participants.trycloudflare.com/ test new site	0 days ago	0 days ago

Cross-Domain JavaScript Source File Inclusion

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	0 days ago

Description

The page includes one or more script files from a third-party domain.

Solution

Ensure JavaScript source files are loaded from only trusted sources, and the sources can't be controlled by end users of the application.

Instances (1 of 2)

uri: https://casa-gotten-nasa-participants.trycloudflare.com/magallanes
method: GET
param: https://unpkg.com/@google/model-viewer/dist/model-viewer.min.js
evidence: <script type="module" src="https://unpkg.com/@google/model-viewer/dist/model-viewer.min.js"></script>

Vulnerable Target	First Detected	Last Detected
https://casa-gotten-nasa-participants.trycloudflare.com/ test new site	0 days ago	0 days ago

Strict-Transport-Security Header Not Set

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	0 days ago

Description

HTTP Strict Transport Security (HSTS) is a web security policy mechanism whereby a web server declares that complying user agents (such as a web browser) are to interact with it using only secure HTTPS connections (i.e. HTTP layered over TLS/SSL). HSTS is an IETF standards track protocol and is specified in RFC 6797.

Solution

Ensure that your web server, application server, load balancer, etc. is configured to enforce Strict-Transport-Security.

Instances (1 of 100)

uri: https://casa-gotten-nasa-participants.trycloudflare.com/
method: GET

References

https://cheatsheetseries.owasp.org/cheatsheets/HTTP_Strict_Transport_Security_Cheat_Sheet.html
https://owasp.org/www-community/Security_Headers
https://en.wikipedia.org/wiki/HTTP_Strict_Transport_Security
https://caniuse.com/stricttransportsecurity
https://datatracker.ietf.org/doc/html/rfc6797

Vulnerable Target	First Detected	Last Detected
https://casa-gotten-nasa-participants.trycloudflare.com/ test new site	0 days ago	0 days ago

5 Glossary

Accepted Vulnerability

An accepted vulnerability is one which has been manually reviewed and classified as acceptable to not fix at this time, such as a false positive scan result or an intentional part of the system's architecture.

Fully Qualified Domain Name (FQDN)

A fully qualified domain name is a complete domain name for a specific website or service on the internet. This includes not only the website or service name, but also the top-level domain name, such as .com, .org, .net, etc. For example, 'www.example.com' is an FQDN.

Passive Web Application Vulnerabilities

The OWASP ZAP Passive Web Application scan crawls the pages of a website or web application. The passive scan inspects each page as well as the requests and responses sent between the server. The passive scan checks for vulnerabilities such as cross-domain misconfigurations, insecure cookies, vulnerable Javascript dependencies, and more.

Vulnerability

A weakness in the computational logic (e.g., code) found in software and hardware components that, when exploited, results in a negative impact to confidentiality, integrity, or availability. Mitigation of the vulnerabilities in this context typically involves coding changes, but could also include specification changes or even specification deprecations (e.g., removal of affected protocols or functionality in their entirety).

Target

A target represents target is a single URL, IP address, or fully qualified domain name (FQDN) that was scanned.

Severity

Severity represents the estimated impact potential of a particular vulnerability. Severity is divided into 5 categories: Critical, High, Medium, Low and Accepted.

CVSS Score

The CVSS 3.0 score is a global standard for evaluating vulnerabilities with a 0 to 10 scale. CVSS maps to threat levels:
0.1 - 3.9 = Low
4.0 - 6.9 = Medium
7.0 - 8.9 = High
9.0 - 10.0 = Critical

This report was prepared using

HostedScan Security ®

For more information, visit **hostedscan.com**

Founded in Seattle, Washington in 2019, HostedScan, LLC. is dedicated to making continuous vulnerability scanning and risk management much more easily accessible to more businesses.



HostedScan, LLC.

2212 Queen Anne Ave N
Suite #521
Seattle, WA 98109

Terms & Policies
hello@hostedscan.com