

Building the Bible Verse Lookup Tool

Bible Verse Lookup Tool - Build-It-Yourself Lab | Estimated time: 45 min

Objectives

- Understand what a REST API is and how PowerShell talks to one.
- Read and write JSON files as simple local storage.
- Build, piece by piece, a working command-line Bible lookup tool with no prior PowerShell experience.
- End with the exact same tool already installed on this computer - so you can compare your work to the real thing.

Background: what are we actually building?

A **REST API** is just a web address you can request data from, the same way your browser requests a page - except the answer comes back as structured data (**JSON**) instead of a web page. We're going to call the Recovery Version Bible text API at `api.lsm.org`. You send it a verse reference like `John 3:16`, and it sends back the verse text.

Three PowerShell ideas make this possible, and you'll use all three today:

- **Invoke-RestMethod** - the cmdlet that fetches a URL and, if the answer is JSON, automatically turns it into a PowerShell object you can dot into (e.g. `$result.verses`).
- **ConvertTo-Json / ConvertFrom-Json** - turning PowerShell objects into JSON text (to save to a file) and back (to read it again). This is how we'll build "local storage" with nothing but a text file.
- **Functions with parameters** - so typing `verse John 3:16` at the prompt runs your code with `"John 3:16"` as the input.

What the API expects

Endpoint	<code>https://api.lsm.org/recver/txo.php</code>
String	The verse reference, e.g. <code>'John 3:16'</code>
Out	json (otherwise it replies in XML)
appid / token	Your personal credentials from <code>api.lsm.org</code> - also accepted as HTTP Basic Auth
Reply shape	<code>{ verses: [{ref, text, urlpfx} ...], message, copyright }</code>

Get your own token: Before you start, register at `https://api.lsm.org` to get an appid and token. Keep them private - treat them like a password. Never paste them into chat, a script you share, or a public file.

Step 1 - Store your credentials safely

We never hard-code a token inside a script (if you ever shared the script, you'd hand over your credentials too). Instead we put them in a small JSON file in your home folder, and have the script read it at runtime.

Create `%USERPROFILE%\lsm-verse.json` containing:

```
{
  "appid": "YOUR_APPID",
  "token": "YOUR_TOKEN"
}
```

Now write a function that loads it and checks it's actually been filled in:

```
function Get-LsmCredential {
    $configPath = Join-Path $HOME ".lsm-verse.json"
    if (-not (Test-Path $configPath)) {
        Write-Host "Credentials file not found: $configPath" -ForegroundColor Yellow
        return $null
    }
    $config = Get-Content $configPath -Raw | ConvertFrom-Json
    if ($config.appid -like "YOUR_*" -or $config.token -like "YOUR_*") {
        Write-Host "Fill in your real appid/token first." -ForegroundColor Yellow
        return $null
    }
    return $config
}
```

Why check for "YOUR_*": It's a friendly guard rail: if you forget to edit the placeholder file, you get a clear message instead of a confusing API error.

Step 2 - Call the API

Next, a function that takes a reference string, builds the URL, and calls `Invoke-RestMethod`. Note the `-f` format operator building the URL, and `[uri]::EscapeDataString` making sure spaces and colons in the reference don't break the URL.

```
function Invoke-LsmApi {
    param([string]$Reference)
    $config = Get-LsmCredential
    if (-not $config) { return $null }

    [Net.ServicePointManager]::SecurityProtocol = [Net.SecurityProtocolType]::Tls12
    $url = "https://api.lsm.org/recver/txo.php?String={0}&Out=json&appid={1}&token={2}" -f
        [uri]::EscapeDataString("$Reference"),
        [uri]::EscapeDataString($config.appid),
        [uri]::EscapeDataString($config.token)

    try {
        return Invoke-RestMethod -Uri $url -TimeoutSec 15
    } catch {
        Write-Host "Request failed: $($_.Exception.Message)" -ForegroundColor Red
        return $null
    }
}
```

Try it now: Dot-source this file (or paste both functions into a PowerShell window) and run `Invoke-LsmApi "John 3:16"`. You should get back an object - try `(Invoke-LsmApi "John 3:16").verses[0].text`.

Step 3 - The 'verse' command, plus clipboard copy

Now wrap that in a function that takes remaining words as the reference (so you can type `verse John 3:16` with no quotes), prints each verse, and copies the text to your clipboard with `Set-Clipboard` - handy for pasting into a message or document.

```
function verse {
    param([Parameter(ValueFromRemainingArguments=$true)][string[]]$Reference)
    if (-not $Reference) { Write-Host "Usage: verse <reference>"; return }

    $result = Invoke-LsmApi -Reference ($Reference -join " ")
    if (-not $result) { return }

    $clipLines = @()
    foreach ($v in $result.verses) {
        Write-Host $v.ref -ForegroundColor Cyan
        Write-Host $v.text
        $clipLines += "$($v.ref) - $($v.text)"
    }
    $clipLines -join "`r`n`r`n" | Set-Clipboard
    Write-Host "(copied to clipboard)" -ForegroundColor DarkGray
}
```

Checkpoint: Run `verse Eph. 4:4-6`. You should see the verse text on screen, and be able to paste it (Ctrl+V) somewhere else.

Step 4 - Local storage: saving verses to a file

A JSON file can act as a tiny database. To save a verse, we read the existing array from disk (or start with an empty one), append the new verse, and write the whole array back.

```

function Save-LsmVerse {
    param($VerseObj)
    $storePath = Join-Path $HOME ".lsm-saved-verses.json"
    $saved = @()
    if (Test-Path $storePath) {
        $saved = @(Get-Content $storePath -Raw | ConvertFrom-Json)
    }
    $saved += [PSCustomObject]@{ ref = $VerseObj.ref; text = $VerseObj.text; savedAt = (Get-Date) }
    $saved | ConvertTo-Json -Depth 5 | Set-Content -Path $storePath -Encoding utf8
    Write-Host "Saved $($VerseObj.ref)" -ForegroundColor Green
}

function savedverses {
    $storePath = Join-Path $HOME ".lsm-saved-verses.json"
    if (-not (Test-Path $storePath)) { Write-Host "No saved verses yet."; return }
    (Get-Content $storePath -Raw | ConvertFrom-Json) | ForEach-Object {
        Write-Host $_.ref -ForegroundColor Cyan
        Write-Host $_.text
    }
}

```

Why @() around Get-Content ...: If only one verse is saved, PowerShell would otherwise hand you a single object instead of an array of one - and += would misbehave. Wrapping in @() guarantees you always get an array. This is a classic PowerShell gotcha - remember it.

Step 5 - The 'bible' command: a paged chapter reader

Reading a whole chapter means showing many verses without flooding the screen. The pattern is a while loop: show a page, ask what to do next, act on the answer, repeat until the user quits.

```

function bible {
    param([Parameter(ValueFromRemainingArguments=$true)][string[]]$Args)
    $chapterRef = $Args -join " "
    $result = Invoke-LsmApi -Reference $chapterRef
    if (-not $result -or -not $result.verses) { Write-Host "No verses found."; return }
    $verses = @($result.verses)
    $pageSize = [Math]::Max(3, $Host.UI.RawUI.WindowSize.Height - 8)

    $index = 0
    while ($true) {
        Clear-Host
        $pageEnd = [Math]::Min($index + $pageSize, $verses.Count) - 1
        for ($i = $index; $i -le $pageEnd; $i++) { Write-Host $verses[$i].text }

        Write-Host "[N]ext [P]revious [S]ave verse [Q]uit" -ForegroundColor Green
        $choice = (Read-Host ">").Trim()
        switch ($choice.ToUpper()) {
            "N" { if (($pageEnd + 1) -lt $verses.Count) { $index += $pageSize } }
            "P" { $index = [Math]::Max(0, $index - $pageSize) }
            "S" {
                $n = Read-Host "Verse number to save"
                $match = $verses | Where-Object { $_.ref -match ":\$n\$" } | Select-Object -First 1
                if ($match) { Save-LsmVerse -VerseObj $match }
            }
            "Q" { return }
        }
    }
}

```

Why \$Host.UI.RawUI.WindowSize.Height: This reads how tall your current terminal window is, so the page size adapts automatically. Split your terminal pane vertically (tall and narrow) before running bible - fewer verses per page, easier to read top to bottom.

A real bug: prefix-matching commands against book names

The first version of this lab used switch -Regex with patterns like '^[Pp]' - "starts with P". That looks fine until someone types `Psalms 23` to jump to a different chapter: it starts with P, so it silently triggered **Previous page** instead. Same problem for Numbers and Song of Songs against N and S.

The fix: Match the **whole trimmed input** against the exact letter (switch (\$choice.Trim().ToUpper()) { "N" {...} "P" {...} }) instead of a prefix. A single letter can only ever mean the command; anything longer falls through to default.

That default case is also where we add the feature you'll want most: if a chapter is short enough to fit on one page, there's no Next/Previous shown - but you can still type. So treat anything that isn't exactly N/P/S/Q/blank as a **new chapter reference** and jump straight to it, without leaving the reader:

```
default {
    $newResult = Invoke-LsmApi -Reference $choice
    if ($newResult -and $newResult.verses -and $newResult.verses.Count -gt 0) {
        $result = $newResult
        $verses = @($newResult.verses)
        $chapterRef = $choice
        $index = 0
    } else {
        Write-Host "Could not find '$choice' - try a format like 'John 4'." -ForegroundColor Red
    }
}
```

Try it: Open a short chapter (e.g. bible Philemon 1 - one chapter, no Next/Previous appears). At the prompt type John 4 and press Enter - the reader should jump straight there without you quitting first.

Step 6 - Wire it into your profile

So these commands exist in every new PowerShell window, dot-source the script from your PowerShell profile. Find your profile path by typing \$PROFILE, then add:

```
. "C:\path\to\BibleVerseTool.ps1"
```

The real, finished version of this file is already installed on this computer as part of the shipped tool - open it and compare your version line by line. Seeing a working reference alongside your own code is the fastest way to catch what you missed.

Checkpoint - prove it all works

- 1 verse John 3:16 - verse prints and clipboard shows "(copied to clipboard)".
- 2 Paste (Ctrl+V) somewhere to confirm the clipboard actually has the verse text.
- 3 bible Ephesians 4 - a page of verses appears, sized to your window.
- 4 Press N then P - you move forward and back a page.
- 5 Press S, enter a verse number, then Q to quit.
- 6 savedverses - the verse you just saved is listed.
- 7 bible Philemon 1 (no Next/Previous shown), then type John 4 and press Enter - the reader jumps to that chapter directly.

Quiz

- 1 What turns the JSON text the API sends back into a PowerShell object you can use with dot notation?
- 2 Why do we store the appid/token in a separate JSON file instead of typing them directly into the script?
- 3 What does wrapping a command in @() guarantee, and why does that matter for a single saved verse?
- 4 In the bible function, what stops the page from going past the last verse when you press N?
- 5 Which cmdlet copies text to the Windows clipboard?
- 6 Why does switch -Regex with pattern '^[Pp]' break when someone types Psalm 23, and what's the fix?

Answers

- 1 Invoke-RestMethod - it calls the URL and parses JSON automatically.
- 2 So the token never appears in a script you might share, copy, or check into somewhere public - and so changing the token doesn't require editing code.
- 3 It guarantees the result is always an array, even with zero or one items - without it, PowerShell can silently give you a single object instead of a one-item array, breaking += and .Count.
- 4 The check if ((\$pageEnd + 1) -lt \$verses.Count) before increasing \$index - it only advances if there are more verses left to show.
- 5 Set-Clipboard.
- 6 '^[Pp]' matches anything *starting* with P, so "Psalm 23" is misread as the Previous-page command. The fix is matching the whole trimmed input against the exact letter instead of a prefix, so only a bare "P" counts as the command.

Stretch goals

- Add a `-Lang spa` option to read in Spanish (the API supports it).
- Add an `unsave` command that removes one verse from `.lsm-saved-verses.json` by reference.
- Add a `randomverse` command that picks a random reference from a small built-in list and calls `verse` with it.
- Make `bible jump` straight to a starting verse number instead of always page 1.