

Aurora X1 Conference Camera

Northwind Devices product datasheet, revision 4.2, published 12 March 2026.

Overview

The Aurora X1 is a 4K pan-tilt-zoom conference camera for meeting rooms of six to sixteen seats. It combines a 1/1.8 inch sensor with an eight-microphone beamforming array and on-device speaker framing, so a room needs one device rather than a camera, a microphone bar, and a separate processor.

The camera is certified for Microsoft Teams Rooms and Zoom Rooms and is managed through the Northwind Device Portal. Firmware is delivered over the air in monthly rings, and a room can be pinned to the stable ring if a customer runs a validated configuration.

Technical specification

Attribute	Value
Product code	AUR-X1
Sensor	1/1.8 inch CMOS, 8.4 megapixel
Video	3840 x 2160 at 30 fps, 1920 x 1080 at 60 fps
Field of view	120 degrees diagonal
Zoom	5x optical, 12x digital
Audio	8-microphone beamforming array, 6 metre pickup
Connectivity	USB-C 3.1, Gigabit Ethernet, Wi-Fi 6
Power	PoE+ (IEEE 802.3at) or 24 W external supply
Dimensions	218 x 96 x 84 mm
Weight	1.24 kg
Operating temperature	0 to 40 degrees Celsius
Warranty	24 months return to base

Room sizing guidance

Use one Aurora X1 for rooms up to 42 square metres. Larger rooms should pair a second unit in follower mode, which shares the audio array of the primary device and adds a second framing angle. Rooms with a glass wall behind the participants should enable backlight compensation in the device portal.

Ordering information

SKU	Description	Included
AUR-X1-STD	Aurora X1, standard bundle	Camera, wall mount, 5 m USB-C cable
AUR-X1-PoE	Aurora X1, PoE bundle	Camera, wall mount, PoE injector
AUR-X1-TAB	Aurora X1, table bundle	Camera, table stand, 2 m USB-C cable

Specifications are subject to change. For current stock and delivery dates, contact the Northwind support desk.