Appendix B. Rules for compiling the rating list (new system)

B.1. General provisions

B.1.1. The Rating is a system of numerical estimates of the strength of teams and players in competitive «What? Where? When?». It is built from the results of tournaments included in the Rating and published as Releases.

B.1.2. A Release is the list of teams sorted by team rating in descending order, as of the Thursday of the week in question. A list of players sorted by individual rating in descending order is published together with each Release.

B.1.3. The identifiers of a team and a player are their identifiers in the rating database (`team_id` and `player_id`). A team keeps its identifier through any change of lineup.

B.1.4. The Rating includes tournaments marked as rated in the database with a start date on or after 1 January 2013 and before 5 September 2026; the upper bound excludes tournaments announced but not yet played. Marathons, asynchronous tournaments and tournaments of unrecognised type are not included.

B.1.5. The weight w_t of a tournament is a multiplier on the evidence its results carry, set by the format:

in-person tournament (regular or regional) – 1;
strictly synchronous tournament – 2/3;
synchronous tournament – 1/2.

B.1.6. A rated result is a team result marked `inRating` in the database. An unrated result belongs to a composite team with no base lineup. It gives the team no rating update, no rated tournament and no right to appear in a Release, and it does not open a team state. The team still stands in the field as an opponent for all others and enters the pairwise comparison (B.3.10) with its tournament strength, and its players are updated in the question model in the usual way.

B.1.7. The number of questions n_q in a tournament is the longest mask among its results. If no masks exist, n_q is the sum of question counts over rounds. The team rating does not read the number of questions.

B.1.8. Events are processed in ascending order of tournament start date, and among equal dates in ascending order of tournament identifier. Processing is done once, in forward chronological order; a published rating value is never revised.

B.1.9. The rated quantities are:

the team rating and its usual lineup – for every team;
the player strength, its uncertainty and its volatility – for every player.

B.1.10. A team rating and a player rating change only through the results of a rated tournament played. Inactivity does not change a team rating; it widens the uncertainty of a player estimate but does not lower the estimate.

B.1.11. A Release includes only the teams and players that played at least one rated tournament in the 365 days before the Release date. For a team only rated results count. Being left out of a Release does not change the state of a team or a player.

B.2. Individual rating

B.2.1. The state of player i is the set of quantities: strength θ_i, uncertainty σ_i^2 and volatility v_i.

B.2.2. The question model is a probabilistic model of a lineup answering a question. Question q has a difficulty b_q and a log discrimination $\ln a_q$. The probability that lineup L answers question q is

$$P_{L,q} = 1 - \exp(-u_q), \quad u_q = \sum_{i \in L} \lambda_{i,q}, \quad \lambda_{i,q} = \exp(a_q(\theta_i - b_q)).$$

where:

$\lambda_{i,q}$ – the intensity of player i on question q;

u_q – the total intensity of the lineup on question q;

a_q – the discrimination of question q;

b_q – the difficulty of question q;

L – the lineup that played the tournament.

B.2.3. The model in B.2.2 is the «noisy OR» model: a question counts as answered if at least one player of the lineup answers it, and the players' contributions are independent.

B.2.4. Saturation is the clamping of u_q to the interval $[\exp(-u_{max}), u_{max}]$ before it enters the probability, with $u_{max} = 15$. Without saturation a maximally confident prediction against the observed outcome makes the log loss infinite.

B.2.5. The prior distributions of the question parameters are $\ln a_q \sim N(0, s_a^2)$ and $b_q \sim N(\bar{b}, s_b^2)$, with $s_a = 0.5$, $\bar{b} = 1.5$, $s_b = 2.0$.

B.2.6. The log likelihood of a tournament is the sum of log probabilities over all questions and all teams of the tournament, multiplied by w_t; the prior terms are not multiplied by the weight. In addition:

B.2.6.1. questions marked in the mask as withdrawn or unknown are excluded;

B.2.6.2. results with no mask take no part in the question model.

B.2.7. The update after a tournament is a sequence of three steps.

B.2.7.1. Question fit. With player strengths fixed, each question q independently takes $a_q = 1$, and the difficulty b_q is set in closed form so that the model predicts exactly the observed answer rate for a lineup of average reach:

$$b_q = \frac{1}{|\mathcal{L}_q|} \sum_{L \in \mathcal{L}_q} \ln R_L - \ln(-\ln(1 - \hat{r}_q)), \quad R_L = \sum_{i \in L} \exp(\theta_i),$$

where:

$\mathcal{L}_q$ – the lineups that played question q; R_L – the reach of lineup L; $\hat{r}_q$ – the share of lineups in $\mathcal{L}_q$ that answered, clamped to no less than 0.02 and no more than 0.98, which keeps a question answered by everyone or by no one on the scale.

B.2.7.2. Player update. With question parameters fixed, for every player i who played the tournament the gradient g_i and the observed Fisher information I_i of the tournament log likelihood with respect to θ_i are computed, and then

$$I_{eff} = w_t I_i d_{info}, \quad \pi'_i = 1/\sigma_i^2 + \max(I_{eff}, I_{min}), \quad \Delta\theta_i = \frac{w_t d_{info} g_i}{\pi'_i}, \quad \sigma_i^2 \leftarrow 1/\pi'_i.$$

where:

d_{info} – the information discount, 0.46;

I_{min} – the information floor, 0.001;

σ_i^2 – the uncertainty after the increment of B.2.11, taken before the update.

B.2.8. The strength increment is capped in absolute value at 1.5.

B.2.8.1. Shrinkage to the lineup. After the update every player of the lineup is pulled towards the mean strength of the lineup:

$$\theta_i \leftarrow \theta_i + f \cdot \left(\frac{1}{|L|} \sum_{j \in L} \theta_j - \theta_i \right), \quad f = 0.005.$$

B.2.9. The discount d_{info} exists because the answers of one team are not independent given the player strengths: one tournament carries less evidence than the curvature of the likelihood claims. Its value is set by the honesty requirement on the published uncertainty (B.7.7).

B.2.10. Shrinkage to the lineup exists because the «noisy OR» likelihood credits an answer to whoever is already stronger and drives partners who play the same questions thousands of places apart. The value $f = 0$ switches shrinkage off.

B.2.11. Between tournaments the uncertainty of a player estimate grows by $\upsilon_i^2 \Delta t$, where Δt is the interval in years and υ_i the player's volatility. Volatility is individual and is updated after every tournament with $I_{eff} > I_{min}$ from the standardised surprise

$$z_i = \frac{g_i / I_i}{\sqrt{\sigma_i^2 + 1/I_{eff}}}, \quad \ln \upsilon_i \leftarrow \ln \upsilon_i + \eta_\upsilon (\ln \upsilon_* - \ln \upsilon_i),$$

where:

σ_i^2 – the uncertainty before the update;

η_υ – the volatility learning rate, 0.15;

$\upsilon_* = \upsilon_{max} = 0.6$ if $|z_i| > 1$, and $\upsilon_* = \upsilon_{min} = 0.05$ otherwise.

B.2.12. A long, steady history therefore drives the uncertainty to its floor regardless of the calendar, and only a run of results unlike the past opens it again. A new player's volatility is 0.25.

B.2.13. A newcomer is a player with no rated tournaments played. A newcomer enters the Rating with $\theta = -1.0$ and $\sigma = 1.0$. For every player the number of rated tournaments played and the date of the last one are stored.

B.2.14. The question parameters of a played tournament are stored for reporting and are not used in later updates: a question is never asked again.

B.2.15. Scale calibration is an operation performed when each Release is compiled. Let

$$\Delta = \frac{1}{|E|} \sum_{i \in E} \theta_i,$$

where:

E – the set of players who played at least 8 rated tournaments in the preceding 365 days;

Δ – the scale shift of this Release.

B.2.16. Δ is subtracted from every player's strength. The mean strength of established players in every Release is therefore zero. Question difficulties are not corrected, since questions are never asked again. The team rating is not corrected either: it is not a quantity on the θ scale, and calibration reaches it only through player strengths, from which the lineup estimate and a new team's first rating are read.

B.2.17. Player states are stored before the shift is subtracted, and the accumulated shift is subtracted on reading. The published change of a quantity since the previous Release that included it is therefore its own movement, free of scale calibration.

B.2.18. The individual rating is a direct estimate of the question model. It is published together with its uncertainty; no grade transition rules, thresholds or limits on change apply to it.

B.2.19. Reserved. The Rules provide for three extensions of the question model that are implemented and tested but switched off in this edition; none of them lowered the cross-validated log loss of test B.7.3. The first is a free number of steps: a question gets a parameter m_q and the answer probability becomes $P_{L,q}^{m_q}$, which penalises lineups of sharply unequal strength relative to even ones; the mean fitted m_q was 1.056 and the gain was in-sample only. The second is editor affinity: a player gets a vector u_i, an editor a vector v_e, and the player's strength in a tournament grows by the mean dot product $u_i \cdot v_e$ over the tournament's editors; the learned values did not exceed 0.01 on the strength scale, since the Fisher information for u_i is smaller than for θ_i and one forward pass is not enough to extract it. The third is the Newton question fit: instead of the closed form of B.2.7.1, $(b_q, \ln a_q)$ are fitted by damped Newton iterations with step halving on the penalised log likelihood, at most 12 iterations, clamped to $a_q \in [0.3, 3.0]$ and $b_q \in [-10, 12]$; the priors of B.2.5 serve this fit. It lowers the cross-validated log loss by

0.0009 and the in-sample log loss by 0.018, within the test tolerance, and was replaced by the closed form for simplicity of exposition. All three extensions remain in the implementation behind their switches and are reserved for a future edition of these Rules.

B.3. Team rating

B.3.1. The strength of player i on the team scale is

$$r_i = r_0 + s \cdot (\theta_i + \ln 6 + \delta_0),$$

where:

r_0 – the zero of the team scale, 6000;

s – the slope of the team scale, 2454.8828;

δ_0 – the lineup estimate correction, −0.2427.

B.3.2. The map B.3.1 is chosen so that six equal players of strength r form a lineup of strength r (B.3.3). The zero r_0 is free: the Rules never read the absolute level of a rating, and a common shift of every quantity changes no forecast and no place. The slope s is not free: it enters the update step relative to the constant D.

B.3.3. The lineup estimate $Q(L)$ of lineup L is

$$Q(L) = s \cdot \left(\ln \sum_{i \in L} \exp(r_i / s) - \ln 6 \right).$$

B.3.4. $Q(L)$ is the strength of a single player who would answer as many questions as the whole lineup together, expressed on the team scale. A short lineup is weaker than a full one, and a strong player in an uneven lineup enters the estimate with more weight than in the arithmetic mean; both follow from the construction, with no separate penalties. The correction δ_0 and the zero r_0 of B.3.1 cancel, so only the slope enters the lineup estimate.

B.3.5. The state of team T is the set of quantities:

R_T – the team rating on the published scale;

$\overline{Q}_T$ – the usual lineup of the team: the lineup estimate of the lineups that earned the rating;

n_T – the number of rated tournaments of the team;

the date of the team's last rated tournament.

B.3.6. A new team is one with no state. The state is opened by the first rated result with $R_T = \overline{Q}_T = Q(L)$, where L is the lineup in that tournament. An unrated result does not open a team state.

B.3.7. The field of a tournament is the set of its results that have a non-empty lineup or a previously opened state; a result with neither is skipped. The quantities of B.3.8–B.3.10 read player states as they were before the tournament and are computed for the whole field before any new state is written.

B.3.8. The tournament strength of a team is

$$F_T = R_T + \left(Q(L) - \overline{Q}_T \right).$$

B.3.9. A team rating is judged against the team's own usual lineup: guest players raise the tournament strength, absent players lower it, and neither changes R_T. A team opening its state enters the field with $F_T = Q(L)$; a result that lists no lineup enters with $F_T = R_T$.

B.3.10. The pairwise comparison is the following procedure. For every pair of teams A and B in the field

$$P_{AB} = \frac{1}{1 + 10^{(F_B - F_A)/D}}, \quad S_A = \frac{\sum_{B \neq A} y_{AB} - \sum_{B \text{ not tied with } A} P_{AB}}{N - 1}.$$

where:

P_{AB} – the expected share of wins of team A over team B;

y_{AB} – the outcome of the pair: 1 if A placed above B, 0 if below;

D – the scale constant, 1200;

N – the number of teams in the field;
S_A – the surprise of team A's result.

B.3.11. A pair of teams that shared a place is skipped in both sums: such a pair says nothing about which of the two is stronger. The score margin does not enter the pairwise comparison.

B.3.12. Since $y_{AB} - P_{AB} \geq 0$ for every pair in which team A placed higher, a team that took first place has $S_A \geq 0$. Such a team therefore never loses rating points, whether its first place is sole or shared. This property is the winner rule; it follows from the construction of the update, not from a separate rule.

B.3.13. The update after a tournament is the following, performed only on a rated result:

$$R_T \leftarrow R_T + K w_t D S_T, \quad \overline{Q}_T \leftarrow \overline{Q}_T + K_q\big(Q(L) - \overline{Q}_T\big), \quad n_T \leftarrow n_T + 1,$$

where:
K – the rating step, 0.4;
K_q – the usual-lineup step, 0.01;
w_t – the tournament weight.

B.3.14. The usual lineup is updated only when the lineup is non-empty. An unrated result stands in the field as an opponent for all others and gives the team no update, no rated tournament and no right to appear in a Release; the date of the last rated tournament advances only on a rated result.

B.3.15. Inactivity does not change a team rating: nothing happens to a team state between tournaments. A change of lineup by itself does not change any team's rating either: today's lineup changes the tournament strength of B.3.8, and the usual lineup follows a real change over subsequent tournaments.

B.3.16. The constants D, K and K_q are set outside the publication loop (B.7.6).

B.4. Forecast

B.4.1. The forecast is an object separate from the rating: an estimate of the strength with which a team will play a given tournament with a given lineup. The forecast takes no part in the rating update and has no effect on it.

B.4.2. The forecast strength of a team is the lineup estimate of its lineup, $Q(L)$ (B.3.3); with no lineup, its tournament strength F_T (B.3.8).

B.4.3. The forecast place of a team is its place in the ordering of the field by forecast strength in descending order; first place is the largest forecast strength, and equal values share the mean of their places.

B.4.4. The forecast does not read the team state at all. This is not a simplification but the outcome of test B.7.2: on in-person tournaments of the last two seasons the lineup predicts the result better than the team rating, better than the rating with the lineup offset, and better than the forecast of the old system. Teams are stable; the lineup is not, and the lineup is what answers that question.

B.5. Tournament difficulty

B.5.1. The difficulty D_t of a tournament is computed from the fitted parameters of its questions against a fixed reference lineup of six equal players of strength θ^*:

$$p_q = \big(1 - \exp\big(-6\exp\big(a_q(\theta^* - b_q)\big)\big)\big)^{m_q}, \quad D_t = 10\left(1 - \frac{1}{|Q|}\sum_{q \in Q} p_q\right),$$

where:
Q – the set of questions of the tournament answered by at least one team;
p_q – the probability that the reference lineup answers question q;
θ^* – the reference strength, 0.2368.

B.5.2. Difficulty is undefined if no question of the tournament was answered.

B.5.3. The reference strength θ^* is the strength of a balanced team of places 251–500, expressed as six equal players. It matches the band taken as reference in the published TrueDL index, so D_t means what that index promises: ten times the share of the package such a team would not answer, computed from fitted difficulties rather than from a table of ratios between bands. θ^* is fixed at launch and is not recomputed.

B.6. Published quantities

B.6.1. The published rating is an affine map of the internal value:

$$R_{team} = A_T + B_T R_T, \quad R_{player} = A_P + B_P \theta_i.$$

where:

A_T = –7295.3562, B_T = 1.1904 – the constants of the team scale;

A_P = 5543.6775, B_P = 4723.7898 – the constants of the individual scale.

B.6.2. The constants of both scales were set once from the condition that the published values at places 50 and 1000 match the old system's values at the same places: for teams 7028 and 2992 in the Release nearest 5 September 2019, for players 12 865 and 9778 in the Release nearest 3 October 2019. The internal team scale is set by the constants r_0 and s of the map B.3.1 the published map only carries it to the familiar level. The top of the table sits where the internal scale puts it. Once adopted, the constants are not revised.

B.6.3. A team rating is provisional when the team has played fewer than five rated tournaments, and a player rating is provisional when its uncertainty exceeds 0.3 on the internal scale. Provisional estimates are published with a mark and are left out of the ranked tables.

B.6.4. Together with a team's published rating the Release shows its number of rated tournaments, its usual lineup, the date of its last rated tournament and the change of rating since the previous Release that included the team. Together with a player's published rating the Release shows the uncertainty of the estimate, the number of rated tournaments in the preceding 365 days, the date of the last one and the same change. The change is free of scale calibration and is zero on first appearance and in a week without games. The uncertainty of a team rating is not published: Model S2 does not estimate it.

B.6.5. For every tournament its difficulty is published, and for every team its forecast strength, forecast and actual places, rating before and after the tournament, tournament strength, lineup offset, lineup estimate, surprise of the result and whether the result is rated.

B.7. Verification

B.7.1. These Rules were adopted on the results of tests run on the data of the whole covered period. The test results:

Test	Requirement	Result	Outcome
Cross-validated log loss on in-person rated tournaments	lower than the nested baseline model	0.4900 over all seasons, 0.5161 in season 2025/26	passed
Spearman rank correlation of the forecast on in-person tournaments of the last two seasons	within 0.02 of the best external system	0.8363 against 0.8177 for the old system; on synchronous tournaments 0.8194 against 0.7897	passed
Overlap of the top 200 of the individual list with external systems	at least 140 of 200	117 of 200 with chgk.quest, 122 of 200 with rating.chgk.fun	failed
Inflation: published value of the 50th team on September Releases 2015–2026	within the band ±10%	largest deviation 6.3% over 11 Releases	passed

Test	Requirement	Result	Outcome
Transfer invariance: swapping the strongest players between two teams	no team rating changes, forecasts change	0 teams changed, largest difference exactly 0; the forecast changed for 286 139 results	passed
Winner rule	the first-placed team's rating after the tournament is not below its rating before	0 violations	passed

B.7.2. The forecast rank correlation test is passed with a margin, not within tolerance: the lineup forecast beats the old system's forecast by 0.8363 against 0.8177 on in-person tournaments and by 0.8194 against 0.7897 on synchronous ones. On the same tournaments the team rating alone gives 0.66 and the rating with the lineup offset 0.83, so the lineup predicts the result better than the accumulated rating.

B.7.3. The log loss test decides the composition of the model: an extension stays in the Rules only if it lowers this figure. For comparison, the external system chgk.quest publishes 0.501, measured in-sample.

B.7.4. September 2021 is excluded from the September Releases: fewer than two hundred rated teams played in the year before it, which is a gap in the data, not inflation.

B.7.5. The top-200 overlap test is failed. The threshold of 140 of 200 is above what mature external systems reach with each other: chgk.quest and rating.chgk.fun agree on 136 of 200. The rank correlation of the strength of players with at least 50 tournaments is 0.90 with chgk.quest and 0.79 with rating.chgk.fun.

B.7.6. Outside the publication loop the following are set: the correction δ_0 – as the mean difference between a team's realised strength and the uncorrected sum of its players' strengths over full six-player lineups on in-person tournaments of 2015–2024; the constant D – as the maximum-likelihood value for the pairwise outcomes, the likelihood being flat from 900 to 2400; the steps K and K_q – as the maximum of the mean Spearman rank correlation of the forecast on in-person tournaments from 1 September 2018 to 29 August 2024 over the grid 0.2, 0.3, 0.4 and 0.6 for K and 0.01, 0.03 and 0.1 for K_q; the constants of the individual scale – from the 2019 Release (B.6.1).

B.7.7. The honesty requirement on uncertainty is the condition that the standardised residuals z_i have unit variance on in-person tournaments from 2018 onwards. This requirement sets the discount d_{info}. It does not apply to the team rating: Model S2 neither estimates nor publishes an uncertainty.

B.8. Transitional provisions

B.8.1. The initial recomputation is the processing of all rated tournaments from 1 January 2013 under the rules of sections B.2 and B.3 in chronological order.

B.8.2. In the first season there is no history: every player enters with the newcomer prior at once, the question difficulties of the strong 2013 field come out too low, and its players too high. The initial recomputation is therefore run in 2 passes, and the outputs are written only on the last.

B.8.2.1. The first pass follows the general rules. On first reaching a tournament dated on or after 1 January 2016 it stores the strength of every player who has appeared so far.

B.8.2.2. Every later pass starts again from 1 January 2013: stored players enter with their stored strength, uncertainty 0.5 and volatility 0.25, and all others count as never seen and enter with the newcomer prior at their first tournament. Team states are rebuilt from scratch in every pass.

B.8.3. Since the store is taken on 1 January 2016 and no player who debuted after that date gets an initial estimate, no value after that date rests on its own future.

B.8.4. After the initial recomputation publication proceeds in a single forward pass. Full recomputations happen only outside the publication loop, to tune constants and for the initial recomputation. A published Release is never rewritten.

B.8.5. The quantities marked tunable in these Rules were set once and frozen on the date the Rules came into force. Any later change to them is a change to these Rules.

* * *