PDA-3505

HANDHELD TERMINAL

- Android 4.4 platform
- IP65 Protect
- Compact design
- Internal 58mm thermal printer
- Internal 3G/GPRS
- Bluetooth,Wi-FI,GPS
- 1D2D Scanner
- PSAM Encryption
- Internal NFC
- 5.0M pixs auto focus camera
- Dual-core 1.4GHz processer
- Provide full technical support

http://www.qspritner.com

SPECIFICATION

INDUSTRY HANDHELD TERMINAL

PDA-3505

HARDWARE SPECIFICATION

PROCESSOR

CPU : MediaTek MT6572
SPEED : Dual-core 1.4GHz

MEMORY

MEORY : 512MB/1GB(optional)
FLASH :4GB
EX-STORAGE: Micro SD up to 32GB

DISPLAY

SCREEN : 3.5Inch Color TFT

INPUT

KEYBOARD : 27 Buttons and 2buttons
TOUCH : Capacitive Multi-Touch

COMMUNICATION

Wi-Fi : IEEE 802.11b/g/n
BLUETOOTH : BT4.0
3G NETWORK: WCDMA 2100MHz
TELPHONE: 3G And GSM
LOCATION: Internal GPS

CAMERA(optional)

Standard: Rear 5.0Mpixs Auto Focus
FLASH: LED Light

POWER

BATTERY: 7.4v 3200mAH Recharge
ADAPTER :   DC9V/1A

PRINTER

TYPE : Thermal receipt / label
WIDTH :58mm
ROLL DIAMETER : Max. Ø 30mm

INGRESS PROTECTION

IP: IP65
DROP: 1.8m(Standard)

TEMPERATURE

OPERATING TEMPERATURE : -10 ~ 50℃

STORAGE TEMPERATURE : -30 ~ 65℃

HUMIDITY

OPERATING HUMIDITY : 10 ~ 90%
OPERATING HUMIDITY : 10 ~ 90%

DATA COLLECT

BARCODE SCANNER

1D : EAN-8, EAN-13, EAN-128, RSS, Postnet, Code39, Code93, Code128,Codabar,
ITF, UPC-A, UPC-E
2D : PDF417, QR Code, Maxicode. GS-1, Datamatrix, Aztec(Optional)

NFC

STANDARD : ISO18092,ISO14443,ISO15693 Write/Read

IC CARD

STANDARD : ISO7816(Optional)

INTERFACE

INTERFACE

STANDARD : Micro USB,RS232C,DC Port, Earphone port,SIM&TF slot
Optional : IC Card slot

SOFTWARE

PLATFORM

OS: Android 4.4

SUPPORT

TECHNICAL SUPPORT: Test Demo,SKD code,API Document

DIMENSION SPECIFICATION

DIMENSION

W x D x H(mm) : 209*83*49mm

WEIGHT

0.58kg (with 3200mAh battery)

OPTIONAL

CHARGING DOCK

PRODUCT FEATURES

IP65   COMPACT   3G/Wi-Fi   Bluetooth   High speed   SCANNER