2. Feld einer Hohlkugel

$$m = 5 \text{ kg}$$
; $k = 2 \text{ N/m}$; $a = 0.1 \text{ m}$; $h = 0.4 \text{ m}$; $l = 0.1 \text{ m}$

a)
$$\rho = \frac{Q}{V}$$

$$V = \int_{V} dV = \int_{0}^{\pi} \int_{0}^{2\pi} \int_{R_{i}}^{R_{a}} r^{2} \sin(\theta) dr d\varphi d\theta$$
$$= \frac{4}{3}\pi (R_{a}^{3} - R_{i}^{3})$$
$$\rho = \frac{3Q}{4\pi} (R_{a}^{3} - R_{i}^{3})$$

b)
$$F = -m\omega^2 x$$
; $\Delta x = x_1 - x_2$

$$m\ddot{x_1} = -m\omega_a^2 x_1 - k(x_1 - x_2)$$

$$m\ddot{x_2} = -m\omega_a^2 x_2 - k(x_2 - x_1)$$

$$\Rightarrow m(\ddot{x_1} - \ddot{x_2}) = -m\omega_a^2(x_1 - x_2) - 2k(x_1 - x_2) = -(m\omega_a^2 + 2k)(x_1 - x_2)$$

$$\Delta \ddot{x} = -\underbrace{(\omega_a^2 + \frac{2k}{m})}_{= \omega_b} \Delta x$$

$$\omega_b = \sqrt{\omega_a^2 + \frac{2k}{m}} = \underline{6.43 \text{ rad/s}}$$

c)
$$\delta\omega = \omega_b - \omega_a$$


$$0 = \cos\left(\frac{1}{2}\delta\omega t\right)$$

$$t = \frac{2\arccos(0)}{\delta\omega} = \underline{50.29 \text{ s}}$$

3. Zwei ringförmige Ladungsträger

$$k = \frac{1}{4\pi\epsilon_0}$$

a)
$$h = \sqrt{r^2 + z^2}$$
; $\cos(\theta) = \frac{z}{h}$; $dQ = \lambda dr$; $dr = r d\varphi$; $Q = 2r\pi\lambda$



Due to the symmetric nature of this problem we can neglect vertical components of forces

$$dE_{1}(z) = k \frac{dQ}{h^{2}} \cos(\theta) = k \frac{\lambda dr}{r^{2} + z^{2}} \frac{z}{\sqrt{r^{2} + z^{2}}} = k \frac{\lambda rz}{(r^{2} + z^{2})^{3/2}} d\varphi$$

$$E_{1}(z) = \int dE_{1} = k \frac{\lambda rz}{(r^{2} + z^{2})^{3/2}} \int_{0}^{2\pi} d\varphi = k \frac{\lambda 2\pi rz}{(r^{2} + z^{2})^{3/2}} = k \frac{Qz}{(r^{2} + z^{2})^{3/2}}$$

$$E_{2}(z) = -E_{1}(z - d) = -k \frac{Q(z - d)}{(r^{2} + (z - d)^{2})^{3/2}}$$

$$E_{ges}(z) = E_{1} + E_{2} = k \frac{Qz}{(r^{2} + z^{2})^{3/2}} - k \frac{Q(z - d)}{(r^{2} + (z - d)^{2})^{3/2}}$$

$$= kQ \left(\frac{z + \frac{d}{2}}{(r^{2} + (z + \frac{d}{2})^{2})^{3/2}} + \frac{\frac{d}{2} - z}{(r^{2} + (z - \frac{d}{2})^{2})^{3/2}}\right)$$

b)
$$F = -m\omega^2 x$$
; $\Delta x = x_1 - x_2$
 $m\ddot{x}_1 = -m\omega_a^2 x_1 - k(x_1 - x_2)$
 $m\ddot{x}_2 = -m\omega_a^2 x_2 - k(x_2 - x_1)$
 $\Rightarrow m(\ddot{x}_1 - \ddot{x}_2) = -m\omega_a^2 (x_1 - x_2) - 2k(x_1 - x_2) = -(m\omega_a^2 + 2k)(x_1 - x_2)$
 $\Delta \ddot{x} = -(\omega_a^2 + \frac{2k}{m})\Delta x$
 $= \omega_b$
 $\omega_b = \sqrt{\omega_a^2 + \frac{2k}{m}} = \underline{6.43 \text{ rad/s}}$

c)
$$\delta\omega = \omega_b - \omega_a$$

$$0 = \cos(\frac{1}{2}\delta\omega t)$$

$$0 = \cos\left(\frac{1}{2}\delta\omega t\right)$$
$$t = \frac{2\arccos(0)}{\delta\omega} = \underline{50.29 \text{ s}}$$