

Shen Zhen MTC Co., LTD

TEST REPORT

SCOPE OF WORK

SAR Assessment—MHDV4080-T9503-S2, MHDV4080-T9503,
MHDV40****- T9503-##, MHDV40****- T9503, (*, # can from
0 to 9, A to Z or blank), 2T-C40HD2225EB, 2T-C40HD2225KB,
2T-C40HD2725KB, 2T-C40HD2725EB, 2T-C40HD3225EB, 2T-
C40HD3225KB, 2T-C40HD2x25EB, 2T-C40HD2x25KB, **-
*40***** (* can from 0 to 9, A to Z or blank),
PR40F2462VKB, F40AR5G, LT-40CR350, L40RFE25

REPORT NUMBER

260508019SZN-007

ISSUE DATE

20 May 2026 [-----]

[REVISED DATE]

PAGES

6

DOCUMENT CONTROL NUMBER

EN 62311_b

© 2017 INTERTEK



Test Report

Applicant: Shen Zhen MTC Co., LTD

Number: 260508019SZN-007

MTC Industry Park, 1st Lilang Road, Xialilang community,
Nanwan Longgang district, Shenzhen, China**Sample Description**

Product : TV/LED TV

Model No. : MHDV4080-T9503-S2, MHDV4080-T9503, MHDV40****-T9503-##, MHDV40****-T9503, (*, # can from 0 to 9, A to Z or blank), 2T-C40HD2225EB, 2T-C40HD2225KB, 2T-C40HD2725KB, 2T-C40HD2725EB, 2T-C40HD3225EB, 2T-C40HD3225KB, 2T-C40HD2x25EB, 2T-C40HD2x25KB, **_40*****(* can from 0 to 9, A to Z or blank), PR40F2462VKB, F40AR5G, LT-40CR350, L40RFE25

Brand Name : AMTC, SHARP, Polariod, VITADO, JVC, Logik

Electrical Rating : 220-240V~, 50/60Hz, 70W or 90W

Date Received : 14 January 2025

Date Test Conducted : 14 January 2025 to 12 February 2025

Test Requested : Test for compliance with EN IEC 62311: 2020

Test Method : EN IEC 62311: 2020

Test Result : See the attached sheets

Conclusion : The submitted samples Complied with the above safety standard. But the note should be noted.

Prepared and Checked By:**Approved By:**

Bruce Zheng
Project Engineer

Rode Liu
Project Engineer
Date: 20 May 2026

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd.

No.101&201, Building B, No. 308, Wuhe Avenue, Zhangkengjing, Guanhu Street, Longhua District, Shenzhen, Guangdong, China

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

Test Report

Test Results:

Number: 260508019SZN-007

EN IEC 62311: 2020

<u>Clause</u>	<u>Title/Description</u>	<u>Result</u>
1	Scope	
2	Normative references	--
3	Terms and definitions	--
4	Compliance criteria	Complied (See Note)
5	Assessment report	--

The Model: MHDV4080-T9503, MHDV40****- T9503-##, MHDV40****- T9503, (*, # can from 0 to 9, A to Z or blank), 2T-C40HD2225EB, 2T-C40HD2225KB, 2T-C40HD2725KB, 2T-C40HD2725EB, 2T-C40HD3225EB, 2T-C40HD3225KB, 2T-C40HD2x25EB, 2T-C40HD2x25KB, **-*40*****(* can from 0 to 9,A to Z or blank), PR40F2462VKB, F40AR5G, LT-40CR350, L40RFE25 are the same as the Model: MHDV4080-T9503-S2 in hardware aspect. The difference in model number serves as marketing strategy.

This report bases on the previous report with report number 251219032SZN-005 Dated 09 January 2026 (original signature by Bruce Zheng, Rode Liu on file). Owing to adding the models, no test was required after evaluation.

This test product may be sold to different regions and different customers with different bases. Different bases have no effect on the test results.

***** End of Page *****

Test Report

Note:

Number: 260508019SZN-007

- (1) When determining the test conclusion, the Measurement Uncertainty of test has been considered. The uncertainty of 30% is used for evaluation of compliance to the limit.
- (2) According to EN IEC 62311: 2020, the apparatus shall comply with the basic restriction specified in Council Recommendation 1999/519/EC. The reference levels in the Council Recommendation 1999/519/EC on public exposure to electromagnetic fields are derived from the basic restrictions using worst-case assumptions about exposure. The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation.

Reference levels for electric, magnetic and electromagnetic fields
(0Hz to 300GHz, unperturbed rms values)

Frequency Range	E-Field Strength (V/m)	H-Field Strength (A/m)	B-Field (uT)	Equivalent plane wave power density Seq (W/m2)
0-1 Hz	-	3.2×10^4	4×10^4	-
1-8 Hz	10000	$3.2 \times 10^4 / f^2$	$4 \times 10^4 / f^2$	-
8-25 Hz	10000	$4000 / f$	$5000 / f$	-
0.025-0.8 kHz	$250 / f$	$4 / f$	$5 / f$	-
0.8-3 kHz	$250 / f$	5	6.25	-
3-150 kHz	87	5	6.25	-
0.15-1 MHz	87	$0.73 / f$	$0.92 / f$	-
1-10 MHz	$87 / f^{1/2}$	$0.73 / f$	$0.92 / f$	-
10-400 MHz	28	0.073	0.092	2
400-2000 MHz	$1375 f^{1/2}$	$0.0037 f^{1/2}$	$0.0046 f^{1/2}$	$f / 200$
2-300 GHz	61	0.16	0.020	10

From above table,

For Wi-Fi function, the maximum power density limits is 10 W/m² at 2400MHz to 2483.5MHz, 5150MHz to 5250MHz, 5725MHz to 5875MHz.

Power density (S) is calculated by the following formula:

$$S = (P \cdot G) / 4\pi R^2$$

$$E.I.R.P = P \cdot G$$

Where, S = Power density (mW/cm²)

P = Output power to antenna (mW)

R = Distance between radiating structure and observation point (cm)

G = Gain of antenna in numeric

$$\pi = 3.14$$

***** End of Page *****

Test Report

APPENDIX:

Number: 260508019SZN-007

For 2.4GHz Wi-Fi – Worst Case Result:

Channel	Channel Frequency (MHz)	Maximum antenna gain (dBi)	Maximum antenna gain (numeric)	E.I.R.P (mW)	Power density (W/m2)	Limit of power density (W/m2)
1	2412	1.72	1.49	77.98	0.155136	10

Note:

1. This E.I.R.P. value is from the CN23DLMM 001 report.
2. The assess distance is 0.2m (20cm).

For 5GHz Wi-Fi – Worst Case Result:

Channel	Channel Frequency (MHz)	Maximum antenna gain (dBi)	Maximum antenna gain (numeric)	E.I.R.P (mW)	Power density (W/m2)	Limit of power density (W/m2)
36	5180	2.57	1.81	49.89	0.099253	10

Note:

1. This E.I.R.P. value is from the CN23DLMM 002 report.
2. The assess distance is 0.2m (20cm).

For 5.8GHz Wi-Fi – Worst Case Result:

Channel	Channel Frequency (MHz)	Maximum antenna gain (dBi)	Maximum antenna gain (numeric)	E.I.R.P (mW)	Power density (W/m2)	Limit of power density (W/m2)
165	5825	2.57	1.81	13.27	0.026400	10

Note:

1. This E.I.R.P. value is from the CN23DLMM 003 report.
2. The assess distance is 0.2m (20cm).

***** End of Page *****

Test Report

APPENDIX:

Number: 260508019SZN-007

Synchronous transmit

Note: 2.4GHz Wi-Fi/5GHz Wi-Fi/5.8GHz Wi-Fi does not support simultaneous transmission.

Based on the above assessment, this device complies with the human exposure restrictions while this device installed and/or operated with a minimum distance of 20 cm between the radiator and your body.

The Notice in Installation Manual should state as below:

The user must maintain a minimum distance of 20 cm from the device at all time.

***** End of Page *****

Test Report

APPENDIX:

Number: 260508019SZN-007

Photos of EUT

Please refer to Annex of EUT Photos_260508019SZN.

***** End of Report *****

DRAFT