

Shen Zhen MTC Co., LTD

TEST REPORT

SCOPE OF WORK

SAR Assessment—MUDV50B0-90106-T2, MUDV50B0-90106-S2, MUDV50B0-90106, MUDV50****-90106-## (*, # can from 0 to 9, A to Z or blank), 4T-C50FJ2KL1FB, 4T-C50FJ2EL2NB, 4T-C50HJ4020EB, 4T-C50HJ4020KB, **_50*****(* can from 0 to 9, A to Z or blank), PR50U3421SKB.

REPORT NUMBER

260508031SZN-007

ISSUE DATE

[REVISED DATE]

21 May 2026 [-----]

PAGES

6

DOCUMENT CONTROL NUMBER

EN 62311_b

© 2017 INTERTEK



Test Report

Applicant: Shen Zhen MTC Co., LTD

Number: 260508031SZN-007

MTC Industry Park, 1st Lilang Road, Xialilang community,
Nanwan street, Longgang district, Shenzhen, China

Sample Description

Product : TV/LCD LED TV/LED LCD TV
Model No. : MUDV50B0-90106-T2, MUDV50B0-90106-S2, MUDV50B0-90106, MUDV50****-90106-## (*, # can from 0 to 9, A to Z or blank), 4T-C50FJ2KL1FB, 4T-C50FJ2EL2NB, 4T-C50HJ4020EB, 4T-C50HJ4020KB, **-*50*****(* can from 0 to 9, A to Z or blank), PR50U3421SKB.

Brand Name : AMTC, Sharp, Polaroid
Electrical Rating : 220-240V~, 50/60Hz, 128W

Date Received : 01 December 2022

Date Test Conducted : 01 December 2022 to 06 January 2023

Test Requested : Test for compliance with EN IEC 62311: 2020

Test Method : EN IEC 62311: 2020

Test Result : See the attached sheets

Conclusion : The submitted samples Complied with the above safety standard. But the note should be noted.

***** End of Page *****

Prepared and Checked By:

Approved By:

Bruce Zheng
Project Engineer

Rode Liu
Project Engineer
Date: 21 May 2026

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Service Shenzhen Ltd.

No. 101&201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen, P.R. China
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

TEST REPORT

Test Report

Test Results: Number: 260508031SZN-007

EN IEC 62311: 2020

<u>Clause</u>	<u>Title/Description</u>	<u>Result</u>
1	Scope	
2	Normative references	--
3	Terms and definitions	--
4	Compliance criteria	Complied (See Note)
5	Assessment report	--

The Model: MUDV50B0-90106-S2, MUDV50B0-90106, MUDV50****-90106-## (*, # can from 0 to 9, A to Z or blank), 4T-C50FJ2KL1FB, 4T-C50FJ2EL2NB, 4T-C50HJ4020EB, 4T-C50HJ4020KB, **-*50*****(* can from 0 to 9, A to Z or blank), PR50U3421SKB are the same as the Model: MUDV50B0-90106-T2 in hardware aspect. The difference in model number and Trade name serves as marketing strategy.

This report is based on previous report with report number 240731081SZN-007 dated 10 September 2024(original signatory: Bruce Zheng, Rode Liu on file). Owing to adding the models, no test was required after evaluation.

This test product may be sold to different regions and different customers with different bases. Different bases have no effect on the test results.

***** End of Page *****

Test Report

Note:

Number: 260508031SZN-007

- (1) When determining the test conclusion, the Measurement Uncertainty of test has been considered. The uncertainty of 30% is used for evaluation of compliance to the limit.
- (2) According to EN IEC 62311: 2020, the apparatus shall comply with the basic restriction specified in Council Recommendation 1999/519/EC. The reference levels in the Council Recommendation 1999/519/EC on public exposure to electromagnetic fields are derived from the basic restrictions using worst-case assumptions about exposure. The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation.

Reference levels for electric, magnetic and electromagnetic fields
(0Hz to 300GHz, unperturbed rms values)

Frequency Range	E-Field Strength (V/m)	H-Field Strength (A/m)	B-Filed (uT)	Equivalent plane wave power density Seq (W/m2)
0-1 Hz	-	$3.2 * 10^4$	$4 * 10^4$	-
1-8 Hz	10000	$3.2 * 10^4 / f^2$	$4 * 10^4 / f^2$	-
8-25 Hz	10000	$4000 / f$	$5000 / f$	-
0.025-0.8 kHz	$250 / f$	$4 / f$	$5 / f$	-
0.8-3 kHz	$250 / f$	5	6.25	-
3-150 kHz	87	5	6.25	-
0.15-1 MHz	87	$0.73 / f$	$0.92 / f$	-
1-10 MHz	$87 / f^{1/2}$	$0.73 / f$	$0.92 / f$	-
10-400 MHz	28	0.073	0.092	2
400-2000 MHz	$1375 f^{1/2}$	$0.0037 f^{1/2}$	$0.0046 f^{1/2}$	$f / 200$
2-300 GHz	61	0.16	0.020	10

From above table,

For Wifi function, the maximum power density limits is 10 W/m² at 2400-2483.5MHz.

Power density (S) is calculated by the following formula:

$$S = (P * G) / 4\pi R^2$$

$$E.I.R.P = P * G$$

Where, S = Power density (mW/cm²)

P = Output power to antenna (mW)

R = Distance between radiating structure and observation point (cm)

G = Gain of antenna in numeric

$\pi = 3.14$

***** End of Page *****

Test Report

APPENDIX:

Number: 260508031SZN-007

For 802.11b/g-2.4G-Worse case: 802.11g SISO

Channel	Channel Frequency (MHz)	Maximum antenna gain (dBi)	Maximum antenna gain (numeric)	E.I.R.P (mW)	Power density (W/m2)	Limit of power density (W/m2)
1	2412	2.0	1.6	66.07	0.1315	10
7	2442	2.0	1.6	66.07	0.1315	10
13	2472	2.0	1.6	67.61	0.1346	10

For 802.11n HT20/HT40-2.4G-Worse case: 802.11N20 MIMO

Channel	Channel Frequency (MHz)	Maximum antenna gain (dBi)	Maximum antenna gain (numeric)	E.I.R.P (mW)	Power density (W/m2)	Limit of power density (W/m2)
3	2422	2.0	1.6	64.57	0.1285	10
7	2442	2.0	1.6	64.57	0.1285	10
11	2462	2.0	1.6	64.57	0.1285	10

The Notice in Installation Manual should state as below:

The user must maintain a minimum distance of 20 cm from the device at all time.

***** End of Page *****

Test Report

APPENDIX:

Number: 260508031SZN-007

For 802.11a/n/ac -5G--Worse case:

Channel	Channel Frequency (MHz)	Maximum antenna gain (dBi)	Maximum antenna gain (numeric)	E.I.R.P (mW)	Power density (W/m2)	Limit of power density (W/m2)
36	5180	3.0	2.0	40.74	0.0811	10
64	5320	3.0	2.0	45.71	0.0910	10
100	5500	3.0	2.0	53.70	0.1069	10
140	5700	3.0	2.0	41.69	0.0830	10
149	5745	3.0	2.0	16.22	0.0323	10
165	5825	3.0	2.0	16.22	0.0323	10

Synchronous transmit

2.4G WIFI Channel Frequency (MHz)	Maximum E.I.R.P (mW)	5G WIFI Channel Frequency (MHz)	Maximum E.I.R.P (mW)	Total E.I.R.P (mW)	Power density (W/m2)	Limit of power density (W/m2)
2472	67.61	5500	53.70	121.31	0.2415	10

The Notice in Installation Manual should state as below:

The user must maintain a minimum distance of 20 cm from the device at all time.

***** End of Page *****

Test Report

APPENDIX:

Number: 260508031SZN-007

Photos of EUT

Please refer to Annex of EUT Photos_260508031SZN.

***** End of Report *****