

Introduction to Audio Content Analysis

Module 10.2: Audio-to-Audio & Audio-to-Score Alignment

alexander lerch



introduction overview

corresponding textbook section

Section 10.2

Section 10.3

■ lecture content

- Audio-to-Audio alignment
 - use cases
 - ► features
 - distance measures
 - ► typical accuracy
- Audio-to-Score alignment

learning objectives

- elaborate on possible use cases for audio-to-audio alignment
- give examples for features and distance measures for alignment
- discuss differences between audio-to-audio and audio-to-score alignment



introduction overview

corresponding textbook section

Section 10.2

Section 10.3

■ lecture content

- Audio-to-Audio alignment
 - use cases
 - ► features
 - distance measures
 - typical accuracy
- Audio-to-Score alignment

■ learning objectives

- elaborate on possible use cases for audio-to-audio alignment
- give examples for features and distance measures for alignment
- discuss differences between audio-to-audio and audio-to-score alignment



audio-to-audio alignment introduction

objective

• align two sequences of audio

use cases

- quick browsing for certain parts in recordings
- timing adjustment (backing vocals, loops, . . .)
- automated dubbing
- musicological analysis (relative timing of several performances)

processing steps

- extract suitable features
- compute distance matrix
- compute alignment path

audio-to-audio alignment introduction

objective

• align two sequences of audio

use cases

- quick browsing for certain parts in recordings
- timing adjustment (backing vocals, loops, ...)
- automated dubbing
- musicological analysis (relative timing of several performances)

processing steps

- extract suitable features
- compute distance matrix
- compute alignment path

audio-to-audio alignment introduction

objective

align two sequences of audio

use cases


- quick browsing for certain parts in recordings
- timing adjustment (backing vocals, loops, ...)
- automated dubbing
- musicological analysis (relative timing of several performances)

processing steps

- extract suitable features
- compute distance matrix
- compute alignment path

audio-to-audio alignment alignment path computation

prerequisite:Module 10.1 — DynamicTime Warping



■ use case examples

- quick browsing find the same part across files ⇒ use pitch based features
- **timing adjustment** backing vocals to lead vocals ⇒ use *intensity based* features
- automated dubbing same speaker several recordings
 use intensity based and timbre based features

feature categories

- intensity: energy, onset probability, ...
- tonal: pitch chroma, ...
- timbral: MFCCs, spectral shape, . . .

plot from¹

¹H. Kirchhoff and A. Lerch, "Evaluation of Features for Audio-to-Audio Alignment," *Journal of New Music Research*, vol. 40, no. 1, pp. 27–41

■ use case examples

- quick browsing find the same part across files
 - ⇒ use *pitch based* features
- timing adjustment backing vocals to lead vocals
 - ⇒ use *intensity based* features
- automated dubbing same speaker several recordings
 - ⇒ use *intensity based* and *timbre based* features


feature categories

- intensity: energy, onset probability, ...
- tonal: pitch chroma, ...
- timbral: MFCCs, spectral shape, . . .

plot from¹

¹H. Kirchhoff and A. Lerch, "Evaluation of Features for Audio-to-Audio Alignment," Journal of New Music Research, vol. 40, no. 1, pp. 27–41,

audio-to-audio alignment



Georgia Center for Music Tech Technology

typical distance measures

- ullet Euclidean distance: $d_{
 m E}({\sf s}) = \sqrt{\sum\limits_{j=0}^{11} ig(
 u_{
 m e}(j)
 u_{
 m t,s}(j)ig)^2}$
- ullet Manhattan distance: $d_{
 m M}(s) = \sum\limits_{j=0}^{11} \left|
 u_{
 m e}(j)
 u_{
 m t,s}(j)
 ight|$
- Cosine distance: $d_{\mathrm{C}}(s) = 1 \left(\frac{\sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j) \cdot \nu_{\mathrm{t,s}}(j)}{\sqrt{\sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j)^2} \sqrt{\cdot \sum\limits_{j=0}^{11} \nu_{\mathrm{t,s}}(j)^2}}\right)$
- Kullback-Leibler divergence: $d_{\mathrm{KL}}(s) = \sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j) \cdot \log\left(\frac{\nu_{\mathrm{e}}(j)}{\nu_{\mathrm{t,s}}(j)}\right)$

■ data-driven approach: train classifier with 2-class problem¹

¹H. Kirchhoff and A. Lerch, "Evaluation of Features for Audio-to-Audio Alignment," *Journal of New Music Research*, vol. 40, no. 1, pp. 27–41

audio-to-audio alignment compute distance matrix — distance measures

- typical distance measures
 - ullet Euclidean distance: $d_{
 m E}(s) = \sqrt{\sum\limits_{j=0}^{11} \left(
 u_{
 m e}(j)
 u_{
 m t,s}(j)
 ight)^2}$
 - ullet Manhattan distance: $d_{
 m M}(s) = \sum\limits_{i=0}^{11} \left|
 u_{
 m e}(j)
 u_{
 m t,s}(j)
 ight|$

• Cosine distance:
$$d_{\mathrm{C}}(s) = 1 - \left(\frac{\sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j) \cdot \nu_{\mathrm{t,s}}(j)}{\sqrt{\sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j)^2} \sqrt{\cdot \sum\limits_{j=0}^{11} \nu_{\mathrm{t,s}}(j)^2}}\right)$$

- Kullback-Leibler divergence: $d_{\mathrm{KL}}(s) = \sum\limits_{i=1}^{11} \nu_{\mathrm{e}}(j) \cdot \log\left(\frac{\nu_{\mathrm{e}}(j)}{\nu_{\mathrm{t,s}}(j)}\right)$
- data-driven approach: train classifier with 2-class problem¹

audio-to-audio alignment compute distance matrix — distance measures

- typical distance measures
 - ullet Euclidean distance: $d_{
 m E}(s) = \sqrt{\sum\limits_{j=0}^{11} \left(
 u_{
 m e}(j)
 u_{
 m t,s}(j)
 ight)^2}$


 - $\text{ Manhattan distance: } d_{\mathrm{M}}(s) = \sum_{j=0}^{11} \left| \nu_{\mathrm{e}}(j) \nu_{\mathrm{t,s}}(j) \right|$ $\text{ Cosine distance: } d_{\mathrm{C}}(s) = 1 \left(\frac{\sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j) \cdot \nu_{\mathrm{t,s}}(j)}{\sqrt{\sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j)^2} \sqrt{\cdot \sum\limits_{j=0}^{11} \nu_{\mathrm{t,s}}(j)^2}} \right)$
 - Kullback-Leibler divergence: $d_{\mathrm{KL}}(s) = \sum\limits_{i=1}^{11} \nu_{\mathrm{e}}(j) \cdot \log\left(\frac{\nu_{\mathrm{e}}(j)}{\nu_{\mathrm{t,s}}(j)}\right)$
- data-driven approach: train classifier with 2-class problem¹

- typical distance measures
 - ullet Euclidean distance: $d_{
 m E}(s) = \sqrt{\sum\limits_{j=0}^{11} \left(
 u_{
 m e}(j)
 u_{
 m t,s}(j)
 ight)^2}$
 - ullet Manhattan distance: $d_{
 m M}(s) = \sum\limits_{j=0}^{11} \left|
 u_{
 m e}(j)
 u_{
 m t,s}(j)
 ight|$
 - $\bullet \ \ \textit{Cosine distance} : \ d_{\mathrm{C}}(s) = 1 \left(\frac{\sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j) \cdot \nu_{\mathrm{t,s}}(j)}{\sqrt{\sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j)^2} \sqrt{\cdot \sum\limits_{j=0}^{11} \nu_{\mathrm{t,s}}(j)^2}} \right)$
 - Kullback-Leibler divergence: $d_{\mathrm{KL}}(s) = \sum\limits_{j=0}^{11} \nu_{\mathrm{e}}(j) \cdot \log\left(\frac{\nu_{\mathrm{e}}(j)}{\nu_{\mathrm{t,s}}(j)}\right)$
- data-driven approach: train classifier with 2-class problem¹

¹H. Kirchhoff and A. Lerch, "Evaluation of Features for Audio-to-Audio Alignment," *Journal of New Music Research*, vol. 40, no. 1, pp. 27–41

audio-to-audio alignment compute distance matrix — distance measures


- typical distance measures
- data-driven approach: train classifier with 2-class problem¹



¹H. Kirchhoff and A. Lerch, "Evaluation of Features for Audio-to-Audio Alignment," Journal of New Music Research, vol. 40, no. 1, pp. 27–41,

audio-to-audio alignment compute distance matrix — distance measures


- typical distance measures
- data-driven approach: train classifier with 2-class problem¹



¹H. Kirchhoff and A. Lerch, "Evaluation of Features for Audio-to-Audio Alignment," *Journal of New Music Research*, vol. 40, no. 1, pp. 27–41, 2011. DOI: 10.1080/09298215.2010.529917.

audio-to-audio alignment typical results





originals synced

left: instrumental right: a capella





²H. Kirchhoff and A. Lerch, "Evaluation of Features for Audio-to-Audio Alignment," *Journal of New Music Research*, vol. 40, no. 1, pp. 27-1, 2011, poi: 10.1080/09298215.2010.529917.

audio-to-score alignment

objective

• align an audio sequence with a score sequence

use cases

- score viewer
- music education
- retrieve matching score/audio via cost function
- musicological analysis

processing steps

see audio-to-audio alignment

audio-to-score alignment

objective

• align an audio sequence with a score sequence

use cases

- score viewer
- music education
- retrieve matching score/audio via cost function
- musicological analysis

processing steps

see audio-to-audio alignment

audio-to-score alignment

objective

• align an audio sequence with a score sequence

use cases

- score viewer
- music education
- retrieve matching score/audio via cost function
- musicological analysis

processing steps

see audio-to-audio alignment

audio-to-score alignment challenges

features from different domains

- score contains no timbre info
- score cannot be expected to contain no loudness info
- score has no clear "time axis"
- ⇒ two prototypical for distance/similarity calculation
 - approach 1: convert score into audio-like representation
 - ▶ MIDI-to-audio
 - use model synthesize
 - approach 2: convert audio into score-like representation
 - audio-to-MIDI
 - pitch chroma
 - event-based segmentation

audio-to-score alignment challenges

- features from different domains
 - score contains no timbre info
 - score cannot be expected to contain no loudness info
 - score has no clear "time axis"
- ⇒ two prototypical for distance/similarity calculation
 - approach 1: convert score into audio-like representation
 - ► MIDI-to-audio
 - use model synthesize
 - approach 2: convert audio into score-like representation
 - ▶ audio-to-MIDI
 - pitch chroma
 - event-based segmentation

■ goal: compare two sequences of time stamps

- evaluation challenges
 - pauses/rests, and long held notes: what is the reference path?
 - noise in the begin and end of the recording
 - data not easily available
 - synthesized
 - piano sensors
 - pseudo-ground truth with time stretching
 - automatic annotation with quality assurance



- goal: compare two sequences of time stamps
- evaluation challenges
 - pauses/rests, and long held notes: what is the reference path?
 - noise in the begin and end of the recording
 - data not easily available
 - synthesized
 - piano sensors
 - pseudo-ground truth with time stretching
 - automatic annotation with quality assurance

- audio-to-score
 - missed note rate
 - misalign rate
 - piece completion
 - average absolute deviation
 - variance of deviation
- audio-to-audio
 - mean deviation
 - mean absolute deviation
 - maximum deviation
 - relative number of matching path points

■ audio-to-audio alignment

- 1 extract features
- 2 create distance matrix with suitable distance measure
- 3 use DTW to find alignment path
- 4 (use time-stretching to actually align the sequences)

■ audio-to-score alignment

- 1 extract usually pitch-based features
- 2 distance measure
- 3 use DTW, HMM, etc to extract alignment path

