
Digital Signal Processing for Music

Part 9: Fast Convolution

alexander lerch





fast convolution introduction

Georgia Center for Music Tech College of Pesign

convolution: measure impulse response h(i) and apply FIR filter to signal

$$y(i) = x(i) * h(i)$$


$$= \sum_{j=-\infty}^{\infty} h(j) \cdot x(i-j)$$

$$Y(z) = X(z) \cdot H(z)$$

DFT convolution

Georgia Center for Music Tech College of Design

- signal and impulse response 1/2
 - multiplication: length of H(z) = M must equal length of X(z) = N
 - minimum DFT length: L < M + N 1



DFT convolution

Georgia Center for Music Tech Technology

signal and impulse response 1/2

- multiplication: length of H(z) = M must equal length of X(z) = N
- minimum DFT length: L < M + N 1
- O H = DFT(h'(i))
- $Y = X \cdot H$
- $v = DFT^{-1}(Y)$
- **1** throw away zeros if DFT was longer than M + N


DFT convolution

Georgia Center for Music Technology

signal and impulse response 1/2

- multiplication: length of H(z) = M must equal length of X(z) = N
- minimum DFT length: L < M + N 1

- $Y = X \cdot H$
- $0 \ y = DFT^{-1}(Y)$
- \odot throw away zeros if DFT was longer than M + N



DFT convolution signal and impulse response 2/2

Georgia Center for Music Tech College of Pesign


properties:

- no real-time: signal has to be known completely
- high memory requirements (signal length N + impulse response length M)
 - when FFT: next larger power of two

Georgia Center for Music Tech College of Design

blocked signal and impulse response 1/2


- split input signal into blocks of length M
- OFT convolution with each block (zeropadding)
- overlap and save



Georgia Center for Music Tech College of Design


blocked signal and impulse response 1/2

- split input signal into blocks of length M
- OFT convolution with each block (zeropadding)
- overlap and save




Georgia Center for Music Tech Technology

- blocked signal and impulse response 1/2
 - split input signal into blocks of length M
 - OFT convolution with each block (zeropadding)
 - overlap and save



Georgia Center for Music Tech College of Design

- blocked signal and impulse response 1/2
 - split input signal into blocks of length M
 - OFT convolution with each block (zeropadding)
 - overlap and save



Georgia Center for Music Tech Technology

blocked signal and impulse response 2/2


properties:

- minimum latency: impulse response length
- long FFT, but more efficient
- FFT of impulse response is only computed once

partitioned convolution blocked signal and blocked impulse response 1/3



- split both input signal and impulse response into blocks of arbitrary length
- DFT convolution with each signal block with each impulse response block (zeropadding)
- overlap and save




partitioned convolution

Georgia Center for Music Tech College of Design

blocked signal and blocked impulse response 1/3


- split **both** input signal and impulse response into blocks of arbitrary length
- DFT convolution with each signal block with each impulse response block (zeropadding)
- overlap and save



partitioned convolution blocked signal and blocked impulse response 1/3

Georgia Center for Music Technology


- split both input signal and impulse response into blocks of arbitrary length
- DFT convolution with each signal block with each impulse response block (zeropadding)
- overlap and save



blocked signal and blocked impulse response 2/3

response 2/3





partitioned convolution

blocked signal and blocked impulse response 3/3

Georgia Center for Music Tech College of Design

properties:

- arbitrary choice of latency/FFT length
 - long FFT: high latency, low workload
 - short FFT: short latency, high workload
- FFTs of IR computed only once

non-uniform partitioned convolution different block lengths



- fast convolution: latency still formidable for efficient implementation
- ⇒ non-uniform block lengths



- advantages
 - any desirable latency
- disadvantages:
 - less efficient due to multiple FFT lengths (but: inefficiency of short FFT partly compensated by very long FFTs)
 - complex implementation
 - comparably high memory usage (IR in many different FFT lengths)

non-uniform partitioned convolution different block lengths

Georgia Center for Music Tech College of Design

- fast convolution: latency still formidable for efficient implementation
- → non-uniform block lengths




- advantages
 - any desirable latency
- disadvantages:
 - less efficient due to multiple FFT lengths (but: inefficiency of short FFT partly compensated by very long FFTs)
 - complex implementation
 - comparably high memory usage (IR in many different FFT lengths)

non-uniform partitioned convolution different block lengths



- fast convolution: latency still formidable for efficient implementation
- ⇒ non-uniform block lengths



- advantages:
 - any desirable latency
- disadvantages:
 - less efficient due to multiple FFT lengths (but: inefficiency of short FFT partly compensated by very long FFTs)
 - complex implementation
 - comparably high memory usage (IR in many different FFT lengths)