


Digital Signal Processing for Music

Part 12: Non-linear Quantization

alexander lerch



non-linear quantization

introduction: linear quantization—SNR & PDF

$$SNR = 6.02 \cdot w + c_S \quad [dB]$$

$\Rightarrow c_S$ depends on signal's PDF (and scaling)

PDF	SNR
square wave	$c_S = 4.8$
sine wave	$c_S = 1.8$
rect	$c_S = 0$
tri	$c_S \approx -3$
Gauss	$c_S \approx -7$
Laplace	$c_S \approx -9$
speech	$c_S \approx -10 \dots -15$

non-linear quantization

introduction: linear quantization—SNR & PDF

$$SNR = 6.02 \cdot w + c_S \quad [dB]$$

$\Rightarrow c_S$ depends on signal's PDF (and scaling)

PDF	SNR
square wave	$c_S = 4.8$
sine wave	$c_S = 1.8$
rect	$c_S = 0$
tri	$c_S \approx -3$
Gauss	$c_S \approx -7$
Laplace	$c_S \approx -9$
speech	$c_S \approx -10 \dots -15$

non-linear quantization

introduction

idea: quantize frequent signal values at higher resolution

- **approach 1**

- ① flatten PDF (companding)
- ② linear quantization
- ③ extract signal (expanding)

- **approach 2**

- ① adapt quantization step size to PDF

⇒ both approaches are equivalent in their result


non-linear quantization

introduction

idea: quantize frequent signal values at higher resolution

● **approach 1**

- 1 flatten PDF (companding)
- 2 linear quantization
- 3 extract signal (expanding)




non-linear quantization

introduction

idea: quantize frequent signal values at higher resolution

● approach 1

- 1 flatten PDF (companding)
- 2 linear quantization
- 3 extract signal (expanding)



● approach 2

- 1 adapt quantization step size to PDF

⇒ both approaches are equivalent in their result


non-linear quantization

introduction

idea: quantize frequent signal values at higher resolution

- **approach 1**

- 1 flatten PDF (companding)
- 2 linear quantization
- 3 extract signal (expanding)



- **approach 2**

- 1 adapt quantization step size to PDF

⇒ both approaches are equivalent in their result

non-linear quantization

A-Law quantization (ITU-T G.711) 1/3

$$F(x) = \text{sign}(x) \begin{cases} \frac{A|x|}{1+\log(A)}, & |x| \leq \frac{1}{A} \\ \frac{1+\log(A|x|)}{1+\log(A)}, & \frac{1}{A} \leq |x| \leq 1 \end{cases}$$

$$F^{-1}(y) = \text{sign}(y) \begin{cases} \frac{|y|(1+\log(A))}{A}, & |y| \leq \frac{1}{1+\log(A)} \\ \frac{\exp(|y|(1+\log(A))-1)}{A}, & \frac{1}{1+\log(A)} \leq |y| \leq 1 \end{cases}$$

with $A = 87.7$

- linear and high resolution for small amplitudes
- log and increasingly low resolution for high amplitudes

non-linear quantization

A-Law quantization (ITU-T G.711) 1/3

$$F(x) = \text{sign}(x) \begin{cases} \frac{A|x|}{1+\log(A)}, & |x| \leq \frac{1}{A} \\ \frac{1+\log(A|x|)}{1+\log(A)}, & \frac{1}{A} \leq |x| \leq 1 \end{cases}$$







$$F^{-1}(y) = \text{sign}(y) \begin{cases} \frac{|y|(1+\log(A))}{A}, & |y| \leq \frac{1}{1+\log(A)} \\ \frac{\exp(|y|(1+\log(A))-1)}{A}, & \frac{1}{1+\log(A)} \leq |y| \leq 1 \end{cases}$$

with $A = 87.7$

- linear and high resolution for small amplitudes
- log and increasingly low resolution for high amplitudes


non-linear quantization

A-Law quantization 2/3



non-linear quantization

A-Law quantization 3/3



- range I: SNR is linear regardless of input level
- range II: SNR increases with input level

non-linear quantization

μ-Law quantization (ITU-T G.711)

$$F(x) = \text{sign}(x) \frac{\log(1 + \mu|x|)}{\log(1 + \mu)}$$

$$F^{-1}(y) = \text{sign}(y) \frac{1}{\mu} \left((1 + \mu)^{|y|} - 1 \right)$$

with $\mu = 255$

compared to A-Law:

- higher dynamic range
- higher error at small amplitudes

non-linear quantization

μ-Law quantization (ITU-T G.711)

$$F(x) = \text{sign}(x) \frac{\log(1 + \mu|x|)}{\log(1 + \mu)}$$

$$F^{-1}(y) = \text{sign}(y) \frac{1}{\mu} \left((1 + \mu)^{|y|} - 1 \right)$$

with $\mu = 255$

compared to A-Law:

- higher dynamic range
- higher error at small amplitudes

non-linear quantization

summary

- **advantages** of non-linear quantization
 - takes advantage of non-uniform distribution of input
 - in line with non-linear loudness perception of the ear
 - ⇒ similar perceptual quality as higher resolution linear quantization
- **disadvantages**
 - processing not easily implemented in non-linear amplitude space
 - ⇒ only used for transmission