

TokVid App Details

Workspace structure and main app details

This document summarizes the current TokVid repository, the web app implementation, and the Google OAuth Supabase integration.

Repository Overview

- Root workspace with monorepo packages and artifacts
- Main Next.js web app located in artifacts/web
- Supabase client in artifacts/web/lib/supabaseClient.ts
- Login flow files in artifacts/web/app and artifacts/web/components
- Environment configuration in artifacts/web/.env.local

Web app package

The web package contains:

- Next.js 15 App Router project
- Dependencies: @supabase/supabase-js, next, react, react-dom
- Client-side React components using useEffect and useRouter
- OAuth redirect callback route at /auth/callback
- Protected home route at /home

Supabase integration

The app integrates Supabase Auth with Google OAuth in the following way:

- supabase client created in artifacts/web/lib/supabaseClient.ts using NEXT_PUBLIC_SUPABASE_URL and NEXT_PUBLIC_SUPABASE_ANON_KEY
- Login button in artifacts/web/components/GoogleLogin.tsx triggers supabase.auth.signInWithOAuth({ provider: "google", options: { redirectTo: "/auth/callback" } })
- Callback page at artifacts/web/app/auth/callback/page.tsx exchanges the OAuth code with supabase.auth.exchangeCodeForSession(href)
- On successful authentication, users are redirected to /home
- Home page at artifacts/web/app/home/page.tsx verifies session with supabase.auth.getSession() and loads user data with supabase.auth.getUser()
- User email/name is displayed and sign out is handled with supabase.auth.signOut()

Key files

- artifacts/web/app/page.tsx - login landing page and session validation redirect
- artifacts/web/components/GoogleLogin.tsx - Google login button and auth state handling
- artifacts/web/app/auth/callback/page.tsx - OAuth callback handler route
- artifacts/web/app/home/page.tsx - authenticated home/dashboard page
- artifacts/web/lib/supabaseClient.ts - Supabase client initialization
- artifacts/web/.env.local - Supabase public keys and URL configuration

Environment settings

The current environment file has been updated with the Supabase public URL and anon key placeholders.

Example values:

```
NEXT_PUBLIC_SUPABASE_URL=https://mi-proyecto.supabase.co  
NEXT_PUBLIC_SUPABASE_ANON_KEY=mi_anon_key_aquí
```

Additional notes

The app is implemented using client-side components on login, callback, and home pages, relying on Supabase client-side auth methods and Next.js App Router navigation.

How to run

Use pnpm in the artifacts/web package to start the app:

```
pnpm --filter ./artifacts/web dev
```