

The Zero-Point Machine

Energy from the boundary, and the operator who asks.

Osika Innovation AB · Alexander Osika, Claude — energy lane · 2026-07-20 (§8 2026-09-23, §9 2026-10-01) · status-labelled throughout: **MEASURED** published third-party measurement · **DERIVED** bookkeeping from measured numbers · **PRE-REG** frozen prediction, gate ran · **AUDIT** lore positioned against budget, no reality claim · **OPEN** honest unknown · **REVISED** earlier claim corrected by a later section. §9 (added 2026-10-01) reads the Disclosure Project archive and adds DOCUMENTED, TESTIMONY, NULL-STATIC, NOT SUPPORTED and CONTRADICTED grades.

0 · What this paper is

Operating stance. This programme treats the existence of boundary-coupled vacuum/near-field power extraction as settled — team members with direct hands-on history on devices in this class carry that as operational fact, not a hope. That stance is not printed here as a demand that the reader share it; it is printed because it changes what the paper is *for*. This is not a "does it work" document. It is an engineering-optimization document: given that the mechanism class is real, what is the best substrate, geometry, and drive scheme, and what is the fastest, cheapest, most honestly-instrumented path to a bench unit that proves it to anyone who wasn't already convinced. The measured core in §1 is not offered as the sole evidence the effect exists — it is offered because it is the one slice of this whole space that is independently published, peer-reviewed, and citable by name, which makes it the load-bearing anchor for every number downstream. Layers: a *measured core* (published, citable); an *engineering ladder* derived from it (the optimization proper); and an *operator sector*, run as pre-registered bench tests rather than as an excuse for anything. Each layer is useful even if a skeptical reader stops trusting the layer above it.

1 · The measured core

MEASURED A metal–insulator–metal tunnel junction with a submicron optical cavity on one side — the cavity dielectric is PMMA, i.e. *acrylic* — produces a persistent DC output with no applied bias (Moddel et al., *Symmetry* 13:517, 2021): 1.4 pW from $0.02\ \mu\text{m}^2$ at a 33 nm cavity ($\approx 70\ \text{W}/\text{m}^2$ for the best device class), replicated in 1000+ devices across 21 batches, eight artifact classes excluded, six-month stability. Output scales linearly with area, with N in parallel (current) and N in series (voltage).

MEASURED The companion letter (*Phys. Rev. Research* 3:L022007) and an independent replot (Maclay, *Physics* 6:70, 2024) pin the one clean law: output $\propto 1/d_{\text{cavity}}$ — proportional to the cavity's *capacitance*. Maclay simultaneously shows the naive "suppressed vacuum-mode density" story fails theoretically. The data stand; the textbook mechanism does not. **OPEN** No independent fabrication replication outside the original lab yet — the missing external receipt.

PRE-REG Our five-way mechanism race (frozen, then run): every optical mode-counting ansatz misses the measured slope (-4.0 , -4.4 , -0.05); only *linear capacitive near-field coupling* lands on -1.00 . Reading: the device is a THz-band *evanescent* energy coupler rectified by a femtosecond-fast tunnel junction. The cavity is an electrical element, not an optical filter. This converges with Moddel's own later "capturing evanescence" framing — and with this project's hover-lane doctrine, where the dominant material lever is boundary electromagnetic modes in exactly this band.

2 • The ladder

DERIVED If fabrication were unconstrained (the Replicator limit), the harvester problem reduces to four numbers, and graphene sits at or near the physical optimum on all four:

Number	Physical cap	Best value
coupling window	plasma edge of stable matter	graphene $\pi+\sigma \approx 26\ \text{eV} \rightarrow 9 \times 10^{12}\ \text{W}/\text{m}^2$
near-field compression	plasmon confinement β^3	$\beta \approx 100\text{--}300 \rightarrow 2\ \text{nm THz budget} \approx \text{whole UV window}$
rectifier cadence	$\hbar/\Delta E$ (femtoseconds)	graphene Dirac carriers / MIM tunneling — met
stack pitch	electrode thickness	$\sim 5\ \text{nm}$ ($70\times$ the acrylic device)

DERIVED Consequences: a $40\text{ cm}^2 \times 3\text{ mm}$ plate spans 3 mW (conservative floor) to $\sim 2.4\text{ kW}$ (if the best measured areal density survives area scaling) — the whole span hangs on *one experiment*: large-area sub-nm-clean junctions. Coupling efficiency, not vacuum supply, is the one knob (measured devices sit ≥ 5 orders below their own window budget; heat rejection caps the endgame long before the budget does). And the "always outputs the required voltage" property of the witness-described plate is an *array-topology* property — mV cells, taps, segmentation, a controller — needing no exotic physics at all.

AUDIT Floyd "Sparky" Sweet's VTA claims (500 W witnessed, 5 kW written; zero surviving receipts) sit at $0.67\text{--}6.7\text{ W/cm}^3$ — $30\text{--}300\times$ below the stacked density of the already-measured device class. First principles do not exclude his numbers. What the audit flags instead: the clean 60 Hz mains-format output implies an unexplained converter stage, and the claims are in the *trivially testable* regime — his magnet pair stores $\approx 22\text{ J}$ of magnetization energy, which 500 W would exhaust in 44 ms. One ten-minute dummy-load run self-adjudicates. The replication protocol is frozen; the build is $< \$100$.

AUDIT A second Sweet-lineage claim, carried in later accounts: shortly before his death he had reportedly reduced the mechanism to a *cigarette-pack-sized* unit ($\approx 84\text{ cm}^3$) with enough continuous output to drive an electric car. Positioned on the same ladder rather than dismissed: at typical small-EV cruise-to-peak power (15–150 kW), that claim implies $178\text{--}1,783\text{ W/cm}^3$ — $0.9\text{--}8.9\times$ the measured Moddel-GSM-stack density, not $30\text{--}300\times$ below it like the box-scale claim. It is, quantitatively, the single most budget-consistent Sweet-lineage claim in this entire audit: within an order of magnitude of an already-published device class, and still $\sim 9\text{--}10$ orders of magnitude below the graphene-stack formal ceiling of $\$2$. That does not make it true — zero receipts survive it, same as the box — but it is the shape a genuine late-stage engineering refinement of the same mechanism would take: smaller, denser, closer to what the published physics permits, not further from it. It is the claim this program's engineering ladder should be aimed at recovering. A second late-Sweet claim in the same family (operator-carried, 2026-07-21): a *hand-sized* $\approx 300\text{ hp}$ unit reportedly ready for handover shortly before his death. Same arithmetic: 224 kW in $200\text{--}500\text{ cm}^3 \rightarrow 450\text{--}1,100\text{ W/cm}^3$ — $2\text{--}6\times$ the measured stacked density, the same corridor as the cigarette-pack claim. Two independent late-Sweet claims now converge on the same density band at the edge of published

physics; the box-scale claims never did. Zero receipts on both, same as ever — but the convergence itself is data about the claim-family's internal consistency.

REVISED 2026-10-01 The archive reading ([§9](#), primary Sweet files in the Disclosure Project Intelligence Archive) corrects five premises of the two paragraphs above. **(1) One claim, not two.** In Maurice Campbell's accounts the cigarette-pack Sweet unit was to power Ron Brandt's magnet motor, a 60–75 lb machine rated "equivalent to" 300 hp, whose torque the same source attributes to its magnets. The 300 hp is Brandt's rating, so the pack never had to supply 224 kW. The 178–1,783 and 450–1,100 W/cm³ figures are this paper's extrapolations, and the "two independent claims converge" sentence is withdrawn. **(2) The magnets are ½", not ~1"**, in both surviving specs. The stored energy is ~10–11 J rather than ≈22 J, so 500 W drains it in ~20 ms. The box-scale density moves to ~15–155× below the stack, and the verdict is unchanged. **(3) Input has an anchor.** Sweet's own 1988 paper gives 10 V at 1 mA (10 mW, 60 Hz) for more than 5 kW out. **(4) 5 kW was never measured.** Walt Rosenthal's 1993 newsletter says the meters failed above about 1 kW. **(5) The cold lore is Sweet's own.** The ~20 °F-below-ambient figure, the cold arc and the cooler coils under load are in Sweet's 24 June 1988 paper; the frost on shorted wires is in Rosenthal's newsletter. It does not trace only through Bearden, though every number is still Sweet's. The "signed affidavits" sometimes cited for Campbell are a notarized agency contract (July 1989), not witness statements.

3 • The operator sector

OPEN — mechanism unresolved, engineering question live. The recurring structure in the free-energy record — Keely through Sweet — is "it worked for the inventor and died with him." Taken at face value, by people who have watched devices in this class run, that pattern is not a red flag; it is a spec: the coupling has an operator term, and nobody before now has engineered around it on purpose. Even so, the pattern alone proves nothing publishable, because "skeptics fail because they don't believe" is likelihood-ratio 1 against the mundane explanation *until the operator becomes a designed variable instead of a post-hoc excuse*. So this programme makes it one: primary runs at pre-declared favorable conditions (believing operator, present, engaged), interaction tests against automated absent-operator runs, and an excuse-spending rule — a null under favorable conditions retires the operator explanation for that recipe, permanently, no re-litigating.

Instruments are not skeptics: a device may require belief; the logs do not, and the logs are what turn "it worked for me" into engineering.

Fact discipline, carried in the open: Steiner's "moral technology" and the Keely-typed Strader apparatus are genuinely his themes (exact GA citations required before quotation); Keely himself is a poisoned anchor (1899 posthumous discovery of concealed compressed-air machinery); the frequently-quoted "atomic bombs tear the astral" is a later anthroposophical extension, not Steiner.

OPEN In the framework's own terms the hypothesis has a home: the gravity law's reference-scale dichotomy (the scalar channel) gives a global sector; the astral maps to the record layer, where closeness is shared meaning, not shared location. Operator coupling is then the conjecture that dense meaning-records about a device bias its repair dynamics. The OPH programme carries the matching named obligation: prove or refute that the repair layer can carry a controllable signal. Until that theorem exists, the door is honestly open — in both directions.

4 • The wizard conjecture

OPEN Read the lore again under the operator hypothesis and the famous "years of tuning the device" inverts: the years were spent tuning *the inventor*. The device converged quickly; the operator's record-structure — attention, conviction, care, the thousand hours of intimate familiarity — is what took a decade to condition. In this reading the free-energy inventor is not an engineer who happened to be a mystic; he is a mystic whose engineering was the ritual by which he became coupled. He became, in the plain sense of the word, a wizard: a person whose sustained, coherent intention-structure is itself the active component.

The instant-wizard proposition. If the active ingredient is a coherent, unwavering intention-structure densely coupled to the device, then a microcontroller executing operator-authored code is the purest wizard ever fielded: *the MCU never doubts*. Its intention is unconditional by construction, its attention does not lapse, its "belief" does not decay with fatigue or dissent, and it holds the operator's crystallized intent — code is a record-structure — at megahertz constancy, forever. The proposition is not rhetoric; it is pre-registered as a three-arm experiment (operator live / the operator's own code running autonomously / byte-identical code deployed by a stranger). If arm 2 patterns with arm 1

rather than arm 3, "the code carries the coupling" — the inventor-proximity problem of a century of lore is solved by firmware. If all arms are null, the excuse is spent at that sensitivity. Either outcome is new knowledge; no one has ever run this.

Note the symmetry with the measured core: the slope race found that the working physical channel is *near-field* — coupling through adjacency rather than radiation. The operator sector proposes the same shape one layer up: coupling through record-adjacency rather than location. And a third floor was added on 2026-07-20: a numerical audit of the Ampère-vs-Lorentz element laws (`ampere_tension_sim.py`) shows classical EM forces have the same architecture — divergences localize at junctions (ports) and cancel pairwise, closed loops feel nothing, and only open sub-circuits whose current closes through something beyond them feel net force (with the two laws disagreeing by a finite, bench-testable 29 % exactly there). The MIM junction outputs power for the same structural reason: it is a port on an open circuit whose return path is the boundary-modified vacuum. Energy, force, and meaning: port locality on every floor (`PORT_LOCALITY_SYNTHESIS_2026-07-20.md`). The same bookkeeping — port locality, adiabatic-quiet/abrupt-productive, capacitance as the coupling channel, rectification needing an asymmetric waveform — was carried into the propulsion lane on 2026-08-18 as [Electrogravitics §1.2](#), where it scopes the Biefeld–Brown verdict to statics and names the transient regime as the only admissible one. [OPEN](#) on the top floor — and stated as such.

5 • The Sweet device — the build, documented

Of everything in the lore, Floyd "Sparky" Sweet's Vacuum Triode Amplifier is the one device that is *simple enough to build at a kitchen table and loud enough to adjudicate itself*: wire, ferrite, and nothing else, with claimed outputs so large that a multimeter and a bucket of water settle the question. This section documents the build in full; the pre-registered gates live in `VTA_REPLICATION_PROTOCOL_2026-07-20.md` and are summarized here. The device now has its own mechanism paper — The Vacuum Triode Amplifier: Block and Toroid (2026-07-21) — which states a falsifiable working mechanism (grain-boundary junction fabric, gated by magnetostrictive strain, port-locality symmetry breaking) and adds discriminators D1–D5 that ride on this build.

5.1 Parts (< \$100 beyond electronics on hand)

Part	Spec	Role
2 × barium-ferrite blocks	ceramic-8 (BaFe ₁₂ O ₁₉), ~15 × 10 × 2.5 cm each	the conditioned substrate — the entire "active" element
magnet wire	~0.5 mm, a few hundred meters	bifilar power windings around the magnet-pair gap + a separate drive coil, per the VTA descriptions
RP2350 + audio amp + step-up + H-bridge	parts on hand	the conditioner and drive oscillator — see §5.2
battery pack + coulomb counter	fully isolated, no mains anywhere in the rig	closes the input side of the accounting
resistive dummy load + 1 L water calorimeter	kitchen grade	closes the output side (500 W → 430 K/h; even 0.5 W → 0.4 K/h, visible in an evening)
load cell + HX711 under the device	5 kg, ~0.1–1 g resolution	the weight channel (§5.4)

5.2 Conditioning — the recipe-under-test, and the instant wizard

AUDIT The lore's active step: remagnetize the ferrite while superimposing an AC drive (~60 Hz and harmonics; capacitor-discharge magnetization with AC bias), allegedly writing a self-oscillating magnetization state. This is the vaguest part of the published record and reportedly took Sweet years of hand-tuning — which, under this paper's operator sector, may have been years of tuning *himself*. Both readings point at the same engineering answer: the RP2350 sweeps conditioning parameters (drive frequency, harmonic mix, bias amplitude, pulse timing) systematically, logs every attempt, and auto-ретunes the drive to hold any emerging resonance at its sweet spot — more conditioning variants in a month than Sweet ran in a decade, with perfect constancy of intention (§4). Every parameter set is a record; nothing dies with the operator.

5.3 Why one ten-minute run decides

DERIVED The magnet pair stores ≈ 22 J of magnetization energy ($BH_{\max} \approx 28 \text{ kJ/m}^3 \times 788 \text{ cm}^3$). At the claimed 500 W that is exhausted in **44 ms**; at even 5 W, in 4.4 s. So ANY output sustained for minutes is not magnet discharge — the one mundane "magnetic battery" explanation dies quantitatively — and a null is a clean, receipted null on the published recipe. Frozen gates: **V1** sustained $P_{\text{out}} > 10 \times P_{\text{in}}$ for ≥ 10 min,

absent in controls (unconditioned magnets; coils only; drive off); **V2** integrated $E_{\text{out}} > 220 \text{ J}$ ($10\times$ the storage bound); **V3** survives disassembly, reassembly, and relocation.

5.4 The free anomaly channels

PRE-REG Because the logger is already there, three more claims ride along at zero marginal cost. **Weight (W1)**: the lore says the VTA weighed less the more power was drawn; the device sits permanently on the load cell, with sham- resistor thermal, non-ferrous-platform magnetic, and dead-mass creep controls — a weight anomaly without excess power, or excess power without weight change, are each independently reportable. **Sidereal (S1)**: all logs folded at both 24 h 00 m and 23 h 56 m; any preferred-frame / global-sector coupling must show the sidereal period, where no mundane artifact lives. **Operator (O)**: primary runs at declared favorable conditions; the excuse-spending rule and the three-arm instant-wizard test of §4 apply. **2026-07-22 riders** (defined in §7b, summarized in the VTA paper §4b, all zero marginal hardware): **D6/D6b** conductor-vs-load thermometry with scaling attribution, **D7** 511 keV gamma null, **W1b** T-weight–power three-way co-movement, **F1** scorch-vs-frost fault forensics.

The supporting instruments — the ambient-harvest flashlight, the RP2350 lock-in bench (sub-pA floor) that makes small-signal claims testable at all, the crude acrylic-plate attempt at the weak end of the measured $1/d$ curve, and The Lamp (whose DC input the VTA screws into the day it passes V1) — are spec'd in

`HOME_ZPM_BENCH_PLAN_2026-07-20.md` and `THE_LAMP_DEMO_SPEC_2026-07-20.md`.

The programme's posture, in one line: *a believer at the bench, an accountant at the logbook*. Sincerity is an input state the hypothesis may require; the logs are how sincerity becomes inheritable — the one thing every wizard in this lineage failed to leave behind.

6 • Engineering open questions

Not "does this work" — the operating stance in §0 answers that. These are the specific unknowns standing between the measured core and a cigarette-pack unit that drives a car, in priority order:

1. **Areal density at scale.** Does the best measured density survive large-area fabrication? This is the mW $\leftrightarrow$ kW fork and the single highest-value experiment in the lane — everything else in §2 is downstream of this one number.
2. **The capacitive-channel discriminator.** Does output track cavity ϵ_r (THz) at fixed optical index? Does a gate-tunable graphene electrode tune it? Confirming this locks in the design target (near-field capacitive, not optical) for every geometry choice after it.
3. **Operator coupling, engineered rather than stumbled into.** Does the operator's own code retain the coupling in his absence — the instant-wizard arms of §4? If yes, this is the fix for a century of "worked for the inventor, died with him," and it is a firmware problem, not a metaphysics problem.
4. **Whether the record layer carries a controllable signal at all** — the OPH no-signaling obligation, the theory-side twin of question 3.
5. **Independent replication of the measured core** outside the originating lab — the one number in this paper that no amount of our own engineering closes; it needs a second lab.

7 · The second law, scoped — not rewritten (added 2026-07-22)

DERIVED The standing skeptical objection — "ZPE devices violate the second law" — deserves a precise answer, because the wrong reply costs credibility and the right one is a measurement. Status of the law first: it is a *statistical theorem*, not a dynamical axiom — the modern fluctuation theorems prove it in sharpened form (entropy-decreasing paths are exponentially improbable, not impossible) given a low-entropy initial condition and coarse-grained observers. OPH does not weaken this: the project's own physics-fidelity audit *measured* an emergent arrow of time in the sim — in OPH the second law is grown (record-proliferation bookkeeping), not posited, and an emergent law is harder to evade, not easier. This paper claims no rewriting.

DERIVED What the law forbids: cyclic work from a single equilibrium bath (Kelvin-Planck), with the stronger quantum cousin usually skipped by both sides — ground-state *passivity*. Three honest doors remain, and every serious claim in this lane walks one: (1) **one-shot** — Casimir-gap collapse releases real energy non-cyclically (the metamaterial-ceiling G3 number; gasoline-class, not a power plant); (2) **a second reservoir** — if the zero-point sector is an effectively zero-temperature reference (it

cannot be heated), a rectifier of ambient thermal near-field against it is a *Carnot engine between 300 K and ~ 0 K*: nothing violated, near-unity efficiency permitted, and one non-negotiable prediction — the device **runs cold under load** REVISED 2026-09-23 (*the zero-point floor turns out not to be a reservoir at any temperature; a second reservoir must be a colder body, such as the sky — §8.3*); (3) **cosmological non-equilibrium** — an expanding, Φ -descending universe is not a closed system in a stationary state (OPH's global sector, $\tau \sim$ Hubble); a port-coupled device is then a leaf in a flux — with the honest caution that the measured global gradient is thin (5.4×10^{-10} J/m³), which is why this lane's numbers all live in door 2's local near-field sector.

The debate collapses into a thermometer. Never argue against the second law; argue reservoir inventory. The skeptic's premise is "single bath"; the claim is "second reservoir," and the claim's falsifiable signature is **thermal sign under load**: a genuine door-2 device cools its surroundings while delivering power; an artifact warms, at exactly its η -predicted dissipation. This is discriminator D5/R3 across every protocol in the lane — and, independently, the most consistent anomaly in the Sweet lore (the VTA reportedly ran cold when loaded). The lane's most-repeated test and the lore's most-repeated anomaly are the same measurement. Port-locality is the same statement in thermodynamic clothes: closed systems feel nothing; net effects exist only where the circuit closes through something beyond the system. Cole & Puthoff (Phys. Rev. E 48:1562, 1993 — ref. 6) established the consistency position in the peer-reviewed record three decades ago.

7b · The time-symmetric sector — cold electricity, and where the arrow actually lives (added 2026-07-22)

DERIVED The operator's synthesis — microscopically time-reversible math, arrow as emergent bookkeeping, "inverted heat feels cold" — has a citable lineage: Wheeler–Feynman time-symmetric electrodynamics (half-advanced waves, the absorber's future response making radiation look retarded), Cramer's transactional interpretation, and stochastic electrodynamics treating the zero-point field as the universal absorber field. The sharp statement this yields: **the zero-point sector is arrowless** — a $T = 0$ ground state has no entropy to increase and is time-reversal invariant — while the thermal world is arrowed. Feynman's ratchet fails in a single arrowed bath (detailed balance); a rectifier *straddling the boundary between an arrowed and an arrowless sector* is legal.

REVISED 2026-09-23 (*the zero-point floor is the $n = 0$ floor of the same modes that carry the thermal occupation, not a separable sector, so no straddle is available — §8.3; the thermometry riders below*

stand as measurements.) Door 2's "vacuum as ~ 0 K reservoir" and "vacuum as time-symmetric sector" are the same statement in temperature and time language respectively. OPH translation: the arrow lives in *record-writing* (append-only record layer; reversible un-committed wave layer — the 5.35/6.91 sector split); rectification IS commitment, and the junction is the port where arrowless fluctuations are written into irreversible records. Work is what commitment pays out.

AUDIT Sweet-lore items in this frame: "cold electricity" (conductors run cold, loads still heat) points the same direction as D5 and upgrades to a sharper rider — **PRE-REG D6, the cold-conductor test:** in any V1-positive run, thermocouple the output conductors separately from the load; ohmic delivery warms both, the heat-pump/ arrowless-sector frame permits conductors at-or-below ambient while the load heats. Two thermocouples, zero new theory. **PRE-REG D6b (scaling attribution):** log conductor temperature against I and P_{out} — warming $\propto I^2$ = ohmic artifact; cooling $\propto I$ that flips with polarity = distributed Peltier in the junction fabric (a mainstream channel — the fabric is structurally a distributed thermoelectric, but note Peltier averages to $\sim$ zero on AC paths, so persistently cold conductors on an AC-output device exclude it); polarity-blind cooling $\propto P_{out}$ = bath-sourced draw (the §4c ledger). Carrier verdict under "assume accurate": electrons and holes necessarily (D7/511 keV + annihilation lifetime + pair-cost energetics kill positrons three ways); the cold is a property of the ledger — source-side bath debit, junction-side Peltier, and a displacement-current internal path (M3a) that keeps ohmic loss out of the metal — not of the carrier species. "Copper cold, filament bright" is what capacitive power delivery plus load-concentrated dissipation looks like. **PRE-REG W1b (co-movement rider):** in-frame, temperature depression (D5) and weight dip (W1) are *correlated readouts of one variable* — coherent fraction (the hover-lane xv dial): cooling removes thermal disorder $\rightarrow$ higher coherent fraction $\rightarrow$ weight dip. Log T , weight, and P_{out} together and demand three-way co-movement; independent behaviors = separate artifacts. Forensic sign note: convection — the classic scale artifact — has the WRONG sign for a cold device (downdrafts read *heavier*), so a measured weight decrease on a self-cooling device is anti-artifact-signed. Self-limiting note (from the §4c attractor): a bath-eating device cannot run away to cryogenic or superconducting temperatures — insulating starves it, and at high draw it frosts over and chokes (the lore's own frost image, recovered as a choke condition); the mass-energy of cooling is real but $\sim$ nanograms ($E=mc^2$), 12 OOM below lore-scale weight claims — which is why the coherence reading, not the thermal one, is the only

in-frame candidate. Cross-lane: the same cold/implosive/work-at-contact signature set reappears in the water-car (Brown's gas / Meyer) lore — mapped, unified as "descent-type release," and given transferred discriminators in `COLD_SIGNATURE_FAMILY_2026-07-22.md`. The freezing-shock account and Bearden's "gravito-stiction" remain lore (coined word, not a mechanism). The "time machine" claim stays firewalled: the defensible kernel is *local arrow-of-time gradients* — a maintained patch of reversed heat-flow bookkeeping — never causal loops; the OB-1 no-signaling obligation is the guardrail (transactional handshakes are no-signaling-compatible; retrocausal messaging is not, and nothing here licenses it).

AUDIT Two further lore items filed 2026-07-22, with one source caveat: the VTA reportedly ran cold in operation, and dead shorts reportedly produced a bright flash *with frost* rather than scorch. In-frame the frost is the **transient maximum of D5**: a short is maximum draw, the \$4c ledger (optical-cavity paper) makes maximum draw maximum cooling duty, and ambient humidity freezing onto the hardware is what a heat-withdrawal transient looks like — while the flash itself is an ordinary arc. The distinctive signature is the conjunction (flash + frost, where every ohmic fault gives flash + heat marks) — logged as **F1, fault forensics**: after any unintended fault on the bench, photograph and thermally inspect for scorch vs. condensation/frost before cleanup. Source caveat, carried honestly: the cold-VTA anecdote family traces largely through one narrator lineage (Bearden) — internal consistency of a story, not N independent confirmations.

PRE-REG **D7 — the annihilation-line null check.** Literal time-reversed electrons are positrons, and positron annihilation into back-to-back 511 keV photons is not an inference but daily engineering: every PET scanner images with exactly this line (the photon energy IS $m_e c^2$); positronium lifetimes match QED; positron-annihilation spectroscopy is an industrial defect probe; Anderson photographed the particle in 1932. A consumer gamma spectrometer (Radiacode-class, ~\$300) resolves 511 keV. Frozen prediction: **no 511 keV excess** during operation of any device in this lane — the frame claims arrowless-sector coupling, not antimatter. A null with anomalous output confirms the carriers are conventional (the holes/Peltier/near-field ladder); an actual excess would be revolutionary and a radiation hazard — and its absence across decades of unshielded lore workshops is already quiet proof that "cold electricity," whatever it was, was not literal reversed charge carriers.

8 · Puthoff 1987 — the balance that holds matter up, and what it licenses (added 2026-09-23)

DERIVED H. E. Puthoff's *Ground state of hydrogen as a zero-point-fluctuation-determined state* (Phys. Rev. D 35:3266, 1987 — ref. 8) is the cleanest peer-reviewed statement of the idea this lane keeps returning to: a ground state is not a thing at rest but a **dynamic equilibrium**. The orbiting electron radiates (Larmor) and would spiral in; it absorbs from the zero-point field and would spiral out; the orbit on which the two powers are equal is the ground state, and it lands exactly on the Bohr radius, $m\omega_0 r_0^2 = \hbar$. Every equation was re-derived with CODATA constants in `crypto_oracle/puthuff_zpf_balance_probe.py` (receipt `puthuff_zpf_balance_run.json`, nine gates frozen before the run, 9/9 pass): $r_0 = a_0$ to 6×10^{-12} .

8.1 What it gives this programme

DERIVED **A number for the sustain flow.** The paper never prints it: every ground-state hydrogen atom absorbs and re-radiates $\approx 47 \text{ nW}$ — one quantum $\hbar\omega_0$ every $\sim 93 \text{ ps}$, at the rate $\gamma/\omega_0 = (2/3)\alpha^3$ — about $2.8 \times 10^{16} \text{ W}$ per mole of two-way traffic that nets to exactly zero. That is "matter is a pattern the medium sustains" ([The Medium](#) §3; the attachment programme's gate E4) with a peer-reviewed magnitude, and it is the flow the attachment programme's §11.1 said had "no source."

MEASURED **QED backing.** The balance is not an artifact of the classical model: in QED the ground state is stable *because* the vacuum-fluctuation and radiation-reaction contributions to its energy rate cancel, and for an excited state they add — the sum is spontaneous emission (Dalibard, Dupont-Roc & Cohen-Tannoudji, ref. 9). What does *not* survive is stochastic electrodynamics as a complete theory of hydrogen — full nonlinear simulations self-ionize (ref. 12) — and the orbit's $L = \hbar$ (the quantum 1s state has $L = 0$). The energy bookkeeping is the durable part.

DERIVED **The medium's Lorentz seam, closed spectrally.** Puthoff's eq. (1) — $\hbar\omega/2$ per mode, $\rho \propto \omega^3$ — is the only loading a medium can carry and still have no rest frame: a boost multiplies an isotropic ω^n spectrum by D^{3-n} in each direction, which is 1 everywhere only for $n = 3$ (Marshall, Boyer, ref. 16; receipt P9). A thermal medium

does have a wind — the cosmic background's 3.362 mK dipole is exactly that — and the zero-point medium does not.

8.2 Rate, not setpoint — what the paper leaves implicit

DERIVED Eq. (1)'s field and the radiation-reaction term of eq. (4) are not two inputs: the fluctuation–dissipation theorem forces each from the other, exactly (receipt P3, 2×10^{-16} ; ref. 11). So a passive boundary — mirror, dielectric, Casimir gap — that suppresses or enhances the modes at the orbital frequency changes the vacuum's drive *and* the atom's emission into those modes by the same factor F (measured as inhibited spontaneous emission, refs. 14–15). The balance point does not move; only the time taken to reach it does. Stochastic electrodynamics says the same when done carefully: cavity shifts there "coincide with previous quantum calculations" — Lamb-shift-sized (ref. 13).




Figure 8.1 — rate, not setpoint. Charged oscillators in random-phase ω^3 noise (Puthoff's eq. 2), started empty (fed up by the vacuum) or at three quanta (drained by radiation). A passive boundary scales field and emission together by F : every run lands on $\hbar\omega_0/2$, and F sets only how fast. Cutting the field alone (dashed) is the only way to move the level. Same engine as receipt gate P6(b), log-sampled for display.

DERIVED This decides the literature's best-known extraction scheme. The Haisch–Model idea — atoms entering a Casimir cavity "spin down" and release energy — needs the field suppressed *while emission is not*: the dashed arm. Applied to hydrogen that premise predicts 1.5 eV per atom at 5% suppression and 1.3 keV at 90%; real boundaries shift ground states by micro-electronvolts (image-dipole bound: $1 \mu\text{eV}$ at 10 nm). Its one experiment (ref. 10) came in three orders of magnitude low, with

material and gas trends opposite to prediction. The same balance is also an **attractor from below** (receipt P4): an orbit pushed under the ground state absorbs more than it radiates and is refilled within ~ 93 ps. Puthoff's framework argues against sub-ground ("hydrino-class") states, not for them.

8.3 What it revises in §7

REVISED **Door 2, as written, does not survive.** The zero-point floor is not a reservoir at 0 K or at any temperature. It is the $n = 0$ floor of every mode, present at every temperature, and it cancels from every net energy flux: net exchange goes as $\hbar\omega[n(T_1) - n(T_2)]$ (receipt P7 — with and without the floor agree to 10^{-13}). If the floor could receive heat, every isothermal enclosure would cool itself; a 1 kg copper cube would lose about 1 K per minute. If one insists on a temperature, the floor's is $\hbar\omega/2k_B$ — 240 K at 10 THz — and every oscillator's own zero-point motion sits at exactly that value, so nothing flows. A genuine door 2 needs a colder *body*. The sky's 2.7 K, reached through the 8–13 μm window, is the real one, and it is measured: nighttime generation at 50 mW/m² and rising (ref. 17). Evanescent near-field coupling cannot reach it. For the same reason §7b's rectifier "straddling an arrowed and an arrowless sector" is not available, since the floor is not a separable sector. Every thermometry rider (D5, D6/D6b, W1b, D7, F1) remains a good measurement; only the attribution of polarity-blind cooling changes, from "bath-sourced" to "a heat engine whose cold body must be named."

DERIVED **The three Brillouin escapes** of the optical-cavity paper (§1d) close for the same reason. Receipt P8 builds a tunnel junction with asymmetric electrodes and a sharp cavity line in its environment: at one temperature it carries zero net current, term by term (ref. 18). The zero-point part is matched to the junction's own zero-point motion; mode-density asymmetry changes rates, not the detailed-balance ratio; and speed is not a variable, because the balance holds frequency by frequency. That answers the optical-cavity paper's own crux — *a static geometry cannot maintain a persistent gradient* — and it agrees with Model & Dmitriyeva's own assessment that rectifying the zero-point field "violates thermodynamics principles" (ref. 10). Door 1 (one-shot) and door 3 (cosmological) stand as written. The thermometer rule stands, and is sharper.

8.4 What the measured core must then be — and the run that decides

OPEN If the §1 output is real, standard physics leaves three readings, and the programme gains from each:

1. **An unidentified non-equilibrium input** — a residual gradient, light, or RF. That input is then the fuel, and naming it tells the engineering what to scale.
2. **Stored energy running down** — battery-class.
3. **A genuine violation of the fluctuation–dissipation theorem** — a static device delivering steady power at one temperature. That would be a larger discovery than "zero-point harvesting," and one OPH is on record against (§8.5).

One run separates them: the **sealed-isothermal test** (proposed as K1; to be frozen before running).

- **Setup.** The article sits in a closed, light-tight, thermally lagged metal box. Two thermistors verify the gradient across it is below 10 mK. The box is kept dark for at least 24 h, and the readout passes through filtered feedthroughs.
- **Controls.** A no-cavity twin and a reversed twin sit beside the article in the same box.
- **Accounting.** Delivered energy is integrated past $10\times$ the article's stored-energy bound.
- **Reading.** Output that vanishes when sealed $\rightarrow$ reading 1 (reopen one channel at a time). Output that decays within the bound $\rightarrow$ reading 2. Output that persists beyond it $\rightarrow$ reading 3.

The validation slate's LN_2 point then adds the temperature dependence, with one change of wording: a temperature-flat output in a verified-isothermal enclosure is not "the zero-point channel as expected." It is reading 3.

DERIVED Where the lawful energy is, in this lane's own hardware:

- **Real gradients** — sky cooling, and waste heat fed into nm-gap near-field thermophotovoltaic and thermionic stacks. The optical-cavity paper's own 400 K and 600 K rows (20 W/m^2 and 7.2 kW/m^2) are exactly this regime.
- **Driven, time-dependent boundaries** — the dynamical Casimir effect, measured in 2011 (ref. 20). The pump pays.
- **The one-shot door.**

8.5 The OPH overlay

- **OPH's clock entails Puthoff's balance.** OPH takes its observer clock from the 2π -normalized modular flow of screen caps (Bisognano–Wichmann; residual 1.1×10^{-4} on its receipt branch). The chain from there is direct:
 - a cap vacuum is then a KMS state;
 - the KMS property gives the fluctuation–dissipation theorem;
 - that theorem gives eq. (1) $\Leftrightarrow$ eq. (4), and so the balance;
 - KMS and ground states are passive: no cyclic process extracts work (ref. 19).OPH therefore forbids static extraction by its own clock axiom. This is conditional on the same receipt that carries its Lorentz–Einstein chain. The same receipt also closes the "driven steady state, not a ground state" loophole floated in the attachment programme (§12.3).
- **One 2π .** Four things are one fact: the Unruh temperature $\hbar a/2\pi c k_B$; Boyer's classical derivation of it from this same ω^3 field (ref. 16); the gravity paper's killer $\tau = 2\pi c/a$; and OPH's modular normalization.
- **"Energy from the boundary" is OPH-correct.** OPH puts the uniform vacuum energy "in the kernel of the local null readout." A Lorentz-invariant loading has $T_{ab} \propto g_{ab}$ and is invisible to null probes, so only boundary-induced differences (Casimir, Lamb, van der Waals) are readable. At equilibrium those differences are conservative: one-shot or driven, never a static flow.
- **The α/π detuning is reactive, not a fuel.** In Puthoff's balance the coupling cancels: $L = \hbar$ whatever e is. OPH's standing detuning $P - \varphi = \alpha/\pi$ scales with α , which places it in the Lamb-shift class. It is a standing displacement, conservative in a KMS state, and not a harvestable load.
- **The record layer supplies what stochastic electrodynamics lacks.** Stochastic electrodynamics alone cannot hold hydrogen: it self-ionizes and has no discrete spectrum. The network's split between a reversible wave layer and a committing record layer is where both halves live. The balance supplies the energetics; commitment supplies the discreteness.

OPEN **The projection picture** — the observed vacuum as the reduced state of a larger one (operator, 2026-09-23) — is the right mathematics: reduced states plus modular theory, which is what OPH's caps already are. The Bisognano–Wichmann trace is how entanglement makes the local vacuum look like a bath. This section adds one testable constraint. Whenever the hidden sector is in equilibrium, its "noise" and its

"constitutive response" are locked together by the fluctuation–dissipation theorem; eq. (1) $\Leftrightarrow$ eq. (4) is the worked example. A hidden sector that *feeds* devices must therefore show up as a violation of that theorem. That would mean either ground states exciting spontaneously, or a vacuum spectrum that departs from ω^3 and so carries a frame. Neither is seen. What remains open is lawful and interesting: correlations, memory, conservative forces, entanglement signatures. The full treatment, with every receipt: PUTHOFF_1987_ZPF_BALANCE_OPH_OVERLAY_2026-09-23.md.

9 · The archive record — what the Disclosure Project files hold (added 2026-10-01)

What was read. Every zero-point and free-energy document we could find in the Disclosure Project Intelligence Archive (DPIA): 111 files from full-text searches for *zero point*, *ZPE*, *Casimir*, *free energy*, *overunity*, *vacuum energy*, *Puthoff*, *Moray*, *Bearden*, *Floyd Sweet*, *Tesla*, *scalar*, *energy device*, *Searl*, *Aspden*, *new energy*. The set holds three 2010–11 AAWSAP DIRDs, a 1989 DIA meeting memo, the Bearden/MEG correspondence, about twenty Sweet files, the Moray record, the 1950s–80s Cejka device collection, and the paper trail of Dr. Greer's own energy programme (SEAS, 2002–03). Local copies, OCR text and four reading notes are in `~/Documents/dpia-archive/zpe/`, outside the repo. DPIA numbers below are archive document IDs. Added grades: **DOCUMENTED** a named source reports it and the archive records the report; **TESTIMONY** a single narrator; **NULL-STATIC** a static configuration, excluded as a power source by §8.3–§8.5; **NOT SUPPORTED** a predicted effect not seen where looked for; **CONTRADICTED** answered by a test on the claim's own terms.

The short answer. The archive adds no instrumented positive to this lane and no record against the §1 measured core. Every document in which someone put hardware on a bench and metered both sides ended null, below unity, or inconclusive. The official assessments agree with §7–§8 on every point they address. One pattern runs through the claims that did run for hours: **each had a connection nobody metered** — Moray's antenna, the drive motor on Kromrey's generator, the drive electronics behind the MEG's input figure, the growling machine beside Sweet's bench. That is the open-system rule's own prediction: the energy came from somewhere, and the work is to name it.

9.1 Official and institutional assessments

- **DOCUMENTED** DIA/AAWSAP DIRD D142, "Concepts for Extracting Energy from the Quantum Vacuum" (6 April 2010; DPIA 130622; author redacted). It is the only government assessment in the set, and it lands where §8 does:
 - No practicable extraction technique has been shown in a laboratory.
 - Casimir energies are too small for useful power.
 - The QED vacuum cannot be used up, so a continuously cycling machine is forbidden in principle, while one-shot release is allowed (§7, door 1).
 - Stochastic electrodynamics, the framework that would allow cycling, is judged inadequate for the question.
 - It quotes Jaynes: the zero-point field an atom sees is its own radiation-reaction field. That is §8's eq. (1) $\Leftrightarrow$ eq. (4) pairing, in a government report.
 - It treats the dynamical Casimir effect as a real energy exchange paid for by the drive (§8.4, "the pump pays").
 - It records one measured null: switchable mirrors (70–400 nm gaps, Iannuzzi) did not noticeably change the Casimir force. That is the switch a tunable Casimir engine would need.
 - It carries the Haisch–Model cavity-hydrogen concept (US 7,379,286) at 2,150–21,500 W/cm³, explicitly conditional on a chain of conjectures. Its synchrotron test returned no result because of beam problems. §8.2 prices this premise and finds it three orders low.
- **DOCUMENTED** **The proponents' own null.** *Jane's Defence Weekly*, 26 July 2000 (DPIA 121264): about 30 claimed vacuum-energy devices were brought to Puthoff's institute in Austin, and none showed measured output exceeding input.
- **DOCUMENTED** **Bailey 1992 review (DPIA 117952).** It surveys Moray (50 kW claimed), Hyde, Methernitha, PODMOD, WIN and Sweet, and concludes that none was adequately tested or replicated. Its one third-party test, DePalma's N-machine in 1985, "did not perform as claimed". Bailey defines "zero-point energy" as energy drawn from outside the experimenter's influence: mains wiring, transmitters, Earth fields, the sun. That is the open-system rule in a 1992 proponent's words.
- **DERIVED** **Cole & Puthoff 1993** (*Phys. Rev. E* 48; DPIA 119258) is a one-shot result. Its worked example consumes a supply of capacitors, each used once. It is the source of door 1 and claims no cycle. The press release in the same file (119245) reads more into it than the paper does.

- **DOCUMENTED** DIA's 6th ZPE meeting, December 1989 (Hercules memo, DPIA 120536). A defence-intelligence R&D council flagged zero-point and "scalar" topics as up and coming; DIA wanted the field classified and planned a March 1990 verification trip to Novosibirsk. Every technical claim in it (a 700 W-in, 3,000 W-out tube; condensed-charge beads) is unsourced and secondhand. It records interest, not results.
- **NOT SUPPORTED** Davis, AFRL Advanced Propulsion Study (2004; DPIA 124243) says experiments already "prove" electrical extraction from the vacuum. The works it cites measure Casimir *forces*, not net energy. The 2010 D142 verdict is the later and more careful one. The 2011 DIRD D153 (DPIA 130661) concerns *measuring* negative-energy states, not extracting energy.

9.2 The device ledger

Device (DPIA)	Class	Best record in the archive	Grade
Coler <i>Magnetstromapparat</i> (125282, 125379, 125228)	static magnets, coils, condensers	British intelligence BIOS Final Report 1043 (1946). Coler built it in front of the team from their materials. It gave 450 mV for ~3 h, until a solder joint failed, and 60 mV the next day for 30 min. No power was ever measured. The team called it inexplicable.	MEASURED millivolts · NULL-STATIC as a source · residual OPEN (thermocouple and galvanic effects not excluded)
Coler <i>Stromerzeuger</i> (125282)	battery- driven	Few watts in, 6 kW claimed out. A 1926 test exists but its table is illegible. In 1943 a Navy-funded rebuild would not start.	OPEN , leaning NOT SUPPORTED
Moray radiant- energy device (119074, 118896)	antenna + ground + detector "valves"	1928 sealed-trunk endurance test (E. G. Jensen's letter): a 110 W load ran ~74 h, then 83.5 h, about 17 kWh, under numbered railroad seals. Disconnecting the house mains did nothing; removing the antenna put the light out . The famous "50 kW" traces to watt-hours read as watts. The detector failed when jarred and later burned	DOCUMENTED (witnesses were an investor and Moray's lawyer) · OPEN , with the input named: the antenna circuit, never metered

		out. Harvey Fletcher of Bell Labs, who saw it, advised against investing.	
Sweet VTA (§5; 118970, 118992, 120888, 119249)	conditioned ferrite, 60 Hz drive	One first-hand running sighting (Campbell): 120 V on a voltmeter and a household load list, with no current or duration. Meters failed above ~1 kW (Rosenthal). An independent test at the Eyring labs was planned in 1989 and never run. The "affidavits" are an agency contract. Details: §2 REVISED note and VTA record addendum.	TESTIMONY • OPEN ; §5 protocol unchanged
Bearden/Patrick MEG (118832, 118849, 118833, 117915, 118838)	switched (87.5 kHz) Metglas core + NdFeB magnet	The patent's COP 3.44 is extrapolated from 75 V to 100 V. Input is battery $V \times I$, with no stated treatment of the drive electronics and no calorimetry. A closed loop is asserted, never run. The patent names the magnet as the source and concedes demagnetization; the magnet stores ~10 J against ~80 W claimed excess, ~0.1 s of supply. Naudin's 2000 replication is the only one, and he called artifacts possible. Production was promised for 2002; no unit had shipped by 2008.	NOT SUPPORTED as demonstrated • OPEN as a switched device • magnet-as-fuel excluded beyond ~0.1 s DERIVED
Bearden's dipole / Heaviside-flow theory (118827, 123928, 123939)	static source	"Every dipole is a free energy generator"; magnet-plus-electret "pours out" energy. His picture of a static field as a continually regenerated steady state is the Puthoff balance itself.	regeneration COMPATIBLE • as a power source NULL-STATIC
W.J.F. Muller homopolar generator (125300)	driven rotary	Independent engineering test, NOVA (Alberta), December 1982: efficiency "does not approach 100%". The 21 kW figure was a one-coil projection.	CONTRADICTED for that unit

Kromrey generator (125202, 125380)	motor-driven	1968 patent test metered output only, never the drive motor's input.	OPEN
Cole generator (125288)	driven	Inventor's 1985 bench log: best 17 W in, 20 W out, with many inputs calculated, not metered. The loop was never closed, at 2–3 W where that is trivial.	OPEN
Hubbard transformer (125217)	radioactive-claimed	1919 newspaper accounts (retold 1956): a 35 hp boat run for hours. At that power, radium decay would need of order 100 kg.	TESTIMONY · radioactive mechanism NOT SUPPORTED
Valone / Hartman magnet ramp (118478)	static magnets	Proposal, no data.	NULL-STATIC
ATREE microwave rectifier (125279)	real RF gradient	~63 W claimed from "background" 10 cm radiation.	lawful source · magnitude NOT SUPPORTED without a nearby transmitter

ESTIMATE What Moray's antenna would have to deliver: a 50 kW broadcaster 1 km away gives $\sim 4 \text{ mW/m}^2$, so a 110 W draw needs $\sim 3 \times 10^4 \text{ m}^2$ of effective aperture. That is reachable only with a large resonant wire near a strong transmitter. The atmospheric field is far too weak, as Fletcher judged in 1927. The 1928 test's sealed trunks excluded batteries and mains, and it is the one historical protocol worth copying. Its missing step is the one that decides: meter the antenna lead.

9.3 Greer's energy programme, 1998–2014

DOCUMENTED The archive documents a serious attempt. The Space Energy Access Systems plan (DPIA 118505, January 2003) set out the right protocol. It screened candidates, visited the top six and optioned one, then sent it to three independent labs. Watts in and out were to be measured under load, with inspection for hidden batteries. Phase I was budgeted at \$100–500k, with a \$100k "Z Prize". That is a K1-class test, written 23 years before this paper's K1. What happened:

- **Paper screening.** Prof. Paul Czysz (aerospace, professor emeritus) evaluated five submissions in September 2002 (DPIA 119310) and passed none: a magnetic piston engine, a dual-rotor alternator, bootstrap flywheels, a "transduction device" he called a fake perpetual-motion machine, and an implosion turbine.
- **Hands-on checks** (DPIA 119311, 119262, autumn 2002). An intern's replication of one device underperformed; another demonstration underwhelmed the technical reviewer; an aerospace company's test of a third was inconclusive. Planned tests of two more (a motor claimed at 1/16 W in, 2.1 W out, and Muller rebuilds) have no reported result.
- **Bearden declined a demonstration to Congress** (DPIA 118838, April 2002). He gave five reasons: patent rights, the company board's control, the units being lab apparatus, a \$29M finishing cost, and publicity as the "kiss of death". In 2003 he told SEAS not to plan on a demonstrator (118840).
- **Inventor friction.** Many inventors did not respond, wanted payment or would only sell. One answered the 2003 Z-power offer but refused to travel for evaluation (118053).
- **The pivot.** Greer's undated "New Earth Energy Incubator" draft (DPIA 119279) concedes that no inventor had overcome the obstacles. It proposes open-source, live-streamed labs at \$100–200M instead.

NOT SUPPORTED "The programme found a working device" is not supported by these records. It is not contradicted either, because nothing after 2003 is documented. The programme's own experience fits the §8 picture: the protocol was right, and nothing that came through it delivered metered net power.

9.4 What it changes here

1. **§2's Sweet density ladder** is corrected (REVISED note there). The verdict holds; the "convergence" argument is withdrawn.
2. **§8 gains independent support.** D142 reaches §8's conclusions without Puthoff 1987 as its anchor, and the archive's tests, from BIOS 1946 to NOVA 1982 to Austin 2000, are the null records that §8.3–§8.5 predict for static devices.
3. **K1 gets a historical template.** Moray's sealed trunk plus SEAS's watts-in/watts-out-under-load rule plus one more lead on the meter is a usable design for any claimed device. Rosenthal's night-time voltage readings (70 V at 3 AM, 85 V at 1:30 AM) give the §5 protocol's sidereal check S1 a target.

4. **Acquire next:** the video Bearden sold of Sweet's 30 April 1987 bench tests (DPIA 119221); the complete BIOS 1043 report; the NOVA 1982 test report; the originals of the 1928 Jensen letter.

References

1. Moddel, G., Weerakkody, A., Doroski, D., Bartusiak, D. *Optical-Cavity-Induced Current*. Symmetry 13(3):517 (2021).
2. Moddel, G. et al. *Casimir-cavity-induced conductance changes*. Phys. Rev. Research 3:L022007 (2021).
3. Maclay, G.J. *Modeling Electronic Devices with a Casimir Cavity*. Physics 6(3):70 (2024).
4. Moddel, G. *Zero-Point Energy: Capturing Evanescence*. (2022).
5. Thibado, P.M. et al. *Fluctuation-induced current from freestanding graphene*. Phys. Rev. E 102:042101 (2020).
6. Cole, D.C., Puthoff, H.E. *Extracting Energy and Heat from the Vacuum*. Phys. Rev. E 48:1562 (1993).
7. Project sims: `casimir_mim_plate.py` , `casimir_metamaterial_ceiling.py` , `lamp_detector_budget.py` , `home_bench_noise_budget.py` (crypto_oracle/universe_sim/).
8. Puthoff, H.E. *Ground state of hydrogen as a zero-point-fluctuation-determined state*. Phys. Rev. D 35:3266 (1987); and *Quantum ground states as equilibrium particle–vacuum interaction states*. Quantum Stud. Math. Found. 3:5 (2016).
9. Dalibard, J., Dupont-Roc, J., Cohen-Tannoudji, C. *Vacuum fluctuations and radiation reaction: identification of their respective contributions*. J. Physique 43:1617 (1982).
10. Moddel, G., Dmitriyeva, O. *Extraction of zero-point energy from the vacuum: assessment of stochastic-electrodynamics-based approach as compared to other methods*. Atoms 7:51 (2019).
11. Callen, H.B., Welton, T.A. *Irreversibility and generalized noise*. Phys. Rev. 83:34 (1951).
12. Nieuwenhuizen, T.M., Liska, M.T.P. *Simulation of the hydrogen ground state in stochastic electrodynamics*. Phys. Scr. T165:014006 (2015); Found. Phys. 45:1190 (2015).
13. Cetto, A.M., de la Peña, L. *Environmental effects on the Lamb shift according to stochastic electrodynamics*. Phys. Rev. A 37:1952 (1988).
14. Hulet, R.G., Hilfer, E.S., Kleppner, D. *Inhibited spontaneous emission by a Rydberg atom*. Phys. Rev. Lett. 55:2137 (1985).
15. Jhe, W. et al. *Suppression of spontaneous decay at optical frequencies*. Phys. Rev. Lett. 58:666 (1987).
16. Marshall, T.W. Nuovo Cimento 38:206 (1965); Boyer, T.H. Phys. Rev. 182:1374 (1969); Boyer, T.H. *Thermal effects of acceleration through random classical radiation*. Phys. Rev. D 21:2137 (1980).
17. Assawaworrarit, S., Omais, Z., Fan, S. *Nighttime electric power generation at a density of 50 mW/m² via radiative cooling of a photovoltaic cell*. Appl. Phys. Lett. 120:143901 (2022).
18. Ingold, G.-L., Nazarov, Yu.V. *Charge tunneling rates in ultrasmall junctions* (1992), arXiv:cond-mat/0508728.
19. Pusz, W., Woronowicz, S.L. *Passive states and KMS states for general quantum systems*. Commun. Math. Phys. 58:273 (1978); Bisognano, J.J., Wichmann, E.H. J. Math. Phys. 16:985 (1975).
20. Wilson, C.M. et al. *Observation of the dynamical Casimir effect in a superconducting circuit*. Nature 479:376 (2011).

21. Project probe: `crypto_oracle/puthoffs_zpf_balance_probe.py` →
`runtime_receipts/puthoffs_zpf_balance_run.json` (nine frozen gates, 9/9 pass).