



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

Alexander Panchenko

**INDUCING INTERPRETABLE WORD
SENSES FOR WSD AND ENRICHMENT OF
LEXICAL RESOURCES**

Overview

■ Inducing word sense representations:

- word sense embeddings via retrofitting [Pelevina et al., 2016, Remus and Biemann, 2018];
- sparse sense representations [Panchenko et al., 2017c];
- inducing synsets [Ustalov et al., 2017]
- sense semantic classes [Panchenko et al., 2018]

■ Inducing word sense representations:

- word sense embeddings via retrofitting [Pelevina et al., 2016, Remus and Biemann, 2018];
- sparse sense representations [Panchenko et al., 2017c];
- inducing synsets [Ustalov et al., 2017]
- sense semantic classes [Panchenko et al., 2018]

■ Making induced senses interpretable

[Panchenko et al., 2017b, Panchenko et al., 2017c]

■ Inducing word sense representations:

- word sense embeddings via retrofitting [Pelevina et al., 2016, Remus and Biemann, 2018];
- sparse sense representations [Panchenko et al., 2017c];
- inducing synsets [Ustalov et al., 2017]
- sense semantic classes [Panchenko et al., 2018]

■ Making induced senses interpretable


[Panchenko et al., 2017b, Panchenko et al., 2017c]

■ Linking induced word senses to lexical


resources [Faralli et al., 2016, Panchenko et al., 2017a, Biemann et al., 2018]

Inducing word sense representations


Word vs sense embeddings



Word vs sense embeddings




Related work



Related work: knowledge-based

- **AutoExtend** [Rothe and Schütze, 2015]




* image is reproduced from the original paper

Related work: Chinese Whispers#1




* source of the image: http://ic.pics.livejournal.com/blagin_anton/33716210/2701748/2701748_800.jpg


Related work: Chinese Whispers#2



Related work: Chinese Whispers#2



Related work: Chinese Whispers#2



Sense embeddings using retrofitting

RepL4NLP@ACL'16 [Pelevina et al., 2016], LREC'18 [Remus and Biemann, 2018]

Prior methods:


- Induce inventory by **clustering of word instances**
- Use **existing** sense inventories

Our method:

- **Input:** word embeddings
- **Output:** word sense embeddings
- **Word sense induction** by **clustering of word ego-networks**


Sense embeddings using retrofitting

■ From word embeddings to sense embeddings



Sense embeddings using retrofitting

■ Word sense induction using ego-network clustering



Sense embeddings using retrofitting

■ Neighbours of Word and Sense Vectors

Vector	Nearest Neighbors
table	tray, bottom, diagram, bucket, brackets, stack, basket, list, parenthesis, cup, saucer, pile, playfield, bracket, pot, drop-down, cue, plate

Sense embeddings using retrofitting

■ Neighbours of Word and Sense Vectors

Vector	Nearest Neighbors
table	tray, bottom, diagram, bucket, brackets, stack, basket, list, parenthesis, cup, saucer, pile, playfield, bracket, pot, drop-down, cue, plate
table#0	leftmost#0, column#1, tableau#1, indent#1, bracket#3, pointer#0, footer#1, cursor#1, diagram#0, grid#0
table#1	pile#1, stool#1, tray#0, basket#0, bowl#1, bucket#0, box#0, cage#0, saucer#3, mirror#1, pan#1, lid#0

Sense embeddings using retrofitting

Word Sense Disambiguation

- 1 **Context extraction**: use context words around the target word
- 2 **Context filtering**: based on context word's relevance for disambiguation
- 3 **Sense choice in context**: maximise similarity between a context vector and a sense vector



Sense embeddings using retrofitting


They bought a **table** and chairs for kitchen.

table senses


data

furniture


Sense embeddings using retrofitting



Sense embeddings using retrofitting



Sense embeddings using retrofitting



Sense embeddings using retrofitting

Evaluation on SemEval 2013 Task 13 WSI&D:

Model	Jacc.	Tau	WNDCG	F.NMI	F.B-Cubed
AI-KU (add1000)	0.176	0.609	0.205	0.033	0.317
AI-KU	0.176	0.619	0.393	0.066	0.382
AI-KU (remove5-add1000)	0.228	0.654	0.330	0.040	0.463
Unimelb (5p)	0.198	0.623	0.374	0.056	0.475
Unimelb (50k)	0.198	0.633	0.384	0.060	0.494
UoS (#WN senses)	0.171	0.600	0.298	0.046	0.186
UoS (top-3)	0.220	0.637	0.370	0.044	0.451
La Sapienza (1)	0.131	0.544	0.332	—	—
La Sapienza (2)	0.131	0.535	0.394	—	—
AdaGram, $\alpha = 0.05$, 100 dim	0.274	0.644	0.318	0.058	0.470
w2v	0.197	0.615	0.291	0.011	0.615
w2v (nouns)	0.179	0.626	0.304	0.011	0.623
JBT	0.205	0.624	0.291	0.017	0.598
JBT (nouns)	0.198	0.643	0.310	0.031	0.595
TWSI (nouns)	0.215	0.651	0.318	0.030	0.573

Sense embeddings using retrofitting

LREC'2018 [Remus and Biemann, 2018]

	AUTOEXTEND	ADAGRAM	SGNS	GLOVE	SYMPAT	LSABOW	LSAHAL	PARAGRAMSL
SIMLEX999	0.45	0.29	0.44	0.37	0.54	0.30	0.27	0.68
MEN	0.72	0.67	0.77	0.73	0.53	0.67	0.71	0.77
SIMVERB	0.43	0.27	0.36	0.23	0.37	0.15	0.19	0.53
WORDSIM353	0.58	0.61	0.70	0.61	0.47	0.67	0.59	0.72
SIMLEX999-N	0.44	0.33	0.45	0.39	0.48	0.32	0.34	0.68
MEN-N	0.72	0.68	0.77	0.76	0.57	0.71	0.73	0.78


Sense embeddings using retrofitting

LREC'2018 [Remus and Biemann, 2018]

	AUTOEXTEND	ADACRAM	SGNS	SGNS+SENSES	GLOVE	GLOVE+SENSES	SYMPAT	SYMPAT+SENSES	LSABOW	LSABOW+SENSES	LSAHAL	LSAHAL+SENSES	PARAGRAMSL	PARAGRAMSL+SENSES
SIMLEX999	0.45	0.29	0.44	0.46	0.37	0.41	0.54	0.55	0.30	0.39	0.27	0.38	0.68	0.64
MEN	0.72	0.67	0.77	0.78	0.73	0.77	0.53	0.68	0.67	0.70	0.71	0.74	0.77	0.80
SIMVERB	0.43	0.27	0.36	0.39	0.23	0.30	0.37	0.45	0.15	0.22	0.19	0.28	0.53	0.53
WORDSIM353	0.58	0.61	0.70	0.69	0.61	0.65	0.47	0.62	0.67	0.66	0.59	0.63	0.72	0.73
SIMLEX999-N	0.44	0.33	0.45	0.50	0.39	0.47	0.48	0.55	0.32	0.46	0.34	0.44	0.68	0.66
MEN-N	0.72	0.68	0.77	0.79	0.76	0.80	0.57	0.74	0.71	0.73	0.73	0.76	0.78	0.81

- Sense-aware similarities are marked with **+SENSES**.
- These results are using a sense inventory based on **sparse dependency features** (JoBimText).

Sense embeddings using retrofitting



- Word and sense embeddings of words **iron** and **vitamin**.

LREC'18 [Remus and Biemann, 2018]



Sparse sense representations



Sparse sense representations



Watset: synset induction



Watset: synset induction



Watset: synset induction



Induction of sense semantic classes



Induction of sense semantic classes



Induction of sense semantic classes

Making induced senses interpretable

Making induced senses interpretable

Knowledge-based sense representations are **interpretable**

bn:01713224n • NOUN • Named Entity • Categories: High-level programming languages, Dutch inventions, Class-based programming languages, Cross platform free software...

Python (programming language) • /usr/bin/python • /usr/local/bin/python • Python language • Python programming language

Python is a widely used general-purpose, high-level programming language. Wikipedia

More definitions

IS A	programming language • free software • scripting language
HAS PART	pandas
HAS KIND	Stackless Python
DESIGNER	Guido van Rossum
DEVELOPER	Python Software Foundation • Guido van Rossum
DIALECTS	Cython • Stackless Python
INFLUENCED BY	ALGOL 68 • alphabet • ruby
LICENSE	Python Software Foundation License

More relations

EXPLORE NETWORK



Making induced senses interpretable

Knowledge-free sense representations are **uninterpretable**

```
In [11]: sv.syn0[sv.vocab["python#2"].index]
```

```
Out[11]:
```

```
array([-0.0493343 , -0.02244579,  0.02296794,  0.03484775,  0.0404554 ,
        0.04304857, -0.02211852, -0.02118347, -0.03212074, -0.01202453,
        0.01206081,  0.05609602, -0.05950832,  0.00859888, -0.01051112,
        0.03177784, -0.06489294,  0.03833736,  0.05437034, -0.01451268,
       -0.02419239, -0.03195219,  0.0620546 ,  0.10284331,  0.07430374,
       -0.04109243, -0.01181133 ,  0.05401124,  0.05283536,  0.00873093,
        0.03662092,  0.03762468,  0.02368712, -0.03980339,  0.02791001,
        0.02529952, -0.02255581, -0.00925604, -0.03940469, -0.02855149,
        ...,
       -0.08179335,  0.02319797, -0.0167018 ,  0.04818865, -0.06946786,
       -0.06530198,  0.00522405, -0.0336296 , -0.05401101,  0.01190361], dtype=float32)
```



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

Making induced senses interpretable



Making induced senses interpretable

Making induced senses interpretable



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

Making induced senses interpretable



Making induced senses interpretable

Linking induced senses to resources

Linking induced senses to resources

Linking induced senses to resources

Linking induced senses to resources

Linking induced senses to resources



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

Linking induced senses to resources



Linking induced senses to resources

Conclusion

Vectors + Graphs = ♥

GRAPHS
~~**ARE**~~
NOT
DEAD.

Take home messages

- We can **induce word senses**, **synsets** and **semantic classes** in a knowledge-free way using **graph clustering** and **distributional models**.

Take home messages

- We can **induce word senses**, **synsets** and **semantic classes** in a knowledge-free way using **graph clustering** and **distributional models**.
- We can make the **induced word senses interpretable** in a knowledge-free way with **hypernyms**, **images**, **definitions**.

Take home messages

- We can **induce word senses**, **synsets** and **semantic classes** in a knowledge-free way using **graph clustering** and **distributional models**.
- We can make the **induced word senses interpretable** in a knowledge-free way with **hypernyms**, **images**, **definitions**.
- We can **link induced senses to lexical resources** to
 - improve **performance of WSD**;
 - **enrich lexical resources** with emerging senses.

An ongoing shared task on WSI&D

- Participate in an **ACL SIGSLAV** sponsored shared task on **word sense induction and disambiguation** for Russian!
- **More details:** <http://russe.nlpub.org/2018/wsi>



Acknowledgments

Thank you! Questions?

This research was supported by



Deutsche
Forschungsgemeinschaft



Deutscher Akademischer Austausch Dienst
German Academic Exchange Service



Bartunov, S., Kondrashkin, D., Osokin, A., and Vetrov, D. (2016).

Breaking sticks and ambiguities with adaptive skip-gram.
In Artificial Intelligence and Statistics, pages 130–138.



Biemann, C., Faralli, S., Panchenko, A., and Ponzetto, S. P. (2018).

A framework for enriching lexical semantic resources with distributional semantics.

In Journal of Natural Language Engineering, pages 56–64.
Cambridge Press.



Faralli, S., Panchenko, A., Biemann, C., and Ponzetto, S. P. (2016).

Linked disambiguated distributional semantic networks.
In International Semantic Web Conference, pages 56–64.
Springer.



Panchenko, A., Faralli, S., Ponzetto, S. P., and Biemann, C. (2017a).

Using linked disambiguated distributional networks for word sense disambiguation.

In Proceedings of the 1st Workshop on Sense, Concept and Entity Representations and their Applications, pages 72–78, Valencia, Spain. Association for Computational Linguistics.



Panchenko, A., Marten, F., Ruppert, E., Faralli, S., Ustalov, D., Ponzetto, S. P., and Biemann, C. (2017b).

Unsupervised, knowledge-free, and interpretable word sense disambiguation.

In Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, pages 91–96, Copenhagen, Denmark. Association for Computational Linguistics.



Panchenko, A., Ruppert, E., Faralli, S., Ponzetto, S. P., and Biemann, C. (2017c).

Unsupervised does not mean uninterpretable: The case for word sense induction and disambiguation.

In Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics, Volume 1

Long Papers, pages 86–98, Valencia, Spain. Association for Computational Linguistics.



Panchenko, A., Ustalov, D., Faralli, S., Ponzetto, S. P., and Biemann, C. (2018).

Improving hypernymy extraction with distributional semantic classes.

In *Proceedings of the LREC 2018*, Miyazaki, Japan. European Language Resources Association.



Pelevina, M., Arefiev, N., Biemann, C., and Panchenko, A. (2016).

Making sense of word embeddings.

In *Proceedings of the 1st Workshop on Representation Learning for NLP*, pages 174–183, Berlin, Germany. Association for Computational Linguistics.



Remus, S. and Biemann, C. (2018).

Retrofitting word representations for unsupervised sense aware word similarities.

In *Proceedings of the LREC 2018*, Miyazaki, Japan. European Language Resources Association.



Rothe, S. and Schütze, H. (2015).

Autoextend: Extending word embeddings to embeddings for synsets and lexemes.

In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1793–1803, Beijing, China. Association for Computational Linguistics.



Ustalov, D., Panchenko, A., and Biemann, C. (2017).

Watset: Automatic induction of synsets from a graph of synonyms.

In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1579–1590, Vancouver, Canada. Association for Computational Linguistics.