



Alexander Panchenko

FROM UNSUPERVISED INDUCTION OF LINGUISTIC STRUCTURES FROM TEXT TOWARDS APPLICATIONS IN DEEP LEARNING





Vectors + Graphs = ♡





Take home messages

We can induce word senses, synsets, semantic classes, and semantic frames in a knowledge-free way using graph clustering and distributional models.





Take home messages

- We can induce word senses, synsets, semantic classes, and semantic frames in a knowledge-free way using graph clustering and distributional models.
- We can make the induced word senses interpretable in a knowledge-free way with hypernyms, images, definitions.



Take home messages

- We can induce word senses, synsets, semantic classes, and semantic frames in a knowledge-free way using graph clustering and distributional models.
- We can make the induced word senses interpretable in a knowledge-free way with hypernyms, images, definitions.
- We can link induced senses to lexical resources to
 - improve performance of WSD;
 - enrich lexical resources with emerging senses.



Take home messages

- We can induce word senses, synsets, semantic classes, and semantic frames in a knowledge-free way using graph clustering and distributional models.
- We can make the induced word senses interpretable in a knowledge-free way with hypernyms, images, definitions.
- We can link induced senses to lexical resources to
 - improve performance of WSD;
 - enrich lexical resources with emerging senses.
- We can represent language graphs using graph embeddings in deep neural models.



Natural Language Engineering journal

- A special issue on informing neural architectures for NLP with linguistic and background knowledge.
- ... with Ivan Vulić and Simone Paolo Ponzetto.



goo.gl/A76NGX



Acknowledgments

Thank you! Questions?

This research was supported by





Deutscher Akademischer Austausch Dienst German Academic Exchange Service