



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

Alexander Panchenko

**INDUCING INTERPRETABLE WORD
SENSES FOR WSD AND ENRICHMENT OF
LEXICAL RESOURCES**

Overview

■ Inducing word sense representations:

- word sense embeddings via retrofitting [Pelevina et al., 2016, Remus and Biemann, 2018];
- sparse sense representations [Panchenko et al., 2017c];
- sense semantic classes [Panchenko et al., 2018]

Overview


- **Inducing word sense representations:**
 - word sense embeddings via retrofitting [Pelevina et al., 2016, Remus and Biemann, 2018];
 - sparse sense representations [Panchenko et al., 2017c];
 - sense semantic classes [Panchenko et al., 2018]

- **Making the induced senses interpretable**
[Panchenko et al., 2017b, Panchenko et al., 2017c]

- **Inducing word sense representations:**
 - word sense embeddings via retrofitting [Pelevina et al., 2016, Remus and Biemann, 2018];
 - sparse sense representations [Panchenko et al., 2017c];
 - sense semantic classes [Panchenko et al., 2018]
- **Making the induced senses interpretable**
[Panchenko et al., 2017b, Panchenko et al., 2017c]
- **Linking induced word senses to lexical resources** [Faralli et al., 2016, Panchenko et al., 2017a, Biemann et al., 2018]


Inducing word sense representations

Related work



Related work: knowledge-based

■ AutoExtend [Rothe and Schütze, 2015]



* image is reproduced from the original paper

Related work: knowledge-free

- **Adagram** [Bartunov et al., 2016]
- Multiple vector representations θ for each word:

$$p(Y, Z, \beta | X, \alpha, \theta) = \prod_{w=1}^V \prod_{k=1}^{\infty} p(\beta_{wk} | \alpha) \prod_{i=1}^N [p(z_i | x_i, \beta) \prod_{j=1}^C p(y_{ij} | z_i, x_i, \theta)],$$

- α – a meta-parameter controlling number of senses;
- z_i – a hidden variable: a sense index in context;
- $p(\beta_{wk} | \alpha)$ – probability of the k -th sense of the word w ;
- $p(z_i | x_i, \beta)$ – probability of observing word x_i in the sense z_i ;
- $\prod_{j=1}^C p(y_{ij} | z_i, x_i, \theta)$ – probability of the context C .

Related work: knowledge-free

- **Adagram** [Bartunov et al., 2016]
- Multiple vector representations θ for each word:

$$p(Y, Z, \beta | X, \alpha, \theta) = \prod_{w=1}^V \prod_{k=1}^{\infty} p(\beta_{wk} | \alpha) \prod_{i=1}^N [p(z_i | x_i, \beta) \prod_{j=1}^C p(y_{ij} | z_i, x_i, \theta)],$$

- α – a meta-parameter controlling number of senses;
 - z_i – a hidden variable: a sense index in context;
 - $p(\beta_{wk} | \alpha)$ – probability of the k -th sense of the word w ;
 - $p(z_i | x_i, \beta)$ – probability of observing word x_i in the sense z_i ;
 - $\prod_{j=1}^C p(y_{ij} | z_i, x_i, \theta)$ – probability of the context C .
- **See also:** [Neelakantan et al., 2014] and [Li and Jurafsky, 2015]



Sense embeddings using retrofitting



Sense embeddings using retrofitting



Sparse sense representations



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

Inducing word sense representations

○○○○○●○○○○○

Sparse sense representations



Sparse sense representations



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

Inducing word sense representations

oooooooo●ooooo

Watset: synset induction



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

Inducing word sense representations

oooooooo●oooo

Watset: synset induction



Universität Hamburg
DER FORSCHUNG | DER LEHRE | DER BILDUNG

Inducing word sense representations

oooooooooooo●ooo

Watset: synset induction



Induction of sense semantic classes



Induction of sense semantic classes



Induction of sense semantic classes

Conclusion

Summary

- How to **induce word senses, synsets** and **semantic classes** from text and synonyms.

Summary

- How to **induce word senses, synsets** and **semantic classes** from text and synonyms.
- **Interpretability can be added** on the top of induced word senses in a model agnostic way.

Summary

- How to **induce word senses, synsets** and **semantic classes** from text and synonyms.
- **Interpretability can be added** on the top of induced word senses in a model agnostic way.
- Hypernymy labels **improve hypernymy extraction**.

Summary

- How to **induce word senses, synsets** and **semantic classes** from text and synonyms.
- **Interpretability can be added** on the top of induced word senses in a model agnostic way.
- Hypernymy labels **improve hypernymy extraction**.
- Linking induced word senses to lexical resources:
 - improves **performance of WSD**;
 - can be used to **enrich lexical resources** with new senses.

A New Shared Task on WSI&D

- Participate in an ACL SIGSLAV sponsored shared task on **word sense induction and disambiguation** for Russian!

A lexical sample task evaluated using the ARI measure

- Target word, e.g. “bank” (in Russian).
- Contexts where the word occurs.
- You need to group the contexts by senses.

A New Shared Task on WSI&D

- Participate in an ACL SIGSLAV sponsored shared task on **word sense induction and disambiguation** for Russian!

A lexical sample task evaluated using the ARI measure

- Target word, e.g. “bank” (in Russian).
 - Contexts where the word occurs.
 - You need to group the contexts by senses.
-
- **More details:** <http://russe.nlpub.org/2018/wsi>
 - You can participate by **31.01.2018**.

Thank you!



Bartunov, S., Kondrashkin, D., Osokin, A., and Vetrov, D. (2016).

Breaking sticks and ambiguities with adaptive skip-gram.
In Artificial Intelligence and Statistics, pages 130–138.



Biemann, C., Faralli, S., Panchenko, A., and Ponzetto, S. P. (2018).

A framework for enriching lexical semantic resources with distributional semantics.

In Journal of Natural Language Engineering, pages 56–64.
Cambridge Press.



Faralli, S., Panchenko, A., Biemann, C., and Ponzetto, S. P. (2016).

Linked disambiguated distributional semantic networks.
In International Semantic Web Conference, pages 56–64.
Springer.



Panchenko, A., Faralli, S., Ponzetto, S. P., and Biemann, C. (2017a).

Using linked disambiguated distributional networks for word sense disambiguation.

In Proceedings of the 1st Workshop on Sense, Concept and Entity Representations and their Applications, pages 72–78, Valencia, Spain. Association for Computational Linguistics.



Panchenko, A., Marten, F., Ruppert, E., Faralli, S., Ustalov, D., Ponzetto, S. P., and Biemann, C. (2017b).

Unsupervised, knowledge-free, and interpretable word sense disambiguation.

In Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing: System Demonstrations, pages 91–96, Copenhagen, Denmark. Association for Computational Linguistics.



Panchenko, A., Ruppert, E., Faralli, S., Ponzetto, S. P., and Biemann, C. (2017c).

Unsupervised does not mean uninterpretable: The case for word sense induction and disambiguation.

In Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics, Volume 1

Long Papers, pages 86–98, Valencia, Spain. Association for Computational Linguistics.



Panchenko, A., Ustalov, D., Faralli, S., Ponzetto, S. P., and Biemann, C. (2018).

Improving hypernymy extraction with distributional semantic classes.

In *Proceedings of the LREC 2018*, Miyazaki, Japan. European Language Resources Association.



Pelevina, M., Arefiev, N., Biemann, C., and Panchenko, A. (2016).

Making sense of word embeddings.

In *Proceedings of the 1st Workshop on Representation Learning for NLP*, pages 174–183, Berlin, Germany. Association for Computational Linguistics.



Remus, S. and Biemann, C. (2018).

Retrofitting word representations for unsupervised sense aware word similarities.

In *Proceedings of the LREC 2018*, Miyazaki, Japan. European Language Resources Association.



Rothe, S. and Schütze, H. (2015).

Autoextend: Extending word embeddings to embeddings for synsets and lexemes.

In Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 1793–1803, Beijing, China. Association for Computational Linguistics.