



BCS2000K-C-HUD/T2 Datasheet

BCS2000K-C-HUD/T2 Datasheet

I. Appearance



II. Overall Configuration

Device	Model	Quantity
PCS	BCS1000K-C-HUD	2
Transformer	SL-2000	1
RMU	DCV	1
AUX power cabinet	5kVA	1
Container	20ft	1

III. Datasheet

PCS*2	
Model	BCS1000K-C-HUD
DC input	
Max. DC voltage	1500Vdc
Full load DC voltage range	1060-1500Vdc
Max. DC current	1122A
Soft start	Yes
AC output (On-grid)	
Rated AC output power	1000kW
Max. AC output power	1100kVA
Rated grid-tied voltage	690Vac, 3P3W+PE
Grid voltage range	-15%~10% (settable)
Grid frequency	50Hz
Max. output current	920.4A
Power factor	>0.99 (at rated power)
Adjustable power factor	1 (leading)~1 (lagging)
THDi	<3% (at rated power)
AC output (Off-grid)	
Rated AC output voltage	690Vac

Output voltage accuracy	1%
Max. output current	920.4A
THDu	<3% (liner load)
Rated output frequency	50Hz
Overload capability	110% overload
PCS efficiency	
Max. efficiency	≥99%
General data	
Isolation mode	None
IP rating	IP65
Operation temperature	-35° C~60° C (>50° C derating)
Relative humidity	0~100% (no-condensing)
Cooling type	Intelligent air cooling
Dimensions (W*H*D)	735*2135*1300mm
Weight	About 950kg
Altitude	4000m (>2000m derating)
Display	LED
Communication protocol	Modbus-RTU, Modbus-TCP, IEC61850, IEC104
Communication interface	RS485, CAN, Ethernet
Compliance	EN/IEC 62477-1, EN/IEC 61000-6-2, EN50549-2/10, IEC62116, IEC61727, IEC60068-2-1/2/14/30
MV Transformer*1	
Model	SL-2000
Type	Oil immersed
Rated power(kVA)	2000@ 40°C
Rated frequency(Hz)	50
Vector group	Dy11 two winding
Rated voltage(kV)	0.69kV/(6-35)kV
Tap changer	0, ± 2x2.5%
Minimum Peak Efficiency Index	Tier2
IP Grade	IP68@oil tank
Altitude(m)	≤1000
Ambient temperature(°C)	-25~40
Ambient humidity	0~100%
Insulation level	A
Material of winding	Aluminum
Oil-temperature Alarm	YES
Oil-temperature Trip	YES
Oil level Alarm	YES
Oil level Trip	YES
RMU*1	
Rated voltage(kV)	12/24/40.5

Rated current(A)	630
Scheme	DCV
Insulation type	SF6(SF6-free optional)
Protection	
Oil-temperature Alarm	YES
Oil-temperature Trip	YES
Oil level Alarm	YES
Oil level Trip	YES
Protection relay	50/51, 50N/51N
AUX power cabinet*1	
Auxiliary transformer	
Type	Dry type
Rated power	5kVA
Rated frequency	50Hz
Vector group	Dyn11
Rated voltage	690V/400V
SPD	YES, Type II on 400V bus
Short-circuit impedance	4%
Cooling method	Air cooling
Altitude	≤1000m
Ambient temperature	-25~45℃
UPS	
Rated power	3kVA
Rated frequency	50Hz
Rated voltage	230V
Power factor	0.9
Cooling method	Air cooling
General	
IP Grade	IP 54
Humidity	0~100% (no-condensing)
Operating temperature range(℃)	-35℃~60℃(> 45℃ derating)
Dimension(mm)	6058L*2438W*2896H
Weight(t)	<13000kg

- END -

XIAMEN KEHUA DIGITAL ENERGY TECH CO.,LTD
ADD: ROOM 208-38, HENGYE BUILDING, NO.100 XIANGXING ROAD, TORCH
HIGH-TECH ZONE (XIANGAN) INDUSTRIAL ZONE, XIAMEN,CHINA
Tel: +86-592-5160516
Fax: +86-592-5162166
Email: Intertrade@kehua.com