

1500Vdc Containerized Energy Storage & Transformer Turnkey System

BCS4000K~5000K-C-HUD/T4 Series



Safe

- On-line insulation detection
- Adapt to extreme environment, such as high temperature, salt, and extreme cold etc.
- Real-time transformer condition monitoring



Smart

- Grid forming technology, providing extra inertial support.
- Millisecond-level power response, stable power grid operation.
- Multiple functions, including Black-Start and VSG etc.



Simple

- Integrated design of converter and transformer system, integrated system, Integrated data acquisition and optic fiber network.
- Wide DC voltage operation range, flexible configuration.
- Adapt to multiple scenarios, including power generation side, grid side and user side application, supporting multi-device parallel.



Technical Specification

Items	BCS4000K-C-HUD/T4		BCS5000K-C-HUD/T4	
DC input				
Max. DC voltage	1500Vdc			
DC voltage range	1000-1500Vdc			
Max. DC current	1122A*4		1403A*4	
Soft start	Yes			
AC output (On-grid)				
Rated AC output power	4000kW		5000kW	
Max. AC output power	4400kVA		5500kVA	
Rated grid-tied voltage	690Vac 3P3W+PE			
Grid voltage range	-15%~10% (settable)			
Grid frequency range	50/60Hz			
Max. output current	3682A		4602A	
Power factor	>0.99 (at rated power)			
Adjustable power factor	1 (leading)~1 (lagging)			
THDi	<3% (at rated power)			
AC output (Off-grid)				
Rated AC output voltage	690Vac			
Output voltage accuracy	1%			
Max. output current	3682A		4602A	
THDu	<3% (liner load)			
Rated output frequency	50/60Hz			
Overload capability	110% overload			
PCS efficiency				
Max. efficiency	99%*			
Transformer				
Rated power	4000kVA		5000kVA	
Voltage transformation ratio	0.69/(6~33)kV (Can be customized)			
Isolation mode	oil-immersed transformer			
General data				
IP rating	IP65(PCS) IP54(Skid)			
Operation temperature	-35°C~60°C (>45°C derating)			
Relative humidity	0~100% (no-condensing)			
Cooling type	Intelligent air cooling			
Dimensions (W×H×D)	12192×2896×2438mm			
Weight	27000kg		28000kg	
Altitude	2000m (>1000m derating)			
Display	LED			
Communication protocol	Modbus-RTU, Modbus-TCP, IEC61850, IEC104			
Communication interface	RS485, CAN, Ethernet			

- * This efficiency value was measured in a laboratory environment.
- * Specification indexes may be subject to changes without further notice

XIAMEN KEHUA DIGITAL ENERGY TECH CO.,LTD.

Add: Room 208 - 38, Hengye Building, No. 100 Xiangxing Road, Torch High-tech Zone (Xiang'an) Industrial Zone, Xiamen, China(361000)

Tel: +86-592-5160516

Fax: +86-592-5162166

Email: Intertrade@kehua.com

Web: www.kehua.com

