



Product Service

Attestation of Conformity

No. N8A 115067 0075 Rev. 00**Holder of Attestation: Xiamen Kehua Digital Energy Tech Co., Ltd.**

Room 208-38, Hengye Building
No. 100 Xiangxing Road
Torch High-tech Zone
(Xiang'an) Industrial Zone
361115 Xiamen
PEOPLE'S REPUBLIC OF CHINA

Product: Converter

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290253032801**Date,** 2025-08-07

(Billy Qiu)

Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. N8A 115067 0075 Rev. 00

Model(s): BCS1250K-C-HUD, BCS1000K-C-HUD

Parameters:

Model:	BCS1000K-C-HUD	BCS1250K-C-HUD
Battery terminal parameters:		
Battery type	Lithium or lead-acid	
Maximum voltage [Vd.c.]	1500	
Rated voltage [Vd.c.]	1250	
Battery voltage range [Vd.c.]	1000-1500	
Maximum charging power [kW]	1078	1347.5
Maximum discharging power [kW]	1122.4	1403
Maximum continuous charging current [Ad.c.]	1078	1347.5
Maximum continuous discharging current [Ad.c.]	1122.4	1403
AC parameters:		
Rated voltage [Va.c.]	690, 3W+PE	
Rated frequency [Hz]	50/60	
Maximum apparent power [kVA]	1100	1375
Maximum active power [kW]	1100	1375
Maximum continuous current [Aa.c.]	920.5	1150.6
Power factor range	0 under-excited to 1 to 0 over-excited	
General		
Operating temperature range [°C]	-40~60	
Protective class	Class I	
Ingress protection	IP65 (except air duct)	

**Tested
according to:**

EN 62477-1:2012/A12:2021
EN 62109-1:2010
EN 62109-2:2011

Page 2 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.