

FABER® dataline fibre optic cable A-DQ(ZN)B2Y ... 1.2 kN (Zentralader) acc. to ISO/IEC 794, DIN VDE 0888



Fibre type:	singlemode
Fibre quality:	see data sheet for fibres on our website
Type of tube:	gel-filled loose tube
Cable metal-free:	yes
Sheathing material:	polyethylene
Meter mark:	yes
Flame-retardant:	no
Permitted outer cable temperature, fixed:	-20 - +70 °C
Permitted outer cable temperature, in motion/ during installation:	-5 - +50 °C
Type of installation:	Installation pipe (Multiple cables installation)

Application: Fibre optic cable with central tubes and non-metallic armour, strain relief and rodent protection. Swelling elements within the strand ensure longitudinally watertightness of the cable. The rugged and abrasion-resistant PE-sheath enables easy installation in tubes and ducts. The sheath is halogen-free, but not flame-retardant.



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

Table: Technical characteristics A-DQ(ZN)B2Y 1.2 kN (Central core)

p/n	part name	D _A [mm]	F _{ZV} [N]	E _v [kWh/m]	G [kg/km]	R _{bz} [mm]	R _b [mm]	F _g [N]
071211	A-DQ(ZN)B2Y 01X12E9/125 SW 1,5 kN	7			40			
071112	A-DQ(ZN)B2Y 01X4G50/125 SW 1,2 kN Standard	6	1200	90	43	160	140	100
071060	A-DQ(ZN)B2Y 01X8G50/125 SW 1,5 kN Standard	6	1200	90	43	160	140	100
070682	A-DQ(ZN)B2Y 01X12G50/125 SW 1,2 kN Standard	6	1200	90	43	160	140	100
070683	A-DQ(ZN)B2Y 01X24G50/125 SW 1,2 kN Standard	7	1200	120	59	160	140	100

DA	Outer diameter approx.
Fzv	Tensile strength (during installation)
Ev	Combustion heat (fire load)
G	weight
Rbz	Bending radius with tension load
Rb	Bending radius without tension load
Fq	Crush resistance