

1500Vdc Energy Storage Converter

BCS1000K~1250K-C-HUD Series



Safe

- On-line insulation detection
- Adapt to extreme environment, such as high temperature (50°C without derating), salt, and extreme cold etc.
- Noise $\leq 75\text{dBA}$, better protecting the hearing of operation and maintenance personnel.



Smart

- Support multi-machine parallel connection & black-start
- H/LVRT function, high adaptation ability to the grid
- Various applications such as peak shaving, frequency modulation, auxiliary grid connection for new energy system, etc.



Simple

- Efficient layout to improve space utilization
- Secondary circuit integration, unified measurement, protection and communication



Technical Specification

Items	BCS1000K-C-HUD	BCS1250K-C-HUD
DC input		
Max. DC voltage	1500Vdc	
DC voltage range	1000-1500Vdc	
Max. DC current	1122A	1403A
Soft start	Yes	
AC output (On-grid)		
Rated AC output power	1000kW	1250kW
Max. AC output power	1100kVA	1375kVA
Rated grid-tied voltage	690Vac 3P3W+PE	
Grid voltage range	-15%~10% (settable)	
Grid frequency range	50/60Hz	
Max. output current	920.4A	1150.6A
Power factor	>0.99 (at rated power)	
Adjustable power factor	1 (leading)~1 (lagging)	
THDi	<3% (at rated power)	
AC output (Off-grid)		
Rated AC output voltage	690Vac	
Output voltage accuracy	1%	
Max. output current	920.4A	1150.6A
THDu	<3% (liner load)	
Rated output frequency	50/60Hz	
Overload capability	110% overload	
PCS efficiency		
Max. efficiency	99%*	
General data		
IP rating	IP65	
Operation temperature	-35°C~60°C (>50°C derating)	
Relative humidity	0~100% (no-condensing)	
Cooling type	Intelligent air cooling	
Dimensions (W×H×D)	735×2135×1300mm	
Weight	950kg	
Altitude	4000m (>2000m derating)	
Display	LED	
Communication protocol	Modbus-RTU, Modbus-TCP, IEC61850, IEC104	
Communication interface	RS485, CAN, Ethernet	
Compliance	EN/IEC 62477-1,EN/IEC 61000-6-2,EN50549-2/10,IEC62116,IEC61727,IEC60068-2-1/2/14/30, EN55011	

- *This efficiency value was measured in a laboratory environment.
- * Specification indexes may be subject to changes without further notice

XIAMEN KEHUA DIGITAL ENERGY TECH CO.,LTD.

Add: Room 208 - 38, Hengye Building, No. 100 Xiangxing Road, Torch High-tech Zone
(Xiang'an) Industrial Zone, Xiamen, China(361000)

Tel: +86-592-5160516

Fax: +86-592-5162166

Email: Intertrade@kehua.com

Web: www.kehua.com

