



Product Service

Attestation of Conformity

No. E8A 115067 0072 Rev. 00

Holder of Attestation: **Xiamen Kehua Digital Energy Tech Co., Ltd.**

Room 208-38, Hengye Building
No. 100 Xiangxing Road
Torch High-tech Zone
(Xiang'an) Industrial Zone
361115 Xiamen
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Converter
(Energy Storage Converter)**

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 64772253033701

Date, 2025-06-26

(Samuel Zhang)

Page 1 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. E8A 115067 0072 Rev. 00

Model(s): BCS1000K-C-HUD, BCS1250K-C-HUD

Description of Object:

Model:	BCS1000K-C-HUD	BCS1250K-C-HUD
Battery input / output terminal parameters:		
Battery type	Lithium or lead-acid	Lithium or lead-acid
Maximum voltage [Vd.c.]	1500	1500
Rated voltage [Vd.c.]	1250	1250
Battery voltage range [Vd.c.]	1000-1500	1000-1500
Maximum charging power [kW]	1078	1347.5
Maximum discharging power [kW]	1122.4	1403
Maximum continuous charging current [Ad.c.]	1078	1347.5
Maximum continuous discharging current [Ad.c.]	1122.4	1403
AC input parameters:		
Maximum input apparent power [kVA]	1100	1375
Maximum input active power [kW]	1100	1375
Rated input voltage [Va.c.]	3P3W, 690	3P3W, 690
Maximum continuous input current [Aa.c.]	920.5	1150.6
Rated input frequency [Hz]	50/60	50/60
AC output parameters:		
Rated output voltage [Va.c.]	3P3W, 690	3P3W, 690
Rated output frequency [Hz]	50/60	50/60
Maximum continuous output current [Aa.c.]	920.5	1150.6
Maximum continuous output active power [kW]	1100	1375
Maximum continuous output apparent power [kVA]	1100	1375
Power factor	1 inductive(under-excited) to -1 capacitive(over-excited)	1 inductive(under-excited) to -1 capacitive(over-excited)
General		
Operating temperature range [°C]	-40~60	-40~60
Protective class	Class I	Class I
Ingress protection	IP65	IP65
Operating altitude range [m]	0~4000	0~4000
Over voltage category	AC: III; DC: II	AC: III; DC: II
Size (W*D*H) [mm]	735*1300*2132.5	735*1300*2132.5
Weight [kg]	950	950
Auxiliary power supply parameters:		
Rated output voltage [Va.c.]	170/230/690	170/230/690
Rated output power [kW]	3	3
Rated input frequency [Hz]	50/60	50/60

Page 2 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. E8A 115067 0072 Rev. 00

Remark:

EN IEC 61000-6-4:2019 for telecommunication/network port only.

The certificate is only valid if no transmitting radio equipment is included in the device (WiFi, 4G, RFID).

Tested

according to:

EN IEC 61000-6-2:2019

EN IEC 61000-6-4:2019

EN 55011:2016/A2:2021

Page 3 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.