MaxQuest

Betsoft Gaming

Version 4.1

1. Lobby Protocol

This document describes the communication protocol between client and the server in the “Max Quest” series of multiplayer games.
Interaction is carried out via websockets in JSON format.
The lobbyUrl and session id of the logged-in user are passed to the client through the http request parameters: lobbyUrl (wss://host:port/websocket/mplobby), sessionId.
Please note, that we recommend to use only secure websocket connections (wss://).
Rooms can be created and deleted by the server as needed, depending on the current number of players.
Type of all identifiers (id, rid, roomid, ..) is long. As some features are game-specific, related fields in other games where not applicable should be ignored.

1.1 Error handling

In response to any client request may come an error message like this:

```
{
  "code": 1,
  "msg": "Internal error",
  "date": 1496748898812,
  "class": "Error",
  "rid": 1
}
```

```
{
  "code": 2,
  "msg": "Server shutdown",
  "date": 1496748898812,
  "class": "Error",
  "rid": -1
}
```

Request parameters:

code

error code

msg

error description (may be localized)

date

datetime in msec. from 01.01.1970 (standart unix timestamp)

class

message class

rid

request Id, type is int. Optional parameter, if not -1 this parameter contains id of original request.

Possible error ranges

1-999

FATAL ERROR

1000-4999

ERROR

5000-9999

WARNING

Full list of error codes could be found in section 4

Handling 'FATAL ERROR':

Display message to user and close lobby.

Handling Lobby Websocket errors:

In case of websocket error, you must re-establishing websocket connection to lobbyUrl and send 'Enter Lobby' request.

1.2 Enter Lobby

This request is a first request which should be send by the client after establishing websocket connection to lobby. After that request, the client will be subscribed to receive asynchronous events: BalanceUpdated

```
{
  "sid": "4_eb0bf169cbb477b6f8430000015cbe83_fwRFDR4FWFZTV142PiQUCQ4H",
  "date": 1496750162302,
  "class": "EnterLobby",
  "rid": 1,
  "serverId": 1,
  "lang": "en",
  "mode": "real",
  "noFRB": false,
  "gameId": 779,
  "tournamentId": 123444,
  "bonusId": 56767,
  "battlegroundBuyIn": 100,
  "continueIncompleteRound": false
}
```

Request parameters:

sid

session identifier (send as request parameter on start lobby client)

rid

unique request id

serverId

serverId for connect (send as request parameter on start lobby client)

mode

money type: free, real, bonus

gameId

game identifier (send as request parameter on start lobby client)

noFRB

true if server should ignore active FRBs

tournamentId

tournament identifier, optional. (send as request parameter on start lobby client for tournament play)

bonusId

cash bonus identifier, optional, not null only for cash bonus mode (send as request parameter on start lobby client)

battlegroundBuyIn

selected buyIn amount for battleground mode

continueIncompleteRound

true when trying launch incomplete btg round

If session not found, invalid or expired server return

```
{
"code": 3,
"msg": "Invalid session",
"date": 1496750162288,
"class": "Error",
"rid": 1
}
```

If selected nickname contains an obscene word, server return:

```
{
  "code": 1000,
  "msg": "Illegal nickname",
  "date": 1496750162288,
  "class": "Error",
  "rid": 1
}
```

If session exist and enter to lobby is success, server return:

```
{
  "players": 600,
  "nickname": "Taras70",
  "nicknameEditable": true,
  "balance": 20000,
  "currency": { "code": "USD", "symbol": "$" },
  "rankPonts": 200,
  "roomId": 20,
  "level": 5,
  "avatar": {"borderStyle": 1, "hero": 1, "background": 2},
  "borders": [0, 1, 2, 3],
  "heroes": [0, 1, 2, 3],
  "backgrounds": [0, 1, 2, 3],
  "stakes": [2.0, 5.0, 10.0, 25.0, 50.0, 100.0],
  "paytable": {
    "enemyPayouts": [
      {
        "idEnemy": 0,
        "nameEnemy": "Scarab black",
        "prize": { "minPayout": 10, "maxPayout": 20 }
      },
      {
        "idEnemy": 4,
        "nameEnemy": "Medium Mummy A",
        "prize": { "minPayout": 30, "maxPayout": 40 }
      }
    ],
    "energyBoss": 48,
    "lootboxPrizes": [
      {
        "number": 0,
        "prizes": [
          {
            "weaponId": 0,
            "min": 30,
            "max": 40
          },
          {
            "weaponId": 1,
```

```
            "min": 6,
            "max": 8
          }
        ]
      }
    ],
    "weaponPaidMultiplier": [
    ],
    "gemPayouts":{
      "0": [25, 30, 40],
      "1": [20, 25, 30],
      "2": [15, 18, 20],
      "3": [10, 12, 15]
    },
    "healthByLevels":{
      "0": [1200, 1350, 1500],
      "1": [180, 200, 220],
      "2": [450, 475, 500],
      "3": [280, 300, 320],
      "10": [400, 450, 500],
      "11": [1000, 2500, 5000]
    },
    "enemyPayoutsByWeapon":{
      "0": {
        "0": {"minPayout": 30, "maxPayout": 150},
        "1": {"minPayout": 15, "maxPayout": 100}
      },
      "1": {
        "0": {"minPayout": 20, "maxPayout": 170},
        "1": {"minPayout": 5, "maxPayout": 200}}
      }
    },
    "possibleBetLevels": [1, 2, 3, 5, 10],
    "moneyWheelPayouts": [25, 50, 100, 250, 500, 1000, 2000],
    "reels": {
      "1": [1, 4, 3, 5, 2, 4, 5],
      "2": [1, 5, 4, 2, 3, 4, 5],
      "3": [1, 4, 2, 5, 3, 4, 5]
    }
  },
  "frBonusInfo": {
    "id": 23142,
    "awardDate": 1533284885209,
    "expirationDate": 1533294885209,
    "totalShots": 500,
    "currentShots": 350,
    "winSum": 20000,
    "stake": 1
  },
  "cashBonusInfo": {
    "id": 23142,
```

```
    "awardDate": 1533284885209,
    "expirationDate": 1533294885209,
    "balance": 1000,
    "amount": 10000,
    "amountToRelease": 200,
    "status": "ACTIVE"
  },
  "tournamentInfo": {
    "id": 23142,
    "name": "New Year's tournament",
    "state": "ACTIVE",
    "startDate": 1533284885209,
    "endDate": 1533284885209,
    "balance": 10000,
    "buyInPrice": 1000,
    "buyInAmount": 10000,
    "reBuyAllowed": true,
    "reBuyPrice": 500,
    "reBuyAmount": 10000,
    "reBuyCount": 1,
    "reBuyLimit": -1,
    "resetBalanceAfterRebuy": false
  },
  "battlegroundInfo": {
     "buyIns": [100, 200, 500, 1000, 2000, 5000],
     "alreadySeatRoomId": 200133,
     "startGameUrl":
"https://host/websocket/mpgame?SID=3453&serverId=1&lang=en&roomId=200133",
     "roomState": "WAIT",
     "buyInConfirmed": true
   }
  "showRefreshBalanceButton": true,
  "kills": 100,
  "treasures": 20,
  "rounds": 15,
  "xp": 123,
  "xpPrev": 100,
  "xpNext": 200,
  "place": 10,
  "disableTooltips": false,
  "needStartBonus": false,
  "nicknameGlyphs": "abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ1234567890",
  "stakesReserve": 300,
  "stakesLimit": 100,
  "alreadySitInStake": 2.0,
  "disableLeaderboard": false,
  "weaponMode": "LOOT_BOX",
  "date": 1496908464148,
  "date": 1587381071243,
  "rid": 1,
  "class": "EnterLobbyResponse"
```

```
}
```

Response parameters:

players

total players logged in lobby

nickname

player nickname, For new player nickname is null. See 'CheckNicknameAvailability' and 'ChangeNickName' requests.

nicknameEditable

true if nickName may be changed, see ChangeNickname request

balance

current player balance in cents (this is casino side balance, ALL available money). For tournament/cashbonus modes equals to tournament.balance and cashbonus.balance

currency

player currency. Further in this document, all money in player currency

rankPoints

total number of points received by the player, see 4.3 section is spec.

avatar:borderStyle

current avatar borderStyle identifier.

avatar:hero

current avatar hero identifier.

avatar:background

current avatar background identifier.

stakes

list stakes (cost per shot) available to player

borders, heroes, backgrounds

- list available avatar parts, see 'ChangeAvatar' request for customize avatar properties.

paytable

paytable for enemies.

bossExtraPayoutsSpecial

Prizes for special weapons at boss.

level

Current player’s level

rid

unique request id

roomId

roomId if player already seat in room; -1 if not. If a player occupies a place in a room, the lobby client must prompt the player to continue the game. If the player agrees, the game is started for the given room (send request “GetStartGameUrl” and open game client window)

frBonusInfo

FRB only parameter, always null for real/free/cashbonus/tournament.

cashBonusInfo

CashBonus only parameter, always null for real/free/frbonus/tournament.

cashBonusInfo:balance

current balance. Shots reduce balance, wins increase

cashBonusInfo:amount

initial bonus balance

cashBonusInfo:amountToRelease

amount of bets required to release the bonus

cashBonusInfo:status

current bonus status (ACTIVE, RELEASED, LOST, CANCELLED, EXPIRED, CLOSED)

tournamentInfo

tournament only parameter, always null for real/free/frbonus/cashbonus

tournamentInfo:id

unique tournament identifier

tournamentInfo:name

tournament name (may be localized)

tournamentInfo:state

current tournament status (READY, ACTIVE, FINISHED, CANCELED)

tournamentInfo:balance

current player balance in tournament

tournamentInfo:buyInPrice

price of participation in tournament

tournamentInfo:buyInAmount

amount of tournament money which player receives at start of tournament

tournamentInfo:reBuyAllowed

flag indicating that re-buys allowed

tournamentInfo:reBuyPrice

price of purchase of additional tournament money

tournamentInfo:reBuyAmount

amount of tournament money which player receives after re-buy

tournamentInfo:reBuyCount

current re-buys count

tournamentInfo:reBuyLimit

re-buys limit, (-1 for unlimited)

tournamentInfo:resetBalanceAfterRebuy

after re-buy all balance reset to re-buy amount

disableTooltips

enabled/disabled tooltips for player. (see 'ChangeToolTips' request)

stakesReserve

number of stakes to be transferred from balance

stakesLimit

limit of stakes after which you need to make additional buyIn

alreadySitInStake

stake if player seat in room (see roomId), 0 if not.

disableLeaderboard

booleader flag, if true - leaderboard functionality in client should be disabled

needStartBonus

true/false, this is welcome bonus for first start game. Player receives a special weapon as a gift

nicknameGlyphs

symbols which could be used for nicknames

weaponMode

LOOT_BOX or PAID_SHOTS

enemyPayoutsByWeapon

map of min/max payouts by weapons for all enemies. keys are enemyTypeId(first), weaponId(second).

reels

in DragonStone order of symbols on reels

battlegroundInfo

info about available battlegrounds

battlegroundInfo:buyIns

buyIns available

battlegroundInfo:alreadySeatRoomId

roomId if the player already has incomplete (paid) battleground round

battlegroundInfo:startGameUrl

url must be used for start game client. If this parameter specified, need immediate open client (see specification about explanatory message before open).

battlegroundInfo:roomState

room state if player open room, possible values: WAIT, PLAY, QUALIFY, CLOSED

battlegroundInfo:buyInConfirmed

buyIn confirmed and room open

1.3 CheckNicknameAvailability

After entering the lobby, the player must choose a nickname that will be visible to all other players. To check whether the selected nickname is available, this request is available.

```
{
  "nickname": "Taras",
  "date": 1531731629785,
  "rid": 234,
  "class": "CheckNicknameAvailability"
}
```

Success response:

```
{
  "date": 1531731629785,
  "rid": 1,
  "class": "Ok"
}
```

Error responses:

```
{
  "code": 1015,
  "msg": "Nickname not available",
  "date": 1531731629785,
  "rid":1,
  "class": "Error"
}
{
  "code": 1000,
  "msg": "Illegal nickname",
  "date": 1531731629785,
  "rid": 1,
  "class": "Error"
}
```

1.4 ChangeNickname

```
{
  "nickname": "Taras",
  "date": 1531731629785,
  "rid": 234,
  "class": "ChangeNickname"
}
```

Success response:

```
{
  "date": 1531731629785,
  "rid": 1,
  "class": "Ok"
}
```

Error responses:

```
{
  "code": 1016,
  "msg": "Nickname not available",
  "date": 1531731629785,
  "rid": 1,
  "class": "Error"
}
{
  "code": 1000,
  "msg": "Illegal nickname",
  "date": 1531731629785,
  "rid": 1,
  "class": "Error"
}
{
  "code": 1028,
  "msg": "Not allowed change nickname",
  "date": 1531731629785,
  "rid": 1,
  "class": "Error"
}
```

1.5 ChangeAvatar

```
{
  "borderStyle": 1,
  "hero": 2,
  "background": 3,
  "date": 1531731629785,
  "rid": 234,
  "class": "ChangeAvatar"
}
```

Success response:

```
{
  "date": 1531731629785,
  "rid": 1,
  "class":
  "Ok"
}
[source,json]
.Error responses:
{
  "code": 1017,
  "msg": "Avatar part not available",
  "date": 1531731629785,
  "rid": 1,
  "class": "Error"
}
```

1.6 GetRoomInfo

When the user selects a particular game room, the client requests the server for detailed information about the selected room by a request like:

```
{
  "roomId": 1,
  "rid": 5,
  "date": 1496921495447,
  "class": "GetRoomInfo"
}
```

Request parameters:

roomId

unique room id

rid

unique request id

Response:

```
{
  "roomId": 1,
  "name": "VIP#1",
  "maxSeats": 8,
  "minBuyIn": 10000,
  "stake": 0.1,
  "playerStake": 0.05,
  "state": "WAIT",
  "seats": [
```

```
    {
      "id": 1,
      "nickname": "Taras",
      "enterDate": 1497004331679,
      "totalScore": 700,
      "currentScore": 10,
      "avatar": {
        "borderStyle": 1,
        "hero": 1,
        "background": 10
      },
      "specialWeaponId": 1,
      "level": 2,
      "unplayedFreeShots": 0,
      "totalDamage": 100,
      "betLevel": 1
    },
    {
      "id": 2,
      "nickname": "Bulba",
      "enterDate": 1497004331679,
      "totalScore": 230,
      "currentScore": 15,
      "avatar": {
        "borderStyle": 1,
        "hero": 1,
        "background": 10
      },
      "specialWeaponId": 2,
      "level": 3,
      "unplayedFreeShots": 0,
      "totalDamage": 0,
      "betLevel": 10
    },
    {
      "id": 3,
      "nickname": "Mikola",
      "enterDate": 1497004331679,
      "totalScore": 10,
      "currentScore": 5,
      "avatar": {
        "borderStyle": 1,
        "hero": 1,
        "background": 10
      },
      "specialWeaponId": 3,
      "level": 4,
      "unplayedFreeShots": 10,
      "totalDamage": 245,
      "betLevel": 5
    }
```

```
  ],
  "ttnx": 7,
  "width": 800,
  "height": 600,
  "enemies": [
    {
      "id": 1,
      "width": 10,
      "height": 30,
      "speed": 10,
      "prizes": 3,
      "sumAward": 6,
      "skins": 1,
      "boss": false
    },
    {
      "id": 2,
      "width": 15,
      "height": 40,
      "speed": 70,
      "prizes": 4,
      "sumAward": 0,
      "skins": 2,
      "boss": true
    }
  ],
  "roomEnemies": [
    {
      "id": 18684,
      "typeId": 1,
      "speed": 10.0,
      "awardedPrizes": "",
      "awardedSum": 0.0,
      "energy": 0,
      "fullEnergy": 100.0,
      "skin": 1,
      "trajectory": [
        { "x": 10, "y": 50, "time": 120 },
        { "x": 20, "y": 30, "time": 150 }
      ],
      "parentEnemyId": -1,
      "members": [],
      "swarmId": 0,
      "swarmType": 0
    },
    {
      "id": 18693,
      "typeId": 8,
      "speed": 10.0,
      "awardedPrizes": "",
      "awardedSum": 0.0,
```

```
      "energy": 0,
      "fullEnergy": 100.0,
      "skin": 1,
      "trajectory": [
        { "x": 15, "y": 40, "time": 120 },
        { "x": 25, "y": 70, "time": 190 }
      ],
      "parentEnemyId": -1,
      "members": [],
      "swarmId": 1,
      "swarmType": 3
    }
  ],
  "alreadySitInNumber": -1,
  "alreadySitInAmmoCount": 0,
  "alreadySitInBalance": 0,
  "alreadySitInWin": 0.25,
  "mapId": 1,
  "subround": "BASE",
  "ammoValues": [100, 200, 500, 1000, 2000, 5000, 10000, 20000, 50000, 1000000],
  "mines": [],
  "freezeTime": {},
  "immortalBoss": false,
  "roundId": 450122,
  "seatGems": {},
  "cashBonusInfo": {
    "id": 23142,
    "awardDate": 1533284885209,
    "expirationDate": 1533294885209,
    "balance": 1000,
    "amount": 10000,
    "amountToRelease": 200,
    "status": "ACTIVE"
  },
  "tournamentInfo": {
    "id": 23142,
    "name": "New Year's tournament",
    "state": "ACTIVE",
    "startDate": 1533284885209,
    "endDate": 1533284885209,
    "balance": 10000,
    "buyInPrice": 500,
    "buyInAmount": 10000,
    "reBuyAllowed": true,
    "reBuyPrice": 500,
    "reBuyAmount": 100000,
    "reBuyCount": 1,
    "reBuyLimit": -1,
    "resetBalanceAfterRebuy": false
  },
  "battlegroundInfo" {
```

```
    "buyIn" : 1000,
    "buyInConfirmed": true,
    "timeToStart" : 30,
    "kingsOfHill": [1,2,3],
    "score": 4620,
    "rank" : 3,
    "pot": 3960,
    "potTaxPercent": 5
  },
  "betLevel": 1,
  "date": 1497004331658,
  "rid": 5,
  "class": "GetRoomInfoResponse"
}
```

Where:

rid

request id from “GetRoomInfo”

roomId

unique room id

name

room name

maxSeats

max seats in room

minBuyIn

minimal buyIn in cents for occupy seat (type – float)

stake

room stake (shot cost) in cents (type – float). This just stake limit.

playerStake

player stake (shot cost) in cents (type – float). Always in player currency. If player not seater, playerStake=-1

state

current room state. Possible values: WAIT, PLAY, QUALIFY, CLOSED

ttnx

rough time to next state in seconds, -1 for unknown (ttnx -Time To NeXt).

mapId

current map identifier

width

virtual width of the playing area

height

virtual height of the playing area

alreadySitInNumber

seat number; -1 if player not seat in room;

alreadySitInAmmoAmount

current ammo amount if player seat in room; 0 if player not seat

alreadySitInBalance

current player balance if player seat in room; 0 if player not seat

alreadySitInWin

player's win in current round

seats

list of players who have taken their seat and ready to play (or already playing)

enemies

list of enemy types that can appear in this room.

roomEnemies

list of alive enemies in this room. Please do not jumble it, "roomEnenemies" are specific instances, but "enemies" are the types of the enemies.

weapons

list of weapons available in the room

seat:id

seat number, may be 0...(maxSeats-1)

seat:nickname

seat nickname

seat:avatar

seat avatar

seat:enterDate

date when the player started the game

seat:totalScore

total number of points awarded player in this room (total win = totalScore*stake), type=integer

seat:currentScore

number of points awarded player for current round (currentWin = currentScore*stake), type=integer

seat:rankPoints

total number of points received by the player, see 4.3 section is spec.

enemy:id

unique enemy type identifier

enemy:name

enemy name

enemy:width,height

rectangle in which should be placed enemy

enemy:speed

max speed in points/sec.

enemy:prizes

number of prizes available for this type of enemy

enemy:sumAward

total awarded ponts available for this type of enemy (real win = sumAward*stake)

enemy:energy

Boss only property (can be used to identify the boss). Total points available for this boss. Each energy point represents 1 credit.

enemy:skins

skins count available for this enemy.

enemy:boss

flag indicating that this enemy is the boss; when this enemy type appears, you need remove the special weapon and use regular weapon.

roomEnemy:id

unique enemy identifier

roomEnemy:typeid

enemy type identifier (reference to enemy.id)

roomEnemy:awardedPrizes

prizes (list!) received from hitting the enemy. May be empty if no hits.

roomEnemy:awardedSum

amount of points received from hits to the enemy

roomEnemy:energy

remaining energy, if energy<0 enemy is dead, remember that energy=0 used for identify regular enemies

roomEnemy:skin

skin number (randomly generated, from 1 to enemy.skins)

roomEnemy:trajectory

Trajectory (set of points) along which enemies move

roomEnemy:trajectory:x, y

current x/y coordinate (x=0, y=0 for bottom left corner)

roomEnemy:trajectory:time

at this time the enemy must be at a given point

ammoValues

possible ammo values for buyIn

cashBonusInfo

same as EnterLobbyResponse.cashBonusInfo

tournamentInfo

same as EnterLobbyResponse.tournamentInfo

betLevel

current player's bet level

battlegroundInfo

battleground info, always null for other modes

battlegroundInfo:buyIn

buyIn amount for join

battlegroundInfo:buyInConfirmed

true if buyIn confirmed by player

battlegroundInfo:timeToStart

time to start next battleground round in seconds

battlegroundInfo:kingsOfHill

Kings of the Hill seat number ids

battlegroundInfo:score

current player score (ath this moment always total win amount)

battlegroundInfo:rank

current player rank

battlegroundInfo:pot

pot amount

battlegroundInfo:potTaxPercent

casino tax percentage of pot amount

1.7 SubscribeRoomInfo

Request removed

1.8 UnsubscribeRoomInfo

Request removed

1.9 GetStartGameUrl

After player double click on any room, lobby client send request to server for obtain url for start game.

```
{
  "roomId": 1,
  "stake": 5,
  "date": 1497154790288,
  "rid": 5,
  "class": "GetStartGameUrl"
}
```

Request parameters:

roomId

unique room id (may be not specified, in this case the room will be selected by the server based on stake param)

stake

selected stake

rid

unique request id Response:

```
{
  "roomId": 5,
  "startGameUrl":
"https://host/mpgameloader.jsp?sid=deb0bf169cbb477b6f8430000015cbe83&serverId=1&roomId
=5&stake=5",
  "date": 1497155412200,
  "rid": 1,
  "class": "GetStartGameUrlResponse"
}
```

Where:

rid

request id from “GetRoomInfo”

roomId

unique room id

startGameUrl

url for start game.

After receiving this response, the client should connect to game room using params from startGameUrl

1.10 CreateRoom

This message is sent by the server after creating a new room

```
{
  "id": 10,
  "date": 1497154444100,
  "rid": -1,
  "name": "VIP#10",
  "seats": 0,
  "maxSeats": 6,
  "minBuyIn": 10000,
  "stake": 0.1,
  "state": "WAIT",
  "ttnx": -1,
  "width": 800,
  "height": 600,
  "mapId": 1,
  "class": "CreateRoom"
}
```

Where:

id

unique room id (type is long)

date

datetime in msec. from 01.01.1970 (standart unix timestamp)

rid

request id, always -1

name

room name

seats

current seats count

maxSeats

max seats in room

minBuyIn

minimal buyIn in cents for occupy seat

stake

cost per shot in cents (type – float)

state

current room state. Possible values: WAIT, PLAY, QUALIFY, CLOSED

ttnx

rough time to next state in seconds, -1 for unknown (ttnx -Time To NeXt).

width

virtual width of the playing area

height

virtual height of the playing area

mapId

current map identifier

class

message class

1.11 RemoveRoom

This message is sent by the server after deleting the room.

```
{
  "id": 10,
  "date": 1497154444100,
  "rid": -1,
  "class": "RemoveRoom"
}
```

Where:

id

unique room id (type is long)

date

datetime in msec. from 01.01.1970 (standart unix timestamp)

rid

request id, always -1

class

message class

1.12 Leaderboards

At any time client can request list of Leaderboards

Request

```
{
  "class": "GetLeaderboards",
  "date": 1496748898812,
  "rid": 1
}
```

Response

```
{
  "class": "Leaderboards",
  "date": 1496748898812,
  "rid": 1,
  "leaderboards": [
    { "id": 1, "start": 140000000000, "end": 141000000000, "awards": 1000 },
    { "id": 2, "start": 141000000000, "end": 142000000000, "awards": 100 }
  ],
  "currentId": 2,
  "previousId": 1
}
```

1.13 Leaderboard Scores

At any time client can request current Leaderboard state

Request

```
{
  "class": "GetLeaderboardScores",
  "date": 1496748898812,
  "rid": 2,
  "leaderboardId": 1,
  "from": 1,
  "to": 6
}
```

Response

```
{
  "class": "LeaderboardScores",
  "date": 1496748898812,
  "rid": 2,
  "leaderboardId": 1,
  "prizePlaces": 5,
  "currency": { "code": "EUR", "symbol": "€" },
  "awards": [
    { "place": 1, "type": "special", "value": "Porsche 911", "name": "Kenny", "score":
1000 },
    { "place": 2, "type": "money", "value": 1000, "name": "Cartman", "score": 800 },
    { "place": 3, "type": "money", "value": 500, "name": "Sten", "score": 700 },
    { "place": 4, "type": "money", "value": 500, "name": "Wendy", "score": 650 },
    { "place": 5, "type": "money", "value": 500, "name": "Kyle", "score": 500 }
    { "place": 6, "name": "Butters", "score": 499 }
  ],
  "totalPlayers": 10000,
  "position": 3
}
```

Note: Leaderboard prize functionality was removed from the game

1.14 LeaderboardPosition

To find position of current player in a leaderboard, client can send following message

Request

```
{
  "class": "GetLeaderboardPosition",
  "date": 1496748898812,
  "rid": 1,
  "leaderboardId": 1
}
```

Response

```
{
  "class": "LeaderboardPosition",
  "date": 1496748898812,
  "rid": 1,
  "leaderboardId": 1,
  "score": {
    "type": "SPECIAL",
    "value": "Porsche 911",
    "place": 1,
    "score": 1000,
    "nickname": "Kenny"
  }
}
```

1.15 BalanceUpdated

This message sent by server side after changing player balance. Balance is checked every 15 seconds on server side.

Response

```
{
  "class": "BalanceUpdated",
  "date": 1496748898812,
  "rid": -1,
  "balance": 1236600,
  "serverAmmo": 293
}
```

1.16 GetLobbyTime

Sended from client each N seconds. N(MQ_TIMER_FREQ) in getParams() in template.jsp.

Request

```
{
  "class": "GetLobbyTime",
  "date": 1496748898812,
  "rid": 10
}
.Response
{
  "class": "LobbyTimeUpdated",
  "date": 1496748898813,
  "rid": 10
}
```

1.18 ChangeToolTips

This message should be send to update Tooltips visibility in player settings

Request

```
{
  "disableTooltips": true,
  "date": 1531731629785,
  "rid": 234,
  "class": "ChangeToolTips"
}
```

This message will be processed without any response

1.19 Active Quests

At any time client can request list of active quests of player

Request

```
{
  "class": "GetQuests",
  "date": 1496748898812,
  "rid": 1
}
[source,json]
.Response
{
  "class": "Quests",
  "date": 1496748898812,
  "rid": 1,
  "quests": [
    {
      "id": 1,
      "type": 1,
      "roomCoin": 5
      "needReset": true,
      "collectAmount": 1,
      "name": "Quest1",
      "progress": {
        "treasures": [
          {"treasureId": 2, "collect": 2, "goal": 3},
          {"treasureId": 1, "collect": 1, "goal": 3},
        ]
      },
      "questPrize": {
        "amount": {
          "from": 50,
          "to": 100
```

```
        },
        "specialWeaponId": 4
      }
    },
    {
      "id": 2,
      "type": 0,
      "roomCoin": 2
      "needReset": false,
      "collectAmount": 2,
      "name": "Quest2",
      "progress": {
        "treasures": [
          { "treasureId": 13, "collect": 1, "goal": 5},
        ]
      },
      "questPrize": {
        "amount": {
          "from": 50,
          "to": 100
        },
        "specialWeaponId": 4
      }
    }
  ]
}
```

Description:

id

unique id of quest.

roomCoin

coin of room. (EUR cents)

desc

description of quest

date

datetime in msec. from 01.01.1970 (standart unix timestamp)

collect/kills

current amount of progress for treasures/enemies.

progress

progress of player. enemies - information about enemies in quest., treasures about treaures.

specialWeaponId

id if special weapon, -1 for prizeType = 0;

Quest Type	Description
0	collect N treasures of specific type. (minor quests, prize - special weapons)
1	collect N treasures of specific type. (major quests, prize - money)

Treasure Id	Name(Ra)	Name(Pirates)	Math
1	GOLDEN_STATUE_OF_THE_SPHYNX	The Tear of Alcyone	prize_1
2	GOLDEN_STATUE_OF_THE_TUTANKHAMUN	The Eye of Cassiopeia	prize_2
3	ONYX_SERVANT_OF_BASTET	The Heart of Betelgeuse	prize_3
4	ONYX_STATUE_OF_THE_PHARAOH	The Soul of Sirius	prize_4
5	GOLDEN_BUST__OF_ANUBIS	Captain’s Hook	prize_5
6	KNIGHT_OF_ANUBIS_BUST	Botswain’s Knife	prize_6
7	SACRED_GOLDEN_PYRAMID	First Mate’s Cutlass	prize_7
8	THE_GOLDEN_BUST_OF_NEFERTITY	Captain’s Pistol	prize_8
9	EAGLE_OF_RUBY_AND_EMERALD	Jeweled Statue	prize_9
10	GARNET_SCARAB_AMULET	The Countess' Necklace	prize_10
11	LAPIS_CUFF_OF_THE_QUEEN	The Governor’s Signet	prize_11
12	THE_JADE_BROOCH	Elaborately Jewelled Goblet	prize_12
13	BRASS_SCARAB_SIGIL	The Golden Guardian of El Dorado	prize_13
14	CARTOUCHE_OF_GOLD_AMULET	Gold Ingots	prize_14
15	JADE_AND_BRASS_VASE	Buccaneer’s Purse	prize_15
16	OFFERING_BOWL_OF_GEMS	Golden Ring	prize_16

1.20 CollectQuest

To collect quest from Lobby (if supported by game logic), client can send following message

```
{
  "id": 1,
  "date": 1496748898812,
  "rid": 10,
  "class": "CollectQuest"
}
```

If player got new level as a result of quest completion, he will receive LevelUpLobby message

```
{
  "seatId": 1,
  "level": 3,
  "xp": 1200,
  "xpPrev": 1000,
  "xpNext": 2000
  "date": 1496748898815,
  "rid": 10,
  "class": "LevelUpLobby"
}
If request processed successfully, client will receive Ok message
```

1.21 GetWeapons

Client can receive amount of player's weapons by sending request GetWeapons

```
{
  "class": "GetWeapons",
  "rid": 11,
  "date": 1587896669683
}
```

Response

```
{
  "weapons": {
    "10.0": [
      {"id": 0, "shots": 0},
      {"id": 1, "shots": 0},
      {"id": 2, "shots": 0},
      {"id": 3, "shots": 0},
      {"id": 4, "shots": 0},
      {"id": 5, "shots": 0},
      {"id": 6, "shots": 5},
      {"id": 7, "shots": 0},
      {"id": 8, "shots": 0},
      {"id": 9, "shots": 0},
      {"id": 10, "shots": 0},
      {"id": 11, "shots": 0}
    ]
  },
  "date": 1587896664560,
  "rid": 11,
  "class": "PlayerWeaponsResponse"
}
```

weapons

map of weapons by coins. id: weapon type id, shots: number of shots.

1.22 TournamentStateChanged

Server sends this message after tournament status changed

```
{
  "id": 323453,
  "oldState": "ACTIVE",
  "newState": "EXPIRED",
  "reason": "Tournament time is up",
  "date": 1531731629785,
  "rid": -1,
  "class": "TournamentStateChanged"
}
```

Where:

id

tournament id

reason

additional info about change state, may be empty.

oldState

READY, ACTIVE

newState

ACTIVE, FINISHED, CANCELED

1.23 BonusStatusChanged

Server sends this message after bonus status changed

```
{
  "id": 345345,
  "type": "FRB",
  "oldStatus": "ACTIVE",
  "newStatus": "FINISHED",
  "reason": "Bonus expired",
  "date": 1531731629785,
  "rid": -1,
  "class": "BonusStatusChanged"
}
```

Where:

id

bonus id

type

bonus type, may be FRB or CASHBONUS

reason

additional info about change state, may be empty.

oldStatus

ACTIVE

newStatus

RELEASED, LOST, CANCELLED, EXPIRED, CLOSED

1.24 GetBattlegroundStartGameUrl

If player click on any battleground buyIn icon, lobby must send this request for obtain start game in battleground mode.

Request:

```
{
  "buyIn": 100,
  "date": 1497154790288,
  "rid": 5,
  "class": "GetBattlegroundStartGameUrl
}
```

Request parameters:

buyIn

selected buyIn amount

rid

unique request id

Response:

```
{
  "roomId": 5,
  "startGameUrl":
"https://host/mpgameloader.jsp?sid=deb0bf169cbb477b6f8430000015cbe83&serverId=1&roomId
=5&stake=5",
  "date": 1497155412200,
  "rid": 1,
  "class": "GetStartGameUrlResponse"
}
```


Where:

rid

request id from “GetRoomInfo”

roomId

unique room id

startGameUrl

url for start game.

2. Game protocol

After the game client is loaded, it should open websocket connection to url passed in request parameter gameServletUrl=wss://host:port/websocket/mpgame and then send “OpenRoom” request.

2.1 Error handling

In response to any client request may come an error message like this:

```
{
  "code": 1,
  "msg": "Internal error",
  "date": 1496748898812,
  "class": "Error",
  "rid": 1
}
```

```
{
  "code": 2,
  "msg": "Server shutdown",
  "date": 1496748898812,
  "class": "Error",
  "rid": -1
}
```

```
{
  "code": 1005,
  "msg": "Room moved to another server",
  "date": 1496748898812,
  "class": "Error",
  "rid": 9
}
```

```
{
  "code": 1003,
  "msg": "Room not found",
  "date": 1496748898812,
  "class": "Error",
  "rid": 10
}
```

Request parameters:

code

error code

msg

error description (may be localized)

date

datetime in msec. from 01.01.1970 (standart unix timestamp)

class

message class

rid

request Id, type is int. Optional parameter, if not -1 this parameter contains id of original request.

Possible error ranges

1-999

FATAL ERROR

1000-4999

ERROR

5000-9999

WARNING

Handling 'FATAL ERROR':

Just display message to user and close game.

Handling Game Websocket errors:

In case of websocket error, you must re-establishing websocket connection to gameServletUrl and resend 'OpenRoom' request.

Handling 1003, 1005 error:

1. Close current websocket connection to game server
2. Call lobby method 'GetStartGameUrl'
3. Re-establish websocket connection to new startGameUrl
4. Send 'OpenRoom' request

2.2 OpenRoom

After this request is completed, the client goes into observer mode and begins to receive all necessary information about the game.

```
{
  "roomId": 1,
  "serverId": 1,
  "lang": "en",
  "sid": "eb0bf169cbb477b6f8430000015cbe83",
  "date": 1497157072066,
  "rid": 5,
  "class": "OpenRoom"
}
```

Request parameters:

roomId

unique room id

serverId

serverId for connect via websocket

lang

preffered language

rid

unique request id

sid

session identifier send as request parameter on start game client.

Response:

GetRoomInfoResponse. See paragraph 1.6

If game state is “PLAY” client immediately receives message:

```
{
  "mapId": 302,
  "subround": "BASE",
  "startTime": 0,
  "state": "PLAY",
  "roomEnemies": [
    {
      "id": 1,
      "typeId": 1,
      "speed": 9.0,
      "awardedPrizes": "1,2",
      "awardedSum": 3.0,
      "energy": 0,
      "fullEnergy": 1250.0,
      "skin": 1,
      "trajectory": [
        { "x": 10, "y": 50, "time": 120, "invulnerable": true },
```

```
        { "x": 20, "y": 30, "time": 150 },
        { "x": 30, "y": 30, "time": 250 }
      ],
      "parentEnemyId": -1,
      "members": [],
      "swarmId": 0,
      "swarmType": 0
    },
    {
      "id": 10,
      "typeId": 2,
      "speed": 6.5,
      "awardedPrizes": "1,3",
      "awardedSum": 4.0,
      "energy": 45,
      "fullEnergy": 50,
      "skin": 1,
      "trajectory": [
        { "x": 10, "y": 50, "time": 120 },
        { "x": 20, "y": 30, "time": 150 }
      ],
      "parentEnemyId": -1,
      "members": [],
      "swarmId": 0,
      "swarmType": 0
    }
  ],
  "seats": [
    {
      "id": 0,
      "nickname": "Player",
      "enterDate": 1587912789921,
      "totalScore": 28230.5,
      "currentScore": 0.0,
      "avatar": {
        "borderStyle": 3,
        "hero": 1,
        "background": 2
      },
      "specialWeaponId": -1,
      "level": 8,
      "unplayedFreeShots": 0,
      "totalDamage": 120,
      "betLevel": 1
    }
  ],
  "mines": [],
  "freezeTime": {},
  "immortalBoss": false,
  "roundId": 450063,
  "seatGems": {},
```

```
  "cashBonusInfo": {
    "id": 23142,
    "awardDate": 1533284885209,
    "expirationDate": 1533294885209,
    "balance": 1000,
    "amount": 10000,
    "amountToRelease": 200,
    "status": "ACTIVE"
  },
  "tournamentInfo": {
    "id": 23142,
    "name": "New Year's tournament",
    "state": "ACTIVE",
    "startDate": 1533284885209,
    "endDate": 1533284885209,
    "balance": 10000,
    "buyInPrice": 500,
    "buyInAmount": 10000,
    "reBuyAllowed": true,
    "reBuyPrice": 500,
    "reBuyAmount": 100000,
    "reBuyCount": 1,
    "reBuyLimit": -1,
    "resetBalanceAfterRebuy": false
  },
  "battlegroundInfo" {
      "buyIn" : 1000,
      "buyInConfirmed": true,
      "timeToStart" : 0,
      "kingsOfHill": [-1],
      "score": 0,
      "rank" : 0,
      "pot": 3960
  },
  "gemPrizes": {0: 120, 1: 80, 2: 40, 3: 25, 4: 10}
  "betLevel": 1,
  "date": 1587912885176,
  "rid": 5,
  "class": "FullGameInfo"
}
```

Where

roomEnemy:id

unique enemy instance id

roomEnemy:typeId

enemy type id.See GetRoomInfoResponse:enemy:id

roomEnemy:awardedPrizes

prizes (list!) received from hitting the enemy.May be empty if no hits.

roomEnemy:awardedSum

amount of points received from hits to the enemy

roomEnemy:energy

remaining energy, if energy<0 enemy is dead, remember that energy=0 used for identify regular enemies

roomEnemy:skin

enemy skin

freezeTime

freeze time remaining.

gemPrizes

prize for each gem

Trajectory points may contain following additional params

invulnerable

enemy will be invulnerable between this point and next point

portal

numeric id of Portal from which enemy should be spawned

teleport

true if enemy should move from this point using teleport animation, teleport reserves 4 points in trajectory

2.3 CloseRoom

This request must be send to server before close client. This required for release all server resources allocated to client.

```
{
  "roomId": 1,
  "date": 1497159892576,
  "rid": 5,
  "class": "CloseRoom"
}
```

Request parameters:

roomId

unique room id

rid

unique request id

Response:

```
{
  "date": 1497154639465,
  "rid": 1,
  "class": "Ok"
}
```

2.4 SitIn

The request is sent by the client to seat in the room.After the successful execution of this request, the user moves from the observer state to the player's state and additional actions available to him. In battleground mode sitIn must be sended only after accept buyIn.If buyIn not accepted need send CloseRoom message.

```
{
  "date": 1497160498696,
  "rid": 1,
  "stake": 5,
  "class": "SitIn"
}
```

Request parameters:

stake

stake in cents. This parameter must be 0 for re-sitIn

Response:

```
{
  "id": 4,
  "nickname": "Andrey",
  "enterDate": 1497160789104,
  "ammoAmount": 120,
  "balance": 15000,
  "weapons": [
    {"id": 0, "shots": 0},
    {"id": 1, "shots": 0},
    {"id": 2, "shots": 0},
    {"id": 3, "shots": 0},
    {"id": 4, "shots": 7},
    {"id": 5, "shots": 0},
    {"id": 6, "shots": 0},
    {"id": 7, "shots": 0},
    {"id": 8, "shots": 3},
    {"id": 9, "shots": 0},
    {"id": 10, "shots": 0},
    {"id": 11, "shots": 0}
  ],
  "weaponLootBoxPrices": [100.0, 200.0, 400.0],
  "avatar": {
    "borderStyle": 1,
    "hero": 1,
    "background": 10
  },
  "showRefreshBalanceButton": true,
  "level": 8,
  "frbMode": false,
  "frbBalance": 0,
  "mode": "FRB",
  "date": 1497160789056,
  "rid": 2,
  "class": "SitInResponse"
}
```

Where:

rid

request id from “SitIn”

id

seat number

nickname

seat nickname

ammoAmount

summary ammo amount

balance

current player balance

avatar

seat avatar

weaponLootBoxPrice

Weapon Loot Box price in cents

showRefreshBalanceButton

need show "Refresh Balance" button

frbMode

deprecated parameter, see 'mode' (will be deleted after client fix)

frbBalance

deprecated parameter (will be deleted after client fix)

mode

game mode, possible values FRB, CASHBONUS, REAL,TOURNAMENT

Other clients also receive this response, but with rid=-1.

2.5 SitOut

The request is sent by the client in order to seat out from the room. After that the user goes into observer mode. For tournaments, cashbonus, frbonus modes, not required send a SitOut request, this will be done automatically and the client will receive a SitOutResponse message.

```
{
  "date": 1497161230259,
  "rid": 1,
  "class": "SitOut"
}
```

Response:

```
{
  "id": 4,
  "nickname": "Andrey",
  "outDate": 1497161341687,
  "compensateSpecialWeapons": 304,
  "surplusHvBonus": 104,
  "totalReturnedSpecialWeapons": 10,
  "nextRoomId": 32445,
  "hasNextFrb": true,
  "date": 1497161341653,
  "rid": 1,
  "class": "SitOutResponse"
}
```

Where:

rid

request id from “SitOut”

id

seat number

nickname

seat nickname

compensateSpecialWeapons

compensate win for unused special weapons

surplusHvBonus

compensate win for pot of HV Runner

totalReturnedSpecialWeapons

amount of returned special weapons

nextRoomId

roomId for sitIn to real room (after cashBonus or tournament), may be -1 if there is no suitable room

hasNextFrb

after cashbonus or frb completed, this flag indicating that exist new FRBonus

Other clients also receive this response, but with rid=-1.

2.6 GameStateChanged

This message sent from server to all clients on each game state change.

```
{
  "state": "PLAY",
  "ttnx": 600,
  "roundId": 12345,
  "date": 1497171419692,
  "rid": 1,
  "class": "GameStateChanged"
}
```

Where:

state

current room state. Possible values: WAIT, PLAY, QUALIFY, CLOSED

ttnx

rough time to next state in seconds, -1 for unknown

roundId

current round id

rid

request id, always -1

2.7 NewEnemy

This message sent from server to all clients when there is a new enemy

```
{
  "newEnemy": {
    "id": 1,
    "typeId": 1,
    "speed": 3.0,
    "awardedPrizes": "",
    "awardedSum": 0,
    "energy": 0,
    "fullEnergy": 100,
    "skin": 2,
    "trajectory": [
      { "x": 10, "y": 50, "time": 120 },
      { "x": 20, "y": 30, "time": 150 }
    ],
    "parendEnemyId": -1,
    "members": [],
    "swarmId": 0,
    "swarmType": 0
  },
  "date": 1497173799426,
  "rid": -1,
  "class": "NewEnemy"
}
```

newEnemy is same as FullGameInfo:roomEnemies in paragraph 2.2

2.7.1 NewEnemies

This message will be sent to all clients when a lot of enemies is spawned at once, for example - scarab swarms

```
{
  "date": 1497173799426,
  "rid": -1,
  "class": "NewEnemies",
  "enemies": [
    {
      "id": 1,
      "typeId": 1,
      "speed": 3.0,
      "awardedPrizes": "",
      "awardedSum": 0,
      "energy": 0,
      "fullEnergy": 100,
      "skin": 2,
      "trajectory": [
        { "x": 10, "y": 50, "time": 120 },
        { "x": 20, "y": 30, "time": 150 }
      ],
      "parendEnemyId": -1,
      "members": [],
      "swarmId": 2,
      "swarmType": 3
    },
    {
      "id": 2,
      "typeId": 1,
      "speed": 3.0,
      "awardedPrizes": "",
      "awardedSum": 0,
      "energy": 0,
      "fullEnergy": 100,
      "skin": 1,
      "trajectory": [
        { "x": 10, "y": 50, "time": 120 },
        { "x": 20, "y": 30, "time": 150 }
      ],
      "parendEnemyId": -1,
      "members": [],
      "swarmId": 2,
      "swarmType": 3
    }
  ]
}
```


2.8 BuyIn

The request is sent by the client if need buy ammo. Not available in battleground mode.

```
{
  "ammoAmount": 100,
  "date": 1497174203319,
  "rid": 10,
  "class": "BuyIn"
}
```

ammoAmount

amount of ammunition purchased

Response:

```
{
  "ammoAmount": 120,
  "balance": 15000,
  "date": 1497174620105,
  "rid": 10,
  "class": "BuyInResponse"
}
```

Where:

rid

request id from “BuyIn” request

ammoAmount

summary ammo amount

balance

current balance in cents

2.10 Shot

This request is sent by the client when the shot is fired. Response for shot request returned to all players. If a special weapon was used, then more than one answer can be sent / miss

```
{
  "bulletId": "0_0"
  "weaponId": -1,
  "enemyId": 5,
  "x": 35.0,
  "y": 250.5,
  "isPaidSpecialShot": false,
  "date": 1497177502148,
  "rid": 34,
  "class": "Shot"
}
```

Where:

enemyId

unique enemy id of who made the shot

weapon

id of used weapon, -1 for regular weapon

bulletId

bulletId for shot. (in new games, see 2.40)

If player miss, server return

```
{
  "seatId": 2,
  "killedMiss": true,
  "awardedWeaponId": -1,
  "enemyId": 2,
  "usedSpecialWeapon": 1,
  "awardedWeaponShots": 0,
  "remainingSWShots": 3,
  "score": 5,
  "hit": false,
  "lastResult": false,
  "x": 55.0,
  "y": 214.0,
  "mineId": "0_1550487688500"
  "shotEnemyId": 5,
  "invulnerable": false,
  "betLevel": 1,
  "bulletId": "0_0",
  "class": "Miss",
  "date": 1497177502148,
  "rid": -1
}
```

Where:

seatId

seat id that made shot

killedMiss

true if a shot is fired on an already killed enemy. The money for this shot is returned to the player.

awardedWeaponId

if special weapon awarded, awardWeaponId contains weapon id, -1 if no award. Any shot has a chance to get special weapons

usedSpecialWeapon

special weapon id used for this shot. For regular weapon, always=-1

remainingSWShots

number of remaining shots for current special weapon. For regular weapon, always=0

enemyId

enemy which is hit by weapon

shotEnemyId

original shot target

invulnerable

true if a shot is fired when an enemy was in invulnerable state. Client should cancel shot animation and return ammo to the player

betLevel

bet level which was active when player performed shot

If player hit, server return:


```
{
  "seatId": 0,
  "damage": 0.0,
  "win": 14.0,
  "awardedWeaponId": -1,
  "usedSpecialWeapon": 7,
  "remainingSWShots": 7,
  "score": 1.4,
  "enemy": {
    "id": 9125,
    "typeId": 4,
    "speed": 6.0,
    "awardedPrizes": "",
    "awardedSum": 0.0,
    "energy": 2.147483647E9,
    "fullEnergy": 100.0,
    "skin": 1,
    "parentEnemyId": -1,
    "members": [],
    "swarmId": 0,
    "swarmType": 0
  },
  "hit": true,
  "awardedWeaponShots": 0,
  "killed": true,
  "lastResult": false,
  "multiplierPay": 0,
  "killBonusPay": 0.0,
```

```
  "currentWin": 14.0,
  "hvEnemyId": -1,
  "x": 822.3107,
  "y": 287.30884,
  "mineId": "",
  "newFreeShots": 0,
  "newFreeShotsSeatId": 0,
  "hitResultBySeats": {
    "0": [
      {"id": 0, "value": "14.0"}
    ]
  },
  "instanceKill": false,
  "chMult": 1,
  "awardedWeapons": [],
  "needExplode": false,
  "isExplode": false,
  "gems": [],
  "enemyId": 9125,
  "shotEnemyId": 9125,
  "enemiesInstantKilled": {},
  "betLevel": 1,
  "isPaidSpecialShot": false,
  "rage": [
    { "id": 123, "damage": 10.0 },
    { "id": 234, "damage": 20.0 }
  ],
  "enemiesWithUpdatedMode": [
        {enemyId: 19, enemyMode: 1}
    ]
  ,
  "bulletId": "0_0",
  "date": 1592283785789,
  "rid": 32,
  "class": "Hit"
}
```


Where:

seatId

seat id that made a shot

damage

caused damage to the enemy

win

base win in cents (type is float)

awardedWeaponId

if special weapon awarded, awardWeaponId contains weapon id, -1 if no award

usedSpecialWeapon

special weapon id used for this shot. For regular weapon, always=-1 (see 5.0)

awardedWeaponShots

number of awarded shots of special weapon from awardedWeaponId

hvEnemyId

id of new HV enemy after killing of current enemy. Info about new HV enemy will be sent via NewEnemy message. Default value is "-1" (no HV enemy).

killed

true/false - enemy is killed or no

lastResult

true/false. true is it is the last hit of shot. (relevant for SW)

remainingSWShots

number of remaining shots for current special weapon. For regular weapon, always=0

multiplierPay

the additional multiplier for wins(not relevant for current Pirates)

killBonusPay

win bonus for killing, for Pirates = 0.

currentWin

Money (in cents). The current win of seat. (include all last payouts for shot together with the unconverted amount to shots)

hvEnemyId

id of HV enemy. (not used in Pirates)

newFreeShots

type is integer. It is number of new appeared free shots.

newFreeShotsSeatId

type is integer. id of seat which received free shots.

hitResultBySeats

map of hit results for all seaters. id: type of result (0 - win (value is win in cents), 1 - treasure (value is name of treasure), 2 - SW (value is type of SW)), 4 - money wheel win (value is win in cents)

instanceKill

type is boolean, instant kill appeared or no. (not relevant for current Pirates)

chMult

type is integer. the additional multiplier for wins(not relevant for current Pirates)

needExplode

type is boolean, true for exploding enemies (not relevant for current Pirates)

isExplode

type is boolean. True if the enemy is the source of the explosion and the explosion occurred (not relevant for current Pirates)

gems

array of integers. appeared gems for this hit. (not relevant for current Pirates)

enemy

state of the affected enemy, same as RoomEnemy in paragraph 2.2

enemyId

id of enemy for this hit.

shotEnemyId

id of shot enemy.

enemiesInstantKilled

map of hit results for instant killing (not relevant for current Pirates) enemy.id and all other attributes may be different from the one for whom the shot was fired. This is possible if the enemy is already killed by another player. The client must correctly process the animation of the rebound and the defeat of another enemy. Also keep in mind that the Hit.message does not contain a field "trajectory", as it is not necessary.

rid

request id for the player who made the shot, -1 for all other players.

mineId

id of mine. (seatId_time of mine placing)

betLevel

bet level which was active when player performed shot

isPaidSpecialShot

true if player used purchased special weapon

rage

(DragonStone) when Hit triggers rage effect, you will receive list of enemies with an amount of damage which should be done to them

effects

(DragonStone) if enemy during hit has some effects applied to him, you will receive list of these effects - for example FIRE_SPECTER, LIGHTNING_SPECTER

enemiesWithUpdatedMode

enemy with updated modes. 0 - X1 enemy mode (default), 1 - X2 enemy mode)

2.11 GetFullGameInfo

```
This request can be sent by the client if connection lost and need refresh all room i
nfo.
{
  "date": 1497178236042,
  "rid": 1,
  "class": "GetFullGameInfo"
}
```

Response: same as FullGameInfo in paragraph 2.2

2.12 RoundResult

After round finished all clients receive message “GameStateChanged” described in paragraph 2.6 with state=QUALIFY. After qualification completed all clients receive round result in message:

```
{
  "winAmount": 500.5,
  "winRebuyAmount": 300.0,
  "balance": 12000,
  "hitCount": 5,
  "missCount": 25,
  "currentScore": 30,
  "totalScore": 350,
  "nextMapId": 504,
  "seats": [
    {
      "id": 0,
      "nickname": "John",
      "enterDate": 1497179064797,
      "totalScore": 700.0,
      "currentScore": 350.0,
      "avatar": {
        "borderStyle": 1,
        "hero": 1,
        "background": 10
      },
      "specialWeaponId": -1,
      "level": 3,
      "unplayedFreeShots": 0,
      "totalDamage": 20.0,
      "betLevel": 1
    },
    {
      "id": 1,
      "nickname": "Mike",
      "enterDate": 1497179064797,
```

```
      "totalScore": 230.0,
      "currentScore": 10.0,
      "avatar": {
        "borderStyle": 1,
        "hero": 1,
        "background": 10
      },
      "specialWeaponId": 1,
      "level": 5,
      "unplayedFreeShots": 0,
      "totalDamage": 200.0,
      "betLevel": 2
    },
    {
      "id": 3,
      "nickname": "Fred",
      "enterDate": 1497179064797,
      "totalScore": 0,
      "currentScore": 0,
      "avatar": {
        "borderStyle": 1,
        "hero": 1,
        "background": 10
      },
      "specialWeaponId": 1,
      "level": 1,
      "unplayedFreeShots": 0,
      "totalDamage": 0.0,
      "betLevel": 1
    }
  ],
  "enemiesKilledCount": 95,
  "winAmountInCredits": 9524,
  "unusedBulletsCount": 95,
  "unusedBulletsMoney": 9524,
  "totalBuyInMoney": 102,
  "surplusHvBonus": 102,
  "xpPrev": 1000,
  "weaponSurplus":[
    {
      "id": 0,
      "shots": 332,
      "winBonus": 234
    },
    {
      "id": 1,
      "shots": 210,
      "winBonus": 1525
    }
  ],
  "totalKillsXP": 767,
```

```
  "totalTreasuresCount": 1,
  "totalTreasuresXP": 100,
  "beforeRound": {
    "level": 2,
    "score": 1885,
    "minScore": 1000,
    "maxScore": 3000
  },
  "afterRound": {
    "level": 2,
    "score": 1885,
    "minScore": 1000,
    "maxScore": 3000
  },
  "surplusHvBonus": 0,
  "questsCompletedCount": 0,
  "questsPayouts": 0,
  "roundId": 1090142,
  "weaponsReturned": [
  ],
  "bulletsFired": 5,
  "realWinAmount": 10.0
  "freeShotsWon": 5,
  "moneyWheelCompleted": 1,
  "moneyWheelPayouts": 25,
  "totalDamage": 10,
  "date": 1497179064748,
  "rid": -1,
  "class": "RoundResult",
  "battlegroundRoundResult": [
    {
       "id": 0,
       "score": 12324,
       "rank": 1,
       "pot": 3960
    },
    {
       "id": 1,
       "score": 11324,
       "rank": 2,
       "pot": 0
    },
    {
       "id": 2,
       "score": 10324,
       "rank": 3,
       "pot": 0
    },
    {
       "id": 5,
       "score": 1324,
```

```
        "rank": 4,
        "pot": 0
      }
    ]
  }
```

Where:

winAmount

amount won in this round (type - float)

winRebuyAmount

win used for rebuy ammo

balance

current player balance

totalScore

total number of points awarded player in this room (total win = totalScore*stake), type=integer

currentScore

number of points awarded player for current round (currentWin = currentScore*stake), type=integer

nextMapId

id of map that will be used in next round (used for preloading of resources)

hitCount

hit count for this round

missCount

miss count for this round

seat:rankPoints

total number of points received by the player, see 4.3 section is spec. seats is same as GetRoomInfoResponse:seats in paragraph 1.4

unusedBulletsCount

count of unused bullets in round.

unusedBulletsMoney

amount of unused bullets in round (cents)

totalBuyInMoney

total amount of all BuyIns in this round (cents)

weaponSurplus

weapons surplus amounts, id - type of special weapon, shots - number of shots. winBonus - amount in cents.

moneyWheelCompleted

number of times player completed money wheel during this round

moneyWheelPayouts

amount of money player received for completing money wheel

totalDamage

total amount of damage player dealt to enemies in this round

battlegroundRoundResult

battleground mode leaderboard info

2.13 ChangeMap

The server can send a message about changing the current map (for example, when a boss appears)

```
{
  "class": "ChangeMap",
  "mapId": 2,
  "subround": "BASE",
  "rid": -1,
  "date": 34534534
}
```

Where:

mapId

new map identifier (now only one map with id=1 available)

subround

reason for changeMap (class of enemies available for this map, also may be classified as subround), possible values: BASE, BOSS

2.14 EnemyDestroyed

After the enemy was destroyed (for example, as a result of a shot), the server sends this message

```
{
  "enemyId": 100,
  "reason": 0,
  "date": 1521872381930,
  "rid": -1,
  "class": "EnemyDestroyed"
}
```

Where:

enemyId

destroyed enemy identifier

reason

identifier of the event as a result of which the enemy was destroyed. The client can use this field for the different death animations. Existing types: 0 - death as a result of a shot from regular weapons

2.15 Awards (Deprecated)

When enemy is killed, player can receive additional non-money award, which consist of leader-board points and collectible items.
When such award is granted, player will receive message:

```
{
  "awards": [
    { "seatId": 0, "score": 1, "qualifyWin": 481, "treasures": [42] },
    { "seatId": 1, "score": 481, "qualifyWin": 481,  "treasures": [5, 10] }
  ],
  "class": "Awards"
  "date": 1529659911798,
  "enemyId": 463,
  "rid": -1
}
```

Where:

awards

complete list of awards for enemy kill

awards.seatId

seatId of player that received award

awards.score

amount of awarded leader-board points

awards.treasures

list of ids of dropped treasures

enemyId

id of killed enemy

qualifyWin

shared prize of player for boss (cents)

For more info about available treasures, please see achievements specification.

2.16 LevelUp

This message is sent to the player when he reaches new character level

Response

```
{
  "class": "LevelUp",
  "date": 1496748898812,
  "rid": -1,
  "seatId": 1,
  "level": 5
}
```

2.17 PurchaseWeaponLootBox

This message is sent by client to purchase loot box with a random special weapon

Request

```
{
  "class": "PurchaseWeaponLootBox",
  "date": 1496748898812,
  "box": 3,
  "rid": 10
}
```

box

number of selected box for purchase

Response

```
{
  "class": "WeaponLootBox",
  "date": 1496748898812,
  "rid": 10,
  "weaponId": 3,
  "shots": 100,
  "balance": 100500,
  "currentWin": 2300,
  "usedAmmoAmount": 10
}
```

weaponId

id of awarded weapon

shots

amount of awarded shots with this weapon

balance

player's balance after purchase

currentWin

remainder of player's win after purchase

usedAmmoAmount

purchase can be made at the expense of ammo

2.18 Weapons

At the start of a round, server will send a message with a description of weapons currently owned by player

Response

```
{
  "class": "Weapons",
  "date": 1496748898812,
  "rid": -1,
  "ammoAmount": 100,
  "freeShots": false,
  "weapons": [
    { "id": 1, "shots": 5 },
    { "id": 2, "shots": 3 }
  ]
}
```

ammoAmount

amount of regular bullets

freeShots

true if regular bullets are free (FRB mode, deprecated)

weapons

list of special weapons currently owned by player with a number of remaining shots

2.19 RefreshBalance

Sended from client after press "Refresh balance" button. Server side return message 1.15 "BalanceUpdated"

Response

```
{
  "clientAmmo": 253,
  "class": "RefreshBalance",
  "date": 1496748898812,
  "rid": 1
}
```

2.20 FRBEnded

After FRB completed, server send FRBEnded message. Client must display close reason (Completed, Canceled, Expired) and win sum. After close message box, need close client and resend from lobby messages: EnterLobby

Response

```
{
  "winSum":1200,
  "closeReason":"Completed",
  "hasNextFrb":true
  "date":1533285929327,
  "rid":-1,
  "class":"FRBEnded"
}
```

2.21 SwitchWeapon

When player activates different weapon, client should send this message to server

Request

```
{
  "class": "SwitchWeapon",
  "date": 1533285929327,
  "rid": 1,
  "weaponId": 2
}
```

If everything is Ok, then response will contain exactly the same message

2.22 SyncLobby

When client plans to show Rooms List in a Lobby while a player still plays in a room, client should send to the game room following message to update list of available Special Weapons:

Request

```
{
  "class": "SyncLobby",
  "date": 1533285929327,
  "rid": 10
}
```

Response

```
{
  "class": "Ok",
  "date": 1533285929327,
  "rid": 10
}
```

If this message was not send, than list of available special weapons for current stake could be empty or outdated.

2.23 UpdateTrajectories

Server may send such message to client to inform it about the changes in movement trajectories of enemies.

```
{
  "class": "UpdateTrajectories",
  "rid": -1,
  "freezeTime": 3000,
  "animationId": 0,
  "trajectories": {
    10: {speed: 4, points: [{x: -240, y: 140.625, time: 1535004949556}, {x: -50, y:
247.5, time: 1535004959056}]},
    11: {speed: 3, points: [{x: -50, y: 472.5, time: 1535004990056}, {x: 860, y:
-39.375, time: 1535005035556}]}
  }
}
```

The key in trajectories field is an enemyId and value is a new trajectory. freezeTime: freezeTime for enemies. (ms)

2.24 CloseRoundResults (Deprecated)

During Qualify state client may send following message to force start of next round.

```
{
  "class": "CloseRoundResults",
  "rid": 10,
  "date": 1533285929327
}
Next round will be started once this message is received from all players in a room or
when maximal wait time is over
```

2.25 RoundFinishSoon

When round is coming to an end server will send following message

```
{
  "class": "RoundFinishSoon",
  "rid": -1,
  "date": 1533285929327
}
```

2.26 NewTreasure

When treasure finish quests server will send following message

```
{
  "class": "NewTreasure",
  "rid": -1,
  "date": 1533285929327,
  "id": 7,
  "enemyId": 23
  "completedQuestId": 1,
  "questId": 1
}
```

2.27 Update Quest

If progress of quest is updated, client will receive following message, if needReset=true amount is new.

```
{
  "class": "UpdateQuest",
  "date": 1496748898812,
  "rid": -1,
  "lastEnemyId": 100,
  "quest": {
    "id": 1,
    "type": 4,
    "roomCoin": 5
    "needReset": false,
    "progress": {
      "treasures": [
        { "treasureId": 2, "collect": 2, "goal": 3 }
      ]
    },
    "questPrize": {
      "amount": { "from": 50, "to": 100 },
      "specialWeaponId": 4
    },
    "collectedAmount": 200
  }
}
```

2.30 Place Mine to Map

This request is sent by the client when need to place mine to map.

```
{
  "x": 25.3,
  "y": 44.8,
  "isPaidSpecialShot": false,
  "date": 1497177502148,
  "rid": 34,
  "class": "MineCoordinates"
}
```

Where:

x, y

coordinates of place

Wrong coordinates

If x,y are wrong coordinates (wall, ...), then server return

```
{
  "code": 1023,
  "msg": "Wrong coordinates",
  "date": 1496748898812,
  "class": "Error",
  "rid": 34
}
```

Success response for all seaters:

```
{
  "mineId": "0_1550487688500",
  "seatId": 0,
  "date": 1496748898812,
  "class": "MinePlace",
  "rid": 34,
  "x": 367.2334,
  "y": 280.29443,
}
```

Where:

mineId

seatId_time of mine placing

2.31 Add Free Shots to queue

This request is sent by the client when need add free shots to current/next queue.

```
{
  "date": 1497177502148,
  "rid": 34,
  "queue": "current"
  "class": "AddFreeShotsToQueue"
}
```

Where:

queue

type of queue. current/next

Wrong adding of unplayed free shots.

```
{
  "code": 1025,
  "msg": "Wrong free shots",
  "date": 1496748898812,
  "class": "Error",
  "rid": 34
}
```

Success response for player:

```
{
  "date": 1496748898812,
  "class": "Ok",
  "rid": 34
}
```

2.32 ReBuy

Request

```
{
  "date": 1496748898812,
  "class": "ReBuy",
  "rid": 5
}
```

Response

```
{
  "date": 1496748898812,
  "class": "ReBuyResponse",
  "rid": 5,
  "ammoAmount": 10000,
  "balance": 12345,
  "rebuyCount": 2
}
```

2.33 TournamentStateChanged

same as 1.22 TournamentStateChanged

2.34 BonusStatusChanged

same as 1.23 BonusStatusChanged

2.35 Change bet level in room

The request is sent by the client if need change bet level in room.

```
{
  "betLevel": 5,
  "date": 1497174203319,
  "rid": 10,
  "class": "BetLevel"
}
```

betLevel

requested bet level

Success response for player:

```
{
  "betLevel": 5,
  "date": 1497174620105,
  "rid": 10,
  "class": "BetLevelResponse"
}
```

Wrong change of bet level

```
{
  "code": 1027,
  "msg": "Not allowed change bet level",
  "date": 1496748898812,
  "class": "Error",
  "rid": 10
}
```

Where:

rid

request id from “BetLevel” request

betLevel

bet level in room

2.36 Rise

When an enemy casts spell Rise in DragonStone, you will receive following message:

```
{
  "caster": 123,
  "target": 234,
  "enemies": [
    {
      "id": 1,
      "typeId": 1,
      "speed": 3.0,
      "awardedPrizes": "",
      "awardedSum": 0,
      "energy": 0,
      "fullEnergy": 100,
      "skin": 2,
      "trajectory": [
        { "x": 10, "y": 50, "time": 120 },
        { "x": 20, "y": 30, "time": 150 }
      ],
      "parendEnemyId": -1,
      "members": [],
      "swarmId": 0,
      "swarmType": 0
    }
  ],
  "date": 1496748898812,
  "class": "Rise",
  "rid": 10
}
```

caster

id of enemy who casts a spell

target

id of recently killed enemy

enemies

list of summoned enemies, all properties are the same as in 2.7 NewEnemy message

2.38 Fragments of Dragon Stone

Note: this message could be updated after feedback from Design team

When enemy is killed, it can drop fragment Dragon Stone In this case player will receive following message:

```
{
  "fragmentId": 2,
  "date": 1496748898812,
  "class": "DragonStone",
  "rid": 10
}
```

fragmentId

id of dragon stone fragment, when all fragments are collected, boss will appear

rid

id of shot message, original message should be used to determine coordinates of enemy for drop animation

2.39 Mini Slot

Note: this message could be updated after feedback from Design team At this moment we decided to send results of all spins at once to reduce game complexity You should subtract win amount of these spins from balance until animation is shown Animation should be delayed during boss fights

When shot triggers Mini Slot feature, you will receive following message:

```
{
  "spins": [
    { "reels": [0, 3, 4], "win": 25.0 },
    { "reels": [2, 5, 6], "win": 0.0 },
    { "reels": [3, 5, 3], "win": 50.0 },
    { "reels": [1, 2, 3], "win": 0.0 },
    { "reels": [2, 3, 4], "win": 0.0 }
  ],
  "date": 1496748898812,
  "class": "Slot",
  "rid": 10
}
```

spins

list of spin results

spins:reels

positions on reels, order of reels will be sent in 1.2 EnterLobbyResponse message

spins:win

win amount in cents of player's currency

rid

id of shot message, which triggered Mini Slot feature

2.40 Place Bullets to Map.

Note: Bullet message client send for Pistol/Turret weapon for synchronization bullet info between clients.

```
{
      "bulletTime":1617613404701,
      "bulletAngle":-0.15,
      "bulletId":"0_1",
      "startPointX":531,
      "startPointY":480,
      "endPointX":869,
      "endPointY":428,
      "class":"Bullet",
      "rid":9,
      "date":1617613405521
}
```

Success response for each player:

```
{
      "bulletTime":1617613404701,
      "bulletAngle":-0.15,
      "bulletId":"0_1",
      "startPointX":531,
      "startPointY":480,
      "endPointX":869,
      "endPointY":428,
      "class":"BulletResponse",
      "rid":9,
      "date":1617613404721
}
```

2.41 CancelBattlegroundRound

Message received to game client if battleground round canceled.Cliet must display meassage and return to lobby.

```
{
      "refundedAmount": 1000,
      "reason": NOT_ENOUGH_PLAYERS,
      "class":"CancelBattlegroundRound",
      "rid":9,
      "date":1617613404721
}
```

refundedAmount

returned buyIn, may be 0 if played not make buyIn

reason

cancel reason. enum with possible values: NOT_ENOUGH_PLAYERS, SERVER_FAILURE

2.42 KingOfHillChanged

Message sended after change King of the Hill

```
{
      "newKings": [1,2,3],
      "class":"KingOfHillChanged",
      "rid":9,
      "date":1617613404721
}
```

newKings

new King seatIds

2.43 ConfirmBattlegroundBuyIn

Message must be sended game client if player confirm buyIn for next battleground

```
{
      "class":"ConfirmBattlegroundBuyIn",
      "rid":9,
      "date":1617613404721
}
```

Success response:

```
{
  "date": 1531731629785,
  "rid": 9,
  "class": "Ok"
}
```

2.44 Crash Bet

The request is sent by the client if need make bet in crash game.

```
{
  "crashBetAmount": 100,
  "multiplier": 1.35,
  "autoPlay": false,
  "date": 1497174203319,
  "rid": 10,
  "class": "CrashBet"
}
```

crashBetAmount

amount of crash bet (cents)

multiplier

crash multiplier of bet

autoPlay

need auto collect on this multiplier.

Response:

```
{
  "ammoAmount": 120,
  "balance": 15000,
  "date": 1497174620105,
  "crashBetKey": 1497174620105_0,
  "rid": 10,
  "class": "CrashBetResponse"
}
```

2.45 Cancel Crash Bet

The request is sent by the client if need cancel bet in crash game. Player will get win with current multiplier.

```
{
  "crashBetId": 1497174620105_0,
  "date": 1497174203319,
  "rid": 10,
  "class": "CrashCancelBet"
}
```

crashBetId

id of crash bet for 2.44 (string)

Response:

```
{
  "currentMult": 2.3,
  "seatId": 45,
  "seatWin": 1550,
  "date": 1497174620105,
   "rid": 10,
  "class": "CrashCancelBetResponse"
}
```

2.46 CrashStateInfo

The response is sent by the server to all players if multipliers was changed in room.

```
{
  "currentMult": 3.1,
  "date": 1497174203319,
  "rid": 10,
  "class": "CrashStateInfo"
}
```

Where:

rid

request id from “BuyIn” request

crashBetAmount

amount of crash bet (cents)

crashBetKey

key of crash bet (will be needed later in cancel of bet)

balance

current balance in cents

3. Enemy Skins (Wrath of Ra)

Table 1. Enemy Skins

Enemy Type	Skin Id	Description
0	1	Scarab
0	2	Black Scarab
1	1	Gold Scarab
2	1	Diamond Scarab
2	2	Ruby Scarab
3	1	Small Mummy
4	1	Small Black Mummy
5	1	Small White Mummy
6	1	Walking Mummy Warrior
6	2	Running Mummy Warrior
7	1	Mummy God Red
8	1	Mummy God Green
16	1	Anubis
16	2	Osiris
16	3	Thoth

4. Error codes

Error code	Error name	Description
1	INTERNAL_ERROR	Unexpected error, please report it to BSG Server team
2	SERVER_SHUTDOWN	
3	INVALID_SESSION	Please use another token to login into the game
4	DEPRECATED_REQUEST	
5	FOUND_PENDING_OPERATION	This user is unable to login due to problems with his account
6	CLOSE_FRB_IN_PROGRESS	Message is removed from the game
7	UNKNOWN_GAME_ID	Wrong game id
8	FOUND_OPEN_LOBBY_SESSION	Found other open lobby for EnterLobby (and game mode conflict).
1000	ILLEGAL_NICKNAME	Nickname contains banned patterns, please use another one
1001	BAD_REQUEST	Message received from the client has invalid format
1002	NOT_LOGGED_IN	Please restart game
1003	ROOM_NOT_FOUND	Please select another room
1004	TOO_MANY_OBSERVERS	Room is full, please select another one
1005	ROOM_MOVED	Room moved to another server
1006	TOO_MANY_PLAYER	All 6 slots for players are taken, you can observe game until one is freed or pick another one
1007	NOT_SEATER	You should perform SitIn operation before you can make actions in this room
1008	NOT_ENOUGH_MONEY	There is not enough money for purchase
1009	BAD_STAKE	Invalid stake size is provided by client
1010	BAD_BUYIN	Invalid BuyIn request is send by client
1011	CHANGE_STAKE_NOT_ALLOWED	Change of stake is forbidden at this moment (not used)

Error code	Error name	Description
1012	ROOM_NOT_OPEN	You should send OpenRoom request first
1013	ROUND_NOT_STARTED	You need to wait until round is started until you can make actions in this room
1014	NEED_SITOUT	You should perform SitOut request
1015	WRONG_WEAPON	You are trying to perform shot using inactive weapon
1016	NICKNAME_NOT_AVAILABLE	Nickname is already taken by another player, please pick another one
1017	AVATAR_PART_NOT_AVAILABLE	You are trying to use avatar which is not available for this account yet
1018	NOT_ENOUGH_BULLETS	You need to purchase bullets before you can shoot
1019	REQUEST_FREQ_LIMIT_EXCEEDED	You are trying to send requests too fast, please limit rate
1020	QUEST_IS_NOT_COMPLETED	You can’t collect quest which is not completed
1021	BUYIN_NOT_ALLOWED	You can perform BuyIn in this game state
1022	QUEST_ALREADY_COLLECTED	You already collected this quest
1023	WRONG_MINE_COORDINATES	You are trying to place mine on invalid location
1024	BOSS_ROUND_STARTED	Not used
1025	WRONG_UNPLAYED_FREE_SHOTS	Not used
1026	NOT_FATAL_BAD_BUYIN	Buy in is failed, but you can proceed with playing
1027	NOT_ALLOWED_CHANGE_BET	This message is sent by server when changing of bet levels is prohibited to avoid cheats with RTP
1028	NOT_ALLOWED_CHANGE_NICKNAME	Change nickname not allowed
1030	NOT_ALLOWED_SITIN	Sit in is not allowed during Qualify game state, client should wait and resend request

5. Special Weapons

Title	Type Id
Shotgun	0
Grenade	1
Machine Gun	2
Laser	3
Plasma Rifle	4
Mine Launcher	5
Railgun	6
Artillery Strike	7
Rocket Launcher	8
Flamethrower	9
Cryogun	10
Rapid Fire Pistol	11