

Getting CMS Up & Running

Version

Table of Contents

Contents:

CONFIGURATIONS	4
• Nginx	4
• Ghost CMS	5
FREQUENTLY USED COMMANDS	6

Getting CMS Up & Running

documentation

Add your content using `reStructuredText` syntax. See the [reStructuredText](#) documentation for details.

CONFIGURATIONS

Nginx

Reverse Proxy Configuration

```
map $status $header_content_type_options {
    204 "";
    default "nosniff";
}

server {
    listen 80;
    listen [::]:80;

    server_name activcount.ca www.activcount.ca;
    root /var/www/activcount/system/nginx-root; # Used for acme.sh
    SSL verification (https://acme.sh)

    location / {
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Proto $scheme;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header Host $http_host;
        proxy_pass http://127.0.0.1:2368;

        add_header X-Content-Type-Options
        $header_content_type_options;
    }

    location ~ /\.well-known {
        allow all;
    }

    client_max_body_size 50m;
}
```

Note

This configuration is for a reverse proxy setup with Nginx, which forwards requests to the Ghost CMS instance running on port 2368. The *X-Content-Type-Options* header is set to *nosniff* to prevent MIME type sniffing, enhancing security.

Ensure that the server name matches your domain and that the root directory is set correctly.

Ghost CMS

FREQUENTLY USED COMMANDS

```
# To specify the Node.js version to use for Ghost CMS  
npm use 20.11.1
```

