

Namespace Solstice.Applications.

Attributes

Classes

[ServiceAttribute](#)

The ServiceAttribute is a custom attribute used for marking classes within the Solstice.Service namespace. This attribute is sealed, implying that it cannot be inherited from.

[ServiceInterfaceAttribute](#)

The ServiceInterfaceAttribute is a custom attribute used for marking interface within the Solstice.Service namespace. This attribute is sealed, implying that it cannot be inherited from.

Class ServiceAttribute

Namespace: [Solstice.Applications.Attributes](#)

Assembly: Solstice.Applications.dll
















The ServiceAttribute is a custom attribute used for marking classes within the Solstice.Service namespace. This attribute is sealed, implying that it cannot be inherited from.

```
[AttributeUsage(AttributeTargets.Class)]  
public sealed class ServiceAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← ServiceAttribute

Inherited Members

[Attribute.Equals\(object\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module\)](#)  , [Attribute.GetCustomAttributes\(Module, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetHashCode\(\)](#)  ,

[Attribute.IsDefaultAttribute\(\)](#) , [Attribute.IsDefined\(Assembly, Type\)](#) ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#) , [Attribute.IsDefined\(MemberInfo, Type\)](#) ,
[Attribute.IsDefined\(MemberInfo, Type, bool\)](#) , [Attribute.IsDefined\(Module, Type\)](#) ,
[Attribute.IsDefined\(Module, Type, bool\)](#) , [Attribute.IsDefined\(ParameterInfo, Type\)](#) ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#) , [Attribute.Match\(object\)](#) ,
[Attribute.TypeId](#) , [object.Equals\(object, object\)](#) , [object.GetType\(\)](#) ,
[object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Class ServiceInterfaceAttribute



Namespace: [Solstice.Applications.Attributes](#)

Assembly: Solstice.Applications.dll












The ServiceInterfaceAttribute is a custom attribute used for marking interface within the Solstice.Service namespace. This attribute is sealed, implying that it cannot be inherited from.

```
[AttributeUsage(AttributeTargets.Interface)]  
public sealed class ServiceInterfaceAttribute : Attribute
```

Inheritance

[object](#)  ← [Attribute](#)  ← ServiceInterfaceAttribute

Inherited Members

[Attribute.Equals\(object\)](#)  , [Attribute.GetCustomAttribute\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Assembly, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type\)](#)  ,
[Attribute.GetCustomAttribute\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttribute\(ParameterInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Assembly, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, bool\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(MemberInfo, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module\)](#)  , [Attribute.GetCustomAttributes\(Module, bool\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type\)](#)  ,
[Attribute.GetCustomAttributes\(Module, Type, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, bool\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type\)](#)  ,
[Attribute.GetCustomAttributes\(ParameterInfo, Type, bool\)](#)  , [Attribute.GetHashCode\(\)](#)  ,

[Attribute.IsDefaultAttribute\(\)](#) , [Attribute.IsDefined\(Assembly, Type\)](#) ,
[Attribute.IsDefined\(Assembly, Type, bool\)](#) , [Attribute.IsDefined\(MemberInfo, Type\)](#) ,
[Attribute.IsDefined\(MemberInfo, Type, bool\)](#) , [Attribute.IsDefined\(Module, Type\)](#) ,
[Attribute.IsDefined\(Module, Type, bool\)](#) , [Attribute.IsDefined\(ParameterInfo, Type\)](#) ,
[Attribute.IsDefined\(ParameterInfo, Type, bool\)](#) , [Attribute.Match\(object\)](#) ,
[Attribute.TypeId](#) , [object.Equals\(object, object\)](#) , [object.GetType\(\)](#) ,
[object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Namespace Solstice.Applications.Core

Classes

[CoreService<TRepository, T>](#)

Abstract class 'CoreService' defines the operations for managing entities of type T in the database.

Interfaces

[ICoreService<T>](#)

This interface describes an abstraction for a data manipulation service on a given type of CoreModel. It includes methods for CRUD operations, queries for specific entities, counting entities, starting transactions, and more.

Class CoreService<TRepository, T>

Namespace: [Solstice.Applications.Core](#)

Assembly: Solstice.Applications.dll

Abstract class 'CoreService' defines the operations for managing entities of type T in the database.

```
public class CoreService<TRepository, T> : ICoreService<T> where TRepository :  
    ICoreRepository<T> where T : class
```

Type Parameters

TRepository

Specifies the repository type handling the operations. TRepository must be an implementation of "ICoreRepository{T}".

T

Specifies the entity type to be handled by this service.








Inheritance

[object](#)  ← CoreService<TRepository, T>

Implements

[ICoreService](#)<T>

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Remarks

This class provides the ability to perform CRUD operations and various queries on entities of type T. Each instance of this class will be associated with a repository which interacts with the database.

Constructors

CoreService(IUnitOfWork)

Constructor for the Solstice service.

```
protected CoreService(IUnitOfWork unitOfWork)
```

Parameters

unitOfWork [IUnitOfWork](#)

Fields

_repository

```
protected readonly IRepository _repository
```

Field Value

IRepository

Methods

AddAndSaveAsync(T)

```
public Task AddAndSaveAsync(T entity)
```

Parameters

entity T

Returns

[Task](#) 

AddAndSaveAsync<TEntity>(TEntity)


```
public Task AddAndSaveAsync<TEntity>(TEntity entity) where TEntity : class
```

Parameters

entity TEntity

Returns

[Task](#)

Type Parameters

TEntity

AddAsync(T)

Method to add new entity to the repository.

```
public Task AddAsync(T entity)
```

Parameters

entity T

Entity of type T which need to be added.

Returns

[Task](#)

Awaitable task.

AddAsync<TEntity>(TEntity)

```
public Task AddAsync<TEntity>(TEntity entity) where TEntity : class
```

Parameters

`entity TEntity`

Returns

[Task](#)

Type Parameters

`TEntity`

AddRangeAndSaveAsync(ICollection<T>)

```
public Task AddRangeAndSaveAsync(ICollection<T> entities)
```

Parameters

`entities` [ICollection](#)<T>

Returns

[Task](#)

AddRangeAndSaveAsync<TEntity> (ICollection<TEntity>)

```
public Task AddRangeAndSaveAsync<TEntity>(ICollection<TEntity> entities) where  
TEntity : class
```

Parameters

`entities` [ICollection](#)<TEntity>

Returns

[Task](#)

Type Parameters

TEntity

AddRangeAsync(ICollection<T>)

Method to add new range of entities to the repository.

```
public Task AddRangeAsync(ICollection<T> entities)
```

Parameters

entities [ICollection](#)<T>

Collection of entities of type T which need to be added.

Returns

[Task](#)

Awaitable task.

AddRangeAsync<TEntity>(ICollection<TEntity>)

```
public Task AddRangeAsync<TEntity>(ICollection<TEntity> entities) where TEntity  
: class
```

Parameters

entities [ICollection](#)<TEntity>

Returns

[Task](#)

Type Parameters

TEntity

AnyAsyncBy(Expression<Func<T, bool>>)

Checks if there are any entities that satisfy the provided condition.

```
public Task<bool> AnyAsyncBy(Expression<Func<T, bool>> where)
```

Parameters

where [Expression](#) <[Func](#) <T, [bool](#)>>

A delegate defining the condition for the entities to meet,

Returns

[Task](#) <[bool](#)>

Bool value indicating whether any entities meet the specified condition.

AnyAsyncBy<TEntity>(Expression<Func<TEntity, bool>>)

```
public Task<bool> AnyAsyncBy<TEntity>(Expression<Func<TEntity, bool>> where) where  
TEntity : class
```

Parameters

where [Expression](#) <[Func](#) <TEntity, [bool](#)>>

Returns

[Task](#) <[bool](#)>

Type Parameters

TEntity

AnyAsyncBy<TEntity>(IQueryable<TEntity>)

```
public Task<bool> AnyAsyncBy<TEntity>(IQueryable<TEntity> queryable) where TEntity
: class
```

Parameters

queryable [IQueryable](#) <TEntity>

Returns

[Task](#) <[bool](#)>

Type Parameters

TEntity

BeginTransactionAsync()

Begins a new transaction in the context of the database.

```
public Task<IDbContextTransaction> BeginTransactionAsync()
```

Returns

[Task](#) <[IDbContextTransaction](#)>

A task representing the asynchronous operation, containing the started database transaction.

CountAllAsync()

Counts the total number of all entities present in the database.

```
public Task<decimal> CountAllAsync()
```

Returns

[Task](#) <[decimal](#)>

Task with the total count of entities available.

CountAllAsyncBy(Expression<Func<T, bool>>)

Counts the number of entities that satisfy the provided condition.

```
public Task<decimal> CountAllAsyncBy(Expression<Func<T, bool>> where)
```

Parameters

where [Expression](#) <[Func](#) <T, [bool](#)>>

A delegate defining the condition for the entities to meet.

Returns

[Task](#) <[decimal](#)>

Task with the total count of entities that meet the specified condition.

CountAllAsyncBy<TEntity>(Expression<Func<TEntity, bool>>)

```
public Task<decimal> CountAllAsyncBy<TEntity>(Expression<Func<TEntity, bool>> where)  
where TEntity : class
```

Parameters

where [Expression](#) <[Func](#) <TEntity, [bool](#)>>

Returns

[Task](#) <[decimal](#)>

Type Parameters

TEntity

FindAsync(int)

```
public Task<T> FindAsync(int id)
```

Parameters

id [int](#)

Returns

[Task](#) <T>

FindAsync<TEntity>(int)

```
public Task<TEntity> FindAsync<TEntity>(int id) where TEntity : class
```

Parameters

id [int](#)

Returns

[Task](#) <TEntity>

Type Parameters

TEntity

GetAllAsync(ICoreSpecifications<T>?)

Gets all entities satisfying the provided specification in the database.

```
public Task<ICollection<T>> GetAllAsync(ICoreSpecifications<T>? coreSpecifications)
```

Parameters

coreSpecifications [ICoreSpecifications](#) <T>

Specifications to be met by the entities.

Returns

[Task](#) <[ICollection](#) <T>>

Task representing the asynchronous operation, containing the list of entities that meet the provided specification.

GetAllAsync(Expression<Func<T, bool>>)

Gets all entities that satisfy the provided condition.

```
public Task<ICollection<T>> GetAllAsync(Expression<Func<T, bool>> where)
```

Parameters

where [Expression](#) <[Func](#) <T, [bool](#)>>

A delegate defining the condition for the entities to meet.

Returns

[Task](#) <[ICollection](#) <T>>

A task representing the asynchronous operation, containing the entities that meet the specified condition.

GetAllAsync(string, ICoreSpecifications<T>?)

Gets all entities based on provided raw SQL query and specifications.

```
public Task<ICollection<T>> GetAllAsync(string query, ICoreSpecifications<T>? coreSpecifications)
```

Parameters

query [string](#)

Raw SQL query to be executed.

`coreSpecifications` [ICollection<T>](#)

Specifications to be met by the entities.

Returns

[Task](#) [ICollection](#) [T](#)

A task representing the asynchronous operation, containing the list of entities that meet the provided query and specification.

GetAllAsync(string, ICollection<DbParameter>, ICollection<T>?)

Gets all entities based on provided raw SQL query, parameters and specifications.

```
public Task<ICollection<T>> GetAllAsync(string query, ICollection<DbParameter> parameters, ICollection<T>? coreSpecifications)
```

Parameters

`query` [string](#)

Raw SQL query to be executed.

`parameters` [ICollection](#) [DbParameter](#)

List of parameters to be used in query.

`coreSpecifications` [ICollection<T>](#)

Specifications to be met by the entities.

Returns

[Task](#) [ICollection](#) [T](#)

A task representing the asynchronous operation, containing the list of entities that meet the provided query, parameters and specification.

GetAllAsync<TEntity>(ICoreSpecifications<TEntity>)

```
public Task<ICollection<TEntity>> GetAllAsync<TEntity>(ICoreSpecifications<TEntity>  
coreSpecifications) where TEntity : class
```

Parameters

coreSpecifications [ICoreSpecifications](#)<TEntity>

Returns

[Task](#)<[ICollection](#)<TEntity>>

Type Parameters

TEntity

GetAllAsync<TEntity>(Expression<Func<TEntity, bool>>)

```
public Task<ICollection<TEntity>> GetAllAsync<TEntity>(Expression<Func<TEntity,  
bool>> where) where TEntity : class
```

Parameters

where [Expression](#)<[Func](#)<TEntity, [bool](#)>>

Returns

[Task](#)<[ICollection](#)<TEntity>>

Type Parameters

TEntity

GetAllAsync<TEntity>(string)

```
public Task<ICollection<TEntity>> GetAllAsync<TEntity>(string query) where TEntity
: class
```

Parameters

query [string](#)

Returns

[Task](#) <[ICollection](#) <TEntity>>

Type Parameters

TEntity

GetAllAsync<TEntity>(string, ICollection<TEntity>)

```
public Task<ICollection<TEntity>> GetAllAsync<TEntity>(string query,
ICollection<TEntity> coreSpecifications) where TEntity : class
```

Parameters

query [string](#)

coreSpecifications [ICollection](#) <TEntity>

Returns

[Task](#) <[ICollection](#) <TEntity>>

Type Parameters

TEntity

GetAllAsync<TEntity>(string, ICollection<DbParameter>)

```
public Task<ICollection<TEntity>> GetAllAsync<TEntity>(string query,
ICollection<DbParameter> parameters) where TEntity : class
```

Parameters

query [string](#)

parameters [ICollection](#) <[DbParameter](#)>

Returns

[Task](#) <[ICollection](#) <TEntity>>

Type Parameters

TEntity

**GetAllAsync<TEntity>(string,
ICollection<DbParameter>,
ICoreSpecifications<TEntity>)**

```
public Task<ICollection<TEntity>> GetAllAsync<TEntity>(string query,
ICollection<DbParameter> parameters, ICoreSpecifications<TEntity>
coreSpecifications) where TEntity : class
```

Parameters

query [string](#)

parameters [ICollection](#) <[DbParameter](#)>

coreSpecifications [ICoreSpecifications](#) <TEntity>

Returns

[Task](#) <[ICollection](#) <TEntity>>

Type Parameters

TEntity

GetAllByQueryable<TEntity>(IQueryable<TEntity>)

Gets all entities based on provided IQueryable query.

```
public Task<ICollection<TEntity>> GetAllByQueryable<TEntity>  
(IQueryable<TEntity> query)
```

Parameters

query [IQueryable](#) <TEntity>

IQueryable query to be executed.

Returns

[Task](#) <[ICollection](#) <TEntity>>

A task representing the asynchronous operation, containing the list of entities that meet the provided query.

Type Parameters

TEntity

GetAllQueryable()

Gets an IQueryable of all entities.

```
public IQueryable<T> GetAllQueryable()
```

Returns

[IQueryable](#) <T>

IQueryable of all entities.

GetAllQueryable(ICoreSpecifications<T>?)

Gets entities based on provided specifications.

```
public IQueryable<T> GetAllQueryable(ICoreSpecifications<T>? coreSpecifications)
```

Parameters

coreSpecifications [ICoreSpecifications](#)<T>

Specifications to be met by the entities.

Returns

[IQueryable](#)<T>

IQueryable of entities that meet the provided specifications.

GetAllQueryable(Expression<Func<T, bool>>)

Gets entities by their specifications and provides a queryable list.

```
public IQueryable<T> GetAllQueryable(Expression<Func<T, bool>> where)
```

Parameters

where [Expression](#)<[Func](#)<T, [bool](#)>>

A delegate defining the condition for the entities to meet.

Returns

[IQueryable](#)<T>

IQueryable of entities that meet the specified condition.

GetAllQueryable(string, ICoreSpecifications<T>?)

Gets entities based on provided raw SQL query and specifications.

```
public IQueryable<T> GetAllQueryable(string query, ICoreSpecifications<T>?
coreSpecifications)
```

Parameters

query [string](#)

Raw SQL query to be executed.

coreSpecifications [ICoreSpecifications](#)<T>

Specifications to be met by the entities.

Returns

[IQueryable](#)<T>

A IQueryable representation of entities that meet the provided query and specification.

GetAllQueryable(string, ICollection<DbParameter>, ICoreSpecifications<T>?)

Gets entities based on provided raw SQL query, parameters and specifications.

```
public IQueryable<T> GetAllQueryable(string query, ICollection<DbParameter>
parameters, ICoreSpecifications<T>? coreSpecifications)
```

Parameters

query [string](#)

Raw SQL query to be executed.

parameters [ICollection](#)<[DbParameter](#)>

List of parameters to be used in the query.

coreSpecifications [ICoreSpecifications](#)<T>

Specifications to be met by the entities.

Returns

[IQueryable](#) <T>

A IQueryable representation of entities that meet the provided query, parameters and specification.

GetBy(ICoreSpecifications<T>)

Get an entity by the given specifications.

```
public Task<T?> GetBy(ICoreSpecifications<T> coreSpecifications)
```

Parameters

`coreSpecifications` [ICoreSpecifications](#) <T>

Specifications to be met by the entity.

Returns

[Task](#) <T>

A task representing the asynchronous operation, containing an entity that meets the provided specification.

GetBy(Expression<Func<T, bool>>)

Get an entity by the given specifications.

```
public Task<T?> GetBy(Expression<Func<T, bool>> where)
```

Parameters

`where` [Expression](#) <[Func](#) <T, [bool](#)>>

A delegate defining the condition for the entity to meet.

Returns

[Task](#) <T>

A task representing the asynchronous operation, containing an entity that meets the provided condition.

GetBy<TEntity>(ICoreSpecifications<TEntity>)

```
public Task<TEntity?> GetBy<TEntity>(ICoreSpecifications<TEntity>  
coreSpecifications) where TEntity : class
```

Parameters

coreSpecifications [ICoreSpecifications](#)<TEntity>

Returns

[Task](#) <TEntity>

Type Parameters

TEntity

GetBy<TEntity>(Expression<Func<TEntity, bool>>)

```
public Task<TEntity?> GetBy<TEntity>(Expression<Func<TEntity, bool>> where) where  
TEntity : class
```

Parameters

where [Expression](#) <[Func](#) <TEntity, [bool](#)>>

Returns

[Task](#) <TEntity>

Type Parameters

TEntity

GetBy<TEntity>(string, ICollection<DbParameter>, ICoreSpecifications<TEntity>)

```
public Task<TEntity?> GetBy<TEntity>(string query, ICollection<DbParameter> parameters, ICoreSpecifications<TEntity> coreSpecifications) where TEntity : class
```

Parameters

query [string](#)

parameters [ICollection](#)<[DbParameter](#)>

coreSpecifications [ICoreSpecifications](#)<TEntity>

Returns

[Task](#)<TEntity>

Type Parameters

TEntity

GetPagedResult(Page)

Retrieves a paginated list of entities from the repository that conforms to the specified page.

```
public Task<Paged<T>> GetPagedResult(Page page)
```

Parameters

page [Page](#)

The page number and size of the entities to be retrieved from the repository.

Returns

[Task](#) <[Paged](#)<T>>

A task that represents the asynchronous operation. The task result is a collection of entities that meet The core specifications, paginated based on the given page object. If no entities meet the specifications, the task result is an empty collection.

GetPagedResult(Page, ICoreSpecifications<T>)

```
public Task<Paged<T>> GetPagedResult(Page page, ICoreSpecifications<T>
coreSpecifications)
```

Parameters

page [Page](#)

coreSpecifications [ICoreSpecifications](#)<T>

Returns

[Task](#) <[Paged](#)<T>>

GetPagedResult(Page, string, ICollection<DbParameter>)

```
public Task<Paged<T>> GetPagedResult(Page page, string query,
ICollection<DbParameter> parameters)
```

Parameters

page [Page](#)

query [string](#)

parameters [ICollection](#)<[DbParameter](#)>

Returns

[Task](#) <[Paged](#)<T>>

GetPagedResult(Page, string, ICollection<DbParameter>, ICoreSpecifications<T>)

```
public Task<Paged<T>> GetPagedResult(Page page, string query,
    ICollection<DbParameter> parameters, ICoreSpecifications<T> coreSpecifications)
```

Parameters

page [Page](#)

query [string](#)

parameters [ICollection](#) <[DbParameter](#)>

coreSpecifications [ICoreSpecifications](#) <T>

Returns

[Task](#) <[Paged](#) <T>>

GetPagedResult<TEntity>(Page)

```
public Task<Paged<TEntity>> GetPagedResult<TEntity>(Page page) where TEntity : class
```

Parameters

page [Page](#)

Returns

[Task](#) <[Paged](#) <TEntity>>

Type Parameters

TEntity

GetPagedResult<TEntity>(Page, ICoreSpecifications<TEntity>)

```
public Task<Paged<TEntity>> GetPagedResult<TEntity>(Page page,
    ICoreSpecifications<TEntity> coreSpecifications) where TEntity : class
```

Parameters

page [Page](#)

coreSpecifications [ICoreSpecifications](#)<TEntity>

Returns

[Task](#)<[Paged](#)<TEntity>>

Type Parameters

TEntity

GetPagedResult<TEntity>(Page, string, ICollection<DbParameter>)

```
public Task<Paged<TEntity>> GetPagedResult<TEntity>(Page page, string query,
    ICollection<DbParameter> parameters) where TEntity : class
```

Parameters

page [Page](#)

query [string](#)

parameters [ICollection](#)<[DbParameter](#)>

Returns

[Task](#)<[Paged](#)<TEntity>>

Type Parameters

TEntity

GetPagedResult<TEntity>(Page, string,
ICollection<DbParameter>,
ICoreSpecifications<TEntity>)

```
public Task<Paged<TEntity>> GetPagedResult<TEntity>(Page page, string query,  
ICollection<DbParameter> parameters, ICoreSpecifications<TEntity>  
coreSpecifications) where TEntity : class
```

Parameters

page [Page](#)

query [string](#)

parameters [ICollection](#)<[DbParameter](#)>

coreSpecifications [ICoreSpecifications](#)<TEntity>

Returns

[Task](#)<[Paged](#)<TEntity>>

Type Parameters

TEntity

PageAllAsync(Page, ICoreSpecifications<T>?)

Gets entities based on provided page and specifications.

```
public Task<ICollection<T>> PageAllAsync(Page page, ICoreSpecifications<T>?  
coreSpecifications)
```

Parameters

page [Page](#)

Defines the page boundaries.

`coreSpecifications` [ICoreSpecifications](#)<T>

Specifications to be met by the entities.

Returns

[Task](#) <[ICollection](#)<T>>

A task with a collection of all entities meeting the provided page and specifications.

PageAllQueryable(Page, ICoreSpecifications<T>?)

Enables paging to the queryable list of represented entities based on provided page and specifications.

```
public IQueryable<T> PageAllQueryable(Page page, ICoreSpecifications<T>?
coreSpecifications)
```

Parameters

`page` [Page](#)

Defines the page boundaries.

`coreSpecifications` [ICoreSpecifications](#)<T>

Specifications to be met by the entities.

Returns

[IQueryable](#)<T>

A IQueryable sublist of all entities meeting the provided page and specifications.

Remove(T)

Deletes the entity from the database.

```
public void Remove(T entity)
```

Parameters

entity T

The entity to be removed.

RemoveAndSaveAsync(T)

```
public Task RemoveAndSaveAsync(T entity)
```

Parameters

entity T

Returns

[Task](#)

RemoveAndSaveAsync<TEntity>(TEntity)

```
public Task RemoveAndSaveAsync<TEntity>(TEntity entity) where TEntity : class
```

Parameters

entity TEntity

Returns

[Task](#)

Type Parameters

TEntity

RemoveRange(ICollection<T>)

Deletes a range of entities from the database.

```
public void RemoveRange(ICollection<T> entities)
```

Parameters

entities [ICollection<T>](#)

The entities to be removed.

RemoveRangeAndSaveAsync(ICollection<T>)

```
public Task RemoveRangeAndSaveAsync(ICollection<T> entities)
```

Parameters

entities [ICollection<T>](#)

Returns

[Task](#)

RemoveRangeAndSaveAsync<TEntity> (ICollection<TEntity>)

```
public Task RemoveRangeAndSaveAsync<TEntity>(ICollection<TEntity> entities) where  
TEntity : class
```

Parameters

entities [ICollection<TEntity>](#)

Returns

[Task](#)

Type Parameters

TEntity

RemoveRange<TEntity>(ICollection<TEntity>)

```
public void RemoveRange<TEntity>(ICollection<TEntity> entities) where TEntity : class
```

Parameters

entities [ICollection](#)  <TEntity>

Type Parameters

TEntity

Remove<TEntity>(TEntity)

```
public void Remove<TEntity>(TEntity entity) where TEntity : class
```

Parameters

entity TEntity

Type Parameters

TEntity

SaveAsync()

Save any changes in the context to the database.

```
public Task SaveAsync()
```

Returns

[Task](#)

Awaitable task.

Update(T)

Updates an entity in the database.

```
public void Update(T entity)
```

Parameters

entity T

Entity to be updated.

UpdateAndSaveAsync(T)

```
public Task UpdateAndSaveAsync(T entity)
```

Parameters

entity T

Returns

[Task](#)

UpdateAndSaveAsync<TEntity>(TEntity)

```
public Task UpdateAndSaveAsync<TEntity>(TEntity entity) where TEntity : class
```

Parameters

entity TEntity

Returns

[Task](#)

Type Parameters

TEntity

UpdateRange(ICollection<T>)

Method to update a range of entities in the repository.

```
public void UpdateRange(ICollection<T> entities)
```

Parameters

entities [ICollection](#)<T>

Collection of entities which need to be updated.

UpdateRangeAndSaveAsync(ICollection<T>)

```
public Task UpdateRangeAndSaveAsync(ICollection<T> entities)
```

Parameters

entities [ICollection](#)<T>

Returns

[Task](#)

UpdateRangeAndSaveAsync<TEntity> (ICollection<TEntity>)

```
public Task UpdateRangeAndSaveAsync<TEntity>(ICollection<TEntity> entities) where
TEntity : class
```

Parameters

entities [ICollection](#) <TEntity>

Returns

[Task](#)

Type Parameters

TEntity

UpdateRange<TEntity>(ICollection<TEntity>)

```
public void UpdateRange<TEntity>(ICollection<TEntity> entities) where TEntity
: class
```

Parameters

entities [ICollection](#) <TEntity>

Type Parameters

TEntity

Update<TEntity>(TEntity)

```
public void Update<TEntity>(TEntity entity) where TEntity : class
```

Parameters

entity TEntity

Type Parameters

TEntity

Interface ICoreService<T>

Namespace: [Solstice.Applications.Core](#)

Assembly: Solstice.Applications.dll

This interface describes an abstraction for a data manipulation service on a given type of CoreModel. It includes methods for CRUD operations, queries for specific entities, counting entities, starting transactions, and more.

```
public interface ICoreService<T> where T : class
```

Type Parameters

T

The type of the class to be processed by the service.

Methods

AddAndSaveAsync(T)

Task **AddAndSaveAsync**(T entity)

Parameters

entity T

Returns

[Task](#)

AddAndSaveAsync<TEntity>(TEntity)

Task **AddAndSaveAsync**<TEntity>(TEntity entity) where TEntity : class

Parameters

entity TEntity

Returns

[Task](#)

Type Parameters

TEntity

AddAsync(T)

Add entity to repository

```
Task AddAsync(T entity)
```

Parameters

entity T

The entity object

Returns

[Task](#)

AddAsync<TEntity>(TEntity)

```
Task AddAsync<TEntity>(TEntity entity) where TEntity : class
```

Parameters

entity TEntity

Returns

[Task](#)

Type Parameters

TEntity

AddRangeAndSaveAsync(ICollection<T>)

```
Task AddRangeAndSaveAsync(ICollection<T> entities)
```

Parameters

entities [ICollection](#) <T>

Returns

[Task](#)

AddRangeAndSaveAsync<TEntity> (ICollection<TEntity>)

```
Task AddRangeAndSaveAsync<TEntity>(ICollection<TEntity> entities) where TEntity  
: class
```

Parameters

entities [ICollection](#) <TEntity>

Returns

[Task](#)

Type Parameters

TEntity

AddRangeAsync(ICollection<T>)

Add range of entities to repository

```
Task AddRangeAsync(ICollection<T> entities)
```

Parameters

entities [ICollection](#)<T>

The entities list

Returns

[Task](#)

AddRangeAsync<TEntity>(ICollection<TEntity>)

```
Task AddRangeAsync<TEntity>(ICollection<TEntity> entities) where TEntity : class
```

Parameters

entities [ICollection](#)<TEntity>

Returns

[Task](#)

Type Parameters

TEntity

AnyAsyncBy(Expression<Func<T, bool>>)

Checks if any entity in the repository matches the provided expression

```
Task<bool> AnyAsyncBy(Expression<Func<T, bool>> where)
```

Parameters

where [Expression](#) <[Func](#) <T, [bool](#)>>

The expression that describes the condition to match

Returns

[Task](#) <[bool](#)>

True if any entity matches the condition, False otherwise

AnyAsyncBy<TEntity>(Expression<Func<TEntity, bool>>)

```
Task<bool> AnyAsyncBy<TEntity>(Expression<Func<TEntity, bool>> where) where TEntity : class
```

Parameters

where [Expression](#) <[Func](#) <TEntity, [bool](#)>>

Returns

[Task](#) <[bool](#)>

Type Parameters

TEntity

AnyAsyncBy<TEntity>(IQueryable<TEntity>)

```
Task<bool> AnyAsyncBy<TEntity>(IQueryable<TEntity> queryable) where TEntity : class
```

Parameters

queryable [IQueryable](#) <TEntity>

Returns

[Task](#) <[bool](#)>

Type Parameters

TEntity

BeginTransactionAsync()

Begins a new transaction asynchronously.

```
Task<IDbContextTransaction> BeginTransactionAsync()
```

Returns

[Task](#) <[IDbContextTransaction](#)>

A task that represents the asynchronous operation. The task result is an IDbContextTransaction object which encapsulates all information about the transaction.

CountAllAsync()

Counts all entities in repository

```
Task<decimal> CountAllAsync()
```

Returns

[Task](#) <[decimal](#)>

Total count of all entities

CountAllAsyncBy(Expression<Func<T, bool>>)

Counts the total entities that match the provided expression

```
Task<decimal> CountAllAsyncBy(Expression<Func<T, bool>> where)
```

Parameters

where [Expression](#) <[Func](#) <T, [bool](#)>>

The expression that describes the condition to match

Returns

[Task](#) <[decimal](#)>

Total matched entities count

CountAllAsyncBy<TEntity>(Expression<Func<TEntity, bool>>)

```
Task<decimal> CountAllAsyncBy<TEntity>(Expression<Func<TEntity, bool>> where) where  
TEntity : class
```

Parameters

where [Expression](#) <[Func](#) <TEntity, [bool](#)>>

Returns

[Task](#) <[decimal](#)>

Type Parameters

TEntity

FindAsync(int)

```
Task<T> FindAsync(int id)
```

Parameters

id [int](#)

Returns

[Task](#) <T>

FindAsync<TEntity>(int)

```
Task<TEntity> FindAsync<TEntity>(int id) where TEntity : class
```

Parameters

id [int](#)

Returns

[Task](#) <TEntity>

Type Parameters

TEntity

GetAllAsync(ICoreSpecifications<T>?)

Retrieves a collection of all entities from the repository asynchronously.

```
Task<ICollection<T>> GetAllAsync(ICoreSpecifications<T>? coreSpecifications)
```

Parameters

coreSpecifications [ICoreSpecifications](#) <T>

The specifications that entities must meet to be retrieved from the repository.

Returns

[Task](#) <[ICollection](#) <T>>

A task that represents the asynchronous operation. The task result contains a collection of entities satisfying The core specifications or an empty collection if no matches.

GetAllAsync(Expression<Func<T, bool>>)

Retrieves a collection of entities from the repository that satisfy the specified condition asynchronously.

```
Task<ICollection<T>> GetAllAsync(Expression<Func<T, bool>> where)
```

Parameters

where [Expression](#) <[Func](#) <T, [bool](#)>>

An expression representing a condition to be matched by entities in the repository.

Returns

[Task](#) <[ICollection](#) <T>>

A task that represents the asynchronous operation. The task result contains a collection of entities satisfying the condition or an empty collection if there are no matches.

GetAllAsync(string, ICoreSpecifications<T>?)

Retrieves a collection of all entities from the repository asynchronously based on a provided SQL-like query and specifications.

```
Task<ICollection<T>> GetAllAsync(string query, ICoreSpecifications<T>? coreSpecifications)
```

Parameters

query [string](#)

A SQL-like query that retrieves entities from the repository.

coreSpecifications [ICollection<T>](#)

The specifications that entities must meet to be retrieved from the repository.

Returns

[Task<ICollection<T>>](#)

A task that represents the asynchronous operation. The task results contains a collection of entities satisfying the query and The core specifications or an empty collection if no matches.

GetAllAsync(string, ICollection<DbParameter>, ICollection<T>?)

Retrieves a collection of all entities from the repository asynchronously based on a provided SQL-like query, parameters and specifications.

```
Task<ICollection<T>> GetAllAsync(string query, ICollection<DbParameter> parameters,
                                ICollection<T>? coreSpecifications)
```

Parameters

query [string](#)

A SQL-like query that retrieves entities from the repository.

parameters [ICollection<DbParameter>](#)

A collection of database parameters used in the query

coreSpecifications [ICollection<T>](#)

The specifications that entities must meet to be retrieved from the repository.

Returns

[Task<ICollection<T>>](#)

A task that represents the asynchronous operation. The task results contains a collection of entities satisfying the query, parameters and The core specifications or an empty collection if no matches.

GetAllAsync<TEntity>(ICoreSpecifications<TEntity>)

```
Task<ICollection<TEntity>> GetAllAsync<TEntity>(ICoreSpecifications<TEntity>  
coreSpecifications) where TEntity : class
```

Parameters

coreSpecifications [ICoreSpecifications](#)<TEntity>

Returns

[Task](#)<[ICollection](#)<TEntity>>

Type Parameters

TEntity

GetAllAsync<TEntity>(Expression<Func<TEntity, bool>>)

```
Task<ICollection<TEntity>> GetAllAsync<TEntity>(Expression<Func<TEntity, bool>>  
where) where TEntity : class
```

Parameters

where [Expression](#)<[Func](#)<TEntity, [bool](#)>>

Returns

[Task](#)<[ICollection](#)<TEntity>>

Type Parameters

TEntity

GetAllAsync<TEntity>(string)

```
Task<ICollection<TEntity>> GetAllAsync<TEntity>(string query) where TEntity : class
```

Parameters

query [string](#)

Returns

[Task](#) <[ICollection](#) <TEntity>>

Type Parameters

TEntity

GetAllAsync<TEntity>(string, ICoreSpecifications<TEntity>)

```
Task<ICollection<TEntity>> GetAllAsync<TEntity>(string query,
ICoreSpecifications<TEntity> coreSpecifications) where TEntity : class
```

Parameters

query [string](#)

coreSpecifications [ICoreSpecifications](#) <TEntity>

Returns

[Task](#) <[ICollection](#) <TEntity>>

Type Parameters

TEntity

GetAllAsync<TEntity>(string, ICollection<DbParameter>)

```
Task<ICollection<TEntity>> GetAllAsync<TEntity>(string query,  
ICollection<DbParameter> parameters) where TEntity : class
```

Parameters

query [string](#)

parameters [ICollection](#) <[DbParameter](#)>

Returns

[Task](#) <[ICollection](#) <TEntity>>

Type Parameters

TEntity

GetAllAsync<TEntity>(string, ICollection<DbParameter>, ICoreSpecifications<TEntity>)

```
Task<ICollection<TEntity>> GetAllAsync<TEntity>(string query,  
ICollection<DbParameter> parameters, ICoreSpecifications<TEntity>  
coreSpecifications) where TEntity : class
```

Parameters

query [string](#)

parameters [ICollection](#) <[DbParameter](#)>

coreSpecifications [ICoreSpecifications](#) <TEntity>

Returns

[Task](#) <[ICollection](#) <TEntity>>

Type Parameters

TEntity

GetAllByQueryable<TEntity>(IQueryable<TEntity>)

Retrieves a collection of entities from a specified IQueryable.

```
Task<ICollection<TEntity>> GetAllByQueryable<TEntity>(IQueryable<TEntity> query)
```

Parameters

query [IQueryable](#) <TEntity>

An IQueryable that retrieves entities from the repository.

Returns

[Task](#) <[ICollection](#) <TEntity>>

A task that represents the asynchronous operation. The task result contains a collection of entities that satisfy the query or an empty collection if no matches.

Type Parameters

TEntity

GetAllQueryable()

Retrieves all entities from the repository asynchronously.

```
IQueryable<T> GetAllQueryable()
```

Returns

[IQueryable](#) <T>

A queryable collection of all entities in the repository.

GetAllQueryable(ICoreSpecifications<T>?)

Retrieves entities that match the specified Solstice specifications from the repository asynchronously.

```
IQueryable<T> GetAllQueryable(ICoreSpecifications<T>? coreSpecifications)
```

Parameters

coreSpecifications [ICoreSpecifications](#)<T>

The specifications that entities must meet to be retrieved from the repository.

Returns

[IQueryable](#)<T>

A queryable collection of entities that satisfy The core specifications.

GetAllQueryable(Expression<Func<T, bool>>)

Retrieves entities that match the specified condition from the repository asynchronously.

```
IQueryable<T> GetAllQueryable(Expression<Func<T, bool>> where)
```

Parameters

where [Expression](#)<[Func](#)<T, [bool](#)>>

An expression representing a condition to be matched by entities in the repository.

Returns

[IQueryable](#)<T>

A queryable collection of entities matching the condition.

GetAllQueryable(string, ICoreSpecifications<T>?)

Retrieves entities from the repository based on a provided SQL-like query and specifications asynchronously.

```
IQueryable<T> GetAllQueryable(string query, ICoreSpecifications<T>? coreSpecifications)
```

Parameters

query [string](#)

A SQL-like query that retrieves entities from the repository.

coreSpecifications [ICoreSpecifications](#)<T>

The specifications that entities must meet to be retrieved from the repository.

Returns

[IQueryable](#)<T>

A queryable collection of entities satisfying the query and The core specifications.

GetAllQueryable(string, ICollection<DbParameter>, ICoreSpecifications<T>?)

Retrieves entities from the repository based on a provided SQL-like query, parameters and specifications asynchronously.

```
IQueryable<T> GetAllQueryable(string query, ICollection<DbParameter> parameters, ICoreSpecifications<T>? coreSpecifications)
```

Parameters

query [string](#)

A SQL-like query that retrieves entities from the repository.

parameters [ICollection](#)<[DbParameter](#)>

A collection of database parameters used in the query

`coreSpecifications` [ICoreSpecifications](#)<T>

The specifications that entities must meet to be retrieved from the repository.

Returns

[IQueryable](#)<T>

A queryable collection of entities satisfying the query, parameters and The core specifications.

GetBy(ICoreSpecifications<T>)

Retrieves an entity from the repository that meets the criteria specified by the given Solstice specification.

```
Task<T?> GetBy(ICoreSpecifications<T> coreSpecifications)
```

Parameters

`coreSpecifications` [ICoreSpecifications](#)<T>

The specifications that an entity must meet to be retrieved from the repository.

Returns

[Task](#)<T>

A task that represents the asynchronous operation. The task result is the first entity that satisfies the specified Solstice specifications. If no entity satisfies the specifications, the task result is null.

GetBy(Expression<Func<T, bool>>)

Retrieves an entity that matches the specified condition from the repository.

```
Task<T?> GetBy(Expression<Func<T, bool>> where)
```

Parameters

where [Expression](#) <[Func](#) <T, [bool](#)>>>

An expression representing a condition to be matched by entities in the repository.

Returns

[Task](#) <T>

A task that represents the asynchronous operation. The task result contains the first matching entity or null if no entity matches the condition.

GetBy<TEntity>(ICoreSpecifications<TEntity>)

```
Task<TEntity?> GetBy<TEntity>(ICoreSpecifications<TEntity> coreSpecifications) where  
TEntity : class
```

Parameters

coreSpecifications [ICoreSpecifications](#)<TEntity>

Returns

[Task](#) <TEntity>

Type Parameters

TEntity

GetBy<TEntity>(Expression<Func<TEntity, bool>>)

```
Task<TEntity?> GetBy<TEntity>(Expression<Func<TEntity, bool>> where) where TEntity  
: class
```

Parameters

where [Expression](#) <[Func](#) <TEntity, [bool](#)>>>

Returns

[Task](#) <TEntity>

Type Parameters

TEntity

GetBy<TEntity>(string, ICollection<DbParameter>, ICoreSpecifications<TEntity>)

```
Task<TEntity?> GetBy<TEntity>(string query, ICollection<DbParameter> parameters,
ICoreSpecifications<TEntity> coreSpecifications) where TEntity : class
```

Parameters

query [string](#)

parameters [ICollection](#) <[DbParameter](#)>

coreSpecifications [ICoreSpecifications](#) <TEntity>

Returns

[Task](#) <TEntity>

Type Parameters

TEntity

GetPagedResult(Page)

Retrieves a paginated list of entities from the repository that conforms to the specified page.

```
Task<Paged<T>> GetPagedResult(Page page)
```

Parameters

page [Page](#)

The page number and size of the entities to be retrieved from the repository.

Returns

[Task](#) [Paged](#) <T>>

A task that represents the asynchronous operation. The task result is a collection of entities that meet The core specifications, paginated based on the given page object. If no entities meet the specifications, the task result is an empty collection.

GetPagedResult(Page, ICoreSpecifications<T>)

```
Task<Paged<T>> GetPagedResult(Page page, ICoreSpecifications<T> coreSpecifications)
```

Parameters

page [Page](#)

coreSpecifications [ICoreSpecifications](#) <T>

Returns

[Task](#) [Paged](#) <T>>

GetPagedResult(Page, string, ICollection<DbParameter>)

```
Task<Paged<T>> GetPagedResult(Page page, string query, ICollection<DbParameter> parameters)
```

Parameters

page [Page](#)

query [string](#)

parameters [ICollection](#) <[DbParameter](#)>

Returns

[Task](#) <[Paged](#) <T>>

GetPagedResult(Page, string, ICollection<DbParameter>, ICoreSpecifications<T>)

```
Task<Paged<T>> GetPagedResult(Page page, string query, ICollection<DbParameter> parameters, ICoreSpecifications<T> coreSpecifications)
```

Parameters

page [Page](#)

query [string](#)

parameters [ICollection](#) <[DbParameter](#)>

coreSpecifications [ICoreSpecifications](#) <T>

Returns

[Task](#) <[Paged](#) <T>>

GetPagedResult<TEntity>(Page)

```
Task<Paged<TEntity>> GetPagedResult<TEntity>(Page page) where TEntity : class
```

Parameters

page [Page](#)

Returns

[Task](#) <[Paged](#) <TEntity>>

Type Parameters

TEntity

GetPagedResult<TEntity>(Page, ICoreSpecifications<TEntity>)

```
Task<Paged<TEntity>> GetPagedResult<TEntity>(Page page, ICoreSpecifications<TEntity>
coreSpecifications) where TEntity : class
```

Parameters

page [Page](#)

coreSpecifications [ICoreSpecifications](#)<TEntity>

Returns

[Task](#) [<Paged](#)<TEntity>>

Type Parameters

TEntity

GetPagedResult<TEntity>(Page, string, ICollection<DbParameter>)

```
Task<Paged<TEntity>> GetPagedResult<TEntity>(Page page, string query,
ICollection<DbParameter> parameters) where TEntity : class
```

Parameters

page [Page](#)

query [string](#)

parameters [ICollection](#) [<DbParameter](#)>

Returns

[Task](#) <[Paged](#)<TEntity>>

Type Parameters

TEntity

GetPagedResult<TEntity>(Page, string,
ICollection<DbParameter>,
ICoreSpecifications<TEntity>)

```
Task<Paged<TEntity>> GetPagedResult<TEntity>(Page page, string query,  
ICollection<DbParameter> parameters, ICoreSpecifications<TEntity>  
coreSpecifications) where TEntity : class
```

Parameters

page [Page](#)

query [string](#)

parameters [ICollection](#) <[DbParameter](#)>

coreSpecifications [ICoreSpecifications](#)<TEntity>

Returns

[Task](#) <[Paged](#)<TEntity>>

Type Parameters

TEntity

PageAllAsync(Page, ICoreSpecifications<T>?)

Retrieves a collection of entities from the repository that satisfy the specified condition asynchronously, and do paging on them.

```
Task<ICollection<T>> PageAllAsync(Page page, ICoreSpecifications<T>?)
```

coreSpecifications)

Parameters

page [Page](#)

The page number and size of the entities to be retrieved from the repository.

coreSpecifications [ICoreSpecifications](#)<T>

The specifications that entities must meet to be retrieved from the repository.

Returns

[Task](#) <[ICollection](#) <T>>

A task that represents the asynchronous operation. The task result contains a collection of entities satisfying the condition. or an empty collection if no matches, paged by the given information in Page object.

PageAllQueryable(Page, ICoreSpecifications<T>?)

Retrieves a queryable collection of entities from the repository that satisfy the specified condition asynchronously, and do paging on them.

```
IQueryable<T> PageAllQueryable(Page page, ICoreSpecifications<T>?  
coreSpecifications)
```

Parameters

page [Page](#)

The page number and size of the entities to be retrieved from the repository.

coreSpecifications [ICoreSpecifications](#)<T>

The specifications that entities must meet to be retrieved from the repository.

Returns

[IQueryable](#) <T>

A queryable collection of all entities in the repository that fulfill the condition, paged by the given information in page object.

Remove(T)

Remove entity from repository

```
void Remove(T entity)
```

Parameters

entity T

The entity object

RemoveAndSaveAsync(T)

```
Task RemoveAndSaveAsync(T entity)
```

Parameters

entity T

Returns

[Task](#)

RemoveAndSaveAsync<TEntity>(TEntity)

```
Task RemoveAndSaveAsync<TEntity>(TEntity entity) where TEntity : class
```

Parameters

entity TEntity

Returns

[Task](#)

Type Parameters

TEntity

RemoveRange(ICollection<T>)

Remove range of entities from repository

```
void RemoveRange(ICollection<T> entities)
```

Parameters

entities [ICollection](#)<T>

The entities list

RemoveRangeAndSaveAsync(ICollection<T>)

```
Task RemoveRangeAndSaveAsync(ICollection<T> entities)
```

Parameters

entities [ICollection](#)<T>

Returns

[Task](#)

RemoveRangeAndSaveAsync<TEntity> (ICollection<TEntity>)

```
Task RemoveRangeAndSaveAsync<TEntity>(ICollection<TEntity> entities) where TEntity  
: class
```


Parameters

entities [ICollection](#) <TEntity>

Returns

[Task](#)

Type Parameters

TEntity

RemoveRange<TEntity>(ICollection<TEntity>)

```
void RemoveRange<TEntity>(ICollection<TEntity> entities) where TEntity : class
```

Parameters

entities [ICollection](#) <TEntity>

Type Parameters

TEntity

Remove<TEntity>(TEntity)

```
void Remove<TEntity>(TEntity entity) where TEntity : class
```

Parameters

entity TEntity

Type Parameters

TEntity

SaveAsync()

Save changes in repository

```
Task SaveAsync()
```

Returns

[Task](#)

Update(T)

Update entity in repository

```
void Update(T entity)
```

Parameters

entity T

The entity object

UpdateAndSaveAsync(T)

```
Task UpdateAndSaveAsync(T entity)
```

Parameters

entity T

Returns

[Task](#)

UpdateAndSaveAsync<TEntity>(TEntity)

```
Task UpdateAndSaveAsync<TEntity>(TEntity entity) where TEntity : class
```

Parameters

entity TEntity

Returns

[Task](#)

Type Parameters

TEntity

UpdateRange(ICollection<T>)

Update range of entities in repository

```
void UpdateRange(ICollection<T> entities)
```

Parameters

entities [ICollection](#)<T>

The entities list

UpdateRangeAndSaveAsync(ICollection<T>)

```
Task UpdateRangeAndSaveAsync(ICollection<T> entities)
```

Parameters

entities [ICollection](#)<T>

Returns

[Task](#)

UpdateRangeAndSaveAsync<TEntity> (ICollection<TEntity>)

```
Task UpdateRangeAndSaveAsync<TEntity>(ICollection<TEntity> entities) where TEntity : class
```

Parameters

entities [ICollection](#)<TEntity>

Returns

[Task](#)

Type Parameters

TEntity

UpdateRange<TEntity>(ICollection<TEntity>)

```
void UpdateRange<TEntity>(ICollection<TEntity> entities) where TEntity : class
```

Parameters

entities [ICollection](#)<TEntity>

Type Parameters

TEntity

Update<TEntity>(TEntity)

```
void Update<TEntity>(TEntity entity) where TEntity : class
```

Parameters

`entity` TEntity

Type Parameters

`TEntity`

Namespace Solstice.Applications. Injections

Classes

[ServiceInjections](#)

A static helper class for service injections.

Class ServiceInjections

Namespace: [Solstice.Applications.Injections](#)

Assembly: Solstice.Applications.dll








A static helper class for service injections.

```
public static class ServiceInjections
```

Inheritance

[object](#)  ← ServiceInjections

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Methods

AddServices(IServiceCollection)

Extension method for the IServiceCollection interface. Adds services to the collection.

```
public static void AddServices(this IServiceCollection services)
```

Parameters

services [IServiceCollection](#) 

The IServiceCollection to which the services need to be added.

Remarks

This method scans all types in all assemblies of the current application domain. It looks for types that have the ServiceAttribute. If no such types are found, an exception about no services is thrown. If there are such types, they are all added as services with scope lifetime into the passed IServiceCollection.

Exceptions

[CoreException](#)

Throws if there are no services with the ServiceAttribute present.

AddServices(IServiceCollection, string)

```
[Obsolete("AddServices with namespace is deprecated, please use AddServices or  
ScanServicesIn with Service Attribute instead.")]
```

```
public static void AddServices(this IServiceCollection services,  
string assemblyName)
```

Parameters

services [IServiceCollection](#)

assemblyName [string](#)

ScanServicesIn(IServiceCollection, Assembly)

Extension method for the IServiceCollection interface. Adds services to the collection.

```
public static void ScanServicesIn(this IServiceCollection services,  
Assembly assembly)
```

Parameters

services [IServiceCollection](#)

The IServiceCollection to which the services need to be added.

assembly [Assembly](#)

The assembly to load

Remarks

This method scans all types in the specified assembly. It looks for types that have the ServiceAttribute. If no such types are found, an exception about no services is thrown. If

there are such types, they are all added as services with scope lifetime into the passed IServiceCollection.

Exceptions

[CoreException](#)

Throws if there are no services with the ServiceAttribute present.

ScanServicesIn(IServiceCollection, string)

Extension method for the IServiceCollection interface. Adds services to the collection.

```
public static void ScanServicesIn(this IServiceCollection services,  
    string assemblyName)
```

Parameters

services [IServiceCollection](#)

The IServiceCollection to which the services need to be added.

assemblyName [string](#)

The name of the assembly to load

Remarks

This method scans all types in the specified assembly. It looks for types that have the ServiceAttribute. If no such types are found, an exception about no services is thrown. If there are such types, they are all added as services with scope lifetime into the passed IServiceCollection.

Exceptions

[CoreException](#)

Throws if there are no services with the ServiceAttribute present.