Namespace Solstice.API.Attributes

Classes

DeleteAttribute

DeleteAttribute is a class that extends the HttpDeleteAttribute class in the Microsoft.AspNetCore.Mvc package. It allows customization of the DELETE HTTP verb attribute in a Controller action method signature.

GetAttribute

GetAttribute class inherits from the HttpGetAttribute class in Microsoft.AspNetCore.Mvc. It works as a HTTP GET method attribute with optional route template. This class has two constructors. The default constructor creates a new GetAttribute with no parameters. The second one accepts a string parameter that represents a route template.

HeadAttribute

Represents an attribute that specifies that an action supports the HTTP HEAD method.

PatchAttribute

The PatchAttribute class represents a custom attribute to indicate that an action method should handle HTTP PATCH requests. It has been derived from the HttpPatchAttribute class provided by the ASP.NET Core MVC framework.

PostAttribute

The 'PostAttribute' class is a decorator extending from the 'HttpPostAttribute' class in the Microsoft ASP.NET Core MVC framework. It is used to specify the HTTP POST request methods for the action methods in the controller class.

PutAttribute

The PutAttribute class inherits from the HttpPutAttribute class and represents an attribute that is used to indicate the HTTP PUT method for an action within a controller.

Class DeleteAttribute

Namespace: Solstice.API.Attributes

Assembly: Solstice.API.dll

DeleteAttribute is a class that extends the HttpDeleteAttribute class in the Microsoft.AspNetCore.Mvc package. It allows customization of the DELETE HTTP verb attribute in a Controller action method signature.

```
public class DeleteAttribute : HttpDeleteAttribute, IActionHttpMethodProvider,
IRouteTemplateProvider
```

Inheritance

object ← Attribute ← HttpMethodAttribute ← HttpDeleteAttribute ← DeleteAttribute

Implements

IActionHttpMethodProvider, IRouteTemplateProvider

Inherited Members

HttpMethodAttribute.HttpMethods , HttpMethodAttribute.Template , HttpMethodAttribute.Order , HttpMethodAttribute.Name , Attribute.Equals(object) , Attribute.GetCustomAttribute(Assembly, Type) , Attribute.GetCustomAttribute(Assembly, Type, bool) , Attribute.GetCustomAttribute(MemberInfo, Type) , Attribute.GetCustomAttribute(MemberInfo, Type, bool) , Attribute.GetCustomAttribute(Module, Type) , Attribute.GetCustomAttribute(Module, Type, bool) , Attribute.GetCustomAttribute(ParameterInfo, Type) , Attribute.GetCustomAttribute(ParameterInfo, Type, bool) , Attribute.GetCustomAttributes(Assembly) , Attribute.GetCustomAttributes(Assembly, bool) , Attribute.GetCustomAttributes(Assembly, Type) , Attribute.GetCustomAttributes(Assembly, Type, bool) , Attribute.GetCustomAttributes(MemberInfo) , Attribute.GetCustomAttributes(MemberInfo, bool) , Attribute.GetCustomAttributes(MemberInfo, Type) , Attribute.GetCustomAttributes(MemberInfo, Type, bool) , Attribute.GetCustomAttributes(Module) , Attribute.GetCustomAttributes(Module, bool) , Attribute.GetCustomAttributes(Module, Type) , Attribute.GetCustomAttributes(Module, Type, bool) ,

Attribute.GetCustomAttributes(ParameterInfo) , Attribute.GetCustomAttributes(ParameterInfo, bool) , Attribute.GetCustomAttributes(ParameterInfo, Type) , Attribute.GetCustomAttributes(ParameterInfo, Type, bool) , Attribute.GetHashCode() , Attribute.IsDefaultAttribute() , Attribute.IsDefined(Assembly, Type) , Attribute.IsDefined(Assembly, Type, bool) , Attribute.IsDefined(MemberInfo, Type) , Attribute.IsDefined(MemberInfo, Type, bool) , Attribute.IsDefined(Module, Type) , Attribute.IsDefined(Module, Type, bool) , Attribute.IsDefined(ParameterInfo, Type) , Attribute.IsDefined(ParameterInfo, Type, bool) , Attribute.Match(object) , Attribute.TypeId , object.Equals(object, object) , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

DeleteAttribute()

Default constructor that creates a new instance of DeleteAttribute.

```
public DeleteAttribute()
```

DeleteAttribute(string)

Constructor that creates a new instance of DeleteAttribute with a route template.

```
public DeleteAttribute(string template)
```

Parameters

`template` string

A string that specifies the URI route template for this attribute.

Class GetAttribute

Namespace: Solstice.API.Attributes

Assembly: Solstice.API.dll

GetAttribute class inherits from the HttpGetAttribute class in Microsoft.AspNetCore.Mvc. It works as a HTTP GET method attribute with optional route template. This class has two constructors. The default constructor creates a new GetAttribute with no parameters. The second one accepts a string parameter that represents a route template.

```
public class GetAttribute : HttpGetAttribute, IActionHttpMethodProvider,
IRouteTemplateProvider
```

Inheritance

object ← Attribute ← HttpMethodAttribute ← HttpGetAttribute ← GetAttribute

Implements

IActionHttpMethodProvider, IRouteTemplateProvider

Inherited Members

HttpMethodAttribute.HttpMethods , HttpMethodAttribute.Template , HttpMethodAttribute.Order , HttpMethodAttribute.Name , Attribute.Equals(object) , Attribute.GetCustomAttribute(Assembly, Type) , Attribute.GetCustomAttribute(Assembly, Type, bool) , Attribute.GetCustomAttribute(MemberInfo, Type) , Attribute.GetCustomAttribute(MemberInfo, Type, bool) , Attribute.GetCustomAttribute(Module, Type) , Attribute.GetCustomAttribute(Module, Type, bool) , Attribute.GetCustomAttribute(ParameterInfo, Type) , Attribute.GetCustomAttribute(ParameterInfo, Type, bool) , Attribute.GetCustomAttributes(Assembly) , Attribute.GetCustomAttributes(Assembly, bool) , Attribute.GetCustomAttributes(Assembly, Type) , Attribute.GetCustomAttributes(Assembly, Type, bool) , Attribute.GetCustomAttributes(MemberInfo) , Attribute.GetCustomAttributes(MemberInfo, bool) , Attribute.GetCustomAttributes(MemberInfo, Type) , Attribute.GetCustomAttributes(MemberInfo, Type, bool) , Attribute.GetCustomAttributes(Module) , Attribute.GetCustomAttributes(Module, bool) , Attribute.GetCustomAttributes(Module, Type) ,

Attribute.GetCustomAttributes(Module, Type, bool) , Attribute.GetCustomAttributes(ParameterInfo) , Attribute.GetCustomAttributes(ParameterInfo, bool) , Attribute.GetCustomAttributes(ParameterInfo, Type) , Attribute.GetCustomAttributes(ParameterInfo, Type, bool) , Attribute.GetHashCode() , Attribute.IsDefaultAttribute() , Attribute.IsDefined(Assembly, Type) , Attribute.IsDefined(Assembly, Type, bool) , Attribute.IsDefined(MemberInfo, Type) , Attribute.IsDefined(MemberInfo, Type, bool) , Attribute.IsDefined(Module, Type) , Attribute.IsDefined(Module, Type, bool) , Attribute.IsDefined(ParameterInfo, Type) , Attribute.IsDefined(ParameterInfo, Type, bool) , Attribute.Match(object) , Attribute.TypeId , object.Equals(object, object) , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Remarks

This attribute is applied to the actions and is used to influence the action selection process during the Routing in ASP.Net Core. It helps the routing mechanism to select the correct action method to execute when a given request arrives. The route template is an optional parameter which can be used to define the route for this attribute.

Constructors

GetAttribute()

```
public GetAttribute()
```

GetAttribute(string)

```
public GetAttribute(string template)
```

Parameters

`template` string

Class HeadAttribute

Namespace: Solstice.API.Attributes

Assembly: Solstice.API.dll

Represents an attribute that specifies that an action supports the HTTP HEAD method.

```
public class HeadAttribute : HttpHeadAttribute, IActionHttpMethodProvider,
IRouteTemplateProvider
```

Inheritance

object ← Attribute ← HttpMethodAttribute ← HttpHeadAttribute ← HeadAttribute

Implements

IActionHttpMethodProvider, IRouteTemplateProvider

Inherited Members

HttpMethodAttribute.HttpMethods , HttpMethodAttribute.Template , HttpMethodAttribute.Order , HttpMethodAttribute.Name , Attribute.Equals(object) , Attribute.GetCustomAttribute(Assembly, Type) , Attribute.GetCustomAttribute(Assembly, Type, bool) , Attribute.GetCustomAttribute(MemberInfo, Type) , Attribute.GetCustomAttribute(MemberInfo, Type, bool) , Attribute.GetCustomAttribute(Module, Type) , Attribute.GetCustomAttribute(Module, Type, bool) , Attribute.GetCustomAttribute(ParameterInfo, Type) , Attribute.GetCustomAttribute(ParameterInfo, Type, bool) , Attribute.GetCustomAttributes(Assembly) , Attribute.GetCustomAttributes(Assembly, bool) , Attribute.GetCustomAttributes(Assembly, Type) , Attribute.GetCustomAttributes(Assembly, Type, bool) , Attribute.GetCustomAttributes(MemberInfo) , Attribute.GetCustomAttributes(MemberInfo, bool) , Attribute.GetCustomAttributes(MemberInfo, Type) , Attribute.GetCustomAttributes(MemberInfo, Type, bool) , Attribute.GetCustomAttributes(Module) , Attribute.GetCustomAttributes(Module, bool) , Attribute.GetCustomAttributes(Module, Type) , Attribute.GetCustomAttributes(Module, Type, bool) , Attribute.GetCustomAttributes(ParameterInfo) , Attribute.GetCustomAttributes(ParameterInfo, bool) ,

Attribute.GetCustomAttributes(ParameterInfo, Type) , Attribute.GetCustomAttributes(ParameterInfo, Type, bool) , Attribute.GetHashCode() , Attribute.IsDefaultAttribute() , Attribute.IsDefined(Assembly, Type) , Attribute.IsDefined(Assembly, Type, bool) , Attribute.IsDefined(MemberInfo, Type) , Attribute.IsDefined(MemberInfo, Type, bool) , Attribute.IsDefined(Module, Type) , Attribute.IsDefined(Module, Type, bool) , Attribute.IsDefined(ParameterInfo, Type) , Attribute.IsDefined(ParameterInfo, Type, bool) , Attribute.Match(object) , Attribute.TypeId , object.Equals(object, object) , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

HeadAttribute()

```
public HeadAttribute()
```

HeadAttribute(string)

```
public HeadAttribute(string template)
```

Parameters

`template` string

Class PatchAttribute

Namespace: Solstice.API.Attributes

Assembly: Solstice.API.dll

The PatchAttribute class represents a custom attribute to indicate that an action method should handle HTTP PATCH requests. It has been derived from the HttpPatchAttribute class provided by the ASP.NET Core MVC framework.

```
public class PatchAttribute : HttpPatchAttribute, IActionHttpMethodProvider,
IRouteTemplateProvider
```

Inheritance

object ← Attribute ← HttpMethodAttribute ← HttpPatchAttribute ← PatchAttribute

Implements

IActionHttpMethodProvider, IRouteTemplateProvider

Inherited Members

HttpMethodAttribute.HttpMethods , HttpMethodAttribute.Template , HttpMethodAttribute.Order , HttpMethodAttribute.Name , Attribute.Equals(object) , Attribute.GetCustomAttribute(Assembly, Type) , Attribute.GetCustomAttribute(Assembly, Type, bool) , Attribute.GetCustomAttribute(MemberInfo, Type) , Attribute.GetCustomAttribute(MemberInfo, Type, bool) , Attribute.GetCustomAttribute(Module, Type) , Attribute.GetCustomAttribute(Module, Type, bool) , Attribute.GetCustomAttribute(ParameterInfo, Type) , Attribute.GetCustomAttribute(ParameterInfo, Type, bool) , Attribute.GetCustomAttributes(Assembly) , Attribute.GetCustomAttributes(Assembly, bool) , Attribute.GetCustomAttributes(Assembly, Type) , Attribute.GetCustomAttributes(Assembly, Type, bool) , Attribute.GetCustomAttributes(MemberInfo) , Attribute.GetCustomAttributes(MemberInfo, bool) , Attribute.GetCustomAttributes(MemberInfo, Type) , Attribute.GetCustomAttributes(MemberInfo, Type, bool) , Attribute.GetCustomAttributes(Module) , Attribute.GetCustomAttributes(Module, bool) , Attribute.GetCustomAttributes(Module, Type) , Attribute.GetCustomAttributes(Module, Type, bool) ,

Attribute.GetCustomAttributes(ParameterInfo) , Attribute.GetCustomAttributes(ParameterInfo, bool) , Attribute.GetCustomAttributes(ParameterInfo, Type) , Attribute.GetCustomAttributes(ParameterInfo, Type, bool) , Attribute.GetHashCode() , Attribute.IsDefaultAttribute() , Attribute.IsDefined(Assembly, Type) , Attribute.IsDefined(Assembly, Type, bool) , Attribute.IsDefined(MemberInfo, Type) , Attribute.IsDefined(MemberInfo, Type, bool) , Attribute.IsDefined(Module, Type) , Attribute.IsDefined(Module, Type, bool) , Attribute.IsDefined(ParameterInfo, Type) , Attribute.IsDefined(ParameterInfo, Type, bool) , Attribute.Match(object) , Attribute.TypeId , object.Equals(object, object) , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

PatchAttribute()

Default constructor for the PatchAttribute class.

```
public PatchAttribute()
```

PatchAttribute(string)

Constructor with a parameter for the PatchAttribute class. The template parameter is the route template associated with this attribute.

```
public PatchAttribute(string template)
```

Parameters

`template` string

The string that contains the template to associate with this attribute.

Class PostAttribute

Namespace: Solstice.API.Attributes

Assembly: Solstice.API.dll

The 'PostAttribute' class is a decorator extending from the 'HttpPostAttribute' class in the Microsoft ASP.NET Core MVC framework. It is used to specify the HTTP POST request methods for the action methods in the controller class.

```
public class PostAttribute : HttpPostAttribute, IActionHttpMethodProvider,
IRouteTemplateProvider
```

Inheritance

object ← Attribute ← HttpMethodAttribute ← HttpPostAttribute ← PostAttribute

Implements

IActionHttpMethodProvider, IRouteTemplateProvider

Inherited Members

HttpMethodAttribute.HttpMethods , HttpMethodAttribute.Template , HttpMethodAttribute.Order , HttpMethodAttribute.Name , Attribute.Equals(object) , Attribute.GetCustomAttribute(Assembly, Type) , Attribute.GetCustomAttribute(Assembly, Type, bool) , Attribute.GetCustomAttribute(MemberInfo, Type) , Attribute.GetCustomAttribute(MemberInfo, Type, bool) , Attribute.GetCustomAttribute(Module, Type) , Attribute.GetCustomAttribute(Module, Type, bool) , Attribute.GetCustomAttribute(ParameterInfo, Type) , Attribute.GetCustomAttribute(ParameterInfo, Type, bool) , Attribute.GetCustomAttributes(Assembly) , Attribute.GetCustomAttributes(Assembly, bool) , Attribute.GetCustomAttributes(Assembly, Type) , Attribute.GetCustomAttributes(Assembly, Type, bool) , Attribute.GetCustomAttributes(MemberInfo) , Attribute.GetCustomAttributes(MemberInfo, bool) , Attribute.GetCustomAttributes(MemberInfo, Type) , Attribute.GetCustomAttributes(MemberInfo, Type, bool) , Attribute.GetCustomAttributes(Module) , Attribute.GetCustomAttributes(Module, bool) , Attribute.GetCustomAttributes(Module, Type) , Attribute.GetCustomAttributes(Module, Type, bool) ,

Attribute.GetCustomAttributes(ParameterInfo) , Attribute.GetCustomAttributes(ParameterInfo, bool) , Attribute.GetCustomAttributes(ParameterInfo, Type) , Attribute.GetCustomAttributes(ParameterInfo, Type, bool) , Attribute.GetHashCode() , Attribute.IsDefaultAttribute() , Attribute.IsDefined(Assembly, Type) , Attribute.IsDefined(Assembly, Type, bool) , Attribute.IsDefined(MemberInfo, Type) , Attribute.IsDefined(MemberInfo, Type, bool) , Attribute.IsDefined(Module, Type) , Attribute.IsDefined(Module, Type, bool) , Attribute.IsDefined(ParameterInfo, Type) , Attribute.IsDefined(ParameterInfo, Type, bool) , Attribute.Match(object) , Attribute.TypeId , object.Equals(object, object) , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

PostAttribute()

```
public PostAttribute()
```

PostAttribute(string)

```
public PostAttribute(string template)
```

Parameters

`template` string

Class PutAttribute

Namespace: Solstice.API.Attributes

Assembly: Solstice.API.dll

The PutAttribute class inherits from the HttpPutAttribute class and represents an attribute that is used to indicate the HTTP PUT method for an action within a controller.

```
public class PutAttribute : HttpPutAttribute, IActionHttpMethodProvider,
IRouteTemplateProvider
```

Inheritance

object ← Attribute ← HttpMethodAttribute ← HttpPutAttribute ← PutAttribute

Implements

IActionHttpMethodProvider, IRouteTemplateProvider

Inherited Members

HttpMethodAttribute.HttpMethods , HttpMethodAttribute.Template , HttpMethodAttribute.Order , HttpMethodAttribute.Name , Attribute.Equals(object) , Attribute.GetCustomAttribute(Assembly, Type) , Attribute.GetCustomAttribute(Assembly, Type, bool) , Attribute.GetCustomAttribute(MemberInfo, Type) , Attribute.GetCustomAttribute(MemberInfo, Type, bool) , Attribute.GetCustomAttribute(Module, Type) , Attribute.GetCustomAttribute(Module, Type, bool) , Attribute.GetCustomAttribute(ParameterInfo, Type) , Attribute.GetCustomAttribute(ParameterInfo, Type, bool) , Attribute.GetCustomAttributes(Assembly) , Attribute.GetCustomAttributes(Assembly, bool) , Attribute.GetCustomAttributes(Assembly, Type) , Attribute.GetCustomAttributes(Assembly, Type, bool) , Attribute.GetCustomAttributes(MemberInfo) , Attribute.GetCustomAttributes(MemberInfo, bool) , Attribute.GetCustomAttributes(MemberInfo, Type) , Attribute.GetCustomAttributes(MemberInfo, Type, bool) , Attribute.GetCustomAttributes(Module) , Attribute.GetCustomAttributes(Module, bool) , Attribute.GetCustomAttributes(Module, Type) , Attribute.GetCustomAttributes(Module, Type, bool) , Attribute.GetCustomAttributes(ParameterInfo) ,

Attribute.GetCustomAttributes(ParameterInfo, bool) , Attribute.GetCustomAttributes(ParameterInfo, Type) , Attribute.GetCustomAttributes(ParameterInfo, Type, bool) , Attribute.GetHashCode() , Attribute.IsDefaultAttribute() , Attribute.IsDefined(Assembly, Type) , Attribute.IsDefined(Assembly, Type, bool) , Attribute.IsDefined(MemberInfo, Type) , Attribute.IsDefined(MemberInfo, Type, bool) , Attribute.IsDefined(Module, Type) , Attribute.IsDefined(Module, Type, bool) , Attribute.IsDefined(ParameterInfo, Type) , Attribute.IsDefined(ParameterInfo, Type, bool) , Attribute.Match(object) , Attribute.TypeId , object.Equals(object, object) , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Constructors

PutAttribute()

Default constructor for the PutAttribute class. Initializes a new instance of the class without any parameters.

```
public PutAttribute()
```

PutAttribute(string)

Overloaded constructor for the PutAttribute class. Initializes a new instance of the class with string parameter to represent the template for route data.

```
public PutAttribute(string template)
```

Parameters

`template` string

The route template. This is a pattern against which the URL path is matched.

Namespace Solstice.API.Controllers

Classes

CoreController

The CoreController is responsible for controlling the behavior of the system when it has to Solstice. This includes authorizing the user who is asking for the system restart, and providing the necessary Radiant API endpoint.

Class CoreController

Namespace: Solstice.API.Controllers

Assembly: Solstice.API.dll

The CoreController is responsible for controlling the behavior of the system when it has to Solstice. This includes authorizing the user who is asking for the system restart, and providing the necessary Radiant API endpoint.

```
[ApiController]
[Route("api/[controller]")]
public class CoreController : ControllerBase
```

Inheritance

object ← ControllerBase ← CoreController

Inherited Members

ControllerBase.StatusCode(int) , ControllerBase.StatusCode(int, object) , ControllerBase.Content(string) , ControllerBase.Content(string, string) , ControllerBase.Content(string, string, Encoding) , ControllerBase.Content(string, MediaTypeHeaderValue) , ControllerBase.NoContent() , ControllerBase.Ok() , ControllerBase.Ok(object) , ControllerBase.Redirect(string) , ControllerBase.RedirectPermanent(string) , ControllerBase.RedirectPreserveMethod(string) , ControllerBase.RedirectPermanentPreserveMethod(string) , ControllerBase.LocalRedirect(string) , ControllerBase.LocalRedirectPermanent(string) , ControllerBase.LocalRedirectPreserveMethod(string) , ControllerBase.LocalRedirectPermanentPreserveMethod(string) , ControllerBase.RedirectToAction() , ControllerBase.RedirectToAction(string) , ControllerBase.RedirectToAction(string, object) , ControllerBase.RedirectToAction(string, string) , ControllerBase.RedirectToAction(string, string, object) , ControllerBase.RedirectToAction(string, string, string) , ControllerBase.RedirectToAction(string, string, object, string) , ControllerBase.RedirectToActionPreserveMethod(string, string, object, string) , ControllerBase.RedirectToActionPermanent(string) , ControllerBase.RedirectToActionPermanent(string, object) , ControllerBase.RedirectToActionPermanent(string, string) , ControllerBase.RedirectToActionPermanent(string, string, string) ,

ControllerBase.RedirectToActionPermanent(string, string, object) ,
ControllerBase.RedirectToActionPermanent(string, string, object, string) ,
ControllerBase.RedirectToActionPermanentPreserveMethod(string, string, object, string) ,
ControllerBase.RedirectToRoute(string) , ControllerBase.RedirectToRoute(object) ,
ControllerBase.RedirectToRoute(string, object) ,
ControllerBase.RedirectToRoute(string, string) ,
ControllerBase.RedirectToRoute(string, object, string) ,
ControllerBase.RedirectToRoutePreserveMethod(string, object, string) ,
ControllerBase.RedirectToRoutePermanent(string) ,
ControllerBase.RedirectToRoutePermanent(object) ,
ControllerBase.RedirectToRoutePermanent(string, object) ,
ControllerBase.RedirectToRoutePermanent(string, string) ,
ControllerBase.RedirectToRoutePermanent(string, object, string) ,
ControllerBase.RedirectToRoutePermanentPreserveMethod(string, object, string) ,
ControllerBase.RedirectToPage(string) , ControllerBase.RedirectToPage(string, object) ,
ControllerBase.RedirectToPage(string, string) ,
ControllerBase.RedirectToPage(string, string, object) ,
ControllerBase.RedirectToPage(string, string, string) ,
ControllerBase.RedirectToPage(string, string, object, string) ,
ControllerBase.RedirectToPagePermanent(string) ,
ControllerBase.RedirectToPagePermanent(string, object) ,
ControllerBase.RedirectToPagePermanent(string, string) ,
ControllerBase.RedirectToPagePermanent(string, string, string) ,
ControllerBase.RedirectToPagePermanent(string, string, object, string) ,
ControllerBase.RedirectToPagePreserveMethod(string, string, object, string) ,
ControllerBase.RedirectToPagePermanentPreserveMethod(string, string, object, string) ,
ControllerBase.File(byte[], string) , ControllerBase.File(byte[], string, bool) ,
ControllerBase.File(byte[], string, string) ,
ControllerBase.File(byte[], string, string, bool) ,
ControllerBase.File(byte[], string, DateTimeOffset?, EntityTagHeaderValue) ,
ControllerBase.File(byte[], string, DateTimeOffset?, EntityTagHeaderValue, bool) ,
ControllerBase.File(byte[], string, string, DateTimeOffset?, EntityTagHeaderValue) ,
ControllerBase.File(byte[], string, string, DateTimeOffset?, EntityTagHeaderValue, bool) ,
ControllerBase.File(Stream, string) , ControllerBase.File(Stream, string, bool) ,
ControllerBase.File(Stream, string, string) ,
ControllerBase.File(Stream, string, string, bool) ,
ControllerBase.File(Stream, string, DateTimeOffset?, EntityTagHeaderValue) ,
ControllerBase.File(Stream, string, DateTimeOffset?, EntityTagHeaderValue, bool) ,
ControllerBase.File(Stream, string, string, DateTimeOffset?, EntityTagHeaderValue) ,
ControllerBase.File(Stream, string, string, DateTimeOffset?, EntityTagHeaderValue, bool) ,

ControllerBase.File(string, string) , ControllerBase.File(string, string, bool) ,
ControllerBase.File(string, string, string) , ControllerBase.File(string, string, string, bool) ,
ControllerBase.File(string, string, DateTimeOffset?, EntityTagHeaderValue) ,
ControllerBase.File(string, string, DateTimeOffset?, EntityTagHeaderValue, bool) ,
ControllerBase.File(string, string, string, DateTimeOffset?, EntityTagHeaderValue) ,
ControllerBase.File(string, string, string, DateTimeOffset?, EntityTagHeaderValue, bool) ,
ControllerBase.PhysicalFile(string, string) ,
ControllerBase.PhysicalFile(string, string, bool) ,
ControllerBase.PhysicalFile(string, string, string) ,
ControllerBase.PhysicalFile(string, string, string, bool) ,
ControllerBase.PhysicalFile(string, string, DateTimeOffset?, EntityTagHeaderValue) ,
ControllerBase.PhysicalFile(string, string, DateTimeOffset?, EntityTagHeaderValue, bool) ,
ControllerBase.PhysicalFile(string, string, string, DateTimeOffset?, EntityTagHeaderValue) ,
ControllerBase.PhysicalFile(string, string, string, DateTimeOffset?, EntityTagHeaderValue, bool) ,
ControllerBase.Unauthorized() , ControllerBase.Unauthorized(object) ,
ControllerBase.NotFound() , ControllerBase.NotFound(object) ,
ControllerBase.BadRequest() , ControllerBase.BadRequest(object) ,
ControllerBase.BadRequest(ModelStateDictionary) ,
ControllerBase.UnprocessableEntity() , ControllerBase.UnprocessableEntity(object) ,
ControllerBase.UnprocessableEntity(ModelStateDictionary) , ControllerBase.Conflict() ,
ControllerBase.Conflict(object) , ControllerBase.Conflict(ModelStateDictionary) ,
ControllerBase.Problem(string, string, int?, string, string) ,
ControllerBase.ValidationProblem(ValidationProblemDetails) ,
ControllerBase.ValidationProblem(ModelStateDictionary) ,
ControllerBase.ValidationProblem() ,
ControllerBase.ValidationProblem(string, string, int?, string, string, ModelStateDictionary)
,
ControllerBase.Created() , ControllerBase.Created(string, object) ,
ControllerBase.Created(Uri, object) , ControllerBase.CreatedAtAction(string, object) ,
ControllerBase.CreatedAtAction(string, object, object) ,
ControllerBase.CreatedAtAction(string, string, object, object) ,
ControllerBase.CreatedAtRoute(string, object) ,
ControllerBase.CreatedAtRoute(object, object) ,
ControllerBase.CreatedAtRoute(string, object, object) , ControllerBase.Accepted() ,
ControllerBase.Accepted(object) , ControllerBase.Accepted(Uri) ,
ControllerBase.Accepted(string) , ControllerBase.Accepted(string, object) ,
ControllerBase.Accepted(Uri, object) , ControllerBase.AcceptedAtAction(string) ,
ControllerBase.AcceptedAtAction(string, string) ,
ControllerBase.AcceptedAtAction(string, object) ,

ControllerBase.AcceptedAtAction(string, string, object) ,
ControllerBase.AcceptedAtAction(string, object, object) ,
ControllerBase.AcceptedAtAction(string, string, object, object) ,
ControllerBase.AcceptedAtRoute(object) , ControllerBase.AcceptedAtRoute(string) ,
ControllerBase.AcceptedAtRoute(string, object) ,
ControllerBase.AcceptedAtRoute(object, object) ,
ControllerBase.AcceptedAtRoute(string, object, object) , ControllerBase.Challenge() ,
ControllerBase.Challenge(params string[]) ,
ControllerBase.Challenge(AuthenticationProperties) ,
ControllerBase.Challenge(AuthenticationProperties, params string[]) ,
ControllerBase.Forbid() , ControllerBase.Forbid(params string[]) ,
ControllerBase.Forbid(AuthenticationProperties) ,
ControllerBase.Forbid(AuthenticationProperties, params string[]) ,
ControllerBase.SignIn(ClaimsPrincipal) , ControllerBase.SignIn(ClaimsPrincipal, string) ,
ControllerBase.SignIn(ClaimsPrincipal, AuthenticationProperties) ,
ControllerBase.SignIn(ClaimsPrincipal, AuthenticationProperties, string) ,
ControllerBase.SignOut() , ControllerBase.SignOut(AuthenticationProperties) ,
ControllerBase.SignOut(params string[]) ,
ControllerBase.SignOut(AuthenticationProperties, params string[]) ,
ControllerBase.TryUpdateModelAsync<TModel>(TModel) ,
ControllerBase.TryUpdateModelAsync<TModel>(TModel, string) ,
ControllerBase.TryUpdateModelAsync<TModel>(TModel, string, IValueProvider) ,
ControllerBase.TryUpdateModelAsync<TModel>(TModel, string, params Expression<Func<TModel, object>>[]) ,
ControllerBase.TryUpdateModelAsync<TModel>(TModel, string, Func<ModelMetadata, bool>) ,
ControllerBase.TryUpdateModelAsync<TModel>(TModel, string, IValueProvider, params Expression<Func<TModel, object>>[]) ,
ControllerBase.TryUpdateModelAsync<TModel>(TModel, string, IValueProvider, Func<ModelMetadata, bool>) ,
ControllerBase.TryUpdateModelAsync(object, Type, string) ,
ControllerBase.TryUpdateModelAsync(object, Type, string, IValueProvider, Func<ModelMetadata, bool>) ,
ControllerBase.TryValidateModel(object) ,
ControllerBase.TryValidateModel(object, string) , ControllerBase.HttpContext ,
ControllerBase.Request , ControllerBase.Response , ControllerBase.RouteData ,
ControllerBase.ModelState , ControllerBase.ControllerContext ,
ControllerBase.MetadataProvider , ControllerBase.ModelBinderFactory ,
ControllerBase.Url , ControllerBase.ObjectValidator ,
ControllerBase.ProblemDetailsFactory , ControllerBase.User , ControllerBase.Empty ,

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Methods

OkOrNoContent<T>(T)

```
public static ActionResult OkOrNoContent<T>(T nullable) where T : class
```

Parameters

`nullable` T

Returns

ActionResult

Type Parameters

`T`

OkOrNotFound<T>(T)

```
public static ActionResult OkOrNotFound<T>(T nullable) where T : class
```

Parameters

`nullable` T

Returns

ActionResult

Type Parameters

`T`

Namespace Solstice.API.Injections

Classes

CoreInjections

The CoreInjections class is a static class containing methods related to core service injections in an ASP.NET Core application.

Class CoreInjections

Namespace: Solstice.API.Injections

Assembly: Solstice.API.dll

The CoreInjections class is a static class containing methods related to core service injections in an ASP.NET Core application.

```
public static class CoreInjections
```

Inheritance

object ← CoreInjections

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Methods

UseLowercaseRoutes(IServiceCollection)

This extension method Configures the URL routing system to generate and recognize URLs in lowercase.

```
public static void UseLowercaseRoutes(this IServiceCollection services)
```

Parameters

`services` IServiceCollection

The instance of IServiceCollection to add the service to.

Namespace Solstice.API.Scanning

Classes

CoreAssemblyScanning

CoreAssemblyScanningExtensions

Class CoreAssemblyScanning

Namespace: Solstice.API.Scanning

Assembly: Solstice.API.dll

```
public class CoreAssemblyScanning : AssemblyLoadContext
```

Inheritance

object ← AssemblyLoadContext ← CoreAssemblyScanning

Inherited Members

AssemblyLoadContext.EnterContextualReflection() , AssemblyLoadContext.EnterContextualReflection(Assembly) , AssemblyLoadContext.GetAssemblyName(string) , AssemblyLoadContext.GetLoadContext(Assembly) , AssemblyLoadContext.LoadFromAssemblyName(AssemblyName) , AssemblyLoadContext.LoadFromAssemblyPath(string) , AssemblyLoadContext.LoadFromNativeImagePath(string, string) , AssemblyLoadContext.LoadFromStream(Stream) , AssemblyLoadContext.LoadFromStream(Stream, Stream) , AssemblyLoadContext.LoadUnmanagedDll(string) , AssemblyLoadContext.LoadUnmanagedDllFromPath(string) , AssemblyLoadContext.SetProfileOptimizationRoot(string) , AssemblyLoadContext.StartProfileOptimization(string) , AssemblyLoadContext.ToString() , AssemblyLoadContext.Unload() , AssemblyLoadContext.All , AssemblyLoadContext.Assemblies , AssemblyLoadContext.CurrentContextualReflectionContext , AssemblyLoadContext.Default , AssemblyLoadContext.IsCollectible , AssemblyLoadContext.Name , AssemblyLoadContext.Resolving , AssemblyLoadContext.ResolvingUnmanagedDll , AssemblyLoadContext.Unloading , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

Constructors

CoreAssemblyScanning()

```
public CoreAssemblyScanning()
```

CoreAssemblyScanning(Assembly)

```
public CoreAssemblyScanning(Assembly assembly)
```

Parameters

`assembly` Assembly

CoreAssemblyScanning(string)

```
public CoreAssemblyScanning(string directoryPath)
```

Parameters

`directoryPath` string

Methods

Load(AssemblyName)

When overridden in a derived class, allows an assembly to be resolved based on its AssemblyName.

```
protected override Assembly Load(AssemblyName assemblyName)
```

Parameters

`assemblyName` AssemblyName

The object that describes the assembly to be resolved.

Returns

Assembly

The resolved assembly, or null.

Scan(Assembly)

```
public static void Scan(Assembly assembly)
```

Parameters

`assembly` Assembly

ScanAndLoadAssemblies()

```
public void ScanAndLoadAssemblies()
```

ScanByCompanyName(string)

```
public static void ScanByCompanyName(string companyName)
```

Parameters

`companyName` string

ScanByMetadata()

```
public static void ScanByMetadata()
```

ScanByPrefix(string)

```
public static void ScanByPrefix(string assemblyPrefix)
```

Parameters

`assemblyPrefix` string

Class CoreAssemblyScanningExtensions

Namespace: Solstice.API.Scanning

Assembly: Solstice.API.dll

```
public static class CoreAssemblyScanningExtensions
```

Inheritance

object ← CoreAssemblyScanningExtensions

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Methods

ScanAndLoadAssemblies(WebApplicationBuilder, Assembly)

```
public static void ScanAndLoadAssemblies(this WebApplicationBuilder builder,
Assembly assembly)
```

Parameters

`builder` WebApplicationBuilder

`assembly` Assembly

ScanAndLoadAssembliesByCompanyName(WebApplicationBuilder, string)

Scan and load assemblies by company name.

```
public static void ScanAndLoadAssembliesByCompanyName(this WebApplicationBuilder
```

```
builder, string companyName)
```

Parameters

`builder` WebApplicationBuilder

Your web api builder

`companyName` string

Your company name set in assemblies settings

ScanAndLoadAssembliesByMetadata(WebApplicationBuilder)

Scan and load assemblies by metadata. Add the metadata attribute "IsSolutionAssembly" to true, surrounded by PropertyGroup.

```
public static void ScanAndLoadAssembliesByMetadata(this WebApplicationBuilder
builder)
```

Parameters

`builder` WebApplicationBuilder

Your web api builder

Remarks

<PropertyGroup><IsSolutionAssembly>true</IsSolutionAssembly></PropertyGroup>

ScanAndLoadAssembliesByPrefix(WebApplicationBuilder, string)

Scan and load assemblies by prefix.

```
public static void ScanAndLoadAssembliesByPrefix(this WebApplicationBuilder builder,
string assemblyPrefix)
```

Parameters

`builder` WebApplicationBuilder

Your web api builder

`assemblyPrefix` string

The assembly prefix of your projects