Namespace Solstice.Domain.Exceptions

Classes

CoreException

Represents an exception that is thrown when there is an error.

CoreExceptionEnumExtension

Provides extension methods for the CoreExceptionEnum enumeration.

Enums

CoreExceptionEnum

Represents the possible exceptions that can be thrown by the Solstice.Domain classes.

Class CoreException

Namespace: Solstice.Domain.Exceptions

Assembly: Solstice.Domain.dll

Represents an exception that is thrown when there is an error.

```
public class CoreException : Exception, ISerializable
```

Inheritance

object ← Exception ← CoreException

Implements

ISerializable

Inherited Members

Exception.GetBaseException() , Exception.GetType() , Exception.ToString() , Exception.Data , Exception.HelpLink , Exception.HResult , Exception.InnerException , Exception.Message , Exception.Source , Exception.StackTrace , Exception.TargetSite , Exception.SerializeObjectState , object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.MemberwiseClone() , object.ReferenceEquals(object, object)

Constructors

CoreException(int, string)

```
public CoreException(int statusCode, string message)
```

Parameters

`statusCode` int

`message` string

CoreException(int, string, Exception)

```
public CoreException(int statusCode, string message, Exception innerException)
```

Parameters

`statusCode` int

`message` string

`innerException` Exception

CoreException(string)

```
public CoreException(string message)
```

Parameters

`message` string

CoreException(string, Exception)

```
public CoreException(string message, Exception innerException)
```

Parameters

`message` string

`innerException` Exception

Properties

StatusCode

```
public int StatusCode { get; }
```

Property Value

int

Methods

Error400(params object[])

Generate a 400 error with or without a message.

```
public static CoreException Error400(params object[] values)
```

Parameters

`values` object[]

Returns

CoreException

Error401(params object[])

Generate a 401 error with or without a message.

```
public static CoreException Error401(params object[] values)
```

Parameters

`values` object[]

Returns

CoreException

Error403(params object[])

Generate a 403 error with or without a message.

```
public static CoreException Error403(params object[] values)
```

Parameters

`values` object[]

Returns

CoreException

Error404(params object[])

Generate a 404 error with or without a message.

```
public static CoreException Error404(params object[] values)
```

Parameters

`values` object[]

Returns

CoreException

Error500(params object[])

Generate a 500 error with or without a message.

```
public static CoreException Error500(params object[] values)
```

Parameters

`values` object[]

Returns

CoreException

Format(CoreExceptionEnum)

Used to generate exception message based on the provided CoreExceptionEnum.

```
public static CoreException Format(CoreExceptionEnum coreExceptionEnum)
```

Parameters

`coreExceptionEnum` CoreExceptionEnum

Returns

CoreException

Format(CoreExceptionEnum, params object[])

```
public static CoreException Format(CoreExceptionEnum coreExceptionEnum, params
object[] values)
```

Parameters

`coreExceptionEnum` CoreExceptionEnum

`values` object[]

Returns

CoreException

Format(Exception, CoreExceptionEnum, params object[])

```
public static CoreException Format(Exception ex, CoreExceptionEnum
coreExceptionEnum, params object[] values)
```

Parameters

`ex` Exception

`coreExceptionEnum` CoreExceptionEnum

`values` object[]

Returns

CoreException

Format(Exception, int, CoreExceptionEnum, params object[])

```
public static CoreException Format(Exception ex, int statusCode, CoreExceptionEnum
coreExceptionEnum, params object[] values)
```

Parameters

`ex` Exception

`statusCode` int

`coreExceptionEnum` CoreExceptionEnum

`values` object[]

Returns

CoreException

Format(int, CoreExceptionEnum, params object[])

```
public static CoreException Format(int statusCode, CoreExceptionEnum
coreExceptionEnum, params object[] values)
```

Parameters

`statusCode` int

`coreExceptionEnum` CoreExceptionEnum

`values` object[]

Returns

CoreException

Enum CoreExceptionEnum

Namespace: Solstice.Domain.Exceptions

Assembly: Solstice.Domain.dll

Represents the possible exceptions that can be thrown by the Solstice.Domain classes.

```
public enum CoreExceptionEnum
```

Extension Methods
CoreExceptionEnumExtension.Get(CoreExceptionEnum)

Fields

```
HTTP_400 = 3

HTTP_400_WITH_MESSAGE = 4

HTTP_401 = 5

HTTP_401_WITH_MESSAGE = 6

HTTP_403 = 7

HTTP_403_WITH_MESSAGE = 8

HTTP_404 = 9

HTTP_404_WITH_MESSAGE = 10

HTTP_500 = 11

HTTP_500_WITH_MESSAGE = 12

NO_QUERY_DTO = 2

NO_REPOSITORY = 0

NO_SERVICE = 1
```

Class CoreExceptionEnumExtension

Namespace: Solstice.Domain.Exceptions

Assembly: Solstice.Domain.dll

Provides extension methods for the CoreExceptionEnum enumeration.

```
public static class CoreExceptionEnumExtension
```

Inheritance

object ← CoreExceptionEnumExtension

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Methods

Get(CoreExceptionEnum)

Gets the error message associated with the specified CoreExceptionEnum value.

```
public static string Get(this CoreExceptionEnum coreExceptionEnum)
```

Parameters

`coreExceptionEnum` CoreExceptionEnum

The CoreExceptionEnum value.

Returns

string

The error message associated with the specified CoreExceptionEnum value.

Namespace Solstice.Domain.Extensions

Classes

EnumerableExtensions

QueryableExtensions

Class EnumerableExtensions

Namespace: Solstice.Domain.Extensions

Assembly: Solstice.Domain.dll

```
public static class EnumerableExtensions
```

Inheritance

object ← EnumerableExtensions

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Methods

IsNotNullOrEmpty<T>(IEnumerable<T>)

```
public static bool IsNotNullOrEmpty<T>(this IEnumerable<T> list)
```

Parameters

`list` IEnumerable<T>

Returns

bool

Type Parameters

`T`

IsNullOrEmpty<T>(IEnumerable<T>)

```
public static bool IsNullOrEmpty<T>(this IEnumerable<T> list)
```

Parameters

`list` IEnumerable<T>

Returns

bool

Type Parameters

`T`

Class QueryableExtensions

Namespace: Solstice.Domain.Extensions

Assembly: Solstice.Domain.dll

```
public static class QueryableExtensions
```

Inheritance

object ← QueryableExtensions

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Methods

IsNotNullOrEmpty<T>(IQueryable<T>)

```
public static bool IsNotNullOrEmpty<T>(this IQueryable<T> list)
```

Parameters

`list` IQueryable<T>

Returns

bool

Type Parameters

`T`

IsNullOrEmpty<T>(IQueryable<T>)

```
public static bool IsNullOrEmpty<T>(this IQueryable<T> list)
```

Parameters

`list` IQueryable<T>

Returns

bool

Type Parameters

`T`

Namespace Solstice.Domain.Models

Classes

CoreModel

CoreModel class provides a structure to encapsulate information related to Radiant functionality in the application. The information mainly includes id associated to each Radiant transaction or operation.

Page

Represents a page in a Radiant context with a specific page number and size.

PageExtension

Provides extension methods on a Page instance.

Paged<T>

The 'Paged' class provides a simple way to encapsulate a collection of items with a certain count. It's generic, able to support any type of object (indicated by 'T') for pagination purposes.

Class CoreModel

Namespace: Solstice.Domain.Models

Assembly: Solstice.Domain.dll

CoreModel class provides a structure to encapsulate information related to Radiant functionality in the application. The information mainly includes id associated to each Radiant transaction or operation.

```
public class CoreModel
```

Inheritance

object ← CoreModel

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Properties

Id

Gets or sets the unique identifier for the Radiant operation.

```
public int Id { get; set; }
```

Property Value

int

Class Page

Namespace: Solstice.Domain.Models

Assembly: Solstice.Domain.dll

Represents a page in a Radiant context with a specific page number and size.

```
public record Page : IEquatable<Page>
```

Inheritance

object ← Page

Implements

IEquatable<Page>

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Extension Methods

PageExtension.LineToSkip(Page)

Constructors

Page(int, int)

Represents a page in a Radiant context with a specific page number and size.

```
public Page(int PageNumber = 1, int PageSize = 10)
```

Parameters

`PageNumber` int

The number of the page, default is 1.

`PageSize` int

The size of the page, default is 10.

Properties

PageNumber

The number of the page, default is 1.

```
public int PageNumber { get; init; }
```

Property Value

int

PageSize

The size of the page, default is 10.

```
public int PageSize { get; init; }
```

Property Value

int

Class PageExtension

Namespace: Solstice.Domain.Models

Assembly: Solstice.Domain.dll

Provides extension methods on a Page instance.

```
public static class PageExtension
```

Inheritance

object ← PageExtension

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Methods

LineToSkip(Page)

Calculates how many entries need to be skipped for pagination.

```
public static int LineToSkip(this Page page)
```

Parameters

`page` Page

A Page instance.

Returns

int

Returns the number of entries that needs to be skipped to get the correct page context.

Class Paged<T>

Namespace: Solstice.Domain.Models

Assembly: Solstice.Domain.dll

The 'Paged' class provides a simple way to encapsulate a collection of items with a certain count. It's generic, able to support any type of object (indicated by 'T') for pagination purposes.

```
public class Paged<T>
```

Type Parameters

T

The type of items held within the 'Paged' object.

Inheritance

object ← Paged<T>

Inherited Members

object.Equals(object) , object.Equals(object, object) , object.GetHashCode() , object.GetType() , object.MemberwiseClone() , object.ReferenceEquals(object, object) , object.ToString()

Remarks

Properties include:

- 'Items': A collection of items of type 'T'. Nullable.
- 'Count': The total count of items present in the 'Items' collection.

Properties

Count

```
public int Count { get; set; }
```

Property Value

int

Items

```
public ICollection<T>? Items { get; set; }
```

Property Value

ICollection<T>