

04 One Sample Test

November 20, 2022

1 One Sample Test

```
[1]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from scipy import stats
```

1.1 Hypothesis

$$H_0 : \mu = \mu_0$$

$$H_1 : \mu > \mu_0 \cap H_1 : \mu < \mu_0 \cap H_1 : \mu \neq \mu_0$$

1.2 z-Test

Test statistic

$$T = \frac{\bar{X} - \mu_0}{\frac{\sigma}{\sqrt{n}}}$$

```
[2]: mu0 = 1 # Hypothesis:  $\mu_0 = 1$ 
sigma = 0.1 # Assume to be known
n = 100 # Number of measurements

alpha = 0.05 # Significance level

c = stats.norm().ppf(1 - alpha) # rejection area - right-sided

values = stats.norm(1.02, 0.1).rvs(n)
x_mean = np.mean(values)

t = (x_mean - mu0) / (sigma / np.sqrt(n))

p_value = 1 - stats.norm().cdf(t)

print(f"Test statistic t: {t}")
print(f"Rejection area: [{c}; inf]")
print(f"Reject H0: {t > c}")
```

```
print(f"P-Value: {p_value}")
```

```
Test statistic t: 2.1460272545454684
Rejection area: [1.6448536269514722; inf]
Reject H0: True
P-Value: 0.015935402159858558
```

1.3 t-Test

Test statistic

$$T = \frac{\bar{X} - \mu_0}{\frac{s_x}{\sqrt{n}}}$$

The statistic T has a student-t distribution with $n - 1$ degrees of freedom

```
[7]: mu0 = 1 # Hypothesis:  $\mu_0 = 1$ 
n = 100 # Number of measurements
alpha = 0.05 # Significance level

# Generate random values
values = stats.norm(mu0 + 0.02, 0.1).rvs(n)
x_mean = np.mean(values)

# Rejection area
c = stats.t(n - 1).ppf(1 - alpha)
s = np.std(values, ddof=1)

t = (x_mean - mu0) / (s / np.sqrt(n))

p_value = 1 - stats.norm().cdf(t)

print(f"Test statistic t: {t}")
print(f"Rejection area: {c}")
print(f"Reject H0: {t > c}")
print(f"P-Value: {p_value}")
```

```
Test statistic t: 2.6019082042417536
Rejection area: 1.6603911559963895
Reject H0: True
P-Value: 0.004635333150248888
```

1.4 scipy.stats.ttest_1samp

Build in function in scipy.stats package for calculating the t-test

```
[10]: n = 100 # Number of measurements
mu0 = 1 # Hypothesis:  $\mu_0 = 1$ 
alpha = 0.05 # Significance level
```

```

values = stats.norm(1.02, 0.1).rvs(n)

# Calculate rejection area
c = stats.t(n - 1).ppf(1 - alpha)

# Execute the t-test
res = stats.ttest_1samp(values, popmean=mu0, alternative='greater')

print(f"Rejection area: {c}")
print(f"Statistic:      {res[0]}")
print(f"P-Value:        {res[1]}")
print(f"Reject H0:       {res[0] > c}")

```

```

Rejection area: 1.6603911559963895
Statistic:      2.40829931379035
P-Value:        0.008938768515980647
Reject H0:      True

```

[]: