

C1W4_Assignment

December 23, 2020

1 Week 4 Assignment: Create a VGG network

In this exercise, you will build a class that implements a [VGG network](#) and then train it to classify images of cats and dogs. The model will look something like this:

It is primarily made up of a series of Conv2D layers followed by a softmax activated layers to classify the image. As you can see, this will be a handful and the code will look huge if you specify each layer individually. As shown in the lectures, you can instead use model subclassing to build complex architectures. You can encapsulate repeating parts of a network then reuse that code when building the final model. You will get to practice that in this exercise. Let's get started!

```
[1]: import tensorflow as tf
import tensorflow_datasets as tfds
import utils
```

1.1 Create named-variables dynamically

In this assignment, you will see the use of the Python function `vars()`. This will allow you to use a for loop to define and set multiple variables with a similar name, such as `var1`, `var2`, `var3`.

Please go through the following examples to get familiar with `vars()`, as you will use it when building the VGG model. - You'll start by defining a class `MyClass` - It contains one variable `var1`.
- Create an object of type `MyClass`.

```
[2]: # Define a small class MyClass
class MyClass:
    def __init__(self):
        # One class variable 'a' is set to 1
        self.var1 = 1

# Create an object of type MyClass()
my_obj = MyClass()
```

Python classes have an attribute called `__dict__`. - `__dict__` is a Python dictionary that contains the object's instance variables and values as key value pairs.

```
[3]: my_obj.__dict__
```

```
[3]: {'var1': 1}
```

If you call `vars()` and pass in an object, it will call the object's `__dict__` attribute, which is a Python dictionary containing the object's instance variables and their values as ke

```
[4]: vars(my_obj)
```

```
[4]: {'var1': 1}
```

You may be familiar with adding new variable like this:

```
[5]: # Add a new instance variable and give it a value
my_obj.var2 = 2

# Calls vars() again to see the object's instance variables
vars(my_obj)
```

```
[5]: {'var1': 1, 'var2': 2}
```

Here is another way that you can add an instance variable to an object, using `vars()`. - Retrieve the Python dictionary `__dict__` of the object using `vars(my_obj)`. - Modify this `__dict__` dictionary using square bracket notation and passing in the variable's name as a string: `['var3'] = 3`

```
[6]: # Call vars, passing in the object. Then access the __dict__ dictionary using
    ↪ square brackets
vars(my_obj)['var3'] = 3

# Call vars() to see the object's instance variables
vars(my_obj)
```

```
[6]: {'var1': 1, 'var2': 2, 'var3': 3}
```

Why this is helpful! You may be wondering why you would need another way to access an object's instance variables.

- Notice that when using `vars()`, you can now pass in the name of the variable `var3` as a string. - What if you plan to use several variables that are similarly named (`var4`, `var5` ... `var9`) and wanted a convenient way to access them by incrementing a number?

Try this!

```
[7]: # Use a for loop to increment the index 'i'
for i in range(4,10):
    # Format a string that is var
    vars(my_obj)[f'var{i}'] = 0

# View the object's instance variables!
vars(my_obj)
```

```
[7]: {'var1': 1,
      'var2': 2,
      'var3': 3,
      'var4': 0,
      'var5': 0,
      'var6': 0,
      'var7': 0,
      'var8': 0,
      'var9': 0}
```

There are couple equivalent ways in Python to format a string. Here are two of those ways: -
f-string: `f"var{i}"` - `.format`: `"var{}".format(i)`

```
[8]: # Format a string using f-string notation
i=1
print(f"var{i}")

# Format a string using .format notation
i=2
print("var{}".format(i))
```

```
var1
var2
```

You can access the variables of a class inside the class definition using `vars(self)`

```
[9]: # Define a small class MyClass
class MyClass:
    def __init__(self):
        # Use vars(self) to access the class's dictionary of variables
        vars(self)['var1'] = 1

# Create an object of type MyClass()
my_obj = MyClass()
vars(my_obj)
```

```
[9]: {'var1': 1}
```

You'll see this in the upcoming code. Now you'll start building the VGG network!

1.2 Create a generic VGG block (TODO)

The VGG Network has blocks of layers, where each block has a varied number of layers. - In order to create blocks of layers that have a customizable number of conv2D layers, you'll define a class `Block`, which can generate a customizable block of layers

1.2.1 __init__

In the constructor `__init__`, store the conv2D parameters and also define the number of conv2D layers using the parameters passed into `__init__`. - Store the filters, kernel_size, and repetitions as class variables so that they can be used later in the `call` function. - Using a for loop, define a number of Conv2D [Conv2D](#) layers, based on the number of repetitions desired for this block. - You can define each conv2D layer using `vars` and string formatting to create `conv2D_0`, `conv2D_1`, `conv2D_3` etc. - Set these four parameters of Conv2D: - filters - kernel_size - activation: set this to 'relu' - padding: set this to 'same' (default padding is 'valid').

- Define the [MaxPool2D](#) layer that follows these Conv2D layers.
 - Set the following parameters for MaxPool2D:
 - * pool_size: this will be a tuple with two values.
 - * strides: this will also be a tuple with two values.

1.2.2 call

In `call`, you will connect the layers together. - The 0-th conv2D layer, `conv2D_0`, immediately follows the `inputs`. - For conv2D layers 1,2 and onward, you can use a for loop to connect `conv2D_1` to `conv2D_0`, and connect `conv2D_2` to `conv2D_1`, and so on. - After connecting all of the `conv2D_i` layers, add connect the `max_pool` layer and return the `max_pool` layer.

```
[64]: ## Please uncomment all lines in this cell and replace those marked with `#`  
      ↪YOUR CODE HERE`.  
## You can select all lines in this code cell with Ctrl+A (Windows/Linux) or  
      ↪Cmd+A (Mac), then press Ctrl+/ (Windows/Linux) or Cmd+/ (Mac) to uncomment.  
  
class Block(tf.keras.Model):  
  
    def __init__(self, filters, kernel_size, repetitions, pool_size=2,  
    ↪strides=2):  
        super(Block, self).__init__()  
        self.filters = filters  
        self.kernel_size = kernel_size  
        self.repetitions = repetitions  
  
#         # Define a conv2D_0, conv2D_1, etc based on the number of repetitions  
        for i in range(repetitions):
```

```

        vars(self)[f'conv2D_{i}'] = tf.keras.layers.Conv2D(self.filters,
↪self.kernel_size, padding='same',
                                                                activation='relu')

        #self.act = tf.keras.layers.Activation('relu')

#         # Define the max pool layer that will be added after the Conv2D blocks
        self.max_pool = tf.keras.layers.MaxPool2D(pool_size, strides=strides)

    def call(self, inputs):

#         # access the class's conv2D_0 layerconv2D_0 = # YOUR CODE HERE

#         # Connect the conv2D_0 layer to inputs
        x = self.conv2D_0(inputs)

#         # for the remaining conv2D_i layers from 1 to `repetitions` they will
↪be connected to the previous layer
        for i in range(1, self.repetitions):

#             # access conv2D_i by formatting the integer `i`. (hint: check how
↪these were saved using `vars()` earlier)
            conv2D_i = vars(self)[f'conv2D_{i}']

#             # Use the conv2D_i and connect it to the previous layer
            x = conv2D_i(x)

#             # Finally, add the max_pool layer
            max_pool = self.max_pool(x)

        return max_pool

```

[65]:

[]:

[66]: `utils.test_block_class(Block)`

All public tests passed

[]:

1.3 Create the Custom VGG network (TODO)

This model stack has a series of VGG blocks, which can be created using the `Block` class that you defined earlier.

1.3.1 `__init__`

- Recall that the `__init__` constructor of `Block` takes several function parameters,
 - `filters`, `kernel_size`, `repetitions`: you'll set these.
 - `kernel_size` and `strides`: you can use the default values.
- For blocks a through e, build the blocks according to the following specifications:
- `block_a`: 64 filters, `kernel_size` 3, repetitions 2
- `block_b`: 128 filters, `kernel_size` 3, repetitions 2
- `block_c`: 256 filters, `kernel_size` 3, repetitions 3
- `block_d`: 512 filters, `kernel_size` 3, repetitions 3
- `block_e`: 512 filters, `kernel_size` 3, repetitions 3

After block 'e', add the following layers: - `flatten`: use `Flatten`. - `fc`: create a fully connected layer using `Dense`. Give this 256 units, and a 'relu' activation. - `classifier`: create the classifier using a `Dense` layer. The number of units equals the number of classes. For multi-class classification, use a 'softmax' activation.

1.3.2 `call`

Connect these layers together using the functional API syntax: - `inputs` - `block_a` - `block_b` - `block_c` - `block_d` - `block_e` - `flatten` - `fc` - `classifier`

Return the classifier layer.

```
[67]: class MyVGG(tf.keras.Model):

    def __init__(self, num_classes):
        super(MyVGG, self).__init__()

        # Creating blocks of VGG with the following
        # (filters, kernel_size, repetitions) configurations
        self.block_a = Block(filters=64, kernel_size=3, repetitions=2)
        self.block_b = Block(filters=128, kernel_size=3, repetitions=2)
        self.block_c = Block(filters=256, kernel_size=3, repetitions=3)
        self.block_d = Block(filters=512, kernel_size=3, repetitions=3)
        self.block_e = Block(filters=512, kernel_size=3, repetitions=3)

        # Classification head
        # Define a Flatten layer
        self.flatten = tf.keras.layers.Flatten()
        # Create a Dense layer with 256 units and ReLU as the activation
        self.fc = tf.keras.layers.Dense(256, activation='relu')

        self.classifier = tf.keras.layers.Dense(num_classes, activation='softmax')
```

```

        self.fc = tf.keras.layers.Dense(256, activation='relu')
        # Finally add the softmax classifier using a Dense layer
        self.classifier = tf.keras.layers.Dense(num_classes,
        ↪activation='softmax')

    def call(self, inputs):
        # Chain all the layers one after the other
        x = self.block_a(inputs)
        x = self.block_b(x)
        x = self.block_c(x)
        x = self.block_d(x)
        x = self.block_e(x)
        x = self.flatten(x)
        x = self.fc(x)
        x = self.classifier(x)
        return x

```

```
[68]: utils.test_myvgg_class(MyVGG, Block)
```

All public tests passed

1.3.3 Load data and train the VGG network (Optional)

You can now load the dataset and proceed to train your VGG network. - This will take a few minutes to complete and is **not required to complete the assignment**. - You can submit your work before starting the training.

```

[69]: dataset = tfds.load('cats_vs_dogs', split=tfds.Split.TRAIN, data_dir='data/')

# Initialize VGG with the number of classes
vgg = MyVGG(num_classes=2)

# Compile with losses and metrics
vgg.compile(optimizer='adam', loss='sparse_categorical_crossentropy',
        ↪metrics=['accuracy'])

# Define preprocessing function
def preprocess(features):
    # Resize and normalize
    image = tf.image.resize(features['image'], (224, 224))
    return tf.cast(image, tf.float32) / 255., features['label']

# Apply transformations to dataset
dataset = dataset.map(preprocess).batch(32)

# Train the custom VGG model

```

```
vgg.fit(dataset, epochs=10)
```

Epoch 1/10

2/Unknown - 35s 18s/step - loss: 0.6942 - accuracy: 0.4062

```
KeyboardInterrupt                                Traceback (most recent call
last)

<ipython-input-69-a97d1c255550> in <module>
    17
    18 # Train the custom VGG model
--> 19 vgg.fit(dataset, epochs=10)

/opt/conda/lib/python3.7/site-packages/tensorflow_core/python/keras/
engine/training.py in fit(self, x, y, batch_size, epochs, verbose, callbacks,
validation_split, validation_data, shuffle, class_weight, sample_weight,
initial_epoch, steps_per_epoch, validation_steps, validation_freq,
max_queue_size, workers, use_multiprocessing, **kwargs)
    817         max_queue_size=max_queue_size,
    818         workers=workers,
--> 819         use_multiprocessing=use_multiprocessing)
    820
    821     def evaluate(self,

/opt/conda/lib/python3.7/site-packages/tensorflow_core/python/keras/
engine/training_v2.py in fit(self, model, x, y, batch_size, epochs, verbose,
callbacks, validation_split, validation_data, shuffle, class_weight,
sample_weight, initial_epoch, steps_per_epoch, validation_steps,
validation_freq, max_queue_size, workers, use_multiprocessing, **kwargs)
    340         mode=ModeKeys.TRAIN,
    341         training_context=training_context,
--> 342         total_epochs=epochs)
    343         cbks.make_logs(model, epoch_logs, training_result,
ModeKeys.TRAIN)
    344

/opt/conda/lib/python3.7/site-packages/tensorflow_core/python/keras/
engine/training_v2.py in run_one_epoch(model, iterator, execution_function,
dataset_size, batch_size, strategy, steps_per_epoch, num_samples, mode,
training_context, total_epochs)
```



```

126         step=step, mode=mode, size=current_batch_size) as batch_logs:
127     try:
--> 128         batch_outs = execution_function(iterator)
129     except (StopIteration, errors.OutOfRangeError):
130         # TODO(kaftan): File bug about tf function and errors.
↳ OutOfRangeError?

```

```

/opt/conda/lib/python3.7/site-packages/tensorflow_core/python/keras/
↳ engine/training_v2_utils.py in execution_function(input_fn)
    96     # `numpy` translates Tensors to values in Eager mode.
    97     return nest.map_structure(_non_none_constant_value,
--> 98                             distributed_function(input_fn))
    99
100     return execution_function

```

```

/opt/conda/lib/python3.7/site-packages/tensorflow_core/python/eager/
↳ def_function.py in __call__(self, *args, **kwargs)
    566         xla_context.Exit()
    567     else:
--> 568         result = self._call(*args, **kwargs)
    569
    570     if tracing_count == self._get_tracing_count():

```

```

/opt/conda/lib/python3.7/site-packages/tensorflow_core/python/eager/
↳ def_function.py in _call(self, *args, **kwargs)
    597         # In this case we have created variables on the first call, so
↳ we run the
    598         # defunned version which is guaranteed to never create
↳ variables.
--> 599         return self._stateless_fn(*args, **kwargs) # pylint:
↳ disable=not-callable
    600     elif self._stateful_fn is not None:
    601         # Release the lock early so that multiple threads can perform
↳ the call

```

```

/opt/conda/lib/python3.7/site-packages/tensorflow_core/python/eager/
↳ function.py in __call__(self, *args, **kwargs)
    2361         with self._lock:
    2362             graph_function, args, kwargs = self.
↳ _maybe_define_function(args, kwargs)
-> 2363         return graph_function._filtered_call(args, kwargs) # pylint:
↳ disable=protected-access
    2364

```

2365 @property

```
    /opt/conda/lib/python3.7/site-packages/tensorflow_core/python/eager/
↳function.py in _filtered_call(self, args, kwargs)
    1609         if isinstance(t, (ops.Tensor,
    1610                               resource_variable_ops.
↳BaseResourceVariable))),
    -> 1611         self.captured_inputs)
    1612
    1613     def _call_flat(self, args, captured_inputs,
↳cancellation_manager=None):

    /opt/conda/lib/python3.7/site-packages/tensorflow_core/python/eager/
↳function.py in _call_flat(self, args, captured_inputs, cancellation_manager)
    1690         # No tape is watching; skip to running the function.
    1691         return self._build_call_outputs(self._inference_function.call(
    -> 1692             ctx, args, cancellation_manager=cancellation_manager))
    1693         forward_backward = self._select_forward_and_backward_functions(
    1694             args,
```

```
    /opt/conda/lib/python3.7/site-packages/tensorflow_core/python/eager/
↳function.py in call(self, ctx, args, cancellation_manager)
    543             inputs=args,
    544             attrs=("executor_type", executor_type, "config_proto",
↳config),
    --> 545             ctx=ctx)
    546         else:
    547             outputs = execute.execute_with_cancellation(
```

```
    /opt/conda/lib/python3.7/site-packages/tensorflow_core/python/eager/
↳execute.py in quick_execute(op_name, num_outputs, inputs, attrs, ctx, name)
    59         tensors = pywrap_tensorflow.TFE_Py_Execute(ctx._handle,
↳device_name,
    60                                                         op_name, inputs,
↳attrs,
    ---> 61                                                         num_outputs)
    62     except core._NotOkStatusException as e:
    63         if name is not None:
```

KeyboardInterrupt:

[]: