

# api.dez.ro

## Ads, Brands, Models & Parts — API Reference

*Last updated: 2026-06-30*

### Base URL

All requests are made to the API root: <https://api.dez.ro/>

### Authentication & Required Headers

Every request must include the following headers:

| Header        | Description                                                                             |
|---------------|-----------------------------------------------------------------------------------------|
| Authorization | Bearer <API_KEY> — a key issued to the consuming app/system. Required on every request. |
| X-MEDIUM      | dezro                                                                                   |

Endpoints that require a logged-in user additionally require:

| Header          | Description                                                        |
|-----------------|--------------------------------------------------------------------|
| X-Session-Token | Token returned by POST /user/login. Identifies the logged-in user. |

*Endpoints in this document are marked "No session token required" where login is not needed.*

### Response Format

All responses are JSON. HTTP status codes are used alongside the body.

Success:

```
{ "data": { ... } }
```

Error:

```
{ "error": "Human readable message" }
```

Error messages are translated based on X-MEDIUM (Romanian for dezro). Any message not yet translated falls back to English.

### Brands

Brand endpoints return vehicle makes. The available types depend on the active X-MEDIUM:

| Medium | Available types  |
|--------|------------------|
| dezro  | car, truck, tire |

*tire brands have no corresponding models.*

### GET /brands

Returns the available brands, grouped by type.

Headers: Authorization and X-MEDIUM only (no session token required).

Query parameters:

| Parameter   | Description                                                                                                                                                                      |
|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| with_models | If present and not 0/false (e.g. ?with_models or ?with_models=1), each car/truck brand includes its models array inline. tire brands never include models. Omit for brands only. |

Response 200 (with\_models=1, dezro):

```
{
  "data": {
    "brands": {
      "car": [
        {
          "id": 1,
          "name": "Audi",
          "alias": "audi",
          "models": [
            { "id": 10, "name": "A3", "alias": "a3" },
            { "id": 11, "name": "A4", "alias": "a4" }
          ]
        }
      ],
      "truck": [
        {
          "id": 100,
          "name": "Volvo",
          "alias": "volvo",
          "models": [
            { "id": 200, "name": "FH", "alias": "fh" }
          ]
        }
      ],
      "tire": [
        { "id": 300, "name": "Michelin", "alias": "michelin" }
      ]
    }
  }
}
```

Without with\_models, brand objects omit the models key.

## GET /brands/{type}

Returns the available brands for a single type, instead of all types at once. {type} must be one of the brand types listed for the active X-MEDIUM.

Headers: Authorization and X-MEDIUM only (no session token required).

Query parameters:

| Parameter   | Description                                                                             |
|-------------|-----------------------------------------------------------------------------------------|
| with_models | If present and not 0/false, each brand includes its models array inline (not for tire). |

Response 200 (/brands/car?with\_models=1):

```
{
  "data": {
    "brands": [
      {
        "id": 1,
        "name": "Audi",
        "alias": "audi",
        "models": [
          { "id": 10, "name": "A3", "alias": "a3" },
          { "id": 11, "name": "A4", "alias": "a4" }
        ]
      }
    ]
  }
}
```

Errors:

| Status | Body                                     | Reason                                          |
|--------|------------------------------------------|-------------------------------------------------|
| 404    | {"error": "Invalid brand type<br>'...'"} | {type} is not available for the active X-MEDIUM |

## GET /brands/{type}/{idBrand}/models

Returns the models for a single brand. {type} must be one of the brand types for the active X-MEDIUM. {idBrand} is the id of a brand returned by GET /brands.

Headers: Authorization and X-MEDIUM only (no session token required).

Response 200:

```
{
  "data": {
    "models": [
      { "id": 10, "name": "A3", "alias": "a3" },
      { "id": 11, "name": "A4", "alias": "a4" }
    ]
  }
}
```

Errors:

| Status | Body                                          | Reason                                          |
|--------|-----------------------------------------------|-------------------------------------------------|
| 404    | {"error": "Invalid brand type<br>'...'"}      | {type} is not available for the active X-MEDIUM |
| 422    | {"error": "Invalid brand id"}                 | {idBrand} is not numeric                        |
| 400    | {"error": "'tire' brands do not have models"} | Requested models for a tire-type brand          |

## Parts

Part endpoints return vehicle parts categories. Categories form a tree — a part can have children, and each child can have its own children.

## GET /parts

Returns the available parts categories, grouped by type.

Headers: Authorization and X-MEDIUM only (no session token required).

Query parameters:

| Parameter     | Description                                                                                                                                                      |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| with_children | If present and not 0/false (e.g. ?with_children or ?with_children=1), each part recursively includes its full children tree. Omit for top-level categories only. |

Response 200 (?with\_children, dezro):

```
{
  "data": {
    "parts": {
      "car": [
        {
          "id": 1,
          "name": "Engine",
          "alias": "engine",
          "selectable": 1,
          "children": [
            {
              "id": 11,
              "name": "Pistons",
              "alias": "pistons",
              "selectable": 1,
              "children": [
                { "id": 111, "name": "Rings", "alias": "rings", "selectable": 1,
"children": [] }
              ]
            }
          ]
        }
      ],
      "truck": [
        { "id": 1, "name": "Cabin", "alias": "cabin", "selectable": 1, "children": [] }
      ]
    }
  }
}
```

Field notes:

| Field      | Description                                                                                                                                                                    |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| selectable | 0 for categories that exist only to group sub-categories and cannot be picked directly (e.g. when posting an ad). If selectable = 0, the user must choose one of its children. |

*Without with\_children, part objects omit the children key and only top-level categories are returned.*

## GET /parts/{type}

Returns the top-level parts categories for a single type, instead of all types at once. {type} must be one of the part types for the active X-MEDIUM.

Headers: Authorization and X-MEDIUM only (no session token required).

Query parameters:

| Parameter     | Description         |
|---------------|---------------------|
| with_children | Same as GET /parts. |

Response 200:

```
{
  "data": {
    "parts": [
      { "id": 1, "name": "Engine", "alias": "engine", "selectable": 1 },
      { "id": 2, "name": "Body", "alias": "body", "selectable": 1 }
    ]
  }
}
```

Errors:

| Status | Body                                 | Reason                                          |
|--------|--------------------------------------|-------------------------------------------------|
| 404    | {"error": "Invalid part type '...'"} | {type} is not available for the active X-MEDIUM |

## GET /parts/{type}/{idPart}/children

Returns the direct children of a single parts category. {type} must be one of the part types for the active X-MEDIUM. {idPart} is the id of a part returned by GET /parts or this endpoint.

Headers: Authorization and X-MEDIUM only (no session token required).

Query parameters:

| Parameter     | Description                                            |
|---------------|--------------------------------------------------------|
| with_children | Same as GET /parts, applied recursively to each child. |

Response 200:

```
{
  "data": {
    "children": [
      { "id": 11, "name": "Pistons", "alias": "pistons", "selectable": 1 },
      { "id": 12, "name": "Valves", "alias": "valves", "selectable": 0 }
    ]
  }
}
```

*An empty children array means the part has no further children (it is a leaf node).*

Errors:

| Status | Body                                 | Reason                                          |
|--------|--------------------------------------|-------------------------------------------------|
| 404    | {"error": "Invalid part type '...'"} | {type} is not available for the active X-MEDIUM |
| 422    | {"error": "Invalid part id"}         | {idPart} is not numeric                         |

## Ads

Ad endpoints allow authenticated users to create, retrieve, update, and delete their own listings. **Ads are not published immediately; they appear live on the site only after admin approval.**

## Ad Types

Each ad belongs to one of the following types. Available types depend on X-MEDIUM:

| Type ID | dezro label     | idModel required | idPart required |
|---------|-----------------|------------------|-----------------|
| 0       | Piese Auto      | Yes              | Yes             |
| 1       | Dezmembrări     | Yes              | No              |
| 2       | Mașini Avariate | Yes              | No              |
| 3       | Anvelope SH     | No               | No              |
| 4       | Piese camioane  | Yes              | Yes             |

Use `GET /ads/types` to retrieve these labels programmatically.

## GET /ads/types

Returns the available ad types for the active medium with their human-readable labels. No authentication required.

Headers: Authorization and X-MEDIUM only (no session token required).

Response 200 (dezro):

```
{
  "data": {
    "types": [
      { "id": 0, "label": "Piese Auto" },
      { "id": 1, "label": "Dezmembrari" },
      { "id": 2, "label": "Masini Avariate" },
      { "id": 3, "label": "Anvelope SH" },
      { "id": 4, "label": "Piese camioane" }
    ]
  }
}
```

## POST /ads

Creates a new ad for the authenticated user. The ad is immediately visible on the site.

Headers:

| Header          | Value                                  |
|-----------------|----------------------------------------|
| Authorization   | Bearer <API_KEY>                       |
| X-MEDIUM        | dezro                                  |
| X-Session-Token | The token returned by POST /user/login |

Body (multipart/form-data for image uploads, or application/json without images):

| Field   | Required    | Description                                                          |
|---------|-------------|----------------------------------------------------------------------|
| title   | Yes         | Ad title.                                                            |
| type    | Yes         | Ad category (integer 0–4, see type table above).                     |
| idBrand | Yes         | Brand ID (must be > 0).                                              |
| idModel | Conditional | Model ID (must be > 0).<br>Required for all types except 3.          |
| idPart  | Conditional | Parts category ID (must be > 0).<br>Required for types 0 and 4 only. |

|             |     |                                                                  |
|-------------|-----|------------------------------------------------------------------|
| description | Yes | Long description.                                                |
| year        | No  | 4-digit year.                                                    |
| price       | No  | Price (integer, in RON for dezro).                               |
| qty         | No  | Quantity (integer).                                              |
| variant     | No  | Engine / version variant.                                        |
| oem         | No  | OEM part number.                                                 |
| images[]    | No  | Image files (JPEG, PNG, or WebP; max 8 MB each; up to 10 total). |

Response 201:

```
{
  "data": {
    "ad": {
      "id": 42,
      "alias": "janta-aliaj-bmw-2019",
      "approved": true,
      "url": "https://www.dez.ro/janta-aliaj-bmw-2019-42.html",
      "images": [
        { "id": 101, "url": "https://www.dez.ro/media/images/ads/5/42/janta-aliaj-bmw-2019.jpg" }
      ]
    }
  }
}
```

Errors:

| Status | Body                                 | Reason                                     |
|--------|--------------------------------------|--------------------------------------------|
| 401    | (401 Unauthorized)                   | Missing or invalid session token           |
| 422    | {"error": "title is required"}       | title is missing or empty                  |
| 422    | {"error": "description is required"} | description is missing or empty            |
| 422    | {"error": "type is required"}        | type is missing or not an integer          |
| 422    | {"error": "Invalid ad type"}         | type is not one of 0-4                     |
| 422    | {"error": "idBrand is required"}     | idBrand is missing or 0                    |
| 422    | {"error": "idModel is required"}     | idModel is missing or 0 when type is not 3 |
| 422    | {"error": "idPart is required"}      | idPart is missing or 0 when type is 0 or 4 |
| 422    | {"error": "Invalid year"}            | year is not a 4-digit number               |

## GET /ads

Returns the authenticated user's own non-deleted ads, newest first, paginated. If the ?count flag is set, returns a counts summary instead.

Headers:

| Header          | Value                                  |
|-----------------|----------------------------------------|
| Authorization   | Bearer <API_KEY>                       |
| X-MEDIUM        | dezro                                  |
| X-Session-Token | The token returned by POST /user/login |

Query parameters:

| Parameter | Description                                                                  |
|-----------|------------------------------------------------------------------------------|
| count     | If present (e.g. ?count or ?count=1), returns counts instead of the ad list. |
| page      | Page number (default: 1). Ignored when ?count is set.                        |

Response 200 (list):

```
{
  "data": {
    "ads": [
      {
        "id": 42,
        "title": "Janta aliaj BMW",
        "description": "Janta 17 inch, stare buna.",
        "type": 0,
        "idBrand": 5,
        "idModel": 12,
        "idPart": 88,
        "year": 2019,
        "price": 250,
        "qty": 1,
        "variant": "3.0d",
        "oem": null,
        "alias": "janta-aliaj-bmw-2019",
        "approved": true,
        "url": "https://www.dez.ro/janta-aliaj-bmw-2019-42.html",
        "images": [
          { "id": 101, "url": "https://www.dez.ro/media/images/ads/5/42/janta-aliaj-bmw-2019.jpg" }
        ],
        "created": 1750000000,
        "created_at": "2026-06-15T10:00:00+00:00",
        "modified": 1750000000,
        "modified_at": "2026-06-15T10:00:00+00:00"
      }
    ],
    "pagination": {
      "page": 1,
      "per_page": 10,
      "total": 3,
      "has_more": false
    }
  }
}
```

Response 200 (?count):

```
{
  "data": {
    "counts": {
      "total": 3,
      "approved": 2,
      "pending": 1
    }
  }
}
```

Field notes:

| Field    | Description                                                        |
|----------|--------------------------------------------------------------------|
| approved | true if the ad is live on the site.                                |
| url      | Full public URL of the ad on the site. null when not yet approved. |



|                 |                                                                      |
|-----------------|----------------------------------------------------------------------|
| images[].id     | Image ID, used with DELETE /ads/{idAd}/image/{idImage} to remove it. |
| counts.total    | Total non-deleted ads.                                               |
| counts.approved | Ads that are live.                                                   |
| counts.pending  | Ads awaiting approval (should be 0 for API-created ads).             |

Errors:

| Status | Body               | Reason                           |
|--------|--------------------|----------------------------------|
| 401    | (401 Unauthorized) | Missing or invalid session token |

## GET /ads/{idAd}

Returns full details for one of the authenticated user's own non-deleted ads.

Headers:

| Header          | Value                                  |
|-----------------|----------------------------------------|
| Authorization   | Bearer <API_KEY>                       |
| X-MEDIUM        | dezro                                  |
| X-Session-Token | The token returned by POST /user/login |

Response 200:

```
{
  "data": {
    "ad": {
      "id": 42,
      "title": "Janta aliaj BMW",
      "description": "Janta 17 inch, stare buna.",
      "type": 0,
      "idBrand": 5,
      "idModel": 12,
      "idPart": 88,
      "year": 2019,
      "price": 250,
      "qty": 1,
      "variant": "3.0d",
      "oem": null,
      "alias": "janta-aliaj-bmw-2019",
      "approved": true,
      "url": "https://www.dez.ro/janta-aliaj-bmw-2019-42.html",
      "images": [
        { "id": 101, "url": "https://www.dez.ro/media/images/ads/5/42/janta-aliaj-bmw-2019.jpg" }
      ],
      "created": 1750000000,
      "created_at": "2026-06-15T10:00:00+00:00",
      "modified": 1750000000,
      "modified_at": "2026-06-15T10:00:00+00:00"
    }
  }
}
```

Errors:

| Status | Body               | Reason                     |
|--------|--------------------|----------------------------|
| 401    | (401 Unauthorized) | Missing or invalid session |

|     |                            |                                                                 |
|-----|----------------------------|-----------------------------------------------------------------|
|     |                            | token                                                           |
| 422 | {"error": "Invalid ad id"} | {idAd} is not numeric                                           |
| 404 | {"error": "Ad not found"}  | Ad does not exist, belongs to another user, or has been deleted |

## POST /ads/{idAd} — Update ad

Updates an ad owned by the authenticated user. Every field is optional and independent — only supplied fields are changed. The alias is never updated on edit. Image uploads (images[]) are appended to the existing ones, up to 10 total; extras are ignored. Returns the ad's full current state.

*approved is not reset by edits; the admin may re-review if needed.*

Headers:

| Header          | Value                                  |
|-----------------|----------------------------------------|
| Authorization   | Bearer <API_KEY>                       |
| X-MEDIUM        | dezro                                  |
| X-Session-Token | The token returned by POST /user/login |

Body (multipart/form-data for image uploads, or application/json without images):

| Field       | Description                                                |
|-------------|------------------------------------------------------------|
| title       | Ad title.                                                  |
| type        | Ad category (integer 0–4).                                 |
| idBrand     | Brand ID (must be > 0 if sent).                            |
| idModel     | Model ID (must be > 0 if sent).                            |
| idPart      | Parts category ID (must be > 0 if sent).                   |
| description | Long description.                                          |
| year        | 4-digit year, or 0 to clear.                               |
| price       | Price (integer).                                           |
| qty         | Quantity (integer).                                        |
| variant     | Engine / version variant.                                  |
| oem         | OEM part number.                                           |
| images[]    | Image files to append (JPEG, PNG, or WebP; max 8 MB each). |

Response 200: same shape as GET /ads/{idAd}.

Errors:

| Status | Body                             | Reason                                                          |
|--------|----------------------------------|-----------------------------------------------------------------|
| 401    | (401 Unauthorized)               | Missing or invalid session token                                |
| 422    | {"error": "Invalid ad id"}       | {idAd} is not numeric                                           |
| 422    | {"error": "title is required"}   | title sent as empty string                                      |
| 422    | {"error": "Invalid ad type"}     | type sent but not one of 0–4                                    |
| 422    | {"error": "idBrand is required"} | idBrand sent but is 0                                           |
| 422    | {"error": "idModel is required"} | idModel sent but is 0                                           |
| 422    | {"error": "idPart is required"}  | idPart sent but is 0                                            |
| 422    | {"error": "Invalid year"}        | year sent but not a 4-digit number or 0                         |
| 404    | {"error": "Ad not found"}        | Ad does not exist, belongs to another user, or has been deleted |

## DELETE /ads/{idAd}

Soft-deletes an ad owned by the authenticated user. The ad is no longer returned by GET /ads or GET /ads/{idAd}, but remains in the database for admin review. The admin can permanently delete or restore it.

Headers:

| Header          | Value                                  |
|-----------------|----------------------------------------|
| Authorization   | Bearer <API_KEY>                       |
| X-MEDIUM        | dezro                                  |
| X-Session-Token | The token returned by POST /user/login |

Response 200:

```
{ "data": { "message": "Ad deleted" } }
```

Errors:

| Status | Body                       | Reason                                                                  |
|--------|----------------------------|-------------------------------------------------------------------------|
| 401    | (401 Unauthorized)         | Missing or invalid session token                                        |
| 422    | {"error": "Invalid ad id"} | {idAd} is not numeric                                                   |
| 404    | {"error": "Ad not found"}  | Ad does not exist, belongs to another user, or has already been deleted |

## DELETE /ads/{idAd}/image/{idImage}

Deletes a single image from an ad owned by the authenticated user. Use the id returned in the images array of GET /ads or GET /ads/{idAd} to identify the image.

Headers:

| Header          | Value                                  |
|-----------------|----------------------------------------|
| Authorization   | Bearer <API_KEY>                       |
| X-MEDIUM        | dezro                                  |
| X-Session-Token | The token returned by POST /user/login |

Response 200:

```
{ "data": { "message": "Image deleted" } }
```

Errors:

| Status | Body                          | Reason                                                                             |
|--------|-------------------------------|------------------------------------------------------------------------------------|
| 401    | (401 Unauthorized)            | Missing or invalid session token                                                   |
| 422    | {"error": "Invalid ad id"}    | {idAd} is not numeric                                                              |
| 422    | {"error": "Invalid image id"} | {idImage} is not numeric                                                           |
| 404    | {"error": "Image not found"}  | Image does not exist, belongs to a different ad, or the ad belongs to another user |

## Endpoint Quick Reference

| Method | Path                            | Auth          | Description                        |
|--------|---------------------------------|---------------|------------------------------------|
| GET    | /brands                         | API key only  | All brands, all types              |
| GET    | /brands/{type}                  | API key only  | Brands for one type                |
| GET    | /brands/{type}/{idBrand}/models | API key only  | Models for one brand               |
| GET    | /parts                          | API key only  | All parts categories, all types    |
| GET    | /parts/{type}                   | API key only  | Parts categories for one type      |
| GET    | /parts/{type}/{idPart}/children | API key only  | Children of one parts category     |
| GET    | /ads/types                      | API key only  | Available ad type labels           |
| POST   | /ads                            | Session token | Create a new ad (live immediately) |
| GET    | /ads                            | Session token | List own ads (paginated) or counts |
| GET    | /ads/{idAd}                     | Session token | Get one ad                         |
| POST   | /ads/{idAd}                     | Session token | Update an ad                       |
| DELETE | /ads/{idAd}                     | Session token | Soft-delete an ad                  |
| DELETE | /ads/{idAd}/image/{idImage}     | Session token | Delete one image from an ad        |