

NAME

mkdir – make directories

SYNOPSIS

mkdir [*OPTION*]... *DIRECTORY*...

DESCRIPTION

Create the *DIRECTORY*(ies), if they do not already exist.

Mandatory arguments to long options are mandatory for short options too.

-m, --mode=MODE

set file mode (as in `chmod`), not `a=rwx - umask`

-p, --parents

no error if existing, make parent directories as needed

-v, --verbose

print a message for each created directory

-Z, --context=CTX

set the SELinux security context of each created directory to *CTX*

--help display this help and exit

--version output version information and exit

AUTHOR

Written by David MacKenzie.

REPORTING BUGS

Report mkdir bugs to bug-coreutils@gnu.org

GNU coreutils home page: <http://www.gnu.org/software/coreutils/>

General help using GNU software: <http://www.gnu.org/gethelp/>

Report mkdir translation bugs to <http://translationproject.org/team/>

COPYRIGHT

Copyright © 2012 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later [<http://gnu.org/licenses/gpl.html>](http://gnu.org/licenses/gpl.html).

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

mkdir (2)

The full documentation for **mkdir** is maintained as a Texinfo manual. If the **info** and **mkdir** programs are properly installed at your site, the command

```
info coreutils 'mkdir invocation'
```

should give you access to the complete manual.