Rpractical_palermo

Alexa Palermo

2026-11-11

Part A: Basic Operations

```
#A1 *Create v as the sequence 5,10,15,....,50 using seq(). Print its length, sum, meean.*

v <- seq(from = 5, to = 50, by = 5)

# Print length, sum, and mean
length(v)
```

```
## [1] 10
```

```
sum(v)
```

```
## [1] 275
```

```
mean(v)
```

```
## [1] 27.5
```

```
#A2 *Create w that repeats
# Repeat the vector c(1, 2, 3) 4 times
w <- rep(c(1, 2, 3), times = 4)

# Repeat each element of c(1, 2, 3) 4 times
z <- rep(c(1, 2, 3), each = 4)

# Print w and z
w
```

```
##  [1] 1 2 3 1 2 3 1 2 3 1 2 3
```

```
z
```

```
##  [1] 1 1 1 1 2 2 2 2 3 3 3 3
```

```
#A3
17 %% 5
```

```
## [1] 2
```

```
17 %/% 5
```

```
## [1] 3
```

```
2^10
```

```
## [1] 1024
```

```
sqrt(144)
```

```
## [1] 12
```

```
round(pi, 3)
```

```
## [1] 3.142
```

```
#A4
a <- c(2, 4, 6, 8)
b <- c(1, 3, 5, 7)

a + b
```

```
## [1]  3  7 11 15
```

```
a * b
```

```
## [1]  2 12 30 56
```

```
a > b
```

```
## [1] TRUE TRUE TRUE TRUE
```

```
sum(a * b)
```

```
## [1] 100
```

```
#A5

paste("Student", 1:3, sep = "-")
```

```
## [1] "Student-1" "Student-2" "Student-3"
```

```
typeof(42)
```

```
## [1] "double"
```

```
typeof(42L)
```

```
## [1] "integer"
```

```
typeof("42")
```

```
## [1] "character"
```

```
typeof(41i)
```

```
## [1] "complex"
```

```
typeof(TRUE)
```

```
## [1] "logical"
```

Part B:

```
#B1
students <- data.frame(
  id = 1:8,
name = c("Alice", "Bruno", "Chen", "Dana", "Elif", "Farid", "Grace", "Hiro"),
sex = c("F", "M", "M", "F", "F", "M", "F", "M"),
section = c("A", "B", "A", "C", "B", "C", "A", "B"),
midterm = c(78, 85, 92, 67, 74, 88, 95, 59),
final = c(82, 79, 96, 71, 80, 91, 93, 65),
attendance = c(95, 88, 100, 72, 90, 85, 98, 60),
```

```
stringsAsFactors = FALSE
)
```

```
#B2
str(students)
```

```
## 'data.frame':    8 obs. of  7 variables:
##  $ id        : int  1 2 3 4 5 6 7 8
##  $ name      : chr  "Alice" "Bruno" "Chen" "Dana" ...
##  $ sex       : chr  "F" "M" "M" "F" ...
##  $ section   : chr  "A" "B" "A" "C" ...
##  $ midterm   : num  78 85 92 67 74 88 95 59
##  $ final     : num  82 79 96 71 80 91 93 65
##  $ attendance: num  95 88 100 72 90 85 98 60
```

```
dim(students)
```

```
## [1] 8 7
```

```
colnames(students)
```

```
## [1] "id"         "name"       "sex"        "section"    "midterm"
## [6] "final"      "attendance"
```

```
summary(students)
```

```
##        id              name               sex             section     midterm
##  Min.   :1.00   Length   :8   Length   :8   Length   :8   Min.   :59.00
##  1st Qu.:2.75   N.unique :8   N.unique :2   N.unique :3   1st Qu.:72.25
##  Median :4.50   N.blank  :0   N.blank  :0   N.blank  :0   Median :81.50
##  Mean   :4.50   Min.nchar:4   Min.nchar:1   Min.nchar:1   Mean   :79.75
##  3rd Qu.:6.25   Max.nchar:5   Max.nchar:1   Max.nchar:1   3rd Qu.:89.00
##  Max.   :8.00                                           Max.   :95.00
##      final         attendance
##  Min.   :65.00   Min.   : 60.00
##  1st Qu.:77.00   1st Qu.: 81.75
##  Median :81.00   Median : 89.00
##  Mean   :82.12   Mean   : 86.00
##  3rd Qu.:91.50   3rd Qu.: 95.75
##  Max.   :96.00   Max.   :100.00
```

```
#B3
students$average <- round(rowMeans(students[, c("midterm", "final")]), 1)
```

```
#B4
students$passed <- students$average >= 70 & students$attendance >= 75
```

```
#B5
students$standing <- ifelse(students$average >= 90, "Honors",
                     ifelse(students$average >= 75, "Good", "Needs Support"))
```

```
#B6
classify <- function(score) {
  if (score >= 85) {
    return("Distinction")
  } else if (score >= 70) {
    return("Merit")
  } else if (score >= 50) {
```

```
    return("Pass")
  } else {
    return("Fail")
  }
}

sapply(c(90, 73, 55, 40), classify)
```

```
## [1] "Distinction" "Merit"       "Pass"        "Fail"
```

Part C: rbind() cbind()

```
#C1
new_students <- data.frame(
id = c(9, 10),
name = c("Ines", "Jamal"),
sex = c("F", "M"),
section = c("C", "A"),
midterm = c(81, 70),
final = c(84, 68),
attendance = c(92, 80),
stringsAsFactors = FALSE
)
new_students$average <- round(rowMeans(new_students[, c("midterm", "final")]), 1)
new_students$passed <- new_students$average >= 70 & new_students$attendance >= 75
new_students$standing <- ifelse(new_students$average >= 90, "Honors",
                   ifelse(new_students$average >= 75, "Good", "Needs Support"))

students_all <- rbind(students, new_students)
```

```
#C2
quiz <- c(8, 7, 10, 6, 7, 9, 10, 5, 8, 6)
students_all <- cbind(students_all, quiz = quiz)
class(students_all)
```

```
## [1] "data.frame"
```

```
#C3
m <- cbind(midterm = students_all$midterm, final = students_all$final)
m <- rbind(m, mean = colMeans(m))
```

```
#C4
tryCatch(
rbind(students, bad),
error = function(e) {
message("rbind failed: ", conditionMessage(e))
  NULL
  }
)
```

```
## rbind failed: object 'bad' not found
```

```
## NULL
```

Part D: Subsetting

```
#D1
students_all$name
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dana"  "Elif"  "Farid" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

```
students_all[["name"]]
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dana"  "Elif"  "Farid" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

```
students_all[, "name"]
```

```
##  [1] "Alice" "Bruno" "Chen"  "Dana"  "Elif"  "Farid" "Grace" "Hiro"  "Ines"
## [10] "Jamal"
```

```
#D2
students_all[2:5, c("name", "midterm", "final")]
```

```
##    name midterm final
## 2 Bruno      85    79
## 3  Chen      92    96
## 4  Dana      67    71
## 5  Elif      74    80
```

```
#D3
students_all[students_all$attendance > 90, ]
```

```
##   id  name sex section midterm final attendance average passed standing quiz
## 1  1 Alice   F       A      78    82         95    80.0   TRUE     Good    8
## 3  3  Chen   M       A      92    96        100    94.0   TRUE   Honors   10
## 7  7 Grace   F       A      95    93         98    94.0   TRUE   Honors   10
## 9  9  Ines   F       C      81    84         92    82.5   TRUE     Good    8
```

```
#D4
subset(
  students_all,
  sex == "F" & section %in% c("A", "C") & final >= 75,
  select = c(name, section, final)
)
```

```
##    name section final
## 1 Alice       A    82
## 7 Grace       A    93
## 9  Ines       C    84
```

```
#D5
students_all$name[which.max(students_all$average)]
```

```
## [1] "Chen"
```

```
students_all$name[which.min(students_all$average)]
```

```
## [1] "Hiro"
```

```
#D6
students_sorted <- students_all[order(-students_all$average), ]
head(students_sorted, 3)
```

```
##   id  name sex section midterm final attendance average passed standing quiz
## 3  3  Chen   M       A      92    96        100    94.0   TRUE   Honors   10
## 7  7 Grace   F       A      95    93         98    94.0   TRUE   Honors   10
## 6  6 Farid   M       C      88    91         85    89.5   TRUE     Good    9
```

Part E: Basic Factors

```
#E1:
```

```
#E2:
```

‘