

**目录**

1. Week 3 Exercises
  1. sum3str.c
  2. sum3argA.c
  3. sum3argB.c
  4. postfixStack.txt
  5. postfixQueue.txt
  6. qush.c
  7. matcher.c

## Week 3 Exercises

### sum3str.c

Assume you have the following string declarations:

切换行号显示

```
1 char *r = "1";
2 char *s = "23";
3 char *t = "456";
```

Write a short program that uses the `sscanf()` function to read these 3 strings, sums them as if they were integers, and then prints the total on `stdout`. (Remember a `scanf()` returns an `int`, which is the number of arguments it has read.)

### sum3argA.c

Write a short program that uses `sscanf()` to read 3 strings from the command line. If the arguments are all numerical, the program should sum them, and print the total.

- *What happens if one or more of the arguments is not an integer?* For example, try `./sum3argA 1 z 3`

### sum3argB.c

Modify **sum3argA.c** to now use the `stdlib` function `atoi()` instead of `sscanf()`. The program should also print the total of the 3 arguments.

- *What happens if one or more of the arguments is not a number?* For example, try `./sum3argB 1 z 3`

### postfixStack.txt

Consider postfix expressions consisting of integer operands and the operators `+` and `*`.

We saw in lectures that evaluating such a postfix expression using a stack involves *pushing* operands onto the (top of the) stack, and whenever an operator is encountered, *popping* the top 2 elements off the stack, performing the operation, and *pushing* the result back onto the stack. This process is repeated until there is a single operand left on the stack (and there is no more input). This operand is the result of the postfix expression. So for example, given the expression "1 2 +", the contents of the stack after each *push* action is

```
<<1>>
<<2,1>>
<<3>>
```

where left-to-right is considered top-to-bottom.

Show the contents of the stack after each *push* for the postfix expression "1 2 3 + 4 5 \* + 6 \* +".

## postfixQueue.txt

If a queue is used instead of a stack, then instead of pushing onto the stack, operands and results are *qushed* onto the queue (the bottom of the data structure). Evaluate the postfix expression from the previous exercise using a queue, showing the contents after each *qush* action.

## qush.c

- Implement the *qush* operation in the *quack* ADT described in Week 3's lecture.
- Test it by compiling it with the client *Josephus.c*.

## matcher.c

A stack can be used to check that opening and closing brackets: '(', ')', '[', ']', '{' and '}', are balanced in given text. For example,  $(a[i]+b[j])*c[k]$  is balanced, and so is

```
void f(char a[], int n) {int i; for(i=0;i<n;i++) a[i] =
(a[i]*a[i]*a[i])*(i+1); return;}
```

Mismatches can occur for for 3 reasons:

- A. mixed kinds, e.g.  $(a+1\}$
- B. missing opening, e.g.  $a[1])$
- C. missing closing, e.g.  $((a+1)$

A basic algorithm to match brackets  $((), [] \text{ and } \{\})$  can use a stack, in the following way:

- if you read an opening bracket, push it onto the stack
- if you read a closing bracket, pop the stack, and ...
  - ... compare that character with the closing bracket
    - if not the same, then brackets are mismatched // case A above
  - if the pop generates underflow then brackets are mismatched // case B

- after all characters have been read:
  - if the stack is not empty, then mismatched // case C

In this exercise,

1. Using the *quack* ADT, write a program that reads from *stdin*, and reports a mismatch if an opening bracket '(', '[' or '{' is not correctly matched with a closing bracket ')', ']' or '}' (resp.).

If all the brackets match, then the program generates no output, otherwise it prints the string *mismatch detected*. So for example if the file *data.inp* contains the 'bad' text `{ [ ] }`, then

```
prompt$ ./matcher < data.inp
mismatch detected
```

or you can test using a pipe for example

```
prompt$ echo "(() )" | ./matcher
prompt$
```

Also try the following test cases as well as any you create yourself:

```
{ [ { { } } { } ( ( [ ] ( [ ] ( ( ( ( [ ] ) { } ) ) ) ) ) ( ) ( ) ( ) ) { } } ] }
```

and

```
{ [ { { } } { } ( ( [ ] ( [ ] ( ( ( ( [ ] ) { } ) ) ) ) ) ( ) ( ) ( ) ) { } } ] }
```

2. Provide a fragment of C code that contains no syntax errors, but would fail your *matcher* program.