

QSS20: Modern Statistical Computing

Unit 09: Text as data

Goals for today

- ▶ Pset & final project logistics
- ▶ Recap of regex
- ▶ Lecture & code walkthrough: text as data!

Goals for today

- ▶ **Pset & final project logistics**
- ▶ Recap of regex
- ▶ Lecture & code walkthrough: text as data!

Pset logistics

Reminders:

- ▶ Invite Prof & TAs as collaborators to your assignment GitHub repo
 - ▶ Folks that haven't: **Chloe, Aaron, Edgar, Will, Shawn, Charles**
- ▶ Submit pset 3 by pushing completed notebook ('.ipynb' and '.html') to one partner's repo, then create an issue and assign to Prof & TAs
- ▶ Notify Prof. & TAs of your pset 3 pairings **before submitting** (very few have done this)
- ▶ To use a late day, let Prof & TAs know via private Piazza message
- ▶ Pset 3 solutions file and blank pset 4 will be uploaded this week

Suggestions:

- ▶ Confused by a module/method? Then own it! Consider contributing to GitHub Wiki function dictionary
- ▶ Need help? Come to office hours or group tutoring, or ask class via Piazza!

Questions?

Reminders: Installing things locally

By now you should have:

- ▶ Installed Python and terminal locally and become familiar with using them
- ▶ Cloned [the course GitHub repo](#) locally
- ▶ Created your own GitHub repo for psets (and invited Prof & TAs)
- ▶ Installed **all packages mentioned in** `requirements.txt` on course repo (will use these starting **today**)
 - ▶ Forewarning: Some of these packages **can't be installed and/or don't work** on JHub
 - ▶ Not every package can be installed via Anaconda; need to use `pip install` for some (including `mysql-connector-python`)

Soon you will:

- ▶ Submit pset 3 using GitHub repo and issues
- ▶ Create a GitHub repo for each final project group and invite Prof & TAs as collaborators
- ▶ Start building project codebase on GitHub repo

Final projects: SIP meeting tomorrow

- ▶ **When:** Tuesday, Feb. 7th (tomorrow), **4:30-5:15**
- ▶ **Where:** Over Zoom (check your email)
- ▶ **Who:** Andrea Caoili (Director of QA & Research) and Ann Klein (Director of Evaluation and Outcomes) of NCSS, our partner org; all SIP students that can make it (at least one from each group)
- ▶ **What:**
 - ▶ NCSS will overview of START and medical training program in particular
 - ▶ Each student group will share their rough plans and ask questions
 - ▶ NCSS & Prof. will give feedback to help focus & inform group's efforts
- ▶ **Goal:** make students' research useful to partner org & avoid reinventing the wheel

SIP teams: Please complete DUAs

Once all members complete DUA, you will get access to data. Folks who **haven't** signed the DUA are highlighted below:

Project	Partner A	Partner B	Partner C	Partner D
2: SIP: Medical IDD training	Spencer Allen	Emma Els-becker	Sabin Hart	Alex Ma
3: SIP: SIRS	John D'avano	Chloe Terestchenko	Ryan Wu	Mei Xu
4: SIP: SIRS	Leyla Jacoby	Keren Luo	Isabel Pantle	Jessie Wang
7: SIP: Medical IDD training	Aimen Abdulaziz	Esmeralda Abreu-Jerez	Bernardo Burnes Garza	Charles Knight
8: SIP: Medical IDD training	Akshay Kelshiker	Edgar Ozu-zun	Shawn Yoon	Jeremy Rodriguez

Next milestone for final project

Instructions for completing **final project milestone one** due Sunday 02/12 by 11:59 PM:

- ▶ Copy over template to your Overleaf account (**you shouldn't be able to edit shared version**)
 - ▶ Make sure your template has FIVE sections (added section 4 last week)
- ▶ Fill in the memo fields in Overleaf with your group (most of your work right now)
- ▶ Submit **one memo per group** on Canvas AND share on Overleaf with jhaber@berkeley.edu

Next milestone for final project

Activity

- ▶ Access the template and look over it with your group:
<https://www.overleaf.com/9461636581djcs gynkwkgk>
(Link is also on course website under "Final Project → Project Components".)
- ▶ Make a group working plan for how/when to get this done.

For groups doing SIP medical student training option, keep in mind these data limitations (though more data will be added this week):

- ▶ Background form and pre-assessment: **53** completed
- ▶ Foundational post assessment: 13 completed
- ▶ Intermediate post assessment: 5 completed
- ▶ Advanced post assessment: 15 completed
- ▶ Community prescriber feedback: 16 of these have been received
- ▶ Individual training module evaluations: **302**

Goals for today

- ▶ Pset & final project logistics
- ▶ **Recap of regex**
- ▶ Lecture & code walkthrough: text as data!

Recap of regex

What do you remember?

Recap of regex

Tips:

- ▶ Use 're.sub()' to clean strings
- ▶ If you just want to find all matches, use 're.findall()' (DataCamp uses this exclusively)
- ▶ To check for ANY matches (think: boolean output), use 're.match' for a short string or 're.search()' for a long one
- ▶ Practice with metacharacters and find a regex cheatsheet you like ([here's a good one for beginners](#), and [here's one with clear examples](#))

Useful commands/metacharacters:

```
re.sub(pattern, replace_this, string) # for substitution
re.findall(pattern, string) # list all matches
re.search(pattern, string) # search whole string
re.match(pattern, string) # search from start
\w | \s | \d | . : chars alphanum, space, numeric, anything
? : previous char/group MAY occur
+ | * : match one or more, any number
() | (?:) : matching, non-matching group
```

Where we are

- ▶ Pset & final project logistics
- ▶ Recap of regex
- ▶ **Lecture & code walkthrough: text as data!**

Outline of text as data

- ▶ Text as data: where can we find?
- ▶ Text mining/“supervised” analyses: know what we’re looking for in advance
 - ▶ Manual lookup of words or counting words from a dictionary
 - ▶ Automated process 1: part-of-speech tagging
 - ▶ Automated process 2: named entity recognition
 - ▶ Automated process 3: sentiment analysis using a scoring dictionary
- ▶ Unsupervised analyses: how can we more inductively discover themes/patterns in text?
 - ▶ Bag of words representation of text/preprocessing
 - ▶ Topic model: concepts
 - ▶ Topic model: implementation

Outline of text as data

- ▶ **Text as data: where can we find?**
- ▶ Text mining/“supervised” analyses: know what we’re looking for in advance
 - ▶ Manual lookup of words or counting words from a dictionary
 - ▶ Automated process 1: part-of-speech tagging
 - ▶ Automated process 2: named entity recognition
 - ▶ Automated process 3: sentiment analysis using a scoring dictionary
- ▶ Unsupervised analyses: how can we more inductively discover themes/patterns in text?
 - ▶ Bag of words representation of text/preprocessing
 - ▶ Topic model: concepts
 - ▶ Topic model: implementation

Where can you find text to use as data?

- ▶ **General guide:** just as an ethnographer thinks carefully about a field site, begin with your substantive interests—e.g., how do police treat residents of different races? How do college students share knowledge about Dartmouth's hidden curriculum—and think about text generated as things unfold in that area
- ▶ Two broad types:
 1. **One-way text outputs:** official documents (e.g., legislation; news articles; court cases); informal broadcasts (tweets, Yelp reviews, 311 complaints, and other social media data); informal notes professionals write about clients (e.g., caseworker notes; free text fields in medical records)
 2. **Two-way dialogues/interactions (may involve transforming video data \Rightarrow audio data \Rightarrow text):** transcripts from body camera data (Voigt et al. 2017); transcripts from physician-patient conversations (Hagiwara et al. 2017); message board data (Dimaggio et al., 2019); Slack data

Where can you find *openly-available* text to use as data?

- ▶ Usually combined with web scraping or using an API to acquire efficiently. Examples with clickable links:
- ▶ **Kaggle text data**: DOJ press releases; IMDB movie reviews data
 - ▶ Example: “If you like original gut wrenching laughter you will like this movie. If you are young or old then you will love this movie, hell even my mom liked it.”
- ▶ **Restaurant reviews dataset**
- ▶ **NYC housing code violations data**
 - ▶ Example: “Abate the nuisance consisting of roaches in the entire apartment “
- ▶ **Congressional bills data**
- ▶ **Tutorial on scraping Craigslist**, which can be used to study things like how people describe gentrifying neighborhoods
- ▶ **Job addendums**: “Workers may be subject to disciplinary action for failing to obtain employer’s permission for a personal long-distance call or to repay the cost of such call within a reasonable time.”

Outline of text as data

- ▶ Text as data: where can we find
- ▶ **Text mining/“supervised” analyses: know what we’re looking for in advance**
 - ▶ Manual lookup of words or counting words from a dictionary
 - ▶ Automated process 1: part-of-speech tagging
 - ▶ Automated process 2: named entity recognition
 - ▶ Automated process 3: sentiment analysis using a scoring dictionary
- ▶ Unsupervised analyses: how can we more inductively discover themes/patterns in text?
 - ▶ Bag of words representation of text/preprocessing
 - ▶ Topic model: concepts
 - ▶ Topic model: implementation

What do I mean by “supervised”?

1. *Text mining*: look for a pre-specified concept or category. Methods:
 - ▶ **Pattern matching**: look for a match for a specific sequence of characters
 - ▶ **Dictionary**: we have a list of words we think represent a category or concept (e.g., if we want to classify a review as negative, we might have a list of words or phrases we think represent the category like *boring; terrible; awful; literally the worst*)
2. *Supervised machine learning for classification*: pre-specify a category at the document level and learn how text predicts that category
 - ▶ Inputs, training data:
 - ▶ **Text**: movie review; legislative bill; message board chain; admissions essay
 - ▶ **Label for that text**: negative or not; Repub. sponsor or not; contentious or not; accepted or not
 - ▶ **Method**: often binary classification
 - ▶ **Output**: classifier that one can use for unlabeled data

Example of combining text mining with supervised ML

Language from police body camera footage shows racial disparities in officer respect

Rob Voigt^{1,†}, Nicholas R. Camp², Vinodkumar Prabhakaran¹, William L. Hamilton¹, Rebecca C. Hetey³, Camilla M. Griffiths¹, David Jurgens¹, Dan Jurafsky^{1,*,‡}, and Jennifer L. Eberhardt¹

¹Department of Linguistics, Stanford University, Stanford, CA 94305; ²Department of Psychology, Stanford University, Stanford, CA 94305; and ³Department of Computer Science, Stanford University, Stanford, CA 94305

Contributed by Jennifer L. Eberhardt, March 26, 2017; sent for review February 14, 2017; reviewed by James Pennebaker and Tom Tyler

Using footage from body-worn cameras, we analyze the respectfulness of police officer language toward white and black community members during routine traffic stops. We develop computational linguistic methods that extract levels of respect automatically from transcripts, informed by a thin-slicing study of participant ratings of officer utterances. We find that officers speak with consistently less respect toward black versus white community members, even after controlling for the race of the officer, the severity of the infraction, the location of the stop, and the outcome of the stop. Such disparities in common, everyday interactions between police and the communities they serve have important implications for procedural justice and the building of police-community trust.

Some have argued that racial disparities in perceived respect during routine encounters help fuel the mistrust of the controversial officer-involved shootings that have such great attention. However, do officers treat white and black members with a greater degree of respect than it is to blacks?

We address this question by analyzing officers' during vehicle stops of white and black community. Although many factors may shape those interactions, a word is undeniably critical. Through them, the officer communicates respect and understanding of a citizen's life, or contempt and disregard for their voice. Past the language of those in positions of institutional power (officers, judges, work superiors) has greater influence on the course of the interaction than the language used by less powerful (12–16). Measuring officer language thus a quantitative lens on one key aspect of the quality of police–community interactions, and offers new insights.

racial disparities | natural language processing | procedural justice | traffic stops | policing

- ▶ Had human raters code snippets of transcripts to generate labels of whether the interaction was “respectful” or not in a smaller sample of documents
- ▶ Generated features from the text using dictionary-based methods, e.g.
 - ▶ Informal titles: [“dude”, “bro”, “boss”, “bud”, “buddy”, “champ”, “man”, “guy”, “brotha”, “sista”, “son”, “sonny”, “chief”]
 - ▶ Time minimizing: “(minute—min—second—sec—moment)s?—this[^ .,?!]+quick—right back”
- ▶ Built model to predict respect ratings using those features

Our working example: NYC airbnb listings

name	neighbourhood_group	price
Nice and cozy little apt available	Bronx	75
Cozy and privat studio near Times Sq	Manhattan	140
NYCT02-3: Private Sunny Rm, NYU, Baruch, SOHO	Manhattan	75
Prime area in Chinatown and Little Italy	Manhattan	160
Midtown Manhattan Penthouse	Manhattan	100
2BR Comfy Apt - 15min from MIDTOWN	Queens	150
FourTwin bunkbeds- 5 minutes from JFK	Queens	90
Pvt Room in Quiet Home JFK 6mi LGA 10mi	Queens	38

Key variables: name: descriptive listing; neighbourhood_group: borough;
price: price of listing

Where you can find: `QSS20_public/public_data/airbnb_text.zip`

What are some interesting text features that might be correlated with price?

Positive words/euphemisms: nice; cozy; privat/private/pvt; comfy

Proximity to landmarks: Little Italy; Chinatown; NYU; SOHO; Times Sq

Proximity to airports: JFK; LGA

name	neighbourhood_group	price
Nice and cozy little apt available	Bronx	75
Cozy and privat studio near Times Sq	Manhattan	140
NYCT02-3: Private Sunny Rm, NYU, Baruch, SOHO	Manhattan	75
Prime area in Chinatown and Little Italy	Manhattan	160
Midtown Manhattan Penthouse	Manhattan	100
2BR Comfy Apt - 15min from MIDTOWN	Queens	150
FourTwin bunkbeds- 5 minutes from JFK	Queens	90
Pvt Room in Quiet Home JFK 6mi LGA	Queens	38

How might we go about creating indicators for whether the listing contains those attributes?

Code to follow along

```
https://github.com/jhaber-zz/QSS20\_public/blob/main/  
activities/05\_textasdata\_partI\_textmining.ipynb
```


Outline of text as data

- ▶ Text as data: where can we find
- ▶ Text mining/ “supervised” analyses: know what we’re looking for in advance
 - ▶ **Manual lookup of words or counting words from a dictionary**
 - ▶ Automated process 1: part-of-speech tagging
 - ▶ Automated process 2: named entity recognition
 - ▶ Automated process 3: sentiment analysis using a scoring dictionary
- ▶ Unsupervised analyses: how can we more inductively discover themes/patterns in text?
 - ▶ Bag of words representation of text/preprocessing
 - ▶ Topic model: concepts
 - ▶ Topic model: implementation

Manual approach 1: looking for single word

```
1 ## using the `name_upper` var, look at where reviews mention cozy
2 ab['is_cozy'] = np.where(ab.name_upper.str.contains("COZY"),
3                           True, False)
4
5 ## find the mean price by neighborhood and whether mentions cozy
6 mp = pd.DataFrame(ab.groupby(['is_cozy',
7                               'neighbourhood_group'])['price'].mean())
8
9 ## reshape to wide format so that each borough is row
10 ## and one col is the mean price for listings that describe
11 ## the place as cozy; other col is mean price for listings
12 ## without that word
13 mp_wide = pd.pivot_table(mp, index = ['neighbourhood_group'],
14                             columns = ['is_cozy'])
15
16 mp_wide.columns = ['no_mention_cozy', 'mention_cozy']
```

Result: within the same borough, higher prices in Airbnbs that don't describe the listing as cozy

neighbourhood_group	no_mention_cozy	mention_cozy
Bronx	89.231088	74.214286
Brooklyn	128.175441	91.130224
Manhattan	204.109775	129.917140
Queens	102.596682	80.344388
Staten Island	120.650307	74.319149

Manual approach 2: create dictionary of words summarizing concept and score each listing

```
1
2 ## construct dictionary
3 space_indicators = {'small': ['COZY', 'COMFY', 'LITTLE', 'SMALL'],
4                      'large': ['SPACIOUS', 'LARGE', 'HUGE', 'GIANT']}
5
6
7 ## for each listing, find the number of occurrences
8 ## of words in each key
9
10 ### first, let's test with one listing
11 practice_listing = "NICE AND COZY LITTLE APT AVAILABLE"
```

Counting the number of appearances in one listing (double counts if appears twice)

```
1 ### example string
2 practice_listing = "NICE AND COZY LITTLE APT AVAILABLE"
3
4 ### splitting at space and looking at overlap with each key in the
   dictionary
5 words_overlap_small = [word for word in practice_listing.split(" ")
6                         if word in space_indicators['small']]
7
8 words_overlap_large = [word for word in practice_listing.split(" ")
9                        if word in space_indicators['large']]
10
11 ### could then take length as a fraction of all words
12 len(words_overlap_small)/len(practice_listing.split(" "))
13 len(words_overlap_large)/len(practice_listing.split(" "))
```

Outline of text as data

- ▶ Text as data: where can we find
- ▶ Text mining/“supervised” analyses: know what we’re looking for in advance
 - ▶ Manual lookup of words or counting words from a dictionary
 - ▶ **Automated process 1: part-of-speech tagging**
 - ▶ Automated process 2: named entity recognition
 - ▶ Automated process 3: sentiment analysis using a scoring dictionary
- ▶ Unsupervised analyses: how can we more inductively discover themes/patterns in text?
 - ▶ Bag of words representation of text/preprocessing
 - ▶ Topic model: concepts
 - ▶ Topic model: implementation

Intro to part-of-speech tagging (POS) and named entity recognition (NER)

- ▶ Previous approach was very manual — we needed to read some reviews and manually construct a dictionary summarizing adjectives we thought were related to a concept
- ▶ We also didn't yet capture other price-relevant attributes of the review, or what we might call `named entities`
 1. **Places:** e.g., Chinatown, Little Italy, Times Square
 2. **Infrastructure** e.g., LGA; JFK

Part of speech tagging with example

```
1 ## specify example
2 example_for_tag = "This is a chill apt next to the subway in LES
   Chinatown"
3
4 ## try part of speech tagging using nltk
5 tokens = word_tokenize(example_for_tag) # Generate tokens
6 tokens_pos = pos_tag(tokens) # generate part of speech tags for
   those tokens
```

Output: a list of tuples where the first element in the tuple is the original word; second element in the tuple is the part of speech

```
for one_tok in tokens_pos:
    print(one_tok)
```

```
('This', 'DT')
('is', 'VBZ')
('a', 'DT')
('chill', 'NN')
('apt', 'JJ')
('next', 'JJ')
('to', 'TO')
('the', 'DT')
('subway', 'NN')
('in', 'IN')
('LES', 'NNP')
('Chinatown', 'NNP')
```


What do these mean? Common parts of speech

“This is a chill apt next to the subway in LES Chinatown”

tag	meaning	in our example
CC	coordinating conjunction	
CD	cardinal digit	
DT	determiner	This; the; a
JJ	adjective	apt; next
JJR	adjective (comparative; e.g., bigger)	
NN	noun (singular; e.g., desk)	chill; subway
NNS	noun (plural; e.g., desks)	
NNP	proper noun (singular; e.g., Harrison)	LES; Chinatown
NNPS	proper noun (plural; e.g., Americans)	
TO	to	
UH	interjection	
VB	verb (base form; e.g., take)	
VBD	verb (past form; e.g., took)	
VBG	verb (gerund/present; e.g., taking)	
VCN	verb (past participle; e.g., taken)	
VBZ	verb (3rd person singular present; e.g. takes)	

What if, after tagging, we want to extract the words from our text containing a specific part of speech?

Example: in our example string, extract the proper nouns (LES and Chinatown)

```
1 ## use list iteration to extract proper nouns
2 ## i'm first checking if the second element in the tuple is equal
   to NNP
3 ## if so, i'm returning the first element of the tuple (the
4 ## actual word)
5 all_prop_noun = [one_tok[0] for one_tok in tokens_pos
6                   if one_tok[1] == "NNP"]
7 all_prop_noun
```

Output:

```
all_prop_noun
```

```
['LES', 'Chinatown']
```

Outline of text as data

- ▶ Text as data: where can we find
- ▶ Text mining/“supervised” analyses: know what we’re looking for in advance
 - ▶ Manual lookup of words or counting words from a dictionary
 - ▶ Automated process 1: part-of-speech tagging
 - ▶ **Automated process 2: named entity recognition**
 - ▶ Automated process 3: sentiment analysis using a scoring dictionary
- ▶ Unsupervised analyses: how can we more inductively discover themes/patterns in text?
 - ▶ Bag of words representation of text/preprocessing
 - ▶ Topic model: concepts
 - ▶ Topic model: implementation

Named entity recognition

- ▶ Previous was useful for broad categories — e.g., LES and Chinatown both tagged as proper nouns
- ▶ With named entity recognition, we want to be able to classify proper nouns into more granular subtypes. See [spaCy label schemes](#) or [this blog](#) for a longer list of types; some relevant ones:
 - ▶ PERSON: e.g., Professor Xavier
 - ▶ FAC: building; highway; bridges - e.g., Boston Logan International Airport
 - ▶ GPE: countries; cities; states- e.g., Hanover, NH
 - ▶ ORG: organizations; e.g., Dartmouth College
 - ▶ DATE: e.g., October 10th, 2022
- ▶ To execute, we switch from `nltk` package to `spaCy` package

Example tweet to search for named entities

We'll be hosting on-campus COVID-19 booster clinics at Dartmouth College in New Hampshire from 9 a.m. to 6 p.m. on Monday, Jan. 10, and Tuesday, Jan. 11, at Alumni Hall in the Hopkins Center. For information on how to register and additional winter updates, head to

Which words do we think will be tagged as named entities?

Code to get named entities from that tweet

```
1 spacy_dtweet = nlp(d_tweet)
2 for one_tok in spacy_dtweet.ents:
3     print( " Entity: " + one_tok.text +
4           "; NER tag: " + one_tok.label_ )
```

Breaking this down:

- ▶ `nlp`: black-boxy function within `spacy` that adds tags to a string (not only named entities)
- ▶ `spacy_dtweet.ents`: extracting all named entities from the `spacy` object
- ▶ `one_tok`: arbitrary placeholder for one entity
- ▶ `one_tok.text`: original string
- ▶ `one_tok.label_`: named entity label for that string

Output of named entities in tweet

We'll be hosting on-campus COVID-19 booster clinics at Dartmouth College in New Hampshire from 9 a.m. to 6 p.m. on Monday, Jan. 10, and Tuesday, Jan. 11, at Alumni Hall in the Hopkins Center. For information on how to register and additional winter updates, head to

Entity: Dartmouth College; NER tag: ORG
Entity: New Hampshire; NER tag: GPE
Entity: 9 a.m. to 6 p.m.; NER tag: TIME
Entity: Monday, Jan. 10; NER tag: DATE
Entity: Tuesday, Jan. 11; NER tag: DATE
Entity: Alumni Hall; NER tag: WORK_OF_ART
Entity: the Hopkins Center; NER tag: FAC

Coding break

Play around with different variations of the Dartmouth tweet and look at the results. E.g.:

- ▶ What happens if you abbreviate New Hampshire to NH?
- ▶ What happens if you add the word Pfizer before COVID-19?
- ▶ What entities seem misclassified?

Outline of text as data

- ▶ Text as data: where can we find
- ▶ Text mining/“supervised” analyses: know what we’re looking for in advance
 - ▶ Manual lookup of words or counting words from a dictionary
 - ▶ Automated process 1: part-of-speech tagging
 - ▶ Automated process 2: named entity recognition
 - ▶ **Automated process 3: sentiment analysis using a scoring dictionary**
- ▶ Unsupervised analyses: how can we more inductively discover themes/patterns in text?
 - ▶ Bag of words representation of text/preprocessing
 - ▶ Topic model: concepts
 - ▶ Topic model: implementation

Sentiment analysis: dictionary-based approach

- ▶ Operates similarly to our manual dictionary but, in this case, keys are words in a “lexicon”; values are the sentiment score
- ▶ In basic form, a dictionary of two types of words (often non-exhaustive, where others treated as neutral):
 1. Positive
 2. Negative

Code for VADER sentiment scoring: calc. sentiment

```
1 ## initialize a scorer
2 sent_obj = SentimentIntensityAnalyzer()
3
4 ## score one listing
5 practice_listing = "NICE AND COZY LITTLE APT AVAILABLE"
6 sentiment_example = sent_obj.polarity_scores(practice_listing)
```

Breaking this down:

- ▶ `sent_obj = SentimentIntensityAnalyzer()`: initializing a scorer
- ▶ `sent_obj.polarity_scores(practice_listing)`: from that initialized scorer, apply the polarity scores function to the single string we're feeding it
 - ▶ Score is aggregated to the level of the text you feed it; e.g., here we're scoring a sentence; might score a paragraph or document

Code for VADER sentiment scoring: what the output is

Dictionary with four keys: neg, neu, pos, compound (summary of pos, neg, neutral; standardized to be between -1 = most negative to +1 = most positive)

```
print("String: " + practice_listing + " scored as:\n" + str(sentiment_example))
print("String: " + practice_listing_2 + " scored as:\n" + str(sentiment_example_2))
print("String: " + practice_listing_3 + " scored as:\n" + str(sentiment_example_3))
```

```
String: NICE AND COZY LITTLE APT AVAILABLE scored as:
{'neg': 0.0, 'neu': 0.641, 'pos': 0.359, 'compound': 0.4215}
String: NICE AND COZY LITTLE APT AVAILABLE. REALLY TERRIBLE VIEW. scored as:
{'neg': 0.257, 'neu': 0.531, 'pos': 0.212, 'compound': -0.1513}
String: NICE AND COZY LITTLE APT AVAILABLE. HAS RATS THOUGH. scored as:
{'neg': 0.0, 'neu': 0.741, 'pos': 0.259, 'compound': 0.4215}
```

Issues:

- ▶ Many words classified as neutral
- ▶ Appropriately added Terrible to negative score, but didn't know the context-specific rats should be scored negatively

One way to improve: augment the default VADER dictionary

```
1 ## create a dictionary with
2 ## negative scores for pests
3 pest_words = {
4     'rat': -1.9, 'rats': -1.9,
5     'mice': -1.9, 'mouse': -1.9,
6     'roach': -1.9, 'cockroach': -1.9
7 }
8 ## update the lexicon with that
9 ## dictionary (created new sentiment object
10 ## to avoid writing over older one)
11 new_si = SentimentIntensityAnalyzer()
12 new_si.lexicon.update(pest_words)
13 ## use that updated scorer
14 new_si.polarity_scores(practice_listing_3)
```

Output (went from 0 negative to 0.228 negative):

```
print("After lexicon update: " + practice_listing_3 + " scored as:\n" + \
      str(new_si.polarity_scores(practice_listing_3)))
```

```
After lexicon update: NICE AND COZY LITTLE APT AVAILABLE. HAS RATS THOUGH. scored as:
{'neg': 0.228, 'neu': 0.551, 'pos': 0.22, 'compound': -0.0258}
```

Better way to improve: build a custom classifier

listing_id	avg_stars	terms in listing					...
		cozy	rat	spacious	cable	marble	
1	2.4	1	1	0	0	0	
2	3.8	0	0	1	0	1	
3	4.9	1	0	1	1	0	
⋮							

QSS20: Modern Statistical Computing

Unit 09: Text as data

Recap of text mining

What do you remember?

Recap of text mining

Tips:

- ▶ To find text data within a social context, think about what *traces* people leave behind through interaction: reports, emails, notes, etc.
- ▶ Or use large, well-documented, openly accessible data (e.g., Cook County felony sentencing data) because it's there
- ▶ Supervised vs. unsupervised: Do we already know what we're looking for, or do we want to let the data tell us?
- ▶ Methods for creating indicators in text data:
 - ▶ Count words in a *dictionary*: set of conceptually related terms (weighted or not)
 - ▶ Count "parts of speech": what proportion of words are nouns vs. verbs?
 - ▶ Count named entities: buildings vs. people vs. works of art

Useful commands/POS tags/NER labels:

```
nltk.tokenize.word_tokenize(txt) # convert txt into tokens
nltk.pos_tag(tokens) # get POS tags by token
JJ; NN; VB; DT # POS tags for adj, noun, verb, determiner
nlp = en_core_web_sm.load(); nlp(txt) # run NER pipeline (and more)
token.text; token.label_ # retrieve text, NER label
PERSON; FAC; GPE; ORG # NER labels
SentimentIntensityAnalyzer().polarity_scores(text)
```

Outline of text as data

- ▶ Text as data: where can we find
- ▶ Text mining/“supervised” analyses: know what we’re looking for in advance
 - ▶ Manual lookup of words or counting words from a dictionary
 - ▶ Automated process 1: part-of-speech tagging
 - ▶ Automated process 2: named entity recognition
 - ▶ Automated process 3: sentiment analysis using a scoring dictionary
- ▶ **Unsupervised analyses: how can we more inductively discover themes/patterns in text?**
 - ▶ **Bag of words representation of text/preprocessing**
 - ▶ Topic model: concepts
 - ▶ Topic model: implementation in python

Text mining of Airbnb listings versus topic modeling

- ▶ Suppose we were interested in looking at relationship between (1) what words people use to describe their airbnb listing and (2) neighborhood change (e.g., rapid demographic change, as measured through changes in ethnicity/income of those residing in the neighborhood)
- ▶ **Text mining approach:** build a dictionary of words or phrases we think signal gentrifying (*cute; safe; near cold brew*) and look at correlation with neighborhood change
- ▶ Drawbacks:
 - ▶ Might be difficult to know in advance which words to include
 - ▶ Lack of surprise: what if there's a pattern in the listings correlated with demographic change, but that we didn't anticipate?
- ▶ Therefore, rather than search for specific words or phrases, begin with *full text* of the document

Tokenize/represent document as a bag of words

- Represent each document as a “bag of words”, where order doesn't matter

- Examples:

```
['clean', '&', 'quiet', 'apt', 'home', 'by', 'the', 'park']
```

```
['skylit', 'midtown', 'castle']
```

```
['the', 'village', 'of', 'harlem', '....', 'new', 'york', '!']
```

```
['cozy', 'entire', 'floor', 'of', 'brownstone']
```

- Notice that it contains a lot of extraneous information

Open up notebook and follow along

05_textasdata_partII_topicmodeling.ipynb

Step one: create stopwords list to filter out

Why do this early? Especially if you want to create your own list of stopwords for your context, it's easier to do that before additional preprocessing that alters the words (e.g., might abbreviate apartment to apart)

```
1 ## call the specific module
2 from nltk.corpus import stopwords
3
4 ## call a specific set of stopwords from package
5 list_stopwords = stopwords.words('english')
6
7 ## augment with your own
8 list_stopwords = stopwords.words("english")
9
10 custom_words_toadd = ['apartment', 'new york', 'nyc',
11                       'bronx', 'brooklyn',
12                       'manhattan', 'queens',
13                       'staten island']
14
15 list_stopwords_new = list_stopwords + custom_words_toadd
```

Step two: convert text to lowercase and filter out stopwords

```
16 ## convert to lowercase and a list
17 corpus_lower = ab.name.str.lower().to_list()
18
19 ## use wordpunct tokenize and filter out with one
20 example_listing = corpus_lower[0]
21 nostop_listing = [word for word in wordpunct_tokenize(
22     example_listing
23     if word not in list_stopwords_new)]
nostop_listing
```

Before:

```
['cozy', 'entire', 'floor', 'of', 'brownstone']
```

After (removes by and the):

```
['cozy', 'entire', 'floor', 'brownstone']
```

Step three: stem and additional preprocessing

```
24 ## initialize stemmer
25 porter = PorterStemmer()
26
27 ## apply to one tokenized text by iterating
28 ## over the tokens in the text
29 example_listing_preprocess = [porter.stem(token)
30                               for token in nostop_listing
31                               if token.isalpha() and
32                               len(token) > 2]
```

Output:

['cozi', 'entir', 'floor', 'brownston']

Breaking it down:

- ▶ `if token.isalpha()`: only retaining token if it's words (so would strip out things like 1 from 1 bedroom); might skip depending on context
- ▶ `len(token) > 2`: requires that a token is 2 or more characters; e.g., removes `br`
- ▶ `porter.stem(token)`: use the porter stemmer i've initialized to stem the words; e.g., `entire` \Rightarrow `entir`; `cozy` \Rightarrow `cozi`

Small group code break: embed the preprocessing code in 1-2 functions and apply to all the airbnb listings

The previous code used list comprehension to iterate over each word in a single airbnb listing.

To apply to all listings, and to avoid a nested for loop, we want to:

1. Create a function(s) that applies those preprocessing steps (could have one function for stopwords removal; another for stemming; or one combined)
2. Iterate over listings and preprocess. Output could either be a list where each list element is a string of a list (e.g., 'cozy brownstone apt'), or a list of lists where each element is a tokenized string (e.g., ['cozy', 'brownstone', 'apt'])

Output is flexible (could be a list of lists containing tokenized/stemmed text or a list of strings)

Repeat preprocessing over all documents, combine into a “document-term matrix” (DTM)

- ▶ each row is a document (here, an airbnb listing)
- ▶ each column is a term
- ▶ values are 0, 1, ... n for # of times that term occurs in that doc
- ▶ dense format: contains many zeroes (not memory-efficient)

doc	1br	apartment	apt	area	backyard	bdrm ...
1	0	0	1	0	0	0
2	0	0	0	2	0	0
3	0	0	0	0	0	0
4	0	0	0	0	3	0
5	0	0	1	0	0	0
⋮						

How do we create a DTM in Python?

- ▶ **More manual way:** basically, need to find union of all words; can do it by (1) creating an empty dictionary; (2) looping over the documents; (3) when a document contains a new term, it gets added to dictionary as a key; (4) when a document contains a term already in the dictionary, we start counting how many times the term appears in the doc
- ▶ **More automatic way:** uses `sklearn` function (common practice)

Code for more automatic document-term matrix creation

```
33 def create_dtm(list_of_strings, metadata):
34     ## init tokenizer and apply to list of documents
35     vectorizer = CountVectorizer(lowercase = True)
36     dtm_sparse = vectorizer.fit_transform(list_of_strings)
37     ## convert to (1) dense mat; (2) dataframe and (3) add metadata
38     dtm_dense_named = pd.DataFrame(dtm_sparse.todense(),
39                                     columns=vectorizer.get_feature_names())
40     dtm_dense_named_withid = pd.concat([metadata.reset_index(),
41                                         dtm_dense_named], axis = 1)
42     return (dtm_dense_named_withid)
```

Breaking things down:

- ▶ `CountVectorizer`: initializes a sklearn tokenizer to tokenize the preprocessed string
- ▶ `vectorizer.fit_transform`: we feed this a list of documents (each document can be many strings). The output is a sparse matrix that's really a list of tuples: if term t occurs in doc d at least once, then these are listed; if not, that term/doc pair is omitted. This is much lighter than a dense DTM, given the prevalence of zeroes.
- ▶ `dtm_sparse.to_dense()`: if we want to treat the sparse matrix as a normal pandas dataframe, we need to switch it from the sparse representation to the normal dense representation: here, each row is a document; each column is a term; 0 if term t is not in doc d , 1 if term t is in doc d once, etc .
- ▶ Remainder of code just (1) converts the dense matrix to a pandas dataframe to work with; (2) adds back document-level covariates (what I'm calling metadata)

Coding break (if time): Create DTM with preprocessed text

Second activity in

[05_textasdata_partII_topicmodeling.ipynb](#)

Outline of text as data

- ▶ Text as data: where can we find
- ▶ Text mining/“supervised” analyses: know what we’re looking for in advance
 - ▶ Manual lookup of words or counting words from a dictionary
 - ▶ Automated process 1: part-of-speech tagging
 - ▶ Automated process 2: named entity recognition
 - ▶ Automated process 3: sentiment analysis using a scoring dictionary
- ▶ **Unsupervised analyses: how can we more inductively discover themes/patterns in text?**
 - ▶ Bag of words representation of text/preprocessing
 - ▶ **Topic model: concepts**
 - ▶ Topic model: implementation in python

Latent Dirichlet Allocation

- ▶ Idea: documents exhibit each topic in some proportion. This is an **admixture**.
- ▶ Each document is a mixture over topics. Each topic is a mixture over words.
- ▶ Latent Dirichlet Allocation estimates:
 - ▶ The **distribution over words** for each topic.
 - ▶ The **proportion of a document in each topic**, for each document.

Maintained assumptions: Bag of words/fixed number of topics ex ante.


This and next slide with visualization from: Stewart, LDA

What this means in pictures

Say you have
a lot of people.



Each writes
some texts



That discuss a few
different topics

T1: Politics

congress, nations,
power, votes, agree-
ment, bargaining

T2: Statistics

estimator, data, ana-
lysis, variance, model,
inference

The Latent Dirichlet Allocation estimates:

- 1 The topics- each is a distribution over words
- 2 The proportion of each document in each topic

Why does this work \rightsquigarrow Co-occurrence

Where's the information for each word's topic?

Reconsider document-term matrix

	Word ₁	Word ₂	...	Word _J
Doc ₁	0	1	...	0
Doc ₂	2	0	...	3
⋮	⋮	⋮	⋱	⋮
Doc _N	0	1	...	1

We are learning the pattern of what words occur together.

The model wants a topic to contain as few words as possible, but a document to contain as few topics as possible. This **tension** is what makes the model work.

From: Stewart, LDA

Outline of text as data

- ▶ Text as data: where can we find
- ▶ Text mining/“supervised” analyses: know what we’re looking for in advance
 - ▶ Manual lookup of words or counting words from a dictionary
 - ▶ Automated process 1: part-of-speech tagging
 - ▶ Automated process 2: named entity recognition
 - ▶ Automated process 3: sentiment analysis using a scoring dictionary
- ▶ **Unsupervised analyses: how can we more inductively discover themes/patterns in text?**
 - ▶ Bag of words representation of text/preprocessing
 - ▶ Topic model: concepts
 - ▶ **Topic model: implementation in python**

Two routes to topic modeling

1. Create the document-term matrix yourself and then it's compatible with a variety of clustering methods
2. Use built-in functions in `gensim` to start with a list of preprocessed documents and end in estimating a topic model that returns (1) topics and high-probability words, (2) for each document, a k length vector of topic probabilities, where k is the number of topics

Steps for topic modeling using gensim: in words

- ▶ **Create a dictionary:** this is the union of all stemmed/preprocessed words in the corpus (collection of documents); it's fed **tokenized text**; results in dictionary where keys are a "term id"; value is word itself
- ▶ **Filter out words from the dictionary that appear in either a very low proportion of documents (lower bound) or a very high proportion of documents (upper bound):** stopword removal should have gotten rid of most of the latter; former is since we need words to co-occur in multiple documents for the themes to be meaningful
- ▶ **Apply the dictionary to the tokenized text to create a crosswalk between: (1) each word in the text and (2) that word in the filtered dictionary:** this is a final preprocessing that helps get rid of words in the original texts that were filtered out of the corpus dictionary
- ▶ **Estimate the topic model:** use LDA model within gensim

Steps for topic modeling using gensim: preprocessing

```
1 ## Step 1: tokenize documents and store in list
2 text_raw_tokens = [wordpunct_tokenize(one_text)
3                     for one_text in ab_small.name_lower]
4 ## Step 2: use gensim create dictionary – gets all unique
   words across documents
5 text_raw_dict = corpora.Dictionary(text_raw_tokens)
6 ## Step 3: filter out very rare and very common words
   from dictionary; feeding it n docs as lower and upper
   bounds
7 text_raw_dict.filter_extremes(no_below = lower_bound ,
8                               no_above = upper_bound)
9 ## Step 4: map words in dictionary to words in each
   document in the corpus
10 corpus_fromdict = [text_raw_dict.doc2bow(one_text)
11                    for one_text in text_raw_tokens]
```

Steps for topic modeling using gensim: estimation

See documentation for many parameters you can vary!:

<https://radimrehurek.com/gensim/models/ldamodel.html>

```
1 ## Step 5: estimate a model by feeding it: (1) the corpus  
2 ## mapped to the dictionary, (2) the dictionary itself,  
3 ## (3) number of topics (in notation, k),  
4 ## and assorted other arguments  
5 ldamod = gensim.models.ldamodel.LdaModel(corpus_fromdict ,  
6                                           num_topics = 5,  
7                                           id2word=text_raw_dict ,  
8                                           passes=6,  
9                                           alpha = 'auto',  
10                                          per_word_topics = True)
```

Returns a trained Ldamodel class with various methods/attributes

Interacting with the model output

Notebook contains a couple different post-model summaries:

- ▶ **Top words for each topic:** by default, these are the highest-probability words; but they also may just reflect frequently-occurring words in corpus; `pyldavis` has ways to introduce penalties to find words more “unique to” a topic
- ▶ **For each document, a k -length vector of topic probabilities**

Post-modeling diagnostics: how model fit varies as function of number of topics

► **Concept:** tradeoff between two metrics:

1. **Within-topic coherence:** increases when the “top words” for a topic (highest-probability words) tend to co-occur in the same document; tends to be **higher if you have a few topics dominated by frequently-occurring words**
2. **Between-topic exclusivity:** increases when words are “exclusive” to a topic, or only have a high-probability of appearing in a few topics; tends to be **higher as you increase the number of topics**, since each is more granular

► **See here for some code snippets within gensim:**

[https://datascienceplus.com/
evaluation-of-topic-modeling-topic-coherence/](https://datascienceplus.com/evaluation-of-topic-modeling-topic-coherence/)

Coding break: gensim for preprocessing and topic modeling

Third activity in

[05_textasdata_partII_topicmodeling.ipynb](#)