

A Guiding Framework to Improve the Operationalisation of Artificial Intelligence using Enhanced Documentation Standards and Software Engineering Practices

Alex Cummaudo
BSc Swinburne, BIT(Hons)



Applied Artificial Intelligence Institute
Deakin University
Melbourne, Australia

October 9, 2018

Contents

Contents	ii
List of Figures	iv
List of Tables	v
List of Listings	vii
1 Introduction	1
1.1 Background	1
1.1.1 AI Communication Mismatch	2
1.1.2 Mechanics of Model Interpretation	3
1.2 Motivation	4
1.3 Research Goals	4
1.4 Strategy and Roadmap	4
1.5 Contributions	4
2 Literature Review	5
2.1 Software Quality	5
2.2 Probabilistic and Stochastic Systems	5
2.3 Cognitive Biases	5
2.4 UX Consistency Principle	6
2.5 API Documentation and Standards	6
2.6 Validation and Verification	6
2.7 Requirements Specification	6
2.8 Meta-modelling	6
	iii

3	Methodology	7
3.1	Data Collection and Ethics	7
3.2	Approach	7
3.3	Evaluation Methods	7
3.4	Threats to Validity	7
3.4.1	Internal Threats	7
3.4.2	External Threats	7
3.4.3	Construct	7
4	Project Status	9
4.1	Completed Work	9
4.2	Impact	9
4.3	Timeline	9
5	Conclusion	11
	References	20

List of Figures

1.1	Theory of AI communication from information source, y , to intended user as explanations \tilde{y}	3
-----	--	---

List of Tables

List of Listings

Chapter 1

Introduction

1.1 Background

As the rise of applied AI increases, the need for engineering interpretability around models becomes paramount. Model interpretability has been stressed since early machine learning research in the late 1980s and 1990s (such as Quinlan [61] and Michie [54]), and although there has since been a significant body of work in the area [2, 3, 6, 7, 10, 15, 22, 28, 40, 49–51, 58, 62, 66, 71, 78, 79], it is evident that ‘accuracy’ or model ‘confidence’ is still used as a primary criterion for AI evaluation [34, 36, 72]. Indeed, much research into NN or SVM development stresses that ‘good’ models are those with high accuracy. However, is accuracy enough to justify a model’s quality?

To answer this, we revisit what it means for a model to be accurate. Accuracy is an indicator for estimating how well a model’s algorithm will work with future or unforeseen data. It is quantified in the AI testing stage, whereby the algorithm is tested against cases known by humans to have ground truth but such cases are unknown by the algorithm. In production, however, all cases are unknown by both the algorithm *and* the humans behind it, and therefore a single value of quality is “not reliable if the future dataset has a probability distribution significantly different from past data” [24], a problem commonly referred to as the *datashift* problem [74]. Analogously, Freitas [24] provides the following description of the problem:

The military trained [a NN] to classify images of tanks into enemy and friendly tanks. However, when the [NN] was deployed in the field (corresponding to “future data”), it had a very poor accuracy rate. Later, users noted that all photos of friendly (enemy) tanks were taken on a sunny (overcast) day. I.e., the [NN]

learned to discriminate between the colors of the sky in sunny vs. overcast days!
If the [NN] had output a comprehensible model (explaining that it was discriminating between colors at the top of the images), such a trivial mistake would immediately be noted. [24]

So, why must we interpret models? While the formal definition of what it means to be *interpretable* is still somewhat disparate (though some suggestions have been proposed [50]), what is known is (i) there exists a critical trade-off between accuracy and interpretability [18, 23, 30, 39, 42, 85], and (ii) a single quantifiable value cannot satisfy the subjective needs of end-users [24]. As ever-growing domains ML become widespread¹, these applications engage end-users for real-world goals, unlike the aims in early ML research where the aim was to get AI working in the first place. In safety-critical systems where AI provide informativeness to humans to make the final call (see [11, 35, 43]), there is often a mismatch between the formal objectives of the model (e.g., to minimise error) and complex real-world goals, where many other considerations (such as the human factors and cognitive science behind explanations²) are not realised: model optimisation is only worthwhile if they “actually solve the original [human-centred] task of providing explanation” [56] to end-users. **Therefore, when human-decision makers must be interpretable themselves [64], any AI they depend on must also be interpretable.**

Recently, discussion behind such a notion to provide legal implications of interpretability is topical. Doshi-Velez et al. [20] discuss when explanations are not provided from a legal stance—for instance, those affected by algorithmic-based decisions have a ‘right to explanation’ [29, 80] under the European Union’s GDPR³. But, explanations are not the only way to ensure AI accountability: theoretical guarantees (mathematical proofs) or statistical evidence can also serve as guarantees [20], however, in terms of explanations, what form they take and how they are proven correct are still open questions [50].

1.1.1 AI Communication Mismatch

From a SE perspective, explanations and interpretability are, by definition, inherently communication issues: what lacks here is a consistent interface between the AI system and the

¹In areas such as medicine [5, 10, 21, 37, 40, 47, 59, 63, 78, 84, 87], bioinformatics [17, 25, 38, 41, 76], finance [3, 16, 35] and customer analytics [49, 79].

²*Interpretations* and *explanations* are often used interchangeably.

³<https://www.eugdpr.org> last accessed 13 August 2018.

person using it. The ability to encode ‘common sense reasoning’ [52] into programs today has been achieved, but *decoding* that information is what still remains problematic. At a high level, Shannon and Weaver’s theory of communication [70] applies, just as others have done with similar issues in the SE realm [55, 82] (albeit to the domain of visual notations). Humans map the world in higher-level concepts easily when compared to AI systems: while we think of a tree first (not the photons of light or atoms that make up the tree), an algorithm simply sees pixels, and not the concrete object [20] and thusly the AI interprets the tree inversely to humans. Therefore, the interpretation or explanation is done inversely: humans do not explain the individual neurons fired to explain their predictions, and therefore the algorithmic transparent explanations of AI algorithms (“*which neurons were fired to make this AI think this tree is a tree?*”) do not work here.

Therefore, to the user (as mapped using Shannon and Weaver’s theory), an AI pipeline (the communication *channel*) begins with a real-world concept, y , that acts as an *information source*. This information source is fed in as a *message*, x , (as pixels) to an AI system (the *transmitter*). The transmitter encodes the pixels to a prediction, \hat{y} , the *signal* of the message. This signal is decoded by the *receiver*, an explanation system, $e_x(x, \hat{y})$, that tailors the prediction with the given input data to the intended end user (the *destination*) as an explanation, \tilde{y} , another type of *message*. Therefore, the user only sees the channel as an input/output pipeline of real-world objects, y , and explanations, \tilde{y} , tailored to *them*, without needing to see the inner-mechanics of a prediction \hat{y} . We present this diagrammatically in Figure 1.1.




Figure 1.1: Theory of AI communication from information source, y , to intended user as explanations \tilde{y} .

1.1.2 Mechanics of Model Interpretation

How do we interpret models? Methods for developing interpretation models include: decision trees [9, 14, 31, 60, 65], decision tables [4, 49] and decision sets [46, 56]; input gradients, gradient vectors or sensitivity analysis [3, 48, 62, 66, 68]; exemplars [26, 44]; generalised additive models [11]; classification (*if-then*) rules [8, 13, 57, 77, 83] and falling rule lists [71]; nearest neighbours [51, 69, 75, 81, 86] and Naïve Bayes analysis [5, 12, 27, 33, 45, 47, 53, 87]. Several cross-domain studies have assessed the interpretability of these techniques against end-users, measuring response time, accuracy in model response and user confidence [1, 25, 32, 35, 51, 67, 73, 79], although it is generally agreed that decision rules and decision tables provide the most interpretation in non-linear models such as SVM's or NN's [25, 51, 79]. For an extensive survey of the benefits and fallbacks of these techniques, we refer to Freitas [24] and Doshi-Velez and Kim [19].

As it stands, AI presents an issue with. (For a detailed discussion, see Doshi-Velez et al. [20].

1.2 Motivation

1.3 Research Goals

1.4 Strategy and Roadmap

1.5 Contributions

Chapter 2

Literature Review

⟨ TODO: **Reiterate research claims from Chapter 1 - Introduction.** ⟩

⟨ TODO: **Review literature around this claim from theoretical lenses.** ⟩

2.1 Software Quality

⟨ TODO: **Background on the development of software quality models.** *McCall's model was one of the first software quality models introduced. It described quality from X perspectives... this was further developed by the ISO quality model, which enhanced by Y... In the late 1990s, Dromey's interpretation expanded...* ⟩

⟨ TODO: **Relate software quality to CV systems; internal & external quality.** ⟩

⟨ TODO: **Discuss gaps in the software quality literature relating directly to CV quality.** ⟩

2.2 Probabilistic and Stochastic Systems

⟨ TODO: **What are stochastic/probabilistic systems? E.g., model interpretation?** ⟩

⟨ TODO: **What understanding might be missing from model interpretation? Relate back to topic.** ⟩

2.3 Cognitive Biases

⟨ TODO: **Background; what are cognitive biases and how does it relate to SE?** ⟩

⟨ TODO: **Literature of CB specifically in SE.** ⟩

⟨ TODO: **List potential CBs with relation to the AI-based systems.** ⟩

2.4 UX Consistency Principle

⟨ TODO: **Background; what is UX consistency? What does it advocate for and why?** ⟩

⟨ TODO: **What lessons can we learn from UX consistency, and how can we apply it to SE?** ⟩

⟨ TODO: **What are the gaps in SE that do not conform to practices of UX consistency w.r.t. AI systems development?** ⟩

2.5 API Documentation and Standards

⟨ TODO: **What are API documentation standards? What do they advocate for?** ⟩

⟨ TODO: **What is missing for AI documentation? What is the gap?** ⟩

2.6 Validation and Verification

⟨ TODO: **Unsure...** ⟩

2.7 Requirements Specification

⟨ TODO: **Unsure...** ⟩

2.8 Meta-modelling

⟨ TODO: **What is meta-modelling? Can get this from honours thesis...?** ⟩

⟨ TODO: **How does this differ in AI context?** ⟩

Chapter 3

Methodology

3.1 Data Collection and Ethics

3.2 Approach

3.3 Evaluation Methods

3.4 Threats to Validity

3.4.1 Internal Threats

3.4.2 External Threats

3.4.3 Construct

Chapter 4

Project Status

4.1 Completed Work

4.2 Impact

4.3 Timeline

Chapter 5

Conclusion

References

- [1] H. Allahyari and N. Lavesson, “User-oriented assessment of classification model understandability,” in *11th scandinavian conference on Artificial intelligence*. IOS Press, 2011.
- [2] M. G. Augasta and T. Kathirvalavakumar, “Reverse engineering the neural networks for rule extraction in classification problems,” *Neural processing letters*, vol. 35, no. 2, pp. 131–150, 2012.
- [3] D. Baehrens, T. Schroeter, S. Harmeling, M. Kawanabe, K. Hansen, and K.-R. MÅžller, “How to explain individual classification decisions,” *Journal of Machine Learning Research*, vol. 11, no. Jun, pp. 1803–1831, 2010.
- [4] B. Baesens, C. Mues, M. De Backer, J. Vanthienen, and R. Setiono, “Building intelligent credit scoring systems using decision tables,” in *Enterprise Information Systems V*. Springer, 2004, pp. 131–137.
- [5] R. Bellazzi and B. Zupan, “Predictive data mining in clinical medicine: current issues and guidelines,” *International journal of medical informatics*, vol. 77, no. 2, pp. 81–97, 2008.
- [6] A. Ben-David, “Monotonicity maintenance in information-theoretic machine learning algorithms,” *Machine Learning*, vol. 19, no. 1, pp. 29–43, 1995.
- [7] O. Boz, “Extracting decision trees from trained neural networks,” in *Proceedings of the eighth ACM SIGKDD international conference on Knowledge discovery and data mining*. ACM, 2002, pp. 456–461.
- [8] M. Bramer, *Principles of data mining*. Springer, 2007, vol. 180.
- [9] L. Breiman, J. H. Friedman, R. A. Olshen, and C. J. Stone, *Classification and Regression Trees*. CRC press, 1984.

- [10] A. Bussone, S. Stumpf, and D. O’Sullivan, “The Role of Explanations on Trust and Reliance in Clinical Decision Support Systems.” *ICHI*, 2015.
- [11] R. Caruana, Y. Lou, J. Gehrke, P. Koch, M. Sturm, and N. Elhadad, “Intelligible Models for HealthCare - Predicting Pneumonia Risk and Hospital 30-day Readmission.” *KDD*, pp. 1721–1730, 2015.
- [12] J. Cheng and R. Greiner, “Learning bayesian belief network classifiers: Algorithms and system,” in *Conference of the Canadian Society for Computational Studies of Intelligence*. Springer, 2001, pp. 141–151.
- [13] P. Clark and R. Boswell, “Rule induction with CN2: Some recent improvements,” in *European Working Session on Learning*. Springer, 1991, pp. 151–163.
- [14] M. Craven and J. W. Shavlik, “Extracting Tree-Structured Representations of Trained Networks.” *NIPS*, 1995.
- [15] K. Dejaeger, F. Goethals, A. Giangreco, L. Mola, and B. Baesens, “Gaining insight into student satisfaction using comprehensible data mining techniques,” *European Journal of Operational Research*, vol. 218, no. 2, pp. 548–562, 2012.
- [16] V. Dhar, D. Chou, and F. Provost, “Discovering Interesting Patterns for Investment Decision Making with GLOWER—A Genetic Learner Overlaid with Entropy Reduction,” *Data Mining and Knowledge Discovery*, vol. 4, no. 4, pp. 251–280, 2000.
- [17] M. Doderer, K. Yoon, J. Salinas, and S. Kwek, “Protein subcellular localization prediction using a hybrid of similarity search and error-correcting output code techniques that produces interpretable results,” *In silico biology*, vol. 6, no. 5, pp. 419–433, 2006.
- [18] P. Domingos, “Occam’s two razors: The sharp and the blunt,” in *KDD*, 1998, pp. 37–43.
- [19] F. Doshi-Velez and B. Kim, “Towards a rigorous science of interpretable machine learning,” 2017.
- [20] F. Doshi-Velez, M. Kortz, R. Budish, C. Bavitz, S. Gershman, D. O’Brien, S. Schieber, J. Waldo, D. Weinberger, and A. Wood, “Accountability of AI Under the Law: The Role of Explanation,” *arXiv.org*, Nov. 2017.

- [21] W. Elazmeh, W. Matwin, D. O’Sullivan, W. Michalowski, and W. Farion, “Insights from predicting pediatric asthma exacerbations from retrospective clinical data,” in *Evaluation Methods for Machine Learning II—Papers from 2007 AAAI Workshop*, 2007, pp. 10–15.
- [22] A. J. Feelders, “Prior knowledge in economic applications of data mining,” in *European Conference on Principles of Data Mining and Knowledge Discovery*. Springer, 2000, pp. 395–400.
- [23] A. A. Freitas, “A critical review of multi-objective optimization in data mining: a position paper,” *ACM SIGKDD Explorations Newsletter*, vol. 6, no. 2, pp. 77–86, 2004.
- [24] ———, “Comprehensible classification models,” *ACM SIGKDD Explorations Newsletter*, vol. 15, no. 1, pp. 1–10, Mar. 2014.
- [25] A. A. Freitas, D. C. Wieser, and R. Apweiler, “On the importance of comprehensible classification models for protein function prediction,” *IEEE/ACM Transactions on Computational Biology and Bioinformatics (TCBB)*, vol. 7, no. 1, pp. 172–182, 2010.
- [26] B. J. Frey and D. Dueck, “Clustering by Passing Messages Between Data Points,” *Science*, vol. 315, no. 5814, pp. 972–976, Feb. 2007.
- [27] N. Friedman, D. Geiger, and M. Goldszmidt, “Bayesian network classifiers,” *Machine Learning*, vol. 29, no. 2-3, pp. 131–163, 1997.
- [28] G. Fung, S. Sandilya, and R. B. Rao, “Rule extraction from linear support vector machines,” in *Proceedings of the eleventh ACM SIGKDD international conference on Knowledge discovery in data mining*. ACM, 2005, pp. 32–40.
- [29] B. Goodman and S. R. Flaxman, “EU regulations on algorithmic decision-making and a ”right to explanation”.” *CoRR*, 2016.
- [30] P. D. Grünwald, *The minimum description length principle*. MIT press, 2007.
- [31] T. Hastie, R. Tibshirani, and J. H. Friedman, *The Elements of Statistical Learning*, ser. Data Mining, Inference, and Prediction. Springer Science & Business Media, Jan. 2001.
- [32] B. Hayete and J. R. Bienkowska, “Gotrees: predicting go associations from protein domain composition using decision trees,” in *Biocomputing 2005*. World Scientific, 2005, pp. 127–138.

- [33] D. Heckerman, D. M. Chickering, C. Meek, R. Rounthwaite, and C. Kadie, “Dependency networks for inference, collaborative filtering, and data visualization,” *Journal of Machine Learning Research*, vol. 1, no. Oct, pp. 49–75, 2000.
- [34] J. Huang and C. X. Ling, “Using AUC and accuracy in evaluating learning algorithms,” *IEEE Transactions on knowledge and Data Engineering*, vol. 17, no. 3, pp. 299–310, 2005.
- [35] J. Huysmans, K. Dejaeger, C. Mues, J. Vanthienen, and B. Baesens, “An empirical evaluation of the comprehensibility of decision table, tree and rule based predictive models,” *Decision Support Systems*, vol. 51, no. 1, pp. 141–154, Apr. 2011.
- [36] N. Japkowicz and M. Shah, *Evaluating learning algorithms: a classification perspective*. Cambridge University Press, 2011.
- [37] M. W. M. Jaspers, M. Smeulers, H. Vermeulen, and L. W. Peute, “Effects of clinical decision-support systems on practitioner performance and patient outcomes: a synthesis of high-quality systematic review findings,” *Journal of the American Medical Informatics Association*, vol. 18, no. 3, pp. 327–334, 2011.
- [38] T. Jiang and A. E. Keating, “AVID: an integrative framework for discovering functional relationships among proteins,” *BMC bioinformatics*, vol. 6, no. 1, p. 136, 2005.
- [39] Y. Jin, *Multi-objective machine learning*. Springer Science & Business Media, 2006, vol. 16.
- [40] U. Johansson and L. Niklasson, “Evolving decision trees using oracle guides,” in *IEEE Symposium on Computational Intelligence and Data Mining (CIDM)*. IEEE, 2009.
- [41] A. Karwath and R. D. King, “Homology induction: the use of machine learning to improve sequence similarity searches,” *BMC bioinformatics*, vol. 3, no. 1, p. 11, 2002.
- [42] K. A. Kaufman and R. S. Michalski, “Learning from inconsistent and noisy data: the AQ18 approach,” in *International Symposium on Methodologies for Intelligent Systems*. Springer, 1999, pp. 411–419.
- [43] B. Kim, *Interactive and Interpretable Machine Learning Models for Human Machine Collaboration*. Massachusetts Institute of Technology, 2015.

- [44] B. Kim, C. Rudin, and J. A. Shah, “The Bayesian Case Model - A Generative Approach for Case-Based Reasoning and Prototype Classification.” *NIPS*, 2014.
- [45] I. Kononenko, “Inductive and Bayesian learning in medical diagnosis,” *Applied Artificial Intelligence an International Journal*, vol. 7, no. 4, pp. 317–337, 1993.
- [46] H. Lakkaraju, S. H. Bach, and J. Leskovec, “Interpretable Decision Sets - A Joint Framework for Description and Prediction.” *KDD*, pp. 1675–1684, 2016.
- [47] N. Lavrač, “Selected techniques for data mining in medicine,” *Artificial intelligence in medicine*, vol. 16, no. 1, pp. 3–23, 1999.
- [48] T. Lei, R. Barzilay, and T. Jaakkola, “Rationalizing Neural Predictions,” *arXiv.org*, Jun. 2016.
- [49] E. Lima, C. Mues, and B. Baesens, “Domain knowledge integration in data mining using decision tables: Case studies in churn prediction,” *Journal of the Operational Research Society*, vol. 60, no. 8, pp. 1096–1106, 2009.
- [50] Z. C. Lipton, “The Mythos of Model Interpretability.” *CoRR*, 2016.
- [51] D. Martens, J. Vanthienen, W. Verbeke, and B. Baesens, “Performance of classification models from a user perspective,” *Decision Support Systems*, vol. 51, no. 4, pp. 782–793, 2011.
- [52] J. McCarthy, “Programs with Common Sense,” Cambridge, MA, USA, Tech. Rep., 1960.
- [53] D. Michie, D. J. Spiegelhalter, and C. C. Taylor, “Machine Learning and Statistical Classification of Artificial intelligence,” 1994.
- [54] D. Michie, “Machine Learning in the Next Five Years.” *EWSL*, 1988.
- [55] D. L. Moody, “The “Physics” of Notations - Toward a Scientific Basis for Constructing Visual Notations in Software Engineering.” *IEEE Trans. Software Eng.*, 2009.
- [56] M. Narayanan, E. Chen, J. He, B. Kim, S. Gershman, and F. Doshi-Velez, “How do Humans Understand Explanations from Machine Learning Systems? An Evaluation of the Human-Interpretability of Explanation.” *CoRR*, 2018.

- [57] F. E. Otero and A. A. Freitas, “Improving the interpretability of classification rules discovered by an ant colony algorithm,” in *Proceedings of the 15th annual conference on Genetic and evolutionary computation*. ACM, 2013, pp. 73–80.
- [58] M. Pazzani, “Comprehensible knowledge discovery: gaining insight from data,” in *First Federal Data Mining Conference and Exposition*, 1997, pp. 73–82.
- [59] M. J. Pazzani, S. Mani, and W. R. Shankle, “Acceptance of rules generated by machine learning among medical experts,” *Methods of information in medicine*, vol. 40, no. 05, pp. 380–385, 2001.
- [60] J. R. Quinlan, “C4. 5: Programming for machine learning,” *Morgan Kauffmann*, vol. 38, p. 48, 1993.
- [61] —, “Some elements of machine learning,” in *International Conference on Inductive Logic Programming*. Springer, 1999, pp. 15–18.
- [62] M. T. Ribeiro, S. Singh, and C. Guestrin, “”Why Should I Trust You?”,” in *the 22nd ACM SIGKDD International Conference*. New York, New York, USA: ACM Press, 2016, pp. 1135–1144.
- [63] G. Richards, V. J. Rayward-Smith, P. H. Sönksen, S. Carey, and C. Weng, “Data mining for indicators of early mortality in a database of clinical records,” *Artificial intelligence in medicine*, vol. 22, no. 3, pp. 215–231, 2001.
- [64] G. Ridgeway, D. Madigan, T. Richardson, and J. O’Kane, “Interpretable Boosted Naïve Bayes Classification.” *KDD*, 1998.
- [65] L. Rokach and O. Z. Maimon, *Data mining with decision trees: theory and applications*. World scientific, 2008, vol. 69.
- [66] A. S. Ross, M. C. Hughes, and F. Doshi-Velez, “Right for the Right Reasons: Training Differentiable Models by Constraining their Explanations,” *arXiv.org*, Mar. 2017.
- [67] M. Schwabacher, P. Langley, and P. Norvig, “Discovering communicable scientific knowledge from spatio-temporal data,” *ICML*, 2001.
- [68] R. R. Selvaraju, M. Cogswell, A. Das, R. Vedantam, D. Parikh, and D. Batra, “Grad-CAM: Visual Explanations from Deep Networks via Gradient-Based Localization,” in

- 2017 IEEE International Conference on Computer Vision (ICCV)*. IEEE, 2017, pp. 618–626.
- [69] S. Sen and L. Knight, “A genetic prototype learner,” in *IJCAI*. Citeseer, 1995, pp. 725–733.
- [70] C. E. Shannon and W. Weaver, *The mathematical theory of communication*. Urbana, IL: The University of Illinois Press, 1963.
- [71] S. Singh, M. T. Ribeiro, and C. Guestrin, “Programs as Black-Box Explanations,” *arXiv.org*, Nov. 2016.
- [72] M. Sokolova and G. Lapalme, “A systematic analysis of performance measures for classification tasks,” *Information Processing & Management*, vol. 45, no. 4, pp. 427–437, 2009.
- [73] G. H. Subramanian, J. Nosek, S. P. Raghunathan, and S. S. Kanitkar, “A comparison of the decision table and tree,” *Communications of the ACM*, vol. 35, no. 1, pp. 89–94, 1992.
- [74] M. Sugiyama, N. D. Lawrence, and A. Schwaighofer, *Dataset shift in machine learning*. The MIT Press, 2017.
- [75] N. R. Suri, V. S. Srinivas, and M. N. Murty, “A cooperative game theoretic approach to prototype selection,” in *European Conference on Principles of Data Mining and Knowledge Discovery*. Springer, 2007, pp. 556–564.
- [76] D. Szafron, P. Lu, R. Greiner, D. S. Wishart, B. Poulin, R. Eisner, Z. Lu, J. Anvik, C. Macdonell, and A. Fyshe, “Proteome Analyst: custom predictions with explanations in a web-based tool for high-throughput proteome annotations,” *Nucleic acids research*, vol. 32, no. 2, pp. W365–W371, 2004.
- [77] S. Thrun, “Is Learning The n-th Thing Any Easier Than Learning The First?” p. 7, 1996.
- [78] A. Van Assche and H. Blockeel, “Seeing the forest through the trees: Learning a comprehensible model from an ensemble,” in *European conference on machine learning*. Springer, 2007, pp. 418–429.

- [79] W. Verbeke, D. Martens, C. Mues, and B. Baesens, “Building comprehensible customer churn prediction models with advanced rule induction techniques,” *Expert Systems with Applications*, vol. 38, no. 3, pp. 2354–2364, 2011.
- [80] S. Wachter, B. Mittelstadt, and L. Floridi, “Why a Right to Explanation of Automated Decision-Making Does Not Exist in the General Data Protection Regulation,” *International Data Privacy Law*, vol. 7, no. 2, pp. 76–99, Jun. 2017.
- [81] D. Wettschereck, D. W. Aha, and T. Mohri, “A review and empirical evaluation of feature weighting methods for a class of lazy learning algorithms,” *Artificial Intelligence Review*, vol. 11, no. 1-5, pp. 273–314, 1997.
- [82] H. Wickham, “A Layered Grammar of Graphics,” *Journal of Computational and Graphical Statistics*, vol. 19, no. 1, pp. 3–28, Jan. 2010.
- [83] I. H. Witten, E. Frank, M. A. Hall, and C. J. Pal, *Data Mining: Practical machine learning tools and techniques*. Morgan Kaufmann, 2016.
- [84] M. L. Wong and K. S. Leung, *Data mining using grammar based genetic programming and applications*. Springer Science & Business Media, 2006, vol. 3.
- [85] J. Zahálka and F. Železný, “An experimental test of Occam’s razor in classification,” *Machine Learning*, vol. 82, no. 3, pp. 475–481, 2011.
- [86] J. Zhang, “Selecting typical instances in instance-based learning,” in *Machine Learning Proceedings 1992*. Elsevier, 1992, pp. 470–479.
- [87] B. Zupan, J. Demšar, M. W. Kattan, J. R. Beck, and I. Bratko, “Machine learning for survival analysis: a case study on recurrence of prostate cancer,” *Artificial intelligence in medicine*, vol. 20, no. 1, pp. 59–75, 2000.